



CITY OF PORTSMOUTH
DEPARTMENT OF PUBLIC WORKS (DPW)
DRIVEWAY RULES AND PROCEDURES

The purpose of a driveway permit is to secure access from a private property to the public right-of-way. It is required when a new access is requested or an existing access is being altered. The repaving of an existing driveway in-kind does not require a permit.

1.0 Driveway Permit Application Process:

- 1.1 The applicant shall apply for a permit online through the City's permitting center at: <https://portsmouthnh.viewpointcloud.com>.
- 1.2 At time of application, the applicant shall provide a detailed sketch or plan showing information as outlined below:
 - Address of property
 - Location of proposed curb cut
 - Proposed width of driveway
 - City right-of-way line
 - Edge of pavement
 - Any existing sidewalks and curbing (and existing crosswalk, if any)
 - Nearby drainage structures
 - Elimination or relocation of existing parking spaces
 - Grade changes
 - Nearest structures with dimensions
 - Neighboring driveway cuts with dimensions
 - Traffic control devices (traffic signals, stop signs, etc.)
 - Nearby trees, fire hydrants, fences, hedges, etc. (with dimensions)
 - Nearby utility poles (include pole number)
 - Posted speed limit on street
 - Only PDF format will be accepted
- 1.3 Cost for the construction of driveway aprons in the city's right-of-way is the responsibility of the property owner / homeowner.
- 1.4 Sketch or plan in PDF must be uploaded at time of application.
- 1.5 The permit will be approved and printed through ViewPoint Cloud.
- 1.6 Effective July 1, 2017 a permit fee of \$50.00 will be charged.
- 1.7 Applicant is required to contact Dave Desfosses at DPW for a final inspection. See last page for contact information.

2.0 Prior Approvals:

- 2.1 Commercial and/or Industrial driveways, approved by the Planning Board as part of the site review process, do not require a permit through DPW.

3.0 Specifications:

- 3.1 Sketch or plan must meet requirements outlined in this section.
- 3.2 Curb cut locations for new driveway installations shall be selected to most adequately protect the property owner and the safety of the traveling public (both pedestrian & vehicular) in all seasons of the year. The proposed driveway shall provide a safe, independent and direct access through its own lot frontage to a public street. In cases where a proposed driveway is to be shared by two or more lots, or where warranted by traffic flows or adverse topographic conditions, the Director of Public Works may elect to have the application reviewed by such other committees or boards as he deems appropriate and/or necessary. All shared driveways shall be improved to accommodate two-way traffic flow and shall be established by an easement. The easement shall address maintenance responsibilities.
- 3.3 Driveways shall not interfere with the free flowing drainage in the gutter line or roadside swales. Driveways shall be graded in accordance with the typical driveway sections (see below). If a cross culvert is deemed necessary, the installation and maintenance shall be the property owner's responsibility.
- 3.4 Driveways shall be located in accordance with Portsmouth Zoning Ordinance and approved site plans. Expansion of a driveway or parking on a parcel must also conform to the Portsmouth Zoning Ordinance.
- 3.5 Circular driveway designs shall conform to these specifications unless approved by the Parking and Traffic Safety Committee.
- 3.6 Drive openings shall be a maximum of 24 feet wide and a minimum of 10 feet wide at the property line in residential zoning districts.
- 3.7 No driveway shall intersect the street at less than a 60 degree angle or have a grade in excess of 10%.
- 3.8 Stopping sight distance (SDD) should generally be determined in accordance with the latest version of the American Association of State Highway and Transportation Officials (AASHTO) publication, "A Policy on Geometric Designs of Streets and Highways". Minimum required stopping sight distance must be based on the design speed, observed 85th percentile speed, or posted speed limit (whichever is highest) of the major street. The decision point on a minor approach should be 14.5 feet from the edge of the major road travel way. The sight line distance should be measured along the roadway. The sight lines must not cross over private land unless

under the applicant's control. Stopping sight distance is measured from an eye height of 3.5 feet to an object height of 2 feet above street level. The 2 foot object should be at the driveway side edge of the travel lane. For speeds of 20 mph on a level roadway, a minimum stopping sight distance of 115 feet is needed. For speeds of 30 mph, a minimum SSD of 200 feet is needed. The City reserves the right to require greater distances where hazardous conditions exist.

3.9 No driveway shall be located within 30 feet of a street intersection. When installing a new driveway cut through an existing sidewalk, applicant shall:

- Reset granite curbing and sidewalks to appropriate tip downs (1":12") or 8% max grade. Also refer to the Americans with Disabilities Act (ADA).
- Back the curbing up with concrete on the street side.
- Adequately compact the crushed gravel in the reshaped driveway apron. If the driveway apron is in the right-of-way, it shall be asphalt surfaced.
- Reinstall the sidewalk material (concrete, asphalt, brick) to its original depth, with proper transitions into adjacent sidewalks.
- Install good screened loam, re-seed disturbed areas, and maintain until turf is established.
- Corner radii shall be 3 feet unless approved as otherwise, and shall not encroach on abutting parcels.

3.10 Nonstandard Driveway Surface Materials


Aprons of differing materials are allowed subject to the following:

- Apron surface shall be ADA compliant;
- Apron surface shall be constructed on an asphalt substrate for rigidity and longevity;
- The first 12" (inches) of the apron as measured from the edge of the road must be asphalt. Additionally, it must be elevated above the road 1"(inch) and should be at least 3" (inches) thick. There are no exceptions.
- Upon notice from DPW or other City entity/agency to the property owner of any deficiency in the surface of the apron in the future, the owner will have 30 days to repair or replace the apron to the DPW's satisfaction with like or other ADA acceptable materials. If after 30 days, the deficiency is not corrected by the property owner, the City at its option, will remove the brick apron and replace with a new ADA approved surface of its choosing and the property owner will be back charged for the work.


3.11 Excavated granite curbing, bricks, pavers, cobblestones, etc., are the property of the City of Portsmouth and shall be delivered to the Public Works Facility or as designated by the Director of Public Works.

4.0 Typical Driveway Profiles:

4.1 Below Street Grade Profile



4.2 Above Street Grade Profile:



5.0

Notes:

The City of Portsmouth reserves the right to deny any permits when:

- Proposed driveway does not conform to the requirements of the Portsmouth Zoning Ordinance;
- Proposed driveway does not conform to the Driveway Specifications that are part of this permitting process; or
- Proposed driveway would present an unreasonable safety risk to the public.

Staff Contact Information:

Department of Public Works

Dave Desfosses

Office Phone: (603) 766-1411

Email: djdesfosses@cityofportsmouth.com