

**Pease Development Authority**  
**55 International Drive, Portsmouth, NH 03801, (603) 433-6088**



**Conditional Use Permit Application**

<b>For PDA Use Only</b>			
Date Submitted: _____	Municipal Review: _____	Fee: _____	
Application Complete: _____	Date Forwarded: _____	Paid: _____	Check #: _____



**Applicant Information**

Applicant: Lonza Biologics		Agent: Tighe & Bond
Address: 101 International Drive Portsmouth, NH 03801		Address: 177 Corporate Drive Portsmouth, NH 03801
Business Phone: 603-334-6100		Business Phone: 603-433-8818
Mobile Phone: _____		Mobile Phone: _____
Fax: _____		Fax: _____
Portsmouth Tax Map: 305	Lot #: 1 & 2	Zone: Airport Business and Commercial
Address / Location of Work: 70 & 80 Corporate Drive		

**Activity Information**

Proposed Activity (check all that apply)		Impacted Jurisdictional Area(s): Check all that apply	
<input checked="" type="checkbox"/> New Structure		<input checked="" type="checkbox"/> Wetland	
<input type="checkbox"/> Expansion of Existing Structure		<input checked="" type="checkbox"/> Wetland Buffer	
<input type="checkbox"/> Other site alteration (specify): _____			
Total area of wetland on subject lot:		75,430 SF	
Total area of wetland buffer on subject lot:		81,315 SF	
Distance of proposed structure or activity to edge of wetland:		0 LF	
	On subject lot		Off subject lot
Area of wetland impacted:	55,555 SF		
Area of wetland buffer impacted:	66,852 SF		
Total area of wetland and wetland buffer impacted:	122,407 SF		
Provide complete description of site and work to be completed: The project potentially consists of the expansion of Lonza Biologics, which includes the construction of three (3) proposed buildings and two (2) parking garages, along with associated site improvements, including utilities and drainage infrastructure.			
<b>All above information shall be shown on a site plan submitted with this application.</b>			

**Certification**

I hereby certify under the penalties of perjury that the foregoing information and accompanying plans, documents, and supporting data are true and complete to the best of my knowledge.	
 _____ Signature of Applicant	 _____ Date

N:\Engineer\Conditional Use Permit Application.xlsx

L-0700-013  
May 30, 2018

Mr. Steve Miller, Chairman  
Conservation Commission  
City of Portsmouth Planning Department  
1 Junkins Avenue  
Portsmouth, New Hampshire 03801

Re: **Lonza Biologics – Proposed Industrial Development  
Conservation Commission**

Dear Steve:

On behalf of Lonza Biologics, we are pleased to submit the following information to the Conservation Commission to support a request for recommendation of approval to the Pease Development Authority (PDA) for Conditional Use Permit application for a proposed industrial development located at 70 and 80 Corporate Drive on Pease International Tradeport:

- Ten (10) copies of the PDA Conditional Use Permit Application dated May 25, 2018;
- Ten (10) copies of the Site Plan package last revised May 21, 2018;
- Ten (10) copies of the Hodgson Brook Restoration Report prepared by Streamworks dated May 28, 2018;
- Ten (10) copies of the Drainage Memorandum dated May 21, 2018;
- Ten (10) copies of the Wetland Functions and Values Report prepared by GES dated June 16, 2016;
- Ten (10) copies of the Aerial Site Plan Overlay dated May 2018;
- Ten (10) copies of the 1992 Aerial Wetland Overlay Exhibit dated July 1, 2016;
- One (1) copy of the Abutters List;
- One (1) CD containing digital copies (PDF) of the information list above;
- One (1) check in the amount of \$1,000 for the Conditional Use Permit Application fee.

The proposed project will expand Lonza Biologics' facility to support its growing product development services to the pharmaceutical and biologic industries. The proposed project is located on a vacant 24-acre parcel, referred to as the Iron Parcel, that once consisted of row housing and streets for Pease Air Force Base. The houses and roads were removed in the mid to late 1990's as part of the Civil Redevelopment Plan for Pease after the closure of the Air Force Base. These demolition activities resulted in pockets of wetlands that did not previously exist in 1992.

Lonza's existing facilities are located at 101 International Drive which is across Goose Bay Drive from the proposed project site. The existing facility is approximately 800,000 SF in gross floor area and includes approximately 800 employees. Lonza maximized its potential building footprint growth at the 101 International Drive with the completion of a 300,000 SF building expansion project in 2008. In order to continue its growth to further serve existing and new customer demand, Lonza will need to expand its facilities across Goose Bay Drive.

The project will merge 101 International Drive with 70 and 80 Corporate Drive to create a 43-acre parcel for Lonza's campus. This will require that 1,700LF of Goose Bay Drive be abandoned as a public right-of-way and merged with these parcels. The total master plan build-out of the proposed industrial development will include three (3) new buildings totaling approximately 1 million square feet of gross floor area and two (2) new parking





garages. The full master plan build-out has the potential to create approximately 1,000 new jobs. This master plan will be constructed in phases with the shell of Proposed Building #1, the building closest to Lonza's existing facility, being constructed as the first phase.

The project will also consist of site improvements that include drive aisles, sidewalks utilities, lighting, landscaping and a stormwater management system with three (3) gravel wetlands and one (1) rain garden.

The project will result in 55,555 SF of wetland impact and 66,852 SF of impacts in Pease Development Authority's 25 FT wetland buffer. As depicted in the enclosed 1992 Aerial Overlay Plan, most of these wetlands did not previously exist when the site consisted of the row housing and streets for the Pease Air Force Base. To mitigate impacts, the project will include a stream restoration project for Hodgson Brook. There is an existing 50-Inch culvert that bisects the parcel which is a buried portion of Hodgson Brook. The project will remove this culvert and daylight the flow through a new 1,000 LF stream channel. This will result in approximately 42,500 SF of restoration area that has a higher function and value than the existing wetlands on site.

Part 304-A.08 of the PDA Zoning Requirements, indicate that the following criteria shall be addressed for a Conditional Use Permit:

1. The land is reasonably suited to the use;

***The land is reasonably suited as it is located in the Airport Business Commercail District and the proposed use is allowed. The parcel is located to the rear of Lonza's exisiting parcel, which allows for expansion of their facility given there is no more room to expand on their existing parcel.***

2. There is no alternative location outside the wetland buffer that is feasible and reasonable for the proposed use;

***There is no alterative location outside the wetland buffer given the size and scale of the project. As noted above and shown on the enclosed 1992 Aerial Wetland Overlay Plan, this parcel and most of the wetland buffers proposed to be impacted did not exist 20 years ago, as this site was previously developed with row housing and streets for the Air Force Base.***

3. There will be no adverse impact on the wetland functional values of the site or surrounding properties;

***The impacted wetland areas are scrub shrub/emergent wetlands with functions and values that are limited to only some potential for groundwater recharge/discharge, flood flow alteration and nutrient removal in small areas. The proposed stream will have a higher function and value. In addition, the proposed Low Impact Design (LID) stormwater management practices will provide stormwater treatment and recharge as described in the enclosed Drainage Memorandum.***

4. Alteration of the natural vegetative state or managed woodland will occur only to the extent necessary to achieve construction goals;

***Alteration of the natural vegetative state will only occur within the limits of the proposed development area. Areas adjacent to existing wetlands along the east portion of Goose Bay Drive will not be disturbed and will be kept in***

**their existing vegetative state. In addition, the detailed Wetland Planting Plan has been included for the proposed stream.**

5. Potential impacts have been avoided to the maximum extent practicable and unavoidable impacts have been minimized.

**Potential impacts have been avoided to the maximum extent practicable given the size and scale of the proposed project. To the extent possible, the site design avoids impacts to an existing portion of wetland area closest to Goose Bay Drive that appears to have been a wetland when the row housing and streets existed for the Air Force Base. As shown in the 1992 Aerial Wetland Overlay Plan, the remaining wetlands that are being impacted did not exist when this site was previously developed for the Air Force Base. In addition, impacts to wetlands are being mitigated with the construction of a new 1,000 LF stream channel that will result in approximately 42,500 SF of restoration area that has a higher function and value than the existing wetlands on site that will be impacted.**

We respectfully request to be placed on the June 13, 2018 Conservation Commission agenda. If you have any questions or need any additional information, please contact me at 603.433.8818 or [pmcrimmins@tighebond.com](mailto:pmcrimmins@tighebond.com).

Very truly yours,


**TIGHE & BOND, INC.**



Patrick M. Crimmins, P.E.  
Project Manager

Enclosures

Cc: Lonza Biologics (via email)  
DTC Lawyers (via email)  
Streamworks (via email)  
Gove Environmental Services (via email)  
Pease Development Authority (via email)



June 16, 2016

Patrick Crimmins, P.E.  
Tighe & Bond  
177 Corporate Drive  
Portsmouth, NH 03801

Re: Lonza, Corporate Drive, Portsmouth  
Subject: Wetland Delineation Report

Dear Mr. Crimmins:

Per your request, this letter is to verify that Gove Environmental Services, Inc., performed a site inspection to identify functions and values for the wetlands delineated at the above-referenced property.

The site consists of predominantly open land once used as row housing. These houses and associated roads and driveways were removed decades ago, as well as the smoothing of the site. This is still evident today through a layer of smooth fill material across the site. Dominant vegetation across the site is grass, and a few mature trees. A large detention pond is located on the site in the central portion, with a riprap bottom and berms along the edge. A large stockpile of material is also present on site and is stable and well vegetated.

Additionally on site are 5 wetland areas. These wetland areas are all isolated on site with some drainage from wetland 4, which drains to the west through a culvert and into Hogdson Brook. Hydrology is predominantly through ground water and some minor influence through sheet flow over the grass surface.


Wetland areas 1 and 4 are similar in make up and are classified as PSS/EM1E, scrub shrub/emergent wetlands, with dominant vegetation of Red maple and American elm in the tree layer, highbush blueberry, speckled alder and gray dogwood in the shrub layer and Cinnamon and sensitive fern, grasses and sedges in the herbaceous layer. Primary functions and values are Groundwater Recharge/Discharge, Flood flow Alteration, Nutrient Removal.

Wetland areas, 2,3,and 5 are also similar in make up and are classified as PEM1E, emergent wetlands, with dominant vegetation of grasses and sedges. Primary functions and values are Groundwater Recharge/Discharge, Flood flow Alteration, Nutrient Removal.

Copies of the USACE Highway Methodology sheets are included

If you have any questions or need anything else, please let me know.

Sincerely,



Luke D. Hurley, CWS, SSA  
Vice President  
Gove Environmental Services, Inc.



# Wetland Function-Value Evaluation Form

Total area of wetland: 28,915 sf      Human made? No      Is wetland part of a wildlife corridor? no      or a 'habitat island'?

Adjacent land use Commercial/Industrial      Distance to nearest roadway or other development 50 feet

Dominant wetland systems present PEM1E      Contiguous undeveloped buffer zone present no

Is the wetland a separate hydraulic system? No      If not, where does the wetland lie in the drainage basin? Lower

How many tributaries contribute to the wetland? 0      Wildlife & vegetation diversity/abundance (see attached list)

Wetland ID: 1,4  
 Latitude      Longitude  
 Prepared by: LDH      Date 1/7/16  
 Wetland Impact: 28,915  
 Type PEM1E      Area  
 Evaluation based on:  
 Office      Field X  
 Corps manual wetland delineation completed? Y X N

Function/Value	Occurrence Y/N	Rationale (Reference #)*	Principal Function/Value(s)	Comments
Groundwater Recharge/Discharge	Y	1,2,5,6,7,8,15,	Y	This wetland has some Groundwater Recharge/Discharge potential
Floodflow Alteration	Y	3,4,5,6,8,9,10,13,14,16,18	Y	This wetland has some Floodflow Alteration potential
Fish and Shellfish Habitat	N		N	
Sediment/Toxicant Retention	N	1,4	N	This wetland has some Sediment/Toxicant Retention potential
Nutrient Removal	Y	5,6,7,8,9,10,11,12,13	N	This wetland has some potential for Nutrient Removal, but only in small areas
Production Export	N		N	
Sediment/Shoreline Stabilization	N		N	This is not associated with a watercourse
Wildlife Habitat	N	7,8,18,21	N	
Recreation	N			
Educational/Scientific Value	N		N	This wetland has no scientific or educational value
Uniqueness/Heritage	N			
Visual Quality/Aesthetics	N		N	
Endangered Species Habitat	N			
Other				

Notes:

\*Refer to backup list of numbered considerations.

# Wetland Function-Value Evaluation Form

Total area of wetland: 24,759 sf      Human made? No      Is wetland part of a wildlife corridor? no      or a 'habitat island'?

Adjacent land use Commercial/Industrial      Distance to nearest roadway or other development 50 feet

Dominant wetland systems present PEM1E      Contiguous undeveloped buffer zone present no

Is the wetland a separate hydraulic system? No      If not, where does the wetland lie in the drainage basin? Lower

How many tributaries contribute to the wetland? 0      Wildlife & vegetation diversity/abundance (see attached list)

Wetland ID: 2,3,5

Latitude      Longitude

Prepared by: LDH      Date 1/7/16

Wetland Impact: 26,640

Type PEM1E      Area

Evaluation based on:

Office      Field X



Corps manual wetland delineation completed? Y X N

Function/Value	Occurrence Y/N	Rationale (Reference #)*	Principal Function/Value(s)	Comments
Groundwater Recharge/Discharge	Y	1,2,5,6,7,8,15,	Y	This wetland has some Groundwater Recharge/Discharge potential
Floodflow Alteration	Y	3,4,5,6,8,9,10,13,14,16,18	Y	This wetland has some Floodflow Alteration potential
Fish and Shellfish Habitat	N		N	
Sediment/Toxicant Retention	N	1,4	N	This wetland has little Sediment/Toxicant Retention potential
Nutrient Removal	Y	5,6,7,8,9,10,11,12,13	N	This wetland has some potential for Nutrient Removal, but only in small areas
Production Export	N		N	
Sediment/Shoreline Stabilization	N		N	This is not associated with a watercourse
Wildlife Habitat	N		N	
Recreation	N			
Educational/Scientific Value	N		N	This wetland has no scientific or educational value
Uniqueness/Heritage	N			
Visual Quality/Aesthetics	N		N	
Endangered Species Habitat	N			
Other				

Notes:

\*Refer to backup list of numbered considerations.





# LONZA BIOLOGICS - PROPOSED INDUSTRIAL DEVELOPMENT PORTSMOUTH, NEW HAMPSHIRE





1992 AERIAL PHOTOGRAPH - LONZA BIOLOGICS  
PORTSMOUTH, NEW HAMPSHIRE

SCALE IN FEET  
0 80' 160'  
GRAPHIC SCALE



**Tighe & Bond**  
Consulting Engineers

July 1, 2016  
L-0700-10 SITE.dwg



# The Restoration of Hodgson Brook at the Iron Rail Parcel at Pease Tradeport in Portsmouth, NH

---

28 May 2018

*The benefits of stream restoration*

*Collecting and processing reference data*

*Design metrics for the stream and floodplain using natural channel design*

*Construction sequencing*

*Planting plan for the floodplain and riparian corridor*

*Five year monitoring plan and methods*



Streamworks, PLLC

Joel Ballestero

Thomas P. Ballestero

## The Benefits of Stream Restoration

The benefits to stream restoration are numerous to an ecosystem, especially so when land that had been developed into an urban area is reconstructed and allowed to grow more naturally again. This is the case throughout the history of Hodgson Brook, a stream whose watershed has been almost entirely developed. The watershed for the stream begins at the Pease Tradeport in Newington (though most of the watershed, including the site, is in Portsmouth), and ends in the tidal waters of North Mill Pond in Portsmouth. At the project site and upstream, other than flowing through open drainage ditches and some wetlands, the stream is buried through a network of pipes that carry water flowing directly off impervious surfaces. This system prevents precipitation from filtering into the ground and recharging the groundwater table, a process which otherwise would filter the water from the urban contaminants it collects along its path. With the reduction of water lost into the ground, the amount that ends up directly in the waterway is increased, and commonly, the time it spends in a healthier environment is reduced. The time the water does spend in open channels, is spent under a lack of natural cover where it warms due to a lack of shade and a lack of cooler groundwater inflows that recharge the base flow, and moderate biogeochemical processes. The drainage ditch that is now Hodgson Brook is also poor habitat, lacking a diversity of flora and fauna that exist in a more natural setting.

This project proposes to daylight a section (~1,000 feet along the valley, ~1,200 feet of stream) of Hodgson Brook where it currently lies buried in a 4.5-foot diameter culvert before exiting the project site into a drainage ditch; this stream restoration will result in approximately 42,500 sf of stream and riparian buffer being created.

Daylighting the stream will restore a more natural riffle-pool sequence to a system that when it is presently in the open, is unnaturally straight, having been relocated and straightened to make way for development. The new stream corridor will provide an opportunity for storm flows to enter into the channel and adjacent floodplain, providing a connection for water to reenter and filter into the ground, in addition to being filtered and used by vegetation. The stream and corridor are hydraulically rougher and longer than the existing pipe, and will create a slower travel time over the same valley distance, in addition to increased storage volume. The corridor will benefit from native, riparian vegetation that will be allowed to grow unmaintained, encouraging wildlife use, nutrient/pollutant removal, and shade to keep the water cool. The habitat will help filter out common pollutants such as nitrogen and phosphorous, all while reducing the amount of contaminated water that enters North Mill Pond. Obviously this is one piece of a greater system between the Tradeport and North Mill Pond, therefore while the benefits of this specific project are very high, it should be recognized that there are other impairments along the watershed also in need of attention.

The restoration work will provide a reconnection for a portion of a watercourse that has been heavily altered in the past, and hopefully provide an example of how a stream corridor may be restored in an urban environment and serve as a reference for the future.

## Collecting and Processing Existing Data

Natural Channel Design involves obtaining metrics that are measured on natural, healthy systems (reference stream) which are then employed to serve as a template for the design metrics to the impaired watercourse, as long as the watersheds and streams have similar properties. It is not uncommon for this reference stream section to exist in healthy sections of the same stream, or at sections of adjacent streams. In the case of Hodgson Brook, unfortunately there is no existing healthy/natural/undeveloped section to observe, as most of the stream and its watershed exhibit significant urbanization and lack of stormwater management. There also exist few nearby streams that meet the criteria of being healthy, natural, and relatively unaltered that also share similar watershed characteristics; arguably, there exist few healthy, natural, and relatively unaltered streams anywhere that have highly impervious watersheds and little vegetation with such low stream slopes and are located near the New Hampshire coast. Simply put, there aren't many healthy streams (to say nothing of natural) that exist in an urban environment. In this case, the stream should aim to mimic its historic, natural system as best as possible while accounting for the upstream watershed conditions.

Luckily, there exists a relative wealth of information that has already been collected about the history of the Hodgson Brook watershed, the development over the years, how it exists now, and goals for restoring it. A 2004 restoration plan for Hodgson Brook was prepared by D. B. Truslow Associates with cooperation from the Hodgson Brook Local Advisory Committee, with funding provided by NHDES. This publication (among others) is available online at the DES' website for the watershed<sup>1</sup>. The publication contains much information about the history of the watershed, which provides a good place to start in order to find a relevant reference reach.

After reading the report, two sites were identified as having been restored at Pease – Grafton Ditch and Railroad Brook. Upon investigation of the two sites, and taking some brief measurements, neither site was suitable for use as a reference reach for Hodgson Brook. Stream form measurements were taken on Hodgson Brook, immediately at the outlet from the Iron Rail Parcel – where the stream is in no way natural or healthy, but years of flowing through the drainage ditch there has allowed the confined brook to erode some of the banks, and establish some plan form geometry, and can provide metrics on what the channel is able to pass currently. Classification of this section of stream, and the parameters used for evaluating the classification, may be seen in Table 2 below. The pipe system through the site was also surveyed, which provided the controlling upstream and downstream elevation, as well as the valley length.

Knowing the valley slope, the historic properties of the watershed, and approximate metrics from the regional geomorphic curves developed for New Hampshire, a dozen or so reference reaches were walked and visually assessed around the seacoast area. The most representative of all the reference reaches, Hutchins Creek in Kittery (43.106989°N, 70.705805°W), was then surveyed for plan form, cross sections, profile, and geomorphic properties. Overall, a 150-foot section of Hutchins Creek was surveyed (channel and floodplain). Planform geometry was collected for seven riffle-pool sequences over four

---

<sup>1</sup> The website is located at: <https://www.des.nh.gov/organization/divisions/water/wmb/was/hodgson/index.htm>

meander wavelengths along the valley. Profiles of the thalweg, top of bank, bankfull, and water surface elevation were all collected. A total of 11 cross sections (7 riffles and 4 pools) were taken at locations where bankfull indicators were evident, and for each section all stream and floodplain widths, depths, and ratios were extracted and calculated. Of those, the sections were weighted according to which appeared to be the healthiest and most stable in the field.

The parameters for the Hodgson Brook and Hutchins Creek watersheds may be found in Table 1, and the geomorphic metrics for the profile, cross section, and planform of Hutchins Creek in Table 3 and Lower Hodgson Brook in Table 2b. Select values from the observed particle size distribution (done by pebble counts) for Lower Hodgson Brook may be found in Table 2a – with a plot of the data found in Figure 1. Additionally, planform and cross sectional definitions are shown on pages A1 and A2 of the Appendix, for reference.

Table 1 - Watershed Properties				
Property	Code	Units	Lower Hodgson Brook	Hutchins Creek
Drainage Area	DA	mi <sup>2</sup>	0.32	0.4
2-yr Peak Flow	Q2	cfs	6.80	6.46
5-Yr Peak Flow	Q5	cfs	11.1	14.332
10-yr Peak Flow	Q10	cfs	15.5	18.359
25-yr Peak Flow	Q25	cfs	24.0	24.008
50-yr Peak Flow	Q50	cfs	38.2	28.463
100-yr Peak Flow	Q100	cfs	53.0	33.409
Pipe/Valley Slope	S	ft/ft	0.01057	0.00176

Table 2a - Particle Size Results Pebble Counts at Lower Hodgson Brook		
Particle	Size (mm)	Size (in)
D10	0.19	0.007
D50	0.38	0.015
D80	1.5	0.059
D90	7	0.276
D95	14	0.551



**Figure 1 - PSD for Lower Hodgson Brook**




Table 2b - Lower Hodgson Brook Reference Reach Data							
Characteristic		Code	Units	Lower Hodgson Brook Observations			
				1	2	3	4
Profile	Stream Slope	S	ft/ft	0.00316			
	Valley Slope	V <sub>s</sub>	ft/ft	0.00565			
	Sinuosity	k		1.072			
	Pool Length	L <sub>p</sub>	ft	9.2	5.3	20.6	10.6
	Pool to Pool Spacing	P-P	ft	18.7	11.1	22.6	37.6
Cross Section	Bankfull Width	W <sub>bkf</sub>	ft	5.76	4.60	3.69	5.54
	Floodprone Width	W <sub>fp</sub>	ft	7.03	9.35	6.26	9.67
	Maximum Bankfull Depth	D <sub>max</sub>	ft	0.89	0.76	0.62	0.80
	Average Bankfull Depth	D <sub>avg</sub>	ft	0.55	0.44	0.51	0.40
	Entrenchment Ratio	ER	ft/ft	1.21882	2.03221	1.69578	1.74704
	Width to Depth Ratio	W/D	ft/ft	10.4979	10.486	7.21621	13.8066
Plan Form	Radius of Curvature	R <sub>c</sub>	ft	40.66	15.81	22.41	8.93
	Arc Length		ft				
	Average Bankfull Width	W <sub>bkf</sub>	ft	5.8	5.5	5	4.6
	Rc:Wbkf Ratio		ft/ft	7.01	2.87	4.48	1.94
	Meander Belt Width	MBW	ft	13.1	16.9	14.7	
	Average Bankfull Width	W <sub>bkf</sub>	ft	4.6	5	5.8	
	MBW/Wbkf		ft/ft	2.85	3.38	2.53	
	Meander Length	ML	ft	56.04	56.53	46.32	
	Average Bankfull Width	W <sub>bkf</sub>	ft	5.8	5	4.6	
ML/Wbkf		ft/ft	9.66	11.31	10.07		
Classification	Entrenchment Ratio	ER	ft/ft	1.21882	2.03221	1.69578	1.74704
	Width to Depth Ratio	W/D	ft/ft	10.4979	10.486	7.21621	13.8066
	Sinuosity	k		1.072	1.072	1.072	1.072
	Stream Slope	S	ft/ft	0.00316	0.00316	0.00316	0.00316
	Bed Material	-	-	Sand	Sand	Sand	Sand
	Classification	-	-	G5c	B5c	G5c	G5c

Table 3 - Hutchins Creek Reference Reach Data

Characteristic	Code	Units	Hutchins Creek Observations											
			1	2	3	4	5	6	7	8	9	10	11	
Profile	Stream Slope	S	ft/ft	0.00165										
	Valley Slope	V <sub>s</sub>	ft/ft	0.00176										
	Sinuosity	k		1.20										
	Pool Length	L <sub>p</sub>	ft	10.9	7.3	1.4	9.8	11.5	10.3	3.7				
	Pool to Pool Spacing	P-P	ft	24.4	13.5	14.6	15.1	15.1	21					
Cross Section	Bankfull Width	W <sub>bkf</sub>	ft	7	6.5	6.5	5	5	7	5.5	5.5	6	5.5	5.0
	Floodprone Width	W <sub>fp</sub>	ft	25	18	20	30	20	30	20	20	25	39.1	37.8
	Maximum Bankfull Depth	D <sub>max</sub>	ft	0.68	0.62	0.55	0.65	0.58	0.96	0.87	0.65	0.64	0.69	0.74
	Average Bankfull Depth	D <sub>avg</sub>	ft	0.476	0.434	0.385	0.455	0.406	0.672	0.609	0.455	0.448	0.38	0.48
	Entrenchment Ratio	ER	ft/ft	3.57	2.77	3.08	6.00	4.00	4.29	3.64	3.64	4.17	7.11	7.60
	Width to Depth Ratio	W/D	ft/ft	14.71	14.98	16.88	10.99	12.32	10.42	9.03	12.09	13.39	14.42	10.38
Plan Form	Radius of Curvature	R <sub>c</sub>	ft	11.8	7.6	8.3	9.6	7.6	15.3	3.7	13.6			
	Arc Length		ft	16.3	7.0	10.1	11.6	8.1	13.6	7.4	12.0			
	Average Bankfull Width	W <sub>bkf</sub>	ft	4.8	4.0	4.0	4.6	3.3	3.8	3.4	5.0			
	Rc:Wbkf Ratio		ft/ft	2.48	1.91	2.07	2.08	2.33	4.02	1.10	2.72			
	Meander Belt Width	MBW	ft	14.5	13.5	10.0	10.5	9.0	17.0					
	Average Bankfull Width	W <sub>bkf</sub>	ft	5.0	4.5	4.5	4.0	4.0	5.0					
	MBW/Wbkf		ft/ft	2.90	3.00	2.22	2.63	2.25	3.40					
	Meander Length	ML	ft	40.1	23.8	27.2	30.4	30.3	36.0					
	Average Bankfull Width	W <sub>bkf</sub>	ft	5.0	4.5	4.5	4.0	4.0	5.0					
ML/Wbkf		ft/ft	8.02	5.28	6.04	7.59	7.57	7.20						

## Design Metrics for Stream and Floodplain Using Natural Channel Design

The natural channel design process uses the collected reference reach data to develop proposed metrics to create a design which is controlled by site constraints (usually things like incoming flows, upstream and downstream invert elevations, valley width, sediment supply, etc.). The site constraints control selected design metrics, which then are used to calculate – often quite iteratively – the remaining metrics within a range, determined by the reference reach data. The constraints at the project site include the stream inverts at the start and end, the valley width, the watershed properties, and the flows incoming to the site. The most difficult of all the constraints to calculate for this project were the flows incoming to the site. Upstream of the site, the watershed is extremely developed, and in order to calculate flows using common methods (Rational Method, SCS Curve Number Method, regression equations, etc.), a full watershed model would have been necessary. Such a model could have been developed, but the output may not have been very applicable to determining channel-forming flows. The dominant channel-forming flow is referred to as the bankfull flow, and for undeveloped watersheds is commonly in the range of the 1.5 to 2 year peak flow. However, this is just an approximation, and is not globally true for all watersheds and streams. The actual channel-forming flow may have a more or less common return period, and that is the flow to which the channel should be designed.

In order to appropriately estimate what this flow might be, a more site-specific method was used. Immediately downstream of the site, Hodgson Brook has – for decades – existed in an overly deep drainage ditch with no access to a floodplain. Over those years, it has eroded the banks during larger flows, and created some observable bankfull indicators. Using the survey data taken at this location, with specific data taken at bankfull locations, flows could be calculated to estimate what the channel-forming and larger flows likely would be. The flows that formed the more natural sections of the unnatural drainage ditch may be assumed to be the same as what would flow in Hodgson Brook at the site. The return period of these flows were not estimated; rather, the flows which caused bankfull indicators were called the bankfull flows. In theory, the bankfull flow is the flow at which sediment is transported most efficiently; or the discharge at which channel maintenance is most effective. This happens in healthy streams, on average, around the 1.5- to 2-yr flow. For the stream and watershed at the site – the watershed being highly impervious, and lacking a consistent sediment supply – the rate of return of the bankfull flow would be much harder to state in terms of return period. This is why the use of indicators downstream of the site, coupled with the survey of those indicators and the stream, was determined the best way to account for the bankfull flow. These calculated bankfull flows may be found in Table 1. Similarly, the maximum flow – though there is no return period placed on it – can be determined by the constraining factors of the stream system upstream of the restoration. The proposed pipe diameter, material, and slope were used to assume inlet control (no effect of the stream system on the pipe's ability to move water), and calculate the maximum amount of water which may be seen in the system. A quick Manning's Equation check showed that that flow would not overtop the stream corridor valley walls. Regardless of when this flow or any other flow higher than the bankfull overtop the stream banks, the goal of the design metrics were to use as much floodplain as possible, allowing the

flows to interact with the floodplain as frequently as they will, while containing the bankfull flow (regardless of return period).

Knowing all the constraints at the site, the metrics controlled by the constraints were calculated, and the remaining design metrics were iteratively determined to conform to the flows as best as possible. The calculated metrics and constraining variables may be found in Table 4. These proposed metrics were given as a guide for design – they don't have to be followed exactly, but should be near to or within the range of values shown in the table. They are dependent on the controlling factors, such as inlet and outlet inverts, which may adjust the values within the ranges shown (or, if outside the ranges, the metrics may be adjusted based off the ratios shown: entrenchment ratio, width to depth ratio, poo

In addition to the designed stream metrics, several other site-specific factors are important to consider, and should be accounted for in the design. Due to the highly developed nature of the watershed, the sediment supply to the site will be quite limited. There is not much of a source of sediment, other than construction activities and sanding during the winter. Thus, the sediment supply is sure to be of a much finer gradation and in much more limited supply than the natural stream used to have. Because of this, vegetation will be very important to maintaining the stream structure, and the sediment gradation used for construction will need to be sized and mixed well to prevent against vertical erosion of the restored stream. In addition to the vegetation and sediment, in-stream structures (log cross vanes) are recommended to help keep the stream in place, and floodplain sills are recommended to help prevent against avulsion. To help the stream keep its form while vegetation is allowed to grow, the banks may be constructed out of biodegradable compost sock. These usually have a lifespan of 3-5 years before they begin to degrade, which should allow enough growing seasons for faster growing riparian vegetation and plants to take root and hold the stream form. Please refer to Figure 2 for a better idea of how these banks are to be used, and what one such project looks like four years after construction. These coir log banks should also provide stability, and help prevent against any avulsions, though the floodplain and channel should be able to handle them on their own.

Some of the design metrics may be seen on pages A3 and A4 of the Appendix, for reference of what part of the stream they apply to, and their values. A more complete table of the proposed metrics may be found on pages A15 and A16 Conceptual details for constructing a log cross vane and a floodplain sill may also be found in the Appendix, on pages A5 and A6.



**Figure 2 - Coir Log Rolls along Restored Pettee Brook, near Adams Towers on UNH Campus in Durham, four years after construction. Note how the coir logs are still intact, and have trapped sediment. Roots and grasses have grown into and through them.**



Table 4 – Hodgson Brook Proposed Stream Metrics and Ranges					
Property		Code	Units	Value	Range (+/-)
Cross Section	Maximum Bankfull Depth	Dmax	ft	0.75	0.1
	Average Bankfull Depth	Davg	ft	0.50	0.1
	Floodprone Depth	Dfp	ft	1.50	0.2
	Bankfull Width	Wbkf	ft	5.5	0.5
	Floodprone Width	Wfp	ft	30.0	2
	Width/Depth Ratio	W/D	-	11.0	1.3
	Entrenchment Ratio	ER	-	5.5	0.1
	Bankfull Area	Abkf	sqft	2.75	0.8
Plan Form	Sinuosity	k	-	1.23	0.05
	Meander Belt Width	MBW	ft	18.0	2
	Meander Length	ML	ft	40.0	5
	Radius of Curvature	Rc	ft	12.5	2.5
	Pool Length	Lp	ft	16.2	4
	Pool to Pool Spacing	P2P	ft	24.5	4.5
	Stream Slope	Slope	ft/ft	0.00946	0.0020
	Valley Slope	VS	ft/ft	0.01160	0.0010
Flow	Low Flow	Qlf	cfs	0.2	0.1
	Bankfull Flow	Q	cfs	6.9	0.4
	Floodprone Flow	Qfp	cfs	32	2
Stable Particle Size	Low Flow - Rosgen	RDlf	in	0.7	-
	Bankfull - Rosgen	RDbkf	in	2.5	-
	Floodprone - Rosgen	RDfp	in	2.8	-
	Full Flow - Rosgen	RD100	in	5.7	-
	Low Flow - LWM	LDlf	in	0.2	-
	Bankfull - LWM	LDbkf	in	0.9	-
	Floodprone - LWM	LDfp	in	1.1	-
	Full Flow - LWM	LD100	in	2.9	-
	Low Flow	LDlf	in	0.4	0.3
	Bankfull	LDbkf	in	1.7	0.8
	Floodprone	LDfp	in	1.9	0.9
	Full Flow	LD100	in	4.3	1.4

## Construction Sequencing

In general, stream restoration begins at the upstream end of the project and works downstream. At the site, the proposed stream corridor does not follow the path of the existing piping carrying Hodgson Brook, but will be reconnected to the infrastructure at the start and end of the project. This is beneficial, as the stream can be constructed in the dry and temporarily stabilized before being opened up to flows and fully vegetated. As this is a part of a larger development project as a whole, the construction sequence below details only activities pertaining to the stream corridor. It does not include activities that might usually be included in such a sequence, such as (but not limited to) clearing and grubbing, construction layout, traffic control, erosion control, and material disposal. The sequence is subject to change to integrate fluidly with the entire project, and may change to the desires of the contractor, as they see best fit. Any changes shall be discussed, cleared, and/or proposed by project engineers, and may be made in the field during construction. This construction sequence assumes that the existing drainage infrastructure is to remain in place until the stream is built, and that proposed drainage infrastructure that will direct flows into the stream will have already been installed. An overview of the sequence is listed below, followed by a detailed sequence which describes each step in greater detail.

### *Stream Corridor Construction Sequence Overview:*

1. Excavate and grade the stream corridor from the top of the valley, down to the top of the floodplain, and on down towards the center of the corridor.
2. Perform fine grading of stream channel, banks, structures, and sills.
3. Seed the site with temporary stabilization and allow to grow.
4. Open up stream at each end to flows.
5. Seed and plant the site fully.
6. Establish monitoring locations and components.

### *Detailed Stream Corridor Construction Sequence:*

1. Excavate and grade the stream corridor, from the top of the valley, down to the top of the floodplain and into the center of the corridor, leaving an access ramp at the start and end of the project. If required, the grade may be set lower to allow for backfilling of loam, should the existing earth be of poor material. Do not over-compact floodplain or valley slopes; compact only by track-walking or applying pressure with the bucket of the excavator. The floodplain and slopes should be left rough, to allow seed to grow more easily. Leave an access path along the top of the valley to one or both sides, to allow for the transport and temporary staging of in-stream materials and movement of heavy equipment. This may also be done by using the upstream access ramp to deliver materials behind the excavator, using the corridor as the path. This is not preferred, since over-compaction is likely to occur resulting from the excessive use.
2. Because the construction will be performed in the dry, construction will start at the downstream end of the restored Hodgson Brook. Starting at the downstream end of the stream, begin by excavating the pool which will redirect water into the existing culverts below Goose Bay Drive from upstream of the pool. Working from upstream of the section under construction, begin the fine grading of the stream channel. This may be done by over-excavating the channel and banks,

then installing the compost log roll stream banks. Initially the bed slope of the stream is graded uniform, and then riffles and pools graded near the finishing steps. The lower compost log should sit below the thalweg of the stream, and once set in place at the correct elevation, may have fill placed behind the rolls. The stream channel should then be backfilled at the riffles and pools with appropriately graded material, leaving the pools as deeper features in the stream channel. As construction continues upstream, merging the compost log rolls should be done such that the upstream-most end of the rolls is curled out from the bank, such that the next upstream rolls may be placed linearly into the bank, and flows will be directed as to not cause erosion or avulsion between the rolls (shiplapped construction). Extra heavy attachment (connections) of the rolls at these locations should be performed with biodegradable materials. While construction continues, backfilling of any floodplain loam – should it be deemed necessary – should be performed to the final grade of the floodplain. Construct in-stream structures (log cross vanes) as they are reached, as well as floodplain sills. Additional floodplain features may be constructed at this time, such as habitat logs and boulders, tree stands, and vernal pools (all optional, but recommended). Construction materials may be provided on-demand using the access path along the top of the valley. Materials (logs, rebar, geotextile, riffle material, compost rolls, etc.) may be set outside the stream corridor, and gathered by the excavator from inside the corridor, or less preferably, placed behind the excavator in the corridor. All fine grading and structures should be checked for elevations and geomorphic metrics before starting the next upstream section.

3. Seed and mulch the corridor and top of valley with the temporary stabilization seed mix (preferably a conservation mix with at least 10% wildflower seeds, though may be of a perennial ryegrass). Seed to the amounts as specified by the seed manufacturer – with greater application on the steeper valley slopes – and mulch with wood chips (90% ground coverage) or straw (to a depth of 1 inch). Water as specified by the seed manufacturer, if drought persists longer than the recommended watering rate. Allow the grass to grow to a height of 2 inches before proceeding to the next step. If any bare patches exist, reseed and mulch to ensure stabilization. This step may be performed as a section of stream is constructed, which may reduce the overall construction duration, though it may come at a cost of increased watering effort.
4. When all previous steps have been completed, the stream should be opened up to flows. First, the existing drainage culvert at the downstream end should be excavated and removed. Grade and temporarily stabilize the incoming flows to the downstream pool. Proceed to the inlet to the stream and construct (if not already done in step 2) the inlet pool and grading. Flows may then be directed into the stream channel, in a manner that shall be determined in the field, based on the manner in which the incoming culvert and upstream infrastructure is being constructed. Allowing incoming flows to the stream may be performed concurrently with that of the outlet, provided the contractor has the labor and equipment available. However, caution should be exercised to ensure that flows are able to exit the corridor fully and appropriately, to prevent damage and/or flooding to the site.
5. With the stream now carrying flows, the entire site should be seeded and planted as specified in the planting plan. This may be done completely or partially as construction of the stream takes place. At this point the temporary stabilization grass should have taken hold enough to provide

some cover for seeds, and keep in moisture during the day. This step should only be done during a growing season and not in mid-summer or winter, to help ensure planting success. This step may be done after step 6, if construction ends before a planting season is set to begin. This step should be performed when the appropriate equipment is available. This may help expedite the process, rather than performing it all completely by hand.

6. Finally, monitoring devices and components should be installed, measurements recorded, and instruments calibrated as necessary. Please refer to the monitoring plan section of this report for more details on the monitoring methods and schedules.

As noted in the detailed construction sequencing, some aspects of construction may overlap, or may be done concurrently, per the desires of the contractor. For example, backfilling of loam may be reserved for after the stream has been constructed, if it is desired to be performed from the top of the valley. Planting of livestakes and other riparian plants may be done as the stream is constructed. This may require watering to be performed regularly, especially lower on the floodplain, to ensure the vegetation has enough water to grow without any baseflow in the stream. It may also require longer stagnant time for the plants, which would have to be kept healthy during the duration of the construction. More detailed information and planting notes may be found in the following section. Habitat features (floodplain boulders, logs, vernal pools, etc.) may be constructed after the stream is finished, from the top of the valley. As stated before, any alterations to the construction sequence will first be cleared by the project engineers before implementing them during construction.

## Planting Plan for the Floodplain and Riparian Corridor

The stream corridor has two distinct zones for planting: the floodplain (Zone 1) and the upland, or valley slopes (Zone 2). These two zones are set as such, based on the available water, rate of inundation, and the drain rate. The two zones were broken down even further, with each zone having a Lower and an Upper part (1L, 1U; 2L, 2U). Furthermore, Zone 1L contains an additional sub-zone that refers to the stream banks, just up onto the top of the banks. Here, grasses and groundcover is often not successful, but shrubs may, and these are to be planted differently than the rest of Zone 1L, resulting in its own classification. This sub-zone contains two sections, one along the outer bank of each bend, and the other containing all the other banks (inner bend and riffles). The outer bank of each pool is referred to as Zone 1Lp, and the other banks are in Zone 1Lb. The difference in the two zones is only to differentiate between planting densities, and to help determine quantities.

	Planting Species	Common Name	Zone
Grasses	<i>Lolium Perenne</i>	Perennial Ryegrass	1, 2
	<i>Cornus canadensis</i>	Bunchberry	1U
	<i>Solidago spp.</i>	Goldenrod	1
	<i>Impatiens capensis</i>	Jewelweed	1
	<i>Mitchella repens</i>	Partridgeberry	1U, 2
	<i>Asclepias incarnata</i>	Swamp Milkweed	1
	<i>Thalictrum polygamum</i>	Tall Meadow Rue	1
Shrubs	<i>Prunus virginiana</i>	Chokecherry	1U, 2
	<i>Cornus racemosa</i>	Gray Dogwood	1U, 2
	<i>Viburnum alnifolium</i>	Hobblebush	1
	<i>Vaccinium angustifolium</i>	Lowbush Blueberry	2
	<i>Salix discolor</i>	Pussy Willow	1
	<i>Rubus idaeus</i>	Raspberry	2
	<i>Cornus stolonifera</i>	Red Osier Dogwood	1
	<i>Cornus amomum</i>	Silky Dogwood	1
	<i>Alnus rugosa</i>	Speckled Alder	1
<i>Hammamelis virginiana</i>	Witch Hazel	1	
Trees	<i>Salix nigra</i>	Black Willow	2U
	<i>Prunus serotina</i>	Black Cherry	2U
	<i>Acer rubrum</i>	Red Maple	2U
	<i>Quercus alba</i>	White Oak	2U
	<i>Fraxinus americana</i>	White Ash	2U

The species selected for the project are listed in Table 5, and are sorted by the type of species – grasses and ground cover, bush-like trees and shrubs, and trees. Each species is listed by both their common name and Latin name, as well as the zone at which it is to be planted. The zone for each may be listed specifically (1L), or more broadly (2). These species were selected from the list of Native Shoreland/Riparian Buffer Plantings for New Hampshire; a table species which are both native and non-

invasive, which was published by the NH Department of Environmental Services. While this list provides many species, the final species used in construction of the site may not be limited to those listed. Any other species will be checked and approved by the engineer before being ordered, or placed in the field. This is especially true of any seed mix that may be used at the site; the selected mix (mixes) that the contractor shall use should be checked by the engineer before placement, or before ordering any such seed mix.

A list of densities and species to be planted in each zone may be found in Table 6, for quick reference.

Table 6 – Planting Plan Details			
Planting Zone	Zone Description	Species	Density
1Lp	On the outer bend of a pool from the point of curvature to the point of tangency, beginning at the mid-bank elevation, up over the top of the bank, and offset from the top of the bank 1 foot.	Livestakes of Pussy Willow, Red Dogwood, Silky Dogwood, and Speckled Alder	2 livestakes per 1 sf
1Lb	From the mid-bank elevation up over the top of the bank and back 1 foot, for all stream banks other than Zone 1Lp	Livestakes of Pussy Willow, Red Dogwood, Silky Dogwood, and Speckled Alder	1 livestake per 2 sf
1L	From one outer bend of the channel down one meander wavelength to the next outer bend of the channel, inwards along the top of the bank.	Perennial Rye (temporary stabilization); Native Wetland Seed Mix including but not limited to: Tall Meadow Rue, Goldenrod, Swamp Milkweed, Jewelweed, and Ryegrass; Hobblebush, Pussy Willow, Red Dogwood, Silky Dogwood, Speckled Alder, and Witch Hazel	Rye: per seed mix Wetland Mix: per seed mix Shrubs: 1 plant per 75 sf
1U	On the floodplain bench, outside the meander belt width corridor, up to the top of the floodplain bench	Perennial Rye (temporary stabilization); Native Wetland Seed Mix (as described previously); Bunchberry, Partridgeberry, Swamp Milkweed, Chokecherry, Gray Dogwood, Hobblebush, Pussy Willow, Witch Hazel	Rye: per seed mix Wetland Mix: per seed mix Shrubs: 1 plant per 50 sf
2L	From the top of the floodplain bench, up 1/4 of the way up the riparian corridor slope	Perennial Rye (temporary stabilization); Native Conservation Seed Mix; Partridgeberry, Chokecherry, Gray Dogwood, Lowbush Blueberry, Raspberry, Black Willow	Rye: per seed mix Shrubs: 1 plant per 20 lf
2U	From the top of Zone 2L, up over the top of the riparian corridor and back 1 foot.	Perennial Rye (temporary stabilization); Native Conservation Seed Mix; Lowbush Blueberry, Raspberry; Black Willow, Black Cherry, Red Maple, White Oak, White Ash	Rye: per seed mix Shrubs: 1 plant per 25 lf Trees: 1 tree per 40 lf



Vegetating the project site will be done using several types of planting methods. Closest to the stream, livestakes should be placed, rather than planting full shrubs. Livestakes are relatively straight clippings two to four feet in length and no greater than an inch in diameter at the base, cut from live and healthy species, and should be cleared from leaves and smaller branches. Leaves left on the livestake cause it to dry out more easily. From places where branches and buds are removed, roots and new branches will sprout from the clipping. Livestakes should be soaked in water for at least two days prior to installation, if at all possible, long enough for roots to sprout. To plant a livestake, first create a hole using a sledge hammer and a hammer rod (a piece of 1" diameter rebar works as well), to a depth of one third the length of the livestake. Gently place the livestake in the hole without damaging the base, and tamp-down the ground around the hole with a hand or foot. Livestakes should be kept wet for the first two weeks, until they have had the opportunity to sprout roots.

Seed will also be placed and mulched as described following, all along the floodplain and upland slopes. Seeding will first be done with a rye grass to stabilize any bare earth expected to exist longer than 5 days. The floodplain may then be seeded with a wetland, riparian, or conservation seed mix that contains no invasive or non-native species. Seeding with such a mix should follow the manufacturer's guidelines. A general specification for the final seeding is a conservation mix with at least 10% wildflower seeds.

Finally, planting of trees and shrubs (and flowering plants, should no wetland/riparian seed mix be used) will be performed throughout the floodplain and upland areas. It is preferable to have mature plants over planting seeds, and more mature plants are preferred to saplings. Younger plants are more vulnerable to being transplanted, and do not recover well – if at all – from grazing. Again, trees and shrubs should be placed in their appropriate zones, and should be planted in a non-linear fashion.

To begin the planting, first the grounds should be checked for any invasives, or any debris/trash, and cleared. Seeding should occur over the entire construction area, and should begin with temporary stabilization. Stabilization should be of a Rye seed mix, which should be mulched with straw, preferably (to a depth of 1"). The mulch should be clean and free of invasives and any other contaminants. The grounds should be watered as necessary, or as specified by the seed manufacturer. At the same time, livestakes (if they were not already set during construction) may be placed in the stream banks and at the top of the banks.

After the grass has been allowed to grow, and any bare spots have been reseeded, planting and seeding of the remaining site may be performed, beginning at the lowest part of the floodplain, on up to the top of the valley slopes. Protective tubing may be desirable to help prevent any young plants from grazing before they reach a more adult size. Support stakes and twine may also be used, to help stabilize the plants until they develop larger root systems. Planting instructions for each plant should be followed, as some require more specific needs than others, and may even have different planting seasons when they should be installed. The instructions for each may be very important, as a survival rate of 75% within the first 3 years is commonly determined to be the goal of a restoration project in New Hampshire.

When performing the final planting, it is important to note that the densities shown are for an average over the corridor, and to help determine quantities. Plantings should be performed in a non-linear (irregular) fashion, and should avoid being homogenous. Some areas should be more or less dense, with greater or fewer different species than other areas. Trees in the upland should be planted at the top of the valley, and partway down the slope; bushes may be clumped together near or far from the channel; livestock should be planted mid-bank and to the top of the bank. The zones and densities are shown for reference, but are not firm constraints. Natural systems are usually very diverse and random, and projects should attempt to embrace and mimic that variability. In addition to Tables 5 and 6, a list of the wildlife which benefit from the planting species, as well as the food value each species provide, may be found in Table A1, on pages A7 and A8 in the Appendix.

## Five Year Monitoring Plan and Methods

Hodgson Brook is the main source of fresh water to North Mill Pond in Portsmouth, and as such, the health of the stream is important to several local organizations (Advocates for the North Mill Pond [ANMP], Hodgson Brook Local Advisory Committee [HB LAC], Pease Development Authority [PDA]), and governments (city of Portsmouth, NH DES). There have been several studies completed on the watershed that are publicly available, and quite a few documents published that cover the history, water quality, and goals for restoring the watershed. Some of the publicly available documents include<sup>2</sup>: an Environmental Quality Characterization for Hodgson Brook in Portsmouth, New Hampshire (2003), a Watershed Restoration Plan for Hodgson Brook (2004), a Hodgson Brook Watershed Monitoring Plan – A guide for Monitoring Environmental Quality (2004), and an Implementation Plan for Hodgson Brook Watershed Restoration (2005). These documents provide detailed accounts of the history of the watershed, the current use and quality, and sets goals for restoring the watershed and methods to achieve those goals. The information provided in those documents was used to help develop the monitoring plan for the site. Monitoring of the site will be performed for five years after the construction of the project.

The NH DES lists water quality standards that provide a framework for assessing surface waters in the state, based on seven designated uses. The standards are divided into three parts: designated uses, water quality criteria, and antidegradation. The seven designated uses represent the ways in which the surface water is intended to be used: aquatic life, fish consumption, shellfish consumption, drinking water supply, primary contact recreation, secondary contact recreation, and wildlife. The water quality criteria are defined for each designated use by markers and limits, aimed at protecting each surface water use. Finally, the antidegradation provision is set to protect existing uses and to prevent any degradation to any surface water in terms of the existing water quality or designated uses.

Hodgson Brook (as detailed in the Watershed Monitoring Plan [WMP]), has been assigned three designated uses for which monitoring should be performed: Primary and Secondary Contact Recreation, and Aquatic Life. Indicators for each, and the recommended monitoring methods, were defined in the WMP, and are listed below. The methods and indicators below were cropped to eliminate indicators and methods that the report either did not recommend, or were considered not applicable. Also not included are some of the recommended monitoring methods that may not be applicable or may be included within other methods. Some of the monitoring frequencies have been adjusted in order to provide better data for a restoration project, and not existing conditions. In addition to the recommended monitoring methods given in the WMP, methods for monitoring the vegetation and stability of the constructed stream were developed. The full list of monitoring methods, schedules, and frequencies may be found in Table 7.

An annual monitoring report shall be produced and sent to all interested parties (ANMP, HB LAC, NH DES, etc.) and all data provided to NH DES for inclusion in the state databases at the same time. Please

---

<sup>2</sup> All four documents may be found at the DES website for Hodgson Brook:  
<https://www.des.nh.gov/organization/divisions/water/wmb/was/hodgson/reports.htm>

refer to state protocols for data reporting; different data may require different protocols. DES may also provide sampling kits and training for collecting select methods and indicators (1, 2, 3, 4, 5, and 10) through their Volunteer River Assessment Program (VRAP). The monitoring report should be produced annually in January or February, which gives enough time to process all the data collected during the previous year, and is after any sampling, vegetation monitoring, or surveying is likely to be done.

Table 7 - Iron Rail Parcel Restoration Monitoring Methods and Scheduling						
Indicator Number	Indicator	Monitoring Method	Events per Year	Number of Locations	Total Events	
Recreation	1	Bacteria	Minimum of 4 (2 dry and 2 wet) E. Coli samples collected annually between 6/1 and 9/15	4	2	40
	2	Various Indicators	During sampling dates, record water color and the presence of any of the following on the field data sheet: algal bloom, foam, debris, scum, slicks, odors, and surface floating solids	4	2	40
Aquatic Life	3	Dissolved Oxygen	Minimum of 4 (2 dry and 2 wet) measurements taken annually from 6/1 to 9/15 between 5:00 am and 8:00 am	4	2	40
	4	pH	Taken at the same schedule as DO	4	2	40
	5	Habitat Assessment	Complete using DES Habitat Assessment Field Data Sheets annually during late fall	1	1	5
	6	Flow	Monitor flow conditions to determine baseflow and stormwater discharge for a range of flows may be done concurrently with sampling events, or as required to obtain enough flows to develop a comprehensive rating curve	4	2	40
Additional Indicators	7	Stream Stability	Full site survey of all topographic features performed once as an as built, then again in years 3 and 5	1	1	3
	8	Planting Success	Visual site assessment for any high-mortality areas, assessment of 4 vegetation plots three times; once after the first full growing season, then every other year (may be done during full survey)	1	4	12
	9	Visual Health Assessment	Pictures taken at set photo points twice per year, during the spring and the fall	2	1	10
	10	Other Indicators (Temperature, Turbidity, Conductivity)	Taken at the same schedule as DO	4	2	40

In addition to the monitoring methods shown, per the request of DES and the local conservation commission, trash shall be removed from the stream and site as part of the scheduled maintenance for the landscaping at the site. If trash is observed during regular maintenance, it shall be removed and disposed of properly.

Monitoring locations for each of the methods listed in Table 7 should be determined either as construction is ongoing, or after completion. A map of suggested monitoring locations may be found on page A14 of the Appendix. Not all locations shown on the map are definite; many will be determined and set in the field, after construction is completed. For example, benchmarks and photo points will need to be located in locations with good viewing angles, and away from trafficked or maintained areas; staff gages (or monitoring probes) should be set in easily accessible locations, but in permanent water; vegetation plots should be set at areas of high interest, or in locations that represent a diverse range of variables (species, zones, sunlight, infrastructure, etc.), among other things. Detailed descriptions of the monitoring methods, recommended locations, and data are as follows:

### *Sampling*

Sampling is recommended at two locations at the parcel: first at the existing junction box, located where the stream first enters the parcel (access may be obtained via the manhole cover and into the large junction box); the second, at the downstream end of the project where the stream empties into a pool which routes the water under Goose Bay Drive. If the first location is considered too dangerous, or no permission is granted to enter the box, sampling may occur at the outlet of the 54" HDPE pipe directing Hodgson Brook into the proposed stream corridor. It is preferred to sample at the junction box, as the water there has not come into contact with any proposed infrastructure (LID stormwater outfalls, stream corridor). This would be very useful to compare the quality of the water before the project and after. Sampling during high flows may easily be performed from outside the junction box, using sampling rods with attached sample containers. On sampling days, samples should first be taken at the downstream location, then upstream to minimize possible sample disturbance contamination. Performing the sampling should be completed in one day, with as little difference in time and climatic conditions as possible. Concurrent sampling is recommended. All sampling should conform to DES VRAP protocols, unless not available, in which case they should follow any State or EPA guidelines.

Sampling will be performed in two manners, with another set of data being collected observationally. Sampling for bacteria (E. Coli) will be conducted by obtaining samples collected in the field, preserved for transport, and having samples analyzed at a lab, reported in counts per 100 mL. For fresh water, DES has a limit of 126 counts per mL for E. Coli. Sampling for other indicators (Dissolved Oxygen, pH, Temperature, Turbidity, and Conductivity) will be done using probes or meters which can detect each parameter. Kits containing these devices may be available through the DES' VRAP program, and training for using the kit and contents may be available as well. Observational data to be taken at the same time as the samples include the weather, as well as other indicators of stream health: water color, algal bloom, foam, debris, scum, slicks, odors, or surface floating solids. These can be noted and recorded along with all the other indicators – except for bacteria – on the sample Hodgson Brook Field Data

Sheets, seen on pages A12 and A13 in the Appendix. These data sheets were adjusted slightly from the data sheets given as part of the VRAP program.

In the Hodgson Brook WMP document, it is recommended that at least five samples are taken every other year (between 5/24 and 9/15 for E. Coli and 6/1 to 9/30 for all others) at locations defined in the paper. One of the locations is just downstream of the site, on the brook to the east of the intersection of Corporate Drive and Rye Street. This location has quite a bit of environmental monitoring data (EMD) available publicly from the DES' OneStop data server, dating from 2005 to 2016. Sampling for the monitoring of this project is recommended to be performed four times each year – twice during 'dry' weather, and twice during 'wet' weather. Dry weather sampling should occur on a day without precipitation the day of sampling as well as the three full days prior to the sampling date. Wet weather sampling should occur during or immediately after a storm with a precipitation depth of >0.2 inches, when flows are elevated from the baseflow. Sampling during wet and dry weather provides a comparison of the water quality during baseflow and storm events, may help identify sources of contamination, and will show the performance of the site. It is preferable that sampling of all metrics be done at the same time, and to make the timing more easily defined, all sampling should be done between the latest start date and earliest end date defined in the WMP; thus sampling should take place from 6/1 to 9/15 between the hours of 5:00 am and 8:00 am.

### *Observations and Visual Assessments*

Other data that will be taken at the site should assess the stream system health, and should include vegetation plots, photo points, habitat assessments, and flows. Photo points should be set after the construction has been completed, and should be marked at locations that can be repeated in subsequent years by both location and direction, so that pictures may be compared through the years. The photo points should capture the entire site, as well as any notable features, such as the vegetation plots, or any culvert inverts (to show scour, perhaps). Photo points should be taken twice per year, in the spring and fall, and should be included in the annual reports.

The habitat assessments will be performed using the Habitat Assessment Field Data Sheets for Low Gradient Streams. The assessment rates habitat parameters for health on a scale of 0 to 20, using descriptions to guide the assessor as to what to look for. The data should be compiled in the field, using any pictures as evidence and a field book for notes, and should be performed once each year in the fall, during a period of low flow. These sheets were obtained from the DES' VRAP website, and may be found reproduced here in the Appendix, on pages A9-A11.

Vegetation plots should be set after construction and the complete planting and seeding of the site has been completed, and should not be assessed until after one full growing season has passed. It is recommended that four vegetation plots be set, representing a thorough sample of variables; sunlight, planting zones, species density, etc. Two vegetation plots should span the width of the stream corridor, and two should be located in 10'x10' squares on the floodplain. These plots should be assessed for mortality of planted plants, coverage, invasives, and species diversity. In addition to the four plots, a site-wide visual assessment for the mortality of any of the planted plants should be conducted, tallied, and reported. A goal of 75% survival is usually recommended for projects of this type. The reason for the

mortality of any plants should also be recorded to the most accurate extent possible – water content, sunlight, trampling, foraging, animal burrowing, etc.

Finally, flows should be observed, recorded, or downloaded from pressure transducers during each of the sampling events, at a minimum. More data is recommended to help create an accurate rating curve for each location. It is recommended to have two flow locations at the same two sampling locations. To begin, theoretical hydraulic rating curves (water depth versus discharge) for each site should be developed. Over time, and with base flows and storm flows measurements, the curves may be more accurately empirically developed. Flow calibration should be performed at both sites for a range of flows, with a concentration of measurements at the low-flows. Calibration may be performed using a flow meter in the stream, or in a pipe, surveying a pipe and calculating the flow based on the flow depth, or by calibrated weirs or flumes that will give accurate flows, provided the water upstream has filled the reservoir created by the device. For each site, a minimum of 8 calibration flows are recommended for the empirical rating curve, and more points are encouraged. Early and frequent, accurate rating curve calibration will make the collection of this data go much more quickly in subsequent years.

### *Site Survey*

The final monitoring method will be to perform a full site topographic survey, making sure to include all relevant and important features, such as: benchmarks, sampling locations, staff gages, infrastructure, in-stream structures, stream and corridor features, floodplain features, photo points, and all topographic features. From this survey, maps should be produced that display all monitoring locations, comparisons of the stream features from year-to-year, and any other relevant information. Stream comparisons may include stream profiles, cross sections, as well as any notable failures. A full site survey should be conducted first as an as-built survey of the site, then again in years 3 and 5, following the completion of the project. The products built from the site surveys should be included in the annual reports, during the years they are performed.

## **Appendix**

*A1. Metric Definitions – Section*

*A2. Metric Definitions – Plan*

*A3. Planting Zones*

*A4. Proposed Stream Metrics – Section and Plan*

*A5. Generic Log Cross Vane Detail*

*A6. Generic Floodplain Sill Detail*

*A7. Table A1 – Associated Birds & Mammals, and Food Value of Planting Species*

*A8. Table A1 – Associated Birds & Mammals, and Food Value of Planting Species (Cont.)*

*A9. Habitat Assessment Field Data Sheet – Page 1*

*A10. Habitat Assessment Field Data Sheet – Page 2*

*A11. Habitat Assessment Field Data Sheet – Page 3*

*A12. Field Data Sheet – Page 1*


*A13. Field Data Sheet – Page 2*

*A14. Example Monitoring Locations*


*A15. Complete Table of Proposed Metrics*




# Metric Definitions - Section



# Metric Definitions - Plan




# Planting Zones




# Proposed Stream Metrics


## Section



## Plan



# GENERIC LOG CROSS VANE DETAILS



# GENERIC FLOODPLAIN SILL DETAILS




Table A1 – Associated Birds & Mammals, and Food Value	
Species	Wildlife and Food Value
Ryegrass	Temporary stabilization
Bunchberry	<u>Wildlife:</u> sharp-tailed grouse, spruce-grouse, moose <u>Food:</u> fruit, buds
Goldenrod	<u>Wildlife:</u> goldfinch, junco, ruffed grouse, swamp sparrow, butterflies and other insects, cottontail, meadow mice <u>Food:</u> seeds, nectar
Jewelweed	<u>Wildlife:</u> ring-necked pheasant, stuffed grouse, ruby-throated hummingbird, veery, butterflies and insects, white-footed mouse <u>Food:</u> nectar, seeds
Partridgeberry	<u>Wildlife:</u> grouse, mammals <u>Food:</u> berries
Swamp Milkweed	<u>Wildlife:</u> black duck, mallards, red-winged blackbird, ruby-throated hummingbird, monarch butterfly, other butterflies and insects, muskrat <u>Food:</u> nectar, seeds
Tall Meadow Rue	<u>Wildlife:</u> bees, butterflies <u>Food:</u> nectar
Chokecherry	<u>Wildlife:</u> bluebird, brown thrasher, catbird, crow, eastern kingbird, evening grosbeak, orioles, pileated woodpecker, ring-necked pheasant, robin, rose grosbeak, ruffed grouse, thrushes, yellow-bellied sapsucker, rabbit, squirrel <u>Food:</u> berries, buds, foliage
Gray Dogwood	<u>Wildlife:</u> blue jay, cardinal, catbird, cedar warwing, eastern kingbird, finch, flycatcher, grosbeak, hairy woodpecker, northern flicker, phoebe, pileated woodpecker, pine grosbeak, pine warbler, red-bellied woodpecker, ring-necked pheasant, robin, ruffed grouse, starling, swamp sparrow, tufted titmouse, veery, vireo, wild turkey, wood duck, wood thrush, woodcock, yellow-bellied sapsucker, chipmunk, deer, red fox, rabbit, squirrel <u>Food:</u> berries, twigs
Hobblebush	<u>Wildlife:</u> brown thrasher, cardinal, cedar warwing, evening grosbeak, robin <u>Food:</u> fruit
Lowbush Blueberry	<u>Wildlife:</u> blue jay, grouse, kingbird, oriole, robin, tangers, woodpeckers, squirrel <u>Food:</u> berries, foliage, twigs
Pussy Willow	<u>Wildlife:</u> American goldfinch, ruffed grouse, beaver, hare, rabbits, squirrel <u>Food:</u> buds, catkins, twigs, bark

Table A1 – Associated Birds & Mammals, and Food Value (cont.)	
Raspberry	<u>Wildlife:</u> songbirds and mammals <u>Food:</u> fruits
Red Osier Dogwood	<u>Wildlife:</u> bluebird, brown thrasher, cardinal, catbird, cedar waxwing, downy woodpecker, eastern kingbird, finches, northern flicker, pine warbler, purple finch, ringed-neck pheasant, ruffed grouse, vireo, wild turkey, woodpeckers, wood duck, chipmunk, deer, rabbit, squirrel <u>Food:</u> berries, twigs
Silky Dogwood	<u>Wildlife:</u> baltimore oriole, black-capped chickadee, blue jay, brown thrasher, cardinal, catbird, cedar waxwing, downy woodpecker, eastern kingbird, flycatcher, mockingbird, northern flicker, pine warbler, purple finch, red-bellied woodpecker, ringed-neck pheasant, robin, rose-breasted grosbeak, ruffed grouse, song sparrow, starlings, tufted-titmouse, wild turkey, wood duck, wood thrush, veery, chipmunk, deer, rabbit, raccoon, skunk, squirrel, white-footed mouse <u>Food:</u> buds, twigs, bark, leaves
Speckled Alder	<u>Wildlife:</u> alder flycatcher, catbird, goldfinch, mallards, pheasant, pine siskin, red-winged blackbird, ruffed grouse, swamp sparrow, yellow-bellied flycatcher, woodcock, bear, beaver, deer, cottontail, moose, muskrat, snowshoe hare <u>Food:</u> buds, twigs, bark, leaves
Witch Hazel	<u>Wildlife:</u> cardinal, ring-necked pheasant, ruffed grouse, wild turkey, deer, squirrels <u>Food:</u> seeds, buds, twigs, bark
Black Willow	<u>Wildlife:</u> songbirds and mammals <u>Food:</u> buds, catkins
Black Cherry	<u>Wildlife:</u> bluebird, blue jay, brown thrasher, cardinal, catbird, cedar waxwing, common crow, eastern kingbird, evening grosbeak, mockingbird, northern flicker, northern oriole, robin, ruffed grouse, sparrows, thrushes, veery, vireo, yellow-bellied sapsucker, bear, chipmunk, deer, fox, raccoon, squirrel <u>Food:</u> berries, buds, sap
Red Maple	<u>Wildlife:</u> cardinal, chickadee, evening and pine grosbeaks, finches, robin, yellow-bellied sapsucker, beaver, chipmunk, deer, opossum, squirrel, snowshoe hare <u>Food:</u> seeds, buds, bark, twigs, sap
White Oak	<u>Wildlife:</u> blue jay, brown thrasher, nuthatch, quail, ruffed grouse, towhee, wild turkey, wood duck, woodpecker, chipmunk, bear, deer, gopher, opossum, raccoon, squirrel <u>Food:</u> acorns
White Ash	<u>Wildlife:</u> finches, grosbeaks, red-winged blackbird, wood duck, deer, squirrel <u>Food:</u> seeds, foliage



## Habitat Assessment Field Data Sheet Low Gradient Streams

Stream Name _____
Station # _____ Rivermile _____
Lat _____ Long _____
Storet # _____

Form Completed By _____	Date _____ Time _____ AM PM
-------------------------	--------------------------------

Habit Parameter				
<b>1. Epifaunal Substrate/ Available Cover</b>	Greater than 50% of substrate favorable for epifaunal colonization and fish cover, mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are <u>not</u> new fall and <u>not</u> transient).	30 - 50% mix of stable habitat; well-suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	10 - 30% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 10% stable habitat; lack of habitat is obvious; substrate unstable or lacking.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	
<b>2. Pool Substrate Characterization</b>	Mixture of substrate materials, with gravel and firm sand prevalent; root mats and submerged vegetation common.	Mixture of soft sand, mud, or clay; mud may be dominant; some root mats and submerged vegetation present.	All mud or clay or sand bottom; little or no root mat; no submerged vegetation.	Hard-pan clay or bedrock; no root mat or vegetation.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	
<b>3. Pool Variability</b>	Even mix of large-shallow, large-deep, small-shallow, small-deep pools present.	Majority of pools large-deep; very few shallow.	Shallow pools much more prevalent than deep pools.	Majority of pools small-shallow or pools absent.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	

<b>4. Sediment Deposition</b>	Little or no enlargement of islands or point bars and less than 5% (<20% for low-gradient streams) of the bottom affected by sediment deposition.	Some new increase in bar formation, mostly from gravel, sand or fine sediment; 5-30% (20-50% for low-gradient) of the bottom affected; slight deposition in pools.	Moderate deposition of new gravel, sand or fine sediment on old and new bars; 30-50% (50%-80% for low-gradient) of the bottom affected; sediment deposits at obstructions, constrictions, and bends; moderate deposition of pools prevalent.	Heavy deposits of fine material, increased bar development; more than 50% (80% for low-gradient) of the bottom changing frequently; pools almost absent due to substantial sediment deposition.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0
<b>5. Channel Flow Status</b>	Water reaches base of both lower banks, and minimal amount of channel substrate is exposed.	Water fills >75% of the available channel; or <25% of channel substrate is exposed.	Water fills 25-75% of the available channel, and/or riffle substrates are mostly exposed.	Very little water in channel and mostly present as standing pools.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0
<b>6. Channel Alteration</b>	Channelization or dredging absent or minimal; stream with normal pattern.	Some channelization present, usually in areas of bridge abutments; evidence of past channelization, i.e., dredging, (greater than past 20 yr) may be present, but recent channelization is not present.	Channelization may be extensive; embankments or shoring structures present on both banks; and 40 to 80% of stream reach channelized and disrupted.	Banks shored with gabion or cement; over 80% of the stream reach channelized and disrupted. Instream habitat greatly altered or removed entirely.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0
<b>7. Channel Sinuosity</b>	The bends in the stream increase the stream length 3 to 4 times longer than if it was in a straight line. (Note-channel braiding is considered normal in coastal plains and other low-lying areas. This parameter is not easily rated in these areas.	The bends in the stream length 2 to 3 times longer than if it was in a straight line.	The bends in the stream increase the stream length 2 to 1 times longer than if it was in a straight line.	Channel straight; waterway has been channelized for a long distance.
SCORE	20 19 18 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0
<b>8. Bank Stability</b> (score each bank)	Banks stable: evidence of erosion or bank failure absent or minimal; little potential for future problems. <5% of bank affected.	Moderately stable; infrequent, small areas of erosion mostly healed over. 5-30% of bank in reach has areas of erosion.	Moderately unstable; 30-60% of bank in reach has areas of erosion; high erosion potential during floods.	Unstable; many eroded areas; "raw" areas frequent along straight sections and bends; obvious bank sloughing; 60-100% of bank has erosional scars.
SCORE ____ (LB)	Left Bank 10 9	8 7 6	5 4 3	2 1 0
SCORE ____ (RB)	Right Bank 10 9	8 7 6	5 4 3	2 1 0

<p><b>9. Vegetative Protection</b> (score each bank)</p> <p>Note: determine left or right side by facing downstream.</p>	<p>More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally</p>	<p>70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining</p>	<p>50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.</p>	<p>Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.</p>
<p>SCORE ____ (LB)</p>	<p>Left Bank 10 9</p>	<p>8 7 6</p>	<p>5 4 3</p>	<p>2 1 0</p>
<p>SCORE ____ (RB)</p>	<p>Right Bank 10 9</p>	<p>8 7 6</p>	<p>5 4 3</p>	<p>2 1 0</p>
<p><b>10. Riparian Vegetative Zone Width</b> (score each bank riparian zone)</p>	<p>Width of riparian zone &gt;18 meters; human activities (i.e., parking lots, roadbeds, clearcuts, lawns, or crops) have not impacted zone.</p>	<p>Width of riparian zone 12-18 meters; human activities have impacted zone only minimally.</p>	<p>Width of riparian zone 6-12 meters; human activities have impacted zone a great deal.</p>	<p>Width of riparian zone &lt;6 meters; little or no riparian vegetation due to human activities.</p>
<p>SCORE ____ (LB)</p>	<p>Left Bank 10 9</p>	<p>8 7 6</p>	<p>5 4 3</p>	<p>2 1 0</p>
<p>SCORE ____ (RB)</p>	<p>Right Bank 10 9</p>	<p>8 7 6</p>	<p>5 4 3</p>	<p>2 1 0</p>

# Hodgson Brook Field Data Sheet

*\*Customized from the Volunteer River Assessment Program - Hodgson Brook Field Data Sheet, published by NH DES\**

Date: \_\_\_\_\_ Start Time: \_\_\_\_\_ End Time: \_\_\_\_\_

Kit #: \_\_\_\_\_ Data Collected By: \_\_\_\_\_

Initial Turbidity Calibration Value: \_\_\_\_\_ Time Dissolved Oxygen Meter Turned On: \_\_\_\_\_

Initial Conductivity Calibration Value (175-225  $\mu$ S): \_\_\_\_\_ Time of First Dissolved Oxygen Calibration: \_\_\_\_\_

Loca-tion Code	Location Name	Time Sampled (HH:MM)	Turbidity (NTU)	pH Cal. Slope ("SLP" = 92-102%)	pH (std. units)	Water Temp ( $^{\circ}$ C)	Dissolved Oxygen Cal. (96-100%)	Dissolved Oxygen (mg/L)	Dissolved Oxygen (% sat.)	Dissolved Oxygen (% sat. in chamber)	Air Temp ( $^{\circ}$ C)	Specific Conductance ( $\mu$ S)

Zero Oxygen Reading (mg/L): \_\_\_\_\_ Station: \_\_\_\_\_ Time: \_\_\_\_\_

6.0 pH Buffer Reading (5.8-6.3): \_\_\_\_\_ Station: \_\_\_\_\_ Time: \_\_\_\_\_

DI Blank Turbidity Reading: \_\_\_\_\_ Station: \_\_\_\_\_ Time: \_\_\_\_\_

# Hodgson Brook Field Data Sheet

Weather Condition:

Current Weather (circle one)    Clear    Partly Cloudy    Overcast    Foggy    Hazy    Showers    Downpour    Snow    Other: \_\_\_\_\_

Describe the past three days' local weather (days prior):    1: \_\_\_\_\_    2: \_\_\_\_\_    3: \_\_\_\_\_

**Sampling Preparation Checklist (check if complete):** \_\_\_\_\_

Scribe: \_\_\_\_\_

Check Maintenance Log \_\_\_\_\_  
 Fresh Solutions \_\_\_\_\_  
 Batteries \_\_\_\_\_

**Post Calibrations:**  
 pH Cal. Slope: \_\_\_\_\_  
 DO Cal. \_\_\_\_\_  
 Turbidity (1.0 std.) \_\_\_\_\_  
 Conductivity (200 µS std.) \_\_\_\_\_

**End of the Day (check if completed):**  
 All meters dry and off: \_\_\_\_\_  
 DO probe in chamber with wet sponge: \_\_\_\_\_  
 pH probe upright in storage solution: \_\_\_\_\_  
 Turbidity sample vial rinsed and filled with DI water: \_\_\_\_\_  
 Conductivity probe cleaned and in chamber: \_\_\_\_\_  
 Kit clean of kimpwipes, dirt, moisture: \_\_\_\_\_

**NOTES:**

Indicate Presence of Visual Indicators for Each Sampling Station	
Indicator	Site
Color	
Algal Bloom	
Foam	
Debris	
Scum	
Slicks	
Odors	
Surface Floating Solids	
Benthic Deposits	



## Complete Table of Proposed Metrics

	Property	Units	Symbol/Equation	Proposed Design
Proposed Metrics	Maximum Bankfull Depth	ft	Dmax	0.75
	Average Bankfull Depth	ft	Davg	0.50
	Floodprone Depth	ft	Dfp	1.5
	Bankfull Width	ft	Wbkf	5.5
	Floodprone Width	ft	Wfp	30.0
	Width/Depth Ratio	-	W/D	11.00
	Entrenchment Ratio	-	ER	5.45
	Bankfull Area	sqft	Abkf	2.75
	Sinuosity	-	k	1.226
	Meander Belt Width	ft	MBW	18.0
	Belt Width Ratio	-	MBW/Wbkf	3.27
	Meander Length	ft	ML	40.0
	Meander Length Ratio	-	ML/Wbkf	7.27
	Radius of Curvature	ft	Rc	12.5
	Radius of Curvature Ratio	-	Rc/Wbkf	2.27
	Pool Length	ft	Lp	16.22
	Pool Length Ratio	-	Lp/Wbkf	2.95
	Pool to Pool Spacing	ft	P2P	24.52
Pool Spacing Ratio	-	P2P/Wbkf	4.46	
Calculated Values	Stream Length	ft	SL	1204
	Stream Slope	ft/ft	Slope	0.00946
	Valley Slope	ft/ft	VS	0.01160
	Valley Length	ft	VL	982.5
	Invert In	ft	INVin	47.70
	Invert Out	ft	INVout	36.31
	Bankfull Wetted Perimeter	ft	P	5.85
	Bankfull Hydraulic Radius	ft	Rh	0.47
	Bankfull Manning's n	-	n	0.035
	Bankfull Velocity	fps	V	2.50
	Bankfull Flow	cfs	Q	6.87
	Floodprone Wetted Perimeter	ft	Pfp	30.4
	Floodprone Area	sqft	Afp	18.4
	Floodprone Hydraulic Radius	ft	RHfp	0.60
	Floodprone Velocity	fps	Vfp	1.72
	Floodprone Manning's n	-	nfp	0.06
	Floodprone Flow	cfs	Qfp	31.6
	High Flow Wetted Perimeter	ft	P50	39.6
	High Flow Area	sqft	A50	44.3
	High Flow Hydraulic Radius	ft	RH50	1.12
	High Flow Manning's n	-	n50	0.08
	High Flow Velocity	fps	V50	2.16
	High Flow	cfs	Q50	95.4

Full Flow Wetted Perimeter	ft	P100	48.7
Full Flow Area	sqft	A100	76.9
Full Flow Hydraulic Radius	ft	RH100	1.58
Full Flow Manning's n	-	n100	0.09
Full Flow Velocity	fps	V100	2.41
Full Flow	cfs	Q100	185.4
Low Flow Wetted Perimeter	ft	Plf	2.95
Low Flow Area	sqft	Alf	0.27
Low Flow Hydraulic Radius	ft	RHlf	0.09
Low Flow Manning's n	-	nlf	0.035
Low Flow Velocity	fps	Vlf	0.84
Low Flow	cfs	Qlf	0.23
Bankfull Stable Particle - Rosgen	in	RDbkf	2.49
Low Flow Stable Particle - Rosgen	in	RDlf	0.70
Floodprone Stable Particle - Rosgen	in	RDfp	2.80
Full Flow Stable Particle - Rosgen	in	RD100	5.68
Bankfull Stable Particle - LWM	in	LDbkf	0.88
Low Flow Stable Particle - LWM	in	LDlf	0.15
Floodprone Stable Particle - LWM	in	LDfp	1.05
Full Flow Stable Particle - LWM	in	LD100	2.85



## Lonza Biologics - Drainage Analysis

**TO:** City of Portsmouth Technical Advisory Committee (TAC)  
**FROM:** Patrick M. Crimmins, P.E.  
**COPY:** Lonza Biologics  
**DATE:** May 21, 2018

---

### 1.0 Project Description

The proposed project is located on a vacant 24-acre parcel, referred to as the Iron Parcel, that once consisted of row housing and streets for Pease Air Force Base. The houses and roads were removed in the mid to late 1990's as part of the Civil Redevelopment Plan for Pease after the closure of the Air Force Base.

Lonza's existing facilities are located at 101 International Drive which is across Goose Bay Drive from the proposed project site. The project will merge 101 International Drive with 70 and 80 Corporate Drive to create a 43-acre parcel for Lonza's campus. This will require that 1,700LF of Goose Bay Drive be abandoned as a public right-of-way and merged with these parcels. The total master plan build-out of the proposed industrial development will include three (3) new buildings totaling approximately 1 million square feet of gross floor area and two (2) new parking garages.

The project will also consist of site improvements that include drive aisles, sidewalks utilities, lighting, landscaping and a stormwater management system with three (3) gravel wetlands and one (1) rain garden. In addition, the project will include a stream restoration project for Hodgson Brook. There is an existing 50-Inch culvert that bisects the parcel which is a buried portion of Hodgson Brook. The project will remove this culvert and daylight the flow through a new 1,000 LF stream channel. The project will result in 55,555 SF of wetland impact.

The proposed project will require a New Hampshire Department of Environmental Services (NHDES) Alteration of Terrain (AoT) Permit.

### 2.0 Drainage Analysis

#### 2.1 Calculation Methods

The parcel's on-site watersheds were analyzed under this section. The design storms analyzed in this study are the 2-year, 10-year and 50-year 24-hour duration storm as per NHDES AoT Regulations (Env-Wq 1500.) The stormwater modeling system, HydroCAD 10.0 was utilized to predict the peak runoff rates from these storm events. A Type III storm pattern was used in the model.

The time of concentration was computed using the TR-55 Method, which provides a means of determining the time for an entire watershed to contribute runoff to a specific location via sheet flows, shallow concentrated flow and channel flow. Runoff curve numbers were calculated by estimating the coverage areas and then summing the curve number for the coverage area as a percent of the entire watershed.

## References

1. HydroCAD Stormwater Modeling System, by HydroCAD Software Solutions LLC, Chocorua, New Hampshire.
2. New Hampshire Stormwater Management Manual, Volume 2, Post-Construction Best Management Practices Selection and Design, December 2008.

## 2.2 Pre-Development Calculations

In order to analyze the pre-development condition, the site has been divided into two watershed areas modeled at two points of analysis. Enclosed with this memorandum are the Pre-Development Watershed Plan, HydroCAD model and Soil Plan for these two (2) points of analysis.

Each of the points of analysis and their contributing watershed areas are described below:

### **Point of Analysis (PA1)**

PRE 1.0 makes up almost the entire area to be developed. This area consists of the entire undeveloped parcel, as well as, a portion of Corporate Drive that drains onto the parcel via a closed drainage system. Currently the watershed is an undeveloped field area that with a portion of the site being used as a temporary construction parking area with associated stormwater management controls near the center of the parcel. This parcel was previously developed as military housing that was demolished in the mid to late 1990's. Runoff from this area travels southeast via overland flow to Point of Analysis 1 located at the existing Hodgson Brook outlet headwall.

### **Point of Analysis (PA2)**

PRE 2.0 is comprised mostly of runoff from Goose Bay Drive that is located between the undeveloped parcel and the existing Lonza facility. Runoff from this area travels via overland flow to the existing stormwater basin located at the existing Lonza facility. Point of Analysis 2 (PA2) is located at the existing basin.

## 2.3 Post-Development Calculations

The post-development condition was analyzed by dividing the watersheds into seven sub-catchment areas. Stormwater runoff from these sub-catchment areas flow to three gravel wetlands and one rain garden for treatment prior to infiltration or discharging to the existing Hodgson Brook outlet. Flows from these sub-catchment areas are modeled at the same two points of analysis that were modeled in the pre-development analysis, PA1 and PA2. Enclosed with this memorandum are the Pre-Development Watershed Plan, HydroCAD model and Soil Plan for these two (2) points of analysis.

Each of the points of analysis and their contributing watershed areas are described below:

### **Point of Analysis (PA1)**

Point of Analysis 1 (PA1) is located at the existing Hodgson Brook outlet headwall. For the purposes of this analysis, the area contributing to Point of Analysis 1 (PA1) has been divided into six sub-catchment areas (see plan C-802). Sub-catchments POST 1.0, POST 1.1, POST 1.2, POST 1.3, POST 1.4 and POST 1.5 contribute to this point of analysis and consist of grass, paved parking lots, concrete sidewalks, and roof areas. Runoff generated in these sub-catchment areas is collected via one rain garden and three gravel wetlands which treat and discharge stormwater runoff either to infiltration or to PA1. Runoff from sub-catchments POST

1.0, 1.1, 1.2 and 1.5 flow via overland flow to the closed drainage then flows via underground piping to one of the gravel wetlands or rain garden. Flows from sub-catchment POST 1.3 flows via overland flow to the Hodgson Brook restoration area (REACH 1.3) then flows via the brook until reach PA1. Runoff from POND 1.1 and POND 1.2 also flows via REACH 1.3 to PA1. Runoff from sub-catchment area POST 1.4 flows via overland flow to PA1. PA1 is shown on the Post-Development Watershed Plan (C-802).

**Point of Analysis (PA2)**

POST 2.1 is comprised mostly of runoff from Goose Bay Drive that is located between the undeveloped parcel and the existing Lonza facility. Runoff from this area travels via overland flow to the existing stormwater basin located at the existing Lonza facility. Point of Analysis 2 (PA2) is located at the existing basin.

**2.4 Peak Rate Comparisons**

The following table summarizes and compares the pre- and post-development peak runoff rates for the 2-year, 10-year, 25-year and 50-year storm events at each point of analysis. The pre-development 1-year storm event is also included for channel protection requirements.

Point of Analysis	Pre 1-Year Storm (cfs)	Pre/ <b>Post</b> 2-Year Storm (cfs)	Pre/ <b>Post</b> 10-Year Storm (cfs)	Pre/ <b>Post</b> 25-Year Storm (cfs)	Pre/ <b>Post</b> 50-Year Storm (cfs)
PA1	16.94	25.44/ <b>13.07</b>	54.47/ <b>41.55</b>	79.11/ <b>64.50</b>	102.71/ <b>92.68</b>
PA2	1.59	1.99/ <b>0.22</b>	3.18/ <b>0.33</b>	4.09/ <b>0.42</b>	4.94/ <b>.051</b>

As depicted in Table 2.4.1, post-development peak runoff rates are less than the pre-development condition for PA1 and PA2.

**2.5 Stormwater Treatment**

The stormwater management system has been designed to provide stormwater treatment as required by the City of Portsmouth Site Review Regulations and NHDES AoT Regulations (Env-Wq 1500).



Runoff generated from impervious area will be treated three (3) gravel wetlands and one (1) rain garden. The proposed gravel wetlands and rain garden have been designed in accordance with the New Hampshire Stormwater Manual and meet NHDES AoT requirements (Env-Wq 1500) for required water quality volume (WQV) and groundwater recharge volume (GRV)

Enclosed with this memorandum are copies of BMP and GRV worksheets.

**4.0 Conclusion**



The proposed project will result in a reduction in post-development peak runoff rates from the pre-development condition. The impervious area resulting from the proposed project will be treated by the three (3) gravel wetlands and one (1) rain garden. The project will require an NHDES AoT Permit. A complete copy of the AoT Permit Application will be provided to the City of Portsmouth when it is submitted to NHDES.







WATERSHED 1.0

POINT OF ANALYSIS



WATERSHED 2.0

POINT OF ANALYSIS



**L-0700-10 PRE**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Printed 2/9/2018

Page 2

**Area Listing (selected nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.122	74	>75% Grass cover, Good, HSG C (PRE 2.0)
0.835	89	Gravel roads, HSG C (PRE 1.0)
0.103	58	Meadow, non-grazed, HSG B (PRE 1.0)
22.611	71	Meadow, non-grazed, HSG C (PRE 1.0)
1.605	78	Meadow, non-grazed, HSG D (PRE 1.0)
3.322	98	Paved parking, HSG C (PRE 1.0, PRE 2.0)
0.101	55	Woods, Good, HSG B (PRE 1.0)
1.067	70	Woods, Good, HSG C (PRE 1.0)
0.126	77	Woods, Good, HSG D (PRE 1.0)
<b>29.892</b>	<b>75</b>	<b>TOTAL AREA</b>

**L-0700-10 PRE**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Printed 2/9/2018

Page 3

**Soil Listing (selected nodes)**

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.204	HSG B	PRE 1.0
27.957	HSG C	PRE 1.0, PRE 2.0
1.732	HSG D	PRE 1.0
0.000	Other	
<b>29.892</b>		<b>TOTAL AREA</b>

**L-0700-10 PRE**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 1 Year Rainfall=3.05"

Printed 2/9/2018

Page 4

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment PRE 1.0: WATERSHED 1.0** Runoff Area=1,275,757 sf 9.69% Impervious Runoff Depth>0.93"  
Flow Length=1,634' Tc=30.4 min CN=74 Runoff=16.94 cfs 2.276 af

**Subcatchment PRE 2.0: WATERSHED 2.0** Runoff Area=26,354 sf 79.76% Impervious Runoff Depth>2.30"  
Flow Length=650' Slope=0.0250 '/ Tc=5.0 min CN=93 Runoff=1.59 cfs 0.116 af

**Link PA1: POINT OF ANALYSIS**

Inflow=16.94 cfs 2.276 af  
Primary=16.94 cfs 2.276 af

**Link PA2: POINT OF ANALYSIS**

Inflow=1.59 cfs 0.116 af  
Primary=1.59 cfs 0.116 af

**Total Runoff Area = 29.892 ac Runoff Volume = 2.392 af Average Runoff Depth = 0.96"**  
**88.89% Pervious = 26.571 ac 11.11% Impervious = 3.322 ac**



**L-0700-10 PRE**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 2 Year Rainfall=3.68"

Printed 2/9/2018

Page 5

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment PRE 1.0: WATERSHED 1.0** Runoff Area=1,275,757 sf 9.69% Impervious Runoff Depth>1.36"  
Flow Length=1,634' Tc=30.4 min CN=74 Runoff=25.44 cfs 3.308 af

**Subcatchment PRE 2.0: WATERSHED 2.0** Runoff Area=26,354 sf 79.76% Impervious Runoff Depth>2.91"  
Flow Length=650' Slope=0.0250 '/ Tc=5.0 min CN=93 Runoff=1.99 cfs 0.147 af

**Link PA1: POINT OF ANALYSIS**

Inflow=25.44 cfs 3.308 af  
Primary=25.44 cfs 3.308 af

**Link PA2: POINT OF ANALYSIS**

Inflow=1.99 cfs 0.147 af  
Primary=1.99 cfs 0.147 af

**Total Runoff Area = 29.892 ac Runoff Volume = 3.455 af Average Runoff Depth = 1.39"**  
**88.89% Pervious = 26.571 ac 11.11% Impervious = 3.322 ac**

**L-0700-10 PRE**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe & Bond

Printed 2/9/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment PRE 1.0: WATERSHED 1.0** Runoff Area=1,275,757 sf 9.69% Impervious Runoff Depth>2.82"  
Flow Length=1,634' Tc=30.4 min CN=74 Runoff=54.47 cfs 6.875 af

**Subcatchment PRE 2.0: WATERSHED 2.0** Runoff Area=26,354 sf 79.76% Impervious Runoff Depth>4.77"  
Flow Length=650' Slope=0.0250 '/ Tc=5.0 min CN=93 Runoff=3.18 cfs 0.240 af

**Link PA1: POINT OF ANALYSIS**

Inflow=54.47 cfs 6.875 af  
Primary=54.47 cfs 6.875 af

**Link PA2: POINT OF ANALYSIS**

Inflow=3.18 cfs 0.240 af  
Primary=3.18 cfs 0.240 af

**Total Runoff Area = 29.892 ac Runoff Volume = 7.115 af Average Runoff Depth = 2.86"**  
**88.89% Pervious = 26.571 ac 11.11% Impervious = 3.322 ac**

**Summary for Subcatchment PRE 1.0: WATERSHED 1.0**

Runoff = 54.47 cfs @ 12.43 hrs, Volume= 6.875 af, Depth> 2.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
4,505	58	Meadow, non-grazed, HSG B
4,387	55	Woods, Good, HSG B
984,919	71	Meadow, non-grazed, HSG C
123,673	98	Paved parking, HSG C
36,380	89	Gravel roads, HSG C
46,463	70	Woods, Good, HSG C
69,928	78	Meadow, non-grazed, HSG D
5,502	77	Woods, Good, HSG D
1,275,757	74	Weighted Average
1,152,084		90.31% Pervious Area
123,673		9.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	50	0.0400	0.19		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.06"
1.2	80	0.0250	1.11		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
21.4	1,089	0.0147	0.85		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
3.2	368	0.0160	1.90		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
0.2	47	0.0050	4.03	4.95	<b>Pipe Channel,</b> 15.0" Round Area= 1.2 sf Perim= 3.9' r= 0.31' n= 0.012 Concrete pipe, finished
30.4	1,634	Total			

**Summary for Subcatchment PRE 2.0: WATERSHED 2.0**

Runoff = 3.18 cfs @ 12.07 hrs, Volume= 0.240 af, Depth> 4.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
21,021	98	Paved parking, HSG C
5,333	74	>75% Grass cover, Good, HSG C
26,354	93	Weighted Average
5,333		20.24% Pervious Area
21,021		79.76% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.1	100	0.0250	1.47		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.06"
2.9	550	0.0250	3.21		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
4.0	650	Total, Increased to minimum Tc = 5.0 min			

**Summary for Link PA1: POINT OF ANALYSIS**

Inflow Area = 29.287 ac, 9.69% Impervious, Inflow Depth > 2.82" for 10 Year event  
 Inflow = 54.47 cfs @ 12.43 hrs, Volume= 6.875 af  
 Primary = 54.47 cfs @ 12.43 hrs, Volume= 6.875 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

**Summary for Link PA2: POINT OF ANALYSIS**

Inflow Area = 0.605 ac, 79.76% Impervious, Inflow Depth > 4.77" for 10 Year event  
 Inflow = 3.18 cfs @ 12.07 hrs, Volume= 0.240 af  
 Primary = 3.18 cfs @ 12.07 hrs, Volume= 0.240 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

**L-0700-10 PRE**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 2/9/2018

Page 9

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment PRE 1.0: WATERSHED 1.0** Runoff Area=1,275,757 sf 9.69% Impervious Runoff Depth>5.31"  
Flow Length=1,634' Tc=30.4 min CN=74 Runoff=102.71 cfs 12.958 af

**Subcatchment PRE 2.0: WATERSHED 2.0** Runoff Area=26,354 sf 79.76% Impervious Runoff Depth>7.62"  
Flow Length=650' Slope=0.0250 '/ Tc=5.0 min CN=93 Runoff=4.94 cfs 0.384 af

**Link PA1: POINT OF ANALYSIS**


Inflow=102.71 cfs 12.958 af  
Primary=102.71 cfs 12.958 af

**Link PA2: POINT OF ANALYSIS**

Inflow=4.94 cfs 0.384 af  
Primary=4.94 cfs 0.384 af

**Total Runoff Area = 29.892 ac Runoff Volume = 13.341 af Average Runoff Depth = 5.36"**  
**88.89% Pervious = 26.571 ac 11.11% Impervious = 3.322 ac**





**LEGEND**

- PRE-DEVELOPMENT WATERSHED BOUNDARY
- SOIL BOUNDARY
- LONGEST FLOWPATH
- PRE-DEVELOPMENT WATERSHED DESIGNATION
- POINT OF ANALYSIS

**HIGH INTENSITY MAP SYMBOL**  
DRAINAGE CLASS 5

1. EXCESSIVELY DRAINED
2. WELL DRAINED
3. MODERATELY WELL DRAINED
4. SOMEWHAT POORLY DRAINED
5. POORLY DRAINED
6. VERY POORLY DRAINED
7. NOT DETERMINABLE

**PARENT MATERIAL** 2

1. GLACIOFLUVIAL
2. GLACIAL TILL
3. MARINE OR GLACIOLACUSTRINE VERY FINE SAND AND SILT
4. MARINE OR GLACIOLACUSTRINE LOAMY/SANDY OVER SILT/CLAY
5. MARINE OR GLACIOLACUSTRINE SILT AND CLAY
6. EXCAVATED, REGRADED, OR FILLED
7. ALLUVIAL DEPOSITS
8. ORGANIC MATERIALS FRESH WATER
9. ORGANIC MATERIALS TIDAL MARSH


**RESTRICTIVE FEATURES** 3

1. NONE
2. BOULDERY, WITH MORE THAN 15% OF SURFACE COVERED
3. MINERAL RESTRICTIVE LAYER(S) AREA PRESENT AT LESS THAN 40 IN. DEPTH.
4. BEDROCK 0 IN. TO 20 IN. DEPTH.
5. SUBJECT TO FLOODING
6. DOES NOT MEET FILL STANDARDS.
- X. DEPTH TO BEDROCK VARIABLE, COMPLEX OF SOIL TYPES.

**IDENTIFIER** H  
H. INDICATES HIGH INTENSITY SOIL MAP  
P. INDICATES PRELIMINARY MAP

**SLOPE CLASS** B  
B. 0 TO 8%  
C. 8 TO 15%  
D. 15 TO 25%  
E. MORE THAN 25%

HIGH INTENSITY MAP SYMBOL 523BH INDICATES A POORLY DRAINED GLACIAL TILL SOIL WITH A RESTRICTIVE FEATURE, ON A SLOPE OF 0 TO 8%



**Permit Plans Not For Construction**

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION

PROJECT NO:	L0700-10
DATE:	MM/DD/YYYY
FILE:	L0700-C-801 to C-804.dwg
DRAWN BY:	NAH
CHECKED:	PMC
APPROVED:	GMM


PRE-DEVELOPMENT WATERSHED AREA PLAN

SCALE: AS SHOWN

Last Save Date: July 12, 2016 4:03 PM By: MAHANSEN  
 Plot Date: Thursday, July 21, 2016 Plotted By: Neil A. Hansen  
 File Location: J:\L0700\Lonza Biologics Expansion\work\B3\DWG\CADD\DESIGN\SHEETS\L0700-C-801 to C-804.dwg Layout Tab: C-801








**LEGEND**

- PRE-DEVELOPMENT WATERSHED BOUNDARY
- SOIL BOUNDARY
- LONGEST FLOWPATH
- PRE-DEVELOPMENT WATERSHED DESIGNATION
- POINT OF ANALYSIS



**Permit Plans Not For Construction**

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

**HIGH INTENSITY MAP SYMBOL DRAINAGE CLASS**  
5

- EXCESSIVELY DRAINED
- WELL DRAINED
- MODERATELY WELL DRAINED
- SOMEWHAT POORLY DRAINED
- POORLY DRAINED
- VERY POORLY DRAINED
- NOT DETERMINABLE

**PARENT MATERIAL**  
2

- GLACIOFLUVIAL
- GLACIAL TILL
- MARINE OR GLACIOLACUSTRINE VERY FINE SAND AND SILT
- MARINE OR GLACIOLACUSTRINE LOAMY/SANDY OVER SILT/CLAY
- MARINE OR GLACIOLACUSTRINE SILT AND CLAY
- EXCAVATED, REGRADED, OR FILLED
- ALLUVIAL DEPOSITS
- ORGANIC MATERIALS FRESH WATER
- ORGANIC MATERIALS TIDAL MARSH

**RESTRICTIVE FEATURES**  
3

- NONE
- BOULDERY, WITH MORE THAN 15% OF SURFACE COVERED
- MINERAL RESTRICTIVE LAYER(S) AREA PRESENT AT LESS THAN 40 IN. DEPTH.
- BEDROCK 0 IN. TO 20 IN. DEPTH.
- SUBJECT TO FLOODING
- DOES NOT MEET FILL STANDARDS.
- DEPTH TO BEDROCK VARIABLE, COMPLEX OF SOIL TYPES.

**IDENTIFIER**  
H  
H. INDICATES HIGH INTENSITY SOIL MAP  
P. INDICATES PRELIMINARY MAP

**SLOPE CLASS**  
B  
B. 0 TO 8%  
C. 8 TO 15%  
D. 15 TO 25%  
E. MORE THAN 25%

**HYDROLOGIC SOIL GROUP RATING**




- IMPERVIOUS AREA
- HYDROLOGIC SOIL GROUP A
- HYDROLOGIC SOIL GROUP B
- HYDROLOGIC SOIL GROUP C
- HYDROLOGIC SOIL GROUP D

HIGH INTENSITY MAP SYMBOL 523BH INDICATES A POORLY DRAINED GLACIAL TILL SOIL WITH A RESTRICTIVE FEATURE, ON A SLOPE OF 0 TO 8%

Last Save Date: July 12, 2016 4:03 PM By: MAHANSEN  
 Plot Date: Thursday, July 21, 2016 Plotted By: Neil A. Hansen  
 File Location: J:\L0700\Lonza Biologics Expansion.was.12717.DWG-CADD\DESIGN\SHEETS\L0700-C-801 to C-804.dwg Layout Tab: C-803

MARK	DATE	DESCRIPTION
PROJECT NO:	L0700-10	
DATE:	MM/DD/YYYY	
FILE:	L0700-C-801 to C-804.dwg	
DRAWN BY:	NAH	
CHECKED:	PMC	
APPROVED:	GMM	
<b>PRE-DEVELOPMENT SOIL PLAN</b>		
SCALE:	AS SHOWN	
<b>C-803</b>		





**Routing Diagram for L-0700-13 POST**  
 Prepared by Tighe & Bond, Printed 5/21/2018  
 HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Printed 5/21/2018

Page 2

**Area Listing (selected nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.025	61	>75% Grass cover, Good, HSG B (POST 1.5)
12.422	74	>75% Grass cover, Good, HSG C (POST 1.0, POST 1.1, POST 1.2, POST 1.3, POST 1.4, POST 1.5)
0.222	80	>75% Grass cover, Good, HSG D (POST 1.0, POST 1.1, POST 1.2, POST 1.4)
0.504	78	Meadow, non-grazed, HSG D (POST 1.4)
0.037	98	Paved parking, HSG B (POST 1.5)
6.876	98	Paved parking, HSG C (POST 1.0, POST 1.1, POST 1.2, POST 1.3, POST 1.4, POST 1.5, POST 2.1)
0.295	98	Paved parking, HSG D (POST 1.0, POST 1.1, POST 1.2)
0.142	98	Roofs, HSG B (POST 1.5)
8.659	98	Roofs, HSG C (POST 1.0, POST 1.1, POST 1.2, POST 1.5)
0.710	98	Roofs, HSG D (POST 1.0, POST 1.1, POST 1.2, POST 1.5)
<b>29.892</b>	<b>88</b>	<b>TOTAL AREA</b>

**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Printed 5/21/2018

Page 3

**Soil Listing (selected nodes)**

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.204	HSG B	POST 1.5
27.957	HSG C	POST 1.0, POST 1.1, POST 1.2, POST 1.3, POST 1.4, POST 1.5, POST 2.1
1.732	HSG D	POST 1.0, POST 1.1, POST 1.2, POST 1.4, POST 1.5
0.000	Other	
<b>29.892</b>		<b>TOTAL AREA</b>

**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 2 Year Rainfall=3.68"

Printed 5/21/2018

Page 4

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment POST 1.0: WATERSHED** Runoff Area=412,828 sf 74.83% Impervious Runoff Depth>2.80"  
 Flow Length=1,013' Tc=16.2 min CN=92 Runoff=22.26 cfs 2.213 af

**Subcatchment POST 1.1: WATERSHED 1.1** Runoff Area=93,833 sf 45.41% Impervious Runoff Depth>2.17"  
 Flow Length=738' Tc=13.6 min CN=85 Runoff=4.28 cfs 0.389 af

**Subcatchment POST 1.2: WATERSHED** Runoff Area=196,367 sf 41.29% Impervious Runoff Depth>2.09"  
 Flow Length=641' Tc=11.1 min CN=84 Runoff=9.27 cfs 0.784 af

**Subcatchment POST 1.3: WATERSHED 1.3** Runoff Area=89,680 sf 65.38% Impervious Runoff Depth>2.61"  
 Flow Length=1,602' Tc=7.3 min CN=90 Runoff=5.86 cfs 0.449 af

**Subcatchment POST 1.4: WATERSHED** Runoff Area=290,401 sf 21.74% Impervious Runoff Depth>1.77"  
 Flow Length=1,388' Tc=32.9 min CN=80 Runoff=7.49 cfs 0.982 af

**Subcatchment POST 1.5: WATERSHED** Runoff Area=216,369 sf 79.15% Impervious Runoff Depth>2.90"  
 Flow Length=1,088' Tc=15.7 min CN=93 Runoff=12.11 cfs 1.201 af

**Subcatchment POST 2.1: WATERSHED 2.1** Runoff Area=2,635 sf 100.00% Impervious Runoff Depth>3.44"  
 Tc=5.0 min CN=98 Runoff=0.22 cfs 0.017 af

**Reach REACH 1.2:** Avg. Flow Depth=0.12' Max Vel=1.63 fps Inflow=0.18 cfs 0.175 af  
 54.0" Round Pipe n=0.013 L=395.0' S=0.0059 '/' Capacity=151.68 cfs Outflow=0.18 cfs 0.174 af

**Reach REACH 1.3: HODGSON BROOK** Avg. Flow Depth=0.60' Max Vel=2.01 fps Inflow=6.01 cfs 0.771 af  
 n=0.040 L=1,211.0' S=0.0091 '/' Capacity=2,707.81 cfs Outflow=4.46 cfs 0.760 af

**Pond POND 1.0: GRAVEL WETLAND 1** Peak Elev=45.31' Storage=56,791 cf Inflow=22.26 cfs 2.213 af  
 Primary=3.22 cfs 1.458 af Secondary=0.00 cfs 0.000 af Outflow=3.22 cfs 1.458 af

**Pond POND 1.1: GRAVEL WETLAND 2** Peak Elev=51.63' Storage=11,984 cf Inflow=4.28 cfs 0.389 af  
 Outflow=0.16 cfs 0.149 af

**Pond POND 1.2: GRAVEL WETLAND 3** Peak Elev=52.94' Storage=26,894 cf Inflow=9.27 cfs 0.784 af  
 Outflow=0.18 cfs 0.175 af

**Pond POND 1.5: RAINGARDEN 1.0** Peak Elev=46.84' Storage=27,217 cf Inflow=12.11 cfs 1.201 af  
 Discarded=0.08 cfs 0.102 af Primary=1.34 cfs 0.988 af Outflow=1.42 cfs 1.090 af

**Link PA1: POINT OF ANALYSIS** Inflow=13.07 cfs 4.188 af  
 Primary=13.07 cfs 4.188 af

**Link PA2: POINT OF ANALYSIS** Inflow=0.22 cfs 0.017 af  
 Primary=0.22 cfs 0.017 af

**Total Runoff Area = 29.892 ac Runoff Volume = 6.036 af Average Runoff Depth = 2.42"**  
**44.07% Pervious = 13.174 ac 55.93% Impervious = 16.719 ac**

**L-0700-13 POST**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe &amp; Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 5

**Summary for Subcatchment POST 1.0: WATERSHED 1.0**

Runoff = 35.97 cfs @ 12.21 hrs, Volume= 3.670 af, Depth&gt; 4.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
158,334	98	Roofs, HSG C
98,983	74	>75% Grass cover, Good, HSG C
108,837	98	Paved parking, HSG C
11,206	98	Roofs, HSG D
4,917	80	>75% Grass cover, Good, HSG D
12,560	98	Paved parking, HSG D
17,991	98	Paved parking, HSG C
412,828	92	Weighted Average
103,900		25.17% Pervious Area
308,928		74.83% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.2	100	0.0150	0.15		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.06"
0.8	100	0.0200	2.12		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
4.2	813	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
16.2	1,013	Total			

**Summary for Subcatchment POST 1.1: WATERSHED 1.1**

Runoff = 7.59 cfs @ 12.19 hrs, Volume= 0.700 af, Depth&gt; 3.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
32,905	98	Roofs, HSG C
50,995	74	>75% Grass cover, Good, HSG C
9,307	98	Paved parking, HSG C
245	98	Roofs, HSG D
231	80	>75% Grass cover, Good, HSG D
150	98	Paved parking, HSG D
93,833	85	Weighted Average
51,226		54.59% Pervious Area
42,607		45.41% Impervious Area

**L-0700-13 POST**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe &amp; Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 6

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.2	93	0.0167	0.15		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.06"
3.4	645	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
13.6	738	Total			

**Summary for Subcatchment POST 1.2: WATERSHED 1.2**

Runoff = 16.69 cfs @ 12.15 hrs, Volume= 1.427 af, Depth&gt; 3.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
46,063	98	Roofs, HSG C
114,389	74	>75% Grass cover, Good, HSG C
17,726	98	Paved parking, HSG C
17,158	98	Roofs, HSG D
904	80	>75% Grass cover, Good, HSG D
127	98	Paved parking, HSG D
196,367	84	Weighted Average
115,293		58.71% Pervious Area
81,074		41.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.3	72	0.0167	0.14		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.06"
0.2	68	0.1129	5.04		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
2.6	501	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
11.1	641	Total			

**Summary for Subcatchment POST 1.3: WATERSHED 1.3**

Runoff = 9.69 cfs @ 12.10 hrs, Volume= 0.761 af, Depth&gt; 4.43"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
31,051	74	>75% Grass cover, Good, HSG C
58,629	98	Paved parking, HSG C
89,680	90	Weighted Average
31,051		34.62% Pervious Area
58,629		65.38% Impervious Area



**L-0700-13 POST**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=5.58"

Printed 5/21/2018

Page 7

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.6	100	0.0100	1.02		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.06"
1.0	153	0.0150	2.49		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
1.6	343	0.0050	3.47	2.73	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.012 Concrete pipe, finished
0.1	13	0.0050	3.72	4.57	<b>Pipe Channel,</b> 15.0" Round Area= 1.2 sf Perim= 3.9' r= 0.31' n= 0.013 Corrugated PE, smooth interior
1.8	453	0.0050	4.20	7.43	<b>Pipe Channel,</b> 18.0" Round Area= 1.8 sf Perim= 4.7' r= 0.38' n= 0.013 Corrugated PE, smooth interior
0.4	129	0.0050	5.91	29.00	<b>Pipe Channel,</b> 30.0" Round Area= 4.9 sf Perim= 7.9' r= 0.63' n= 0.013 Corrugated PE, smooth interior
0.8	411	0.0050	8.08	101.57	<b>Pipe Channel,</b> 48.0" Round Area= 12.6 sf Perim= 12.6' r= 1.00' n= 0.013 Corrugated PE, smooth interior
7.3	1,602	Total			

**Summary for Subcatchment POST 1.4: WATERSHED 1.4**

Runoff = 14.39 cfs @ 12.45 hrs, Volume= 1.880 af, Depth> 3.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
201,658	74	>75% Grass cover, Good, HSG C
63,139	98	Paved parking, HSG C
3,633	80	>75% Grass cover, Good, HSG D
21,971	78	Meadow, non-grazed, HSG D
290,401	80	Weighted Average
227,262		78.26% Pervious Area
63,139		21.74% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.2	84	0.0150	1.16		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.06"
1.2	62	0.0150	0.86		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
0.1	31	0.3230	8.52		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
30.4	1,211	0.0090	0.66		<b>Shallow Concentrated Flow,</b> Short Grass Pasture Kv= 7.0 fps
32.9	1,388	Total			

**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=5.58"

Printed 5/21/2018

Page 8

**Summary for Subcatchment POST 1.5: WATERSHED 1.5**

Runoff = 19.34 cfs @ 12.21 hrs, Volume= 1.969 af, Depth&gt; 4.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
6,192	98	Roofs, HSG B
1,098	61	>75% Grass cover, Good, HSG B
1,601	98	Paved parking, HSG B
139,882	98	Roofs, HSG C
44,025	74	>75% Grass cover, Good, HSG C
21,245	98	Paved parking, HSG C
2,326	98	Roofs, HSG D
216,369	93	Weighted Average
45,123		20.85% Pervious Area
171,246		79.15% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	92	0.0150	0.15		<b>Sheet Flow,</b> Grass: Short n= 0.150 P2= 3.06"
5.2	996	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
15.7	1,088	Total			

**Summary for Subcatchment POST 2.1: WATERSHED 2.1**

Runoff = 0.33 cfs @ 12.07 hrs, Volume= 0.027 af, Depth&gt; 5.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10 Year Rainfall=5.58"

Area (sf)	CN	Description
2,635	98	Paved parking, HSG C
2,635		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Reach REACH 1.2:**

Inflow Area = 4.508 ac, 41.29% Impervious, Inflow Depth > 1.76" for 10 Year event  
 Inflow = 2.12 cfs @ 12.95 hrs, Volume= 0.661 af  
 Outflow = 2.12 cfs @ 12.97 hrs, Volume= 0.660 af, Atten= 0%, Lag= 1.4 min

**L-0700-13 POST**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=5.58"

Printed 5/21/2018

Page 9

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Max. Velocity= 3.39 fps, Min. Travel Time= 1.9 min

Avg. Velocity = 2.15 fps, Avg. Travel Time= 3.1 min

Peak Storage= 246 cf @ 12.97 hrs

Average Depth at Peak Storage= 0.37'


Bank-Full Depth= 4.50' Flow Area= 15.9 sf, Capacity= 151.68 cfs

54.0" Round Pipe

n= 0.013 Corrugated PE, smooth interior

Length= 395.0' Slope= 0.0059 '/'

Inlet Invert= 49.35', Outlet Invert= 47.00'



**Summary for Reach REACH 1.3: HODGSON BROOK**

Inflow Area = 8.721 ac, 47.99% Impervious, Inflow Depth > 2.30" for 10 Year event

Inflow = 9.96 cfs @ 12.10 hrs, Volume= 1.669 af

Outflow = 6.62 cfs @ 12.09 hrs, Volume= 1.655 af, Atten= 34%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Max. Velocity= 2.24 fps, Min. Travel Time= 9.0 min

Avg. Velocity = 1.01 fps, Avg. Travel Time= 19.9 min

Peak Storage= 5,572 cf @ 12.32 hrs

Average Depth at Peak Storage= 0.80'

Bank-Full Depth= 6.75' Flow Area= 291.0 sf, Capacity= 2,707.81 cfs

Custom cross-section, Length= 1,211.0' Slope= 0.0091 '/' (101 Elevation Intervals)

Constant n= 0.040 Winding stream, pools & shoals

Inlet Invert= 47.00', Outlet Invert= 36.00'



‡

**L-0700-13 POST**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe & Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 10

Offset (feet)	Elevation (feet)	Chan.Depth (feet)
0.00	12.00	0.00
18.00	6.00	6.00
30.25	6.00	6.00
31.75	5.25	6.75
34.25	5.25	6.75
35.75	6.00	6.00
48.00	6.00	6.00
66.00	12.00	0.00

Depth (feet)	End Area (sq-ft)	Perim. (feet)	Storage (cubic-feet)	Discharge (cfs)
0.00	0.0	2.5	0	0.00
0.75	3.0	30.4	3,633	2.27
6.75	291.0	68.3	352,401	2,707.81

**Summary for Pond POND 1.0: GRAVEL WETLAND 1**

Inflow Area = 9.477 ac, 74.83% Impervious, Inflow Depth > 4.65" for 10 Year event  
 Inflow = 35.97 cfs @ 12.21 hrs, Volume= 3.670 af  
 Outflow = 21.51 cfs @ 12.47 hrs, Volume= 2.804 af, Atten= 40%, Lag= 15.4 min  
 Primary = 21.51 cfs @ 12.47 hrs, Volume= 2.804 af  
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 46.34' @ 12.47 hrs Surf.Area= 20,404 sf Storage= 76,594 cf  
 Flood Elev= 48.00' Surf.Area= 23,557 sf Storage= 113,085 cf

Plug-Flow detention time= 215.1 min calculated for 2.804 af (76% of inflow)  
 Center-of-Mass det. time= 134.4 min ( 921.7 - 787.3 )

Volume	Invert	Avail.Storage	Storage Description	
#1	39.05'	113,085 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)	
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
39.05	9,854	0.0	0	0
41.35	9,854	30.0	6,799	6,799
42.00	9,854	80.0	5,124	11,923
43.00	11,943	100.0	10,899	22,822
44.00	14,202	100.0	13,073	35,894
45.00	16,891	100.0	15,547	51,441
46.00	19,752	100.0	18,322	69,762
47.00	21,668	100.0	20,710	90,472
48.00	23,557	100.0	22,613	113,085

**L-0700-13 POST**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=5.58"

Printed 5/21/2018

Page 11

Device	Routing	Invert	Outlet Devices
#1	Primary	41.35'	<b>24.0" Round Culvert</b> L= 30.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 41.35' / 41.20' S= 0.0050 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf
#2	Device 1	41.35'	<b>3.0" Vert. Orifice/Grate</b> C= 0.600
#3	Device 1	43.40'	<b>4.0" Vert. Orifice/Grate X 2.00</b> C= 0.600
#4	Device 1	45.00'	<b>3.0' long x 0.50' rise Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#5	Device 1	46.25'	<b>4.0" x 4.0" Horiz. Orifice/Grate X 106.00</b> C= 0.600 Limited to weir flow at low heads
#6	Secondary	46.50'	<b>20.0' long x 26.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 Coef. (English) 2.68 2.70 2.70 2.64 2.63 2.64 2.64 2.63

**Primary OutFlow** Max=20.19 cfs @ 12.47 hrs HW=46.33' TW=0.00' (Dynamic Tailwater)

- ↑ 1=Culvert (Passes 20.19 cfs of 30.19 cfs potential flow)
- ↑ 2=Orifice/Grate (Orifice Controls 0.52 cfs @ 10.61 fps)
- ↑ 3=Orifice/Grate (Orifice Controls 1.40 cfs @ 8.01 fps)
- ↑ 4=Sharp-Crested Rectangular Weir (Orifice Controls 7.38 cfs @ 5.09 fps)
- ↑ 5=Orifice/Grate (Weir Controls 10.89 cfs @ 0.94 fps)

**Secondary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=39.05' TW=0.00' (Dynamic Tailwater)

- ↑ 6=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Summary for Pond POND 1.1: GRAVEL WETLAND 2**

Inflow Area = 2.154 ac, 45.41% Impervious, Inflow Depth > 3.90" for 10 Year event  
 Inflow = 7.59 cfs @ 12.19 hrs, Volume= 0.700 af  
 Outflow = 0.45 cfs @ 14.92 hrs, Volume= 0.248 af, Atten= 94%, Lag= 164.3 min  
 Primary = 0.45 cfs @ 14.92 hrs, Volume= 0.248 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 52.92' @ 14.92 hrs Surf.Area= 8,402 sf Storage= 21,360 cf  
 Flood Elev= 56.00' Surf.Area= 15,452 sf Storage= 57,777 cf

Plug-Flow detention time= 363.1 min calculated for 0.248 af (35% of inflow)  
 Center-of-Mass det. time= 235.5 min ( 1,044.5 - 809.0 )

Volume	Invert	Avail.Storage	Storage Description
#1	47.05'	57,777 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

**L-0700-13 POST**

Prepared by Tighe & Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=5.58"

Printed 5/21/2018

Page 12

Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
47.05	3,293	0.0	0	0
49.35	3,293	30.0	2,272	2,272
50.00	3,643	80.0	1,803	4,076
51.00	5,106	100.0	4,375	8,450
52.00	6,739	100.0	5,923	14,373
53.00	8,541	100.0	7,640	22,013
54.00	10,628	100.0	9,585	31,597
55.00	13,140	100.0	11,884	43,481
56.00	15,452	100.0	14,296	57,777

Device	Routing	Invert	Outlet Devices
#1	Primary	49.35'	<b>18.0" Round Culvert</b> L= 33.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 49.35' / 47.55' S= 0.0545 ' / Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 1.77 sf
#2	Device 1	49.35'	<b>2.0" Vert. Orifice/Grate</b> C= 0.600
#3	Device 1	52.85'	<b>4.0' long x 2.00' rise Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Device 1	55.50'	<b>4.0" W x 4.0" H Vert. Orifice/Grate X 106.00</b> C= 0.600

**Primary OutFlow** Max=0.45 cfs @ 14.92 hrs HW=52.92' TW=47.39' (Dynamic Tailwater)

- 1=Culvert (Passes 0.45 cfs of 14.30 cfs potential flow)
- 2=Orifice/Grate (Orifice Controls 0.20 cfs @ 8.99 fps)
- 3=Sharp-Crested Rectangular Weir (Weir Controls 0.26 cfs @ 0.88 fps)
- 4=Orifice/Grate ( Controls 0.00 cfs)

**Summary for Pond POND 1.2: GRAVEL WETLAND 3**

Inflow Area = 4.508 ac, 41.29% Impervious, Inflow Depth > 3.80" for 10 Year event  
 Inflow = 16.69 cfs @ 12.15 hrs, Volume= 1.427 af  
 Outflow = 2.12 cfs @ 12.95 hrs, Volume= 0.661 af, Atten= 87%, Lag= 47.5 min  
 Primary = 2.12 cfs @ 12.95 hrs, Volume= 0.661 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 53.78' @ 12.95 hrs Surf.Area= 12,619 sf Storage= 36,585 cf  
 Flood Elev= 56.00' Surf.Area= 19,100 sf Storage= 71,490 cf

Plug-Flow detention time= 263.5 min calculated for 0.661 af (46% of inflow)  
 Center-of-Mass det. time= 148.6 min ( 958.5 - 809.9 )

Volume	Invert	Avail.Storage	Storage Description
#1	47.55'	71,490 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

**L-0700-13 POST**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe & Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 13

Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
47.55	5,882	0.0	0	0
49.85	5,882	30.0	4,059	4,059
50.50	5,882	80.0	3,059	7,117
51.00	6,616	100.0	3,125	10,242
52.00	8,580	100.0	7,598	17,840
53.00	10,713	100.0	9,647	27,486
54.00	13,157	100.0	11,935	39,421
55.00	15,940	100.0	14,549	53,970
56.00	19,100	100.0	17,520	71,490

Device	Routing	Invert	Outlet Devices
#1	Primary	49.85'	<b>24.0" Round Culvert</b> L= 22.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 49.85' / 49.45' S= 0.0182 ' / Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf
#2	Device 1	49.85'	<b>2.0" Vert. Orifice/Grate</b> C= 0.600
#3	Device 1	53.50'	<b>4.0' long x 2.00' rise Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#4	Device 1	55.50'	<b>4.0" W x 4.0" H Vert. Orifice/Grate X 106.00</b> C= 0.600

**Primary OutFlow** Max=2.12 cfs @ 12.95 hrs HW=53.78' TW=49.72' (Dynamic Tailwater)

- 1=Culvert (Passes 2.12 cfs of 25.89 cfs potential flow)
- 2=Orifice/Grate (Orifice Controls 0.21 cfs @ 9.44 fps)
- 3=Sharp-Crested Rectangular Weir (Weir Controls 1.91 cfs @ 1.73 fps)
- 4=Orifice/Grate ( Controls 0.00 cfs)

**Summary for Pond POND 1.5: RAINGARDEN 1.0**

Inflow Area = 4.967 ac, 79.15% Impervious, Inflow Depth > 4.76" for 10 Year event  
 Inflow = 19.34 cfs @ 12.21 hrs, Volume= 1.969 af  
 Outflow = 1.67 cfs @ 13.74 hrs, Volume= 1.665 af, Atten= 91%, Lag= 91.7 min  
 Discarded = 0.09 cfs @ 13.74 hrs, Volume= 0.123 af  
 Primary = 1.58 cfs @ 13.74 hrs, Volume= 1.541 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 48.42' @ 13.74 hrs Surf.Area= 13,235 sf Storage= 46,447 cf  
 Flood Elev= 50.00' Surf.Area= 15,470 sf Storage= 69,161 cf

Plug-Flow detention time= 293.4 min calculated for 1.665 af (85% of inflow)  
 Center-of-Mass det. time= 229.3 min ( 1,011.9 - 782.6 )

Volume	Invert	Avail.Storage	Storage Description
#1	41.35'	69,161 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

**L-0700-13 POST**

Type III 24-hr 10 Year Rainfall=5.58"

Prepared by Tighe &amp; Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 14

Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
41.35	8,830	0.0	0	0
43.50	8,830	40.0	7,594	7,594
45.00	8,830	10.0	1,325	8,918
46.00	10,045	100.0	9,438	18,356
48.00	12,645	100.0	22,690	41,046
50.00	15,470	100.0	28,115	69,161

Device	Routing	Invert	Outlet Devices
#1	Primary	42.42'	<b>6.0" Round Culvert</b> L= 48.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 42.42' / 42.20' S= 0.0046 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Primary	49.25'	<b>10.0' long x 12.5' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 Coef. (English) 2.58 2.63 2.70 2.67 2.66 2.67 2.66 2.63
#3	Discarded	41.35'	<b>0.300 in/hr Exfiltration over Surface area</b> Phase-In= 0.01'

**Discarded OutFlow** Max=0.09 cfs @ 13.74 hrs HW=48.42' (Free Discharge)↑**3=Exfiltration** (Exfiltration Controls 0.09 cfs)**Primary OutFlow** Max=1.58 cfs @ 13.74 hrs HW=48.42' TW=0.00' (Dynamic Tailwater)↑**1=Culvert** (Barrel Controls 1.58 cfs @ 8.04 fps)↑**2=Broad-Crested Rectangular Weir** ( Controls 0.00 cfs)**Summary for Link PA1: POINT OF ANALYSIS**

Inflow Area = 29.832 ac, 55.84% Impervious, Inflow Depth > 3.17" for 10 Year event  
 Inflow = 41.55 cfs @ 12.47 hrs, Volume= 7.880 af  
 Primary = 41.55 cfs @ 12.47 hrs, Volume= 7.880 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

**Summary for Link PA2: POINT OF ANALYSIS**

Inflow Area = 0.060 ac, 100.00% Impervious, Inflow Depth > 5.34" for 10 Year event  
 Inflow = 0.33 cfs @ 12.07 hrs, Volume= 0.027 af  
 Primary = 0.33 cfs @ 12.07 hrs, Volume= 0.027 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs



**L-0700-13 POST**

Type III 24-hr 50 Year Rainfall=8.46"

Prepared by Tighe &amp; Bond

Printed 5/21/2018

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Page 15

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points  
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment POST 1.0: WATERSHED** Runoff Area=412,828 sf 74.83% Impervious Runoff Depth>7.48"  
 Flow Length=1,013' Tc=16.2 min CN=92 Runoff=56.44 cfs 5.910 af

**Subcatchment POST 1.1: WATERSHED 1.1** Runoff Area=93,833 sf 45.41% Impervious Runoff Depth>6.64"  
 Flow Length=738' Tc=13.6 min CN=85 Runoff=12.64 cfs 1.193 af

**Subcatchment POST 1.2: WATERSHED** Runoff Area=196,367 sf 41.29% Impervious Runoff Depth>6.53"  
 Flow Length=641' Tc=11.1 min CN=84 Runoff=28.04 cfs 2.452 af

**Subcatchment POST 1.3: WATERSHED 1.3** Runoff Area=89,680 sf 65.38% Impervious Runoff Depth>7.25"  
 Flow Length=1,602' Tc=7.3 min CN=90 Runoff=15.42 cfs 1.244 af

**Subcatchment POST 1.4: WATERSHED** Runoff Area=290,401 sf 21.74% Impervious Runoff Depth>6.02"  
 Flow Length=1,388' Tc=32.9 min CN=80 Runoff=25.27 cfs 3.346 af

**Subcatchment POST 1.5: WATERSHED** Runoff Area=216,369 sf 79.15% Impervious Runoff Depth>7.60"  
 Flow Length=1,088' Tc=15.7 min CN=93 Runoff=30.14 cfs 3.147 af

**Subcatchment POST 2.1: WATERSHED 2.1** Runoff Area=2,635 sf 100.00% Impervious Runoff Depth>8.22"  
 Tc=5.0 min CN=98 Runoff=0.51 cfs 0.041 af

**Reach REACH 1.2:** Avg. Flow Depth=0.92' Max Vel=5.94 fps Inflow=13.83 cfs 1.677 af  
 54.0" Round Pipe n=0.013 L=395.0' S=0.0059 '/' Capacity=151.68 cfs Outflow=13.82 cfs 1.675 af

**Reach REACH 1.3: HODGSON BROOK** Avg. Flow Depth=1.04' Max Vel=2.24 fps Inflow=23.77 cfs 3.638 af  
 n=0.040 L=1,211.0' S=0.0091 '/' Capacity=2,707.81 cfs Outflow=21.77 cfs 3.621 af

**Pond POND 1.0: GRAVEL WETLAND 1** Peak Elev=46.90' Storage=88,237 cf Inflow=56.44 cfs 5.910 af  
 Primary=32.25 cfs 4.616 af Secondary=13.47 cfs 0.285 af Outflow=45.72 cfs 4.901 af

**Pond POND 1.1: GRAVEL WETLAND 2** Peak Elev=53.40' Storage=25,553 cf Inflow=12.64 cfs 1.193 af  
 Outflow=5.33 cfs 0.718 af

**Pond POND 1.2: GRAVEL WETLAND 3** Peak Elev=54.56' Storage=47,298 cf Inflow=28.04 cfs 2.452 af  
 Outflow=13.83 cfs 1.677 af


**Pond POND 1.5: RAINGARDEN 1.0** Peak Elev=49.71' Storage=64,778 cf Inflow=30.14 cfs 3.147 af  
 Discarded=0.10 cfs 0.141 af Primary=10.10 cfs 2.362 af Outflow=10.21 cfs 2.504 af

**Link PA1: POINT OF ANALYSIS** Inflow=92.68 cfs 14.231 af  
 Primary=92.68 cfs 14.231 af

**Link PA2: POINT OF ANALYSIS** Inflow=0.51 cfs 0.041 af  
 Primary=0.51 cfs 0.041 af


**Total Runoff Area = 29.892 ac Runoff Volume = 17.334 af Average Runoff Depth = 6.96"**  
**44.07% Pervious = 13.174 ac 55.93% Impervious = 16.719 ac**





**LEGEND**

- POST-DEVELOPMENT WATERSHED BOUNDARY
- SOIL BOUNDARY
- LONGEST FLOWPATH
- POST-DEVELOPMENT WATERSHED DESIGNATION
- POST-DEVELOPMENT POND DESIGNATION
- POINT OF ANALYSIS



**HIGH INTENSITY MAP SYMBOL**

**DRAINAGE CLASS**  
5

- EXCESSIVELY DRAINED
- WELL DRAINED
- MODERATELY WELL DRAINED
- SOMEWHAT POORLY DRAINED
- POORLY DRAINED
- VERY POORLY DRAINED
- NOT DETERMINABLE

**PARENT MATERIAL**  
2

- GLACIOFLUVIAL
- GLACIAL TILL
- MARINE OR GLACIOLACUSTRINE VERY FINE SAND AND SILT
- MARINE OR GLACIOLACUSTRINE LOAMY/SANDY OVER SILT/CLAY
- MARINE OR GLACIOLACUSTRINE SILT AND CLAY
- EXCAVATED, REGRADED, OR FILLED
- ALLUVIAL DEPOSITS
- ORGANIC MATERIALS FRESH WATER
- ORGANIC MATERIALS TIDAL MARSH

**RESTRICTIVE FEATURES**  
3

- NONE
- BOULDERY, WITH MORE THAN 15% OF SURFACE COVERED
- MINERAL RESTRICTIVE LAYER(S) AREA PRESENT AT LESS THAN 40 IN. DEPTH.
- BEDROCK 0 IN. TO 20 IN. DEPTH.
- SUBJECT TO FLOODING
- DOES NOT MEET FILL STANDARDS.
- DEPTH TO BEDROCK VARIABLE, COMPLEX OF SOIL TYPES.

**IDENTIFIER**  
H  
H. INDICATES HIGH INTENSITY SOIL MAP  
P. INDICATES PRELIMINARY MAP

**SLOPE CLASS**  
B  
B. 0 TO 8%  
C. 8 TO 15%  
D. 15 TO 25%  
E. MORE THAN 25%

HIGH INTENSITY MAP SYMBOL 523BH INDICATES A POORLY DRAINED GLACIAL TILL SOIL WITH A RESTRICTIVE FEATURE, ON A SLOPE OF 0 TO 8%

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
1	4/3/2018	TAC WS SUBMISSION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-C-801 to C-804.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: GMM		

**POST-DEVELOPMENT WATERSHED AREA PLAN**


SCALE: AS SHOWN

**C-802**


Last Save Date: May 21, 2018 11:09 AM By: BCLARK  
 Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
 File Location: J:\L0700\Lonza Biologics Expansion.was\_127620\013 Iron Parcel Redevelopment\Drawings\_Figures\AutoCAD\Sheet\L0700-C-801 to C-804.dwg Layout Tab: C-802







- POST-DEVELOPMENT WATERSHED BOUNDARY
- SOIL BOUNDARY
- LONGEST FLOWPATH
- POST-DEVELOPMENT WATERSHED DESIGNATION
- POST-DEVELOPMENT POND DESIGNATION
- PA1



**HYDROLOGIC SOIL GROUP RATING**

- IMPERVIOUS AREA
- HYDROLOGIC SOIL GROUP A
- HYDROLOGIC SOIL GROUP B
- HYDROLOGIC SOIL GROUP C
- HYDROLOGIC SOIL GROUP D

**HIGH INTENSITY MAP SYMBOL DRAINAGE CLASS**  
5

- EXCESSIVELY DRAINED
- WELL DRAINED
- MODERATELY WELL DRAINED
- SOMEWHAT POORLY DRAINED
- POORLY DRAINED
- VERY POORLY DRAINED
- NOT DETERMINABLE

**PARENT MATERIAL**  
2

- GLACIOFLUVIAL
- GLACIAL TILL
- MARINE OR GLACIOLACUSTRINE VERY FINE SAND AND SILT
- MARINE OR GLACIOLACUSTRINE LOAMY/SANDY OVER SILT/CLAY
- MARINE OR GLACIOLACUSTRINE SILT AND CLAY
- EXCAVATED, REGRADED, OR FILLED
- ALLUVIAL DEPOSITS
- ORGANIC MATERIALS FRESH WATER
- ORGANIC MATERIALS TIDAL MARSH

**SLOPE CLASS**  
3

- 0 TO 8%
- 8 TO 15%
- 15 TO 25%
- MORE THAN 25%

**RESTRICTIVE FEATURES**  
3

- NONE
- BOULDERY, WITH MORE THAN 15% OF SURFACE COVERED
- MINERAL RESTRICTIVE LAYER(S) AREA PRESENT AT LESS THAN 40 IN. DEPTH.
- BEDROCK 0 IN. TO 20 IN. DEPTH.
- SUBJECT TO FLOODING
- DOES NOT MEET FILL STANDARDS.
- DEPTH TO BEDROCK VARIABLE, COMPLEX OF SOIL TYPES.

**IDENTIFIER**  
H  
H. INDICATES HIGH INTENSITY SOIL MAP  
P. INDICATES PRELIMINARY MAP

**523BH**  
HIGH INTENSITY MAP SYMBOL 523BH INDICATES A POORLY DRAINED GLACIAL TILL SOIL WITH A RESTRICTIVE FEATURE, ON A SLOPE OF 0 TO 8%.

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-C-801 to C-804\_CLR.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: GMM

**POST-DEVELOPMENT SOIL PLAN**

SCALE: AS SHOWN

**C-804**

Last Save Date: May 21, 2018 11:38 AM By: BCLARK  
 Plot Date: Thursday, July 26, 2018 Plotted By: Barbara J. Lamb  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was\_15749\013 Iron Parcel Redevelopment\Drawings\_E\Figures\AutoCAD\Sheet\L0700-C-801 to C-804.dwg Layout Tab: C-804







**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Area-Storage for Pond POND 1.0: GRAVEL WETLAND 1**

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)	Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
39.05	9,854	0	44.35	15,143	41,030
39.15	9,854	296	44.45	15,412	42,558
39.25	9,854	591	44.55	15,681	44,112
39.35	9,854	887	44.65	15,950	45,694
39.45	9,854	1,182	44.75	16,219	47,302
39.55	9,854	1,478	44.85	16,488	48,937
39.65	9,854	1,774	44.95	16,757	50,600
39.75	9,854	2,069	45.05	17,034	52,289
39.85	9,854	2,365	45.15	17,320	54,007
39.95	9,854	2,661	45.25	17,606	55,753
40.05	9,854	2,956	45.35	17,892	57,528
40.15	9,854	3,252	45.45	18,178	59,331
40.25	9,854	3,547	45.55	18,465	61,164
40.35	9,854	3,843	45.65	18,751	63,024
40.45	9,854	4,139	45.75	19,037	64,914
40.55	9,854	4,434	45.85	19,323	66,832
40.65	9,854	4,730	45.95	19,609	68,778
40.75	9,854	5,026	46.05	19,848	70,752
40.85	9,854	5,321	46.15	20,039	72,747
40.95	9,854	5,617	46.25	20,231	74,760
41.05	9,854	5,912	46.35	20,423	76,793
41.15	9,854	6,208	46.45	20,614	78,845
41.25	9,854	6,504	46.55	20,806	80,916
41.35	9,854	6,799	46.65	20,997	83,006
41.45	9,854	7,588	46.75	21,189	85,115
41.55	9,854	8,376	46.85	21,381	87,244
41.65	9,854	9,164	46.95	21,572	89,391
41.75	9,854	9,953	47.05	21,762	91,558
41.85	9,854	10,741	47.15	21,951	93,744
41.95	9,854	11,529	47.25	22,140	95,948
42.05	9,958	12,419	47.35	22,329	98,172
42.15	10,167	13,425	47.45	22,518	100,414
42.25	10,376	14,452	47.55	22,707	102,675
42.35	10,585	15,500	47.65	22,896	104,956
42.45	10,794	16,569	47.75	23,085	107,255
42.55	11,003	17,659	47.85	23,274	109,573
42.65	11,212	18,770	47.95	<b>23,463</b>	<b>111,909</b>
42.75	11,421	19,901			
42.85	11,630	21,054			
42.95	11,839	22,227			
43.05	12,056	23,422			
43.15	12,282	24,639			
43.25	12,508	25,878			
43.35	12,734	27,140			
43.45	12,960	28,425			
43.55	13,185	29,732			
43.65	13,411	31,062			
43.75	13,637	32,414			
43.85	13,863	33,789			
43.95	14,089	35,187			
44.05	14,336	36,608			
44.15	14,605	38,055			
44.25	14,874	39,529			



**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Discharge for Pond POND 1.0: GRAVEL WETLAND 1**

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)
39.05	0.00	0.00	0.00	44.35	1.14	1.14	0.00
39.15	0.00	0.00	0.00	44.45	1.20	1.20	0.00
39.25	0.00	0.00	0.00	44.55	1.25	1.25	0.00
39.35	0.00	0.00	0.00	44.65	1.30	1.30	0.00
39.45	0.00	0.00	0.00	44.75	1.34	1.34	0.00
39.55	0.00	0.00	0.00	44.85	1.39	1.39	0.00
39.65	0.00	0.00	0.00	44.95	1.43	1.43	0.00
39.75	0.00	0.00	0.00	45.05	1.58	1.58	0.00
39.85	0.00	0.00	0.00	45.15	2.07	2.07	0.00
39.95	0.00	0.00	0.00	45.25	2.76	2.76	0.00
40.05	0.00	0.00	0.00	45.35	3.57	3.57	0.00
40.15	0.00	0.00	0.00	45.45	4.50	4.50	0.00
40.25	0.00	0.00	0.00	45.55	5.42	5.42	0.00
40.35	0.00	0.00	0.00	45.65	6.11	6.11	0.00
40.45	0.00	0.00	0.00	45.75	6.70	6.70	0.00
40.55	0.00	0.00	0.00	45.85	7.23	7.23	0.00
40.65	0.00	0.00	0.00	45.95	7.72	7.72	0.00
40.75	0.00	0.00	0.00	46.05	8.16	8.16	0.00
40.85	0.00	0.00	0.00	46.15	8.59	8.59	0.00
40.95	0.00	0.00	0.00	46.25	8.99	8.99	0.00
41.05	0.00	0.00	0.00	46.35	23.98	23.98	0.00
41.15	0.00	0.00	0.00	46.45	30.63	30.63	0.00
41.25	0.00	0.00	0.00	46.55	31.60	31.00	0.60
41.35	0.00	0.00	0.00	46.65	34.48	31.37	3.11
41.45	0.02	0.02	0.00	46.75	38.44	31.73	6.71
41.55	0.06	0.06	0.00	46.85	43.25	32.09	11.16
41.65	0.10	0.10	0.00	46.95	48.74	32.44	16.30
41.75	0.12	0.12	0.00	47.05	54.82	32.79	22.03
41.85	0.14	0.14	0.00	47.15	61.28	33.14	28.14
41.95	0.16	0.16	0.00	47.25	67.97	33.48	34.49
42.05	0.18	0.18	0.00	47.35	75.16	33.82	41.34
42.15	0.19	0.19	0.00	47.45	82.91	34.16	48.75
42.25	0.21	0.21	0.00	47.55	91.14	34.49	56.65
42.35	0.22	0.22	0.00	47.65	99.88	34.82	65.05
42.45	0.23	0.23	0.00	47.75	108.94	35.15	73.79
42.55	0.25	0.25	0.00	47.85	118.30	35.48	82.82
42.65	0.26	0.26	0.00	47.95	<b>127.90</b>	<b>35.80</b>	<b>92.10</b>
42.75	0.27	0.27	0.00				
42.85	0.28	0.28	0.00				
42.95	0.29	0.29	0.00				
43.05	0.30	0.30	0.00				
43.15	0.31	0.31	0.00				
43.25	0.31	0.31	0.00				
43.35	0.32	0.32	0.00				
43.45	0.34	0.34	0.00				
43.55	0.44	0.44	0.00				
43.65	0.59	0.59	0.00				
43.75	0.72	0.72	0.00				
43.85	0.81	0.81	0.00				
43.95	0.89	0.89	0.00				
44.05	0.96	0.96	0.00				
44.15	1.03	1.03	0.00				
44.25	1.09	1.09	0.00				





**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Area-Storage for Pond POND 1.1: GRAVEL WETLAND 2**

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)	Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
47.05	3,293	0	52.35	7,370	16,842
47.15	3,293	99	52.45	7,550	17,588
47.25	3,293	198	52.55	7,730	18,352
47.35	3,293	296	52.65	7,910	19,134
47.45	3,293	395	52.75	8,091	19,934
47.55	3,293	494	52.85	8,271	20,752
47.65	3,293	593	52.95	8,451	21,588
47.75	3,293	692	53.05	8,645	22,442
47.85	3,293	790	53.15	8,854	23,317
47.95	3,293	889	53.25	9,063	24,213
48.05	3,293	988	53.35	9,271	25,130
48.15	3,293	1,087	53.45	9,480	26,067
48.25	3,293	1,185	53.55	9,689	27,026
48.35	3,293	1,284	53.65	9,898	28,005
48.45	3,293	1,383	53.75	10,106	29,005
48.55	3,293	1,482	53.85	10,315	30,026
48.65	3,293	1,581	53.95	10,524	31,068
48.75	3,293	1,679	54.05	10,754	32,132
48.85	3,293	1,778	54.15	11,005	33,219
48.95	3,293	1,877	54.25	11,256	34,333
49.05	3,293	1,976	54.35	11,507	35,471
49.15	3,293	2,075	54.45	11,758	36,634
49.25	3,293	2,173	54.55	12,010	37,822
49.35	3,293	2,272	54.65	12,261	39,036
49.45	3,347	2,538	54.75	12,512	40,275
49.55	3,401	2,808	54.85	12,763	41,538
49.65	3,455	3,082	54.95	13,014	42,827
49.75	3,508	3,360	55.05	13,256	44,141
49.85	3,562	3,643	55.15	13,487	45,478
49.95	3,616	3,930	55.25	13,718	46,838
50.05	3,716	4,260	55.35	13,949	48,222
50.15	3,862	4,638	55.45	14,180	49,628
50.25	4,009	5,032	55.55	14,412	51,058
50.35	4,155	5,440	55.65	14,643	52,510
50.45	4,301	5,863	55.75	14,874	53,986
50.55	4,448	6,300	55.85	15,105	55,485
50.65	4,594	6,753	55.95	<b>15,336</b>	<b>57,007</b>
50.75	4,740	7,219			
50.85	4,887	7,701			
50.95	5,033	8,197			
51.05	5,188	8,707			
51.15	5,351	9,234			
51.25	5,514	9,778			
51.35	5,678	10,337			
51.45	5,841	10,913			
51.55	6,004	11,505			
51.65	6,167	12,114			
51.75	6,331	12,739			
51.85	6,494	13,380			
51.95	6,657	14,038			
52.05	6,829	14,712			
52.15	7,009	15,404			
52.25	7,190	16,114			

**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Discharge for Pond POND 1.1: GRAVEL WETLAND 2**

Elevation (feet)	Primary (cfs)	Elevation (feet)	Primary (cfs)
47.05	0.00	52.35	0.18
47.15	0.00	52.45	0.18
47.25	0.00	52.55	0.19
47.35	0.00	52.65	0.19
47.45	0.00	52.75	0.19
47.55	0.00	52.85	0.19
47.65	0.00	52.95	0.61
47.75	0.00	53.05	1.36
47.85	0.00	53.15	2.32
47.95	0.00	53.25	3.45
48.05	0.00	53.35	4.72
48.15	0.00	53.45	6.11
48.25	0.00	53.55	7.61
48.35	0.00	53.65	9.20
48.45	0.00	53.75	10.88
48.55	0.00	53.85	12.65
48.65	0.00	53.95	14.48
48.75	0.00	54.05	16.39
48.85	0.00	54.15	17.12
48.95	0.00	54.25	17.33
49.05	0.00	54.35	17.54
49.15	0.00	54.45	17.75
49.25	0.00	54.55	17.95
49.35	0.00	54.65	18.15
49.45	0.01	54.75	18.35
49.55	0.04	54.85	18.54
49.65	0.05	54.95	18.74
49.75	0.06	55.05	18.93
49.85	0.07	55.15	19.12
49.95	0.08	55.25	19.31
50.05	0.08	55.35	19.50
50.15	0.09	55.45	19.68
50.25	0.09	55.55	19.86
50.35	0.10	55.65	20.05
50.45	0.11	55.75	20.23
50.55	0.11	55.85	20.40
50.65	0.12	55.95	<b>20.58</b>
50.75	0.12		
50.85	0.13		
50.95	0.13		
51.05	0.13		
51.15	0.14		
51.25	0.14		
51.35	0.15		
51.45	0.15		
51.55	0.15		
51.65	0.16		
51.75	0.16		
51.85	0.16		
51.95	0.17		
52.05	0.17		
52.15	0.17		
52.25	0.18		





**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Area-Storage for Pond POND 1.2: GRAVEL WETLAND 3**

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)	Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
47.55	5,882	0	52.85	10,393	25,903
47.65	5,882	176	52.95	10,606	26,953
47.75	5,882	353	53.05	10,835	28,025
47.85	5,882	529	53.15	11,080	29,121
47.95	5,882	706	53.25	11,324	30,241
48.05	5,882	882	53.35	11,568	31,385
48.15	5,882	1,059	53.45	11,813	32,555
48.25	5,882	1,235	53.55	12,057	33,748
48.35	5,882	1,412	53.65	12,302	34,966
48.45	5,882	1,588	53.75	12,546	36,208
48.55	5,882	1,765	53.85	12,790	37,475
48.65	5,882	1,941	53.95	13,035	38,766
48.75	5,882	2,118	54.05	13,296	40,083
48.85	5,882	2,294	54.15	13,574	41,426
48.95	5,882	2,470	54.25	13,853	42,797
49.05	5,882	2,647	54.35	14,131	44,197
49.15	5,882	2,823	54.45	14,409	45,624
49.25	5,882	3,000	54.55	14,688	47,078
49.35	5,882	3,176	54.65	14,966	48,561
49.45	5,882	3,353	54.75	15,244	50,072
49.55	5,882	3,529	54.85	15,523	51,610
49.65	5,882	3,706	54.95	15,801	53,176
49.75	5,882	3,882	55.05	16,098	54,771
49.85	5,882	4,059	55.15	16,414	56,396
49.95	5,882	4,235	55.25	16,730	58,053
50.05	5,882	4,412	55.35	17,046	59,742
50.15	5,882	4,588	55.45	17,362	61,463
50.25	5,882	4,765	55.55	17,678	63,215
50.35	5,882	4,941	55.65	17,994	64,998
50.45	5,882	5,118	55.75	18,310	66,813
50.55	5,955	5,294	55.85	18,626	68,660
50.65	6,102	5,470	55.95	<b>18,942</b>	<b>70,539</b>
50.75	6,249	5,647			
50.85	6,396	5,823			
50.95	6,543	6,000			
51.05	6,714	6,176			
51.15	6,911	6,353			
51.25	7,107	6,529			
51.35	7,303	6,706			
51.45	7,500	6,882			
51.55	7,696	7,059			
51.65	7,893	7,235			
51.75	8,089	7,412			
51.85	8,285	7,588			
51.95	8,482	7,765			
52.05	8,687	7,941			
52.15	8,900	8,118			
52.25	9,113	8,294			
52.35	9,327	8,470			
52.45	9,540	8,647			
52.55	9,753	8,823			
52.65	9,966	9,000			
52.75	10,180	9,176			



**L-0700-13 POST**

Prepared by Tighe &amp; Bond

HydroCAD® 10.00-15 s/n 03436 © 2015 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Rainfall=8.46"

Printed 5/21/2018

**Stage-Discharge for Pond POND 1.2: GRAVEL WETLAND 3**

Elevation (feet)	Primary (cfs)	Elevation (feet)	Primary (cfs)	Elevation (feet)	Primary (cfs)	Elevation (feet)	Primary (cfs)
47.55	0.00	49.67	0.00	51.79	0.14	53.91	3.57
47.59	0.00	49.71	0.00	51.83	0.14	53.95	4.07
47.63	0.00	49.75	0.00	51.87	0.15	53.99	4.59
47.67	0.00	49.79	0.00	51.91	0.15	54.03	5.13
47.71	0.00	49.83	0.00	51.95	0.15	54.07	5.68
47.75	0.00	49.87	0.00	51.99	0.15	54.11	6.26
47.79	0.00	49.91	0.01	52.03	0.15	54.15	6.85
47.83	0.00	49.95	0.01	52.07	0.15	54.19	7.45
47.87	0.00	49.99	0.02	52.11	0.15	54.23	8.08
47.91	0.00	50.03	0.03	52.15	0.16	54.27	8.72
47.95	0.00	50.07	0.04	52.19	0.16	54.31	9.37
47.99	0.00	50.11	0.04	52.23	0.16	54.35	10.04
48.03	0.00	50.15	0.05	52.27	0.16	54.39	10.72
48.07	0.00	50.19	0.05	52.31	0.16	54.43	11.41
48.11	0.00	50.23	0.06	52.35	0.16	54.47	12.11
48.15	0.00	50.27	0.06	52.39	0.16	54.51	12.83
48.19	0.00	50.31	0.06	52.43	0.17	54.55	13.56
48.23	0.00	50.35	0.07	52.47	0.17	54.59	14.30
48.27	0.00	50.39	0.07	52.51	0.17	54.63	15.05
48.31	0.00	50.43	0.07	52.55	0.17	54.67	15.81
48.35	0.00	50.47	0.08	52.59	0.17	54.71	16.59
48.39	0.00	50.51	0.08	52.63	0.17	54.75	17.37
48.43	0.00	50.55	0.08	52.67	0.17	54.79	18.16
48.47	0.00	50.59	0.09	52.71	0.18	54.83	18.96
48.51	0.00	50.63	0.09	52.75	0.18	54.87	19.77
48.55	0.00	50.67	0.09	52.79	0.18	54.91	20.59
48.59	0.00	50.71	0.09	52.83	0.18	54.95	21.42
48.63	0.00	50.75	0.09	52.87	0.18	54.99	22.25
48.67	0.00	50.79	0.10	52.91	0.18	55.03	23.10
48.71	0.00	50.83	0.10	52.95	0.18	55.07	23.95
48.75	0.00	50.87	0.10	52.99	0.18	55.11	24.81
48.79	0.00	50.91	0.10	53.03	0.18	55.15	25.68
48.83	0.00	50.95	0.11	53.07	0.19	55.19	26.55
48.87	0.00	50.99	0.11	53.11	0.19	55.23	27.43
48.91	0.00	51.03	0.11	53.15	0.19	55.27	28.32
48.95	0.00	51.07	0.11	53.19	0.19	55.31	29.21
48.99	0.00	51.11	0.11	53.23	0.19	55.35	30.11
49.03	0.00	51.15	0.12	53.27	0.19	55.39	31.02
49.07	0.00	51.19	0.12	53.31	0.19	55.43	31.93
49.11	0.00	51.23	0.12	53.35	0.19	55.47	32.51
49.15	0.00	51.27	0.12	53.39	0.20	55.51	32.65
49.19	0.00	51.31	0.12	53.43	0.20	55.55	32.79
49.23	0.00	51.35	0.13	53.47	0.20	55.59	32.93
49.27	0.00	51.39	0.13	53.51	0.21	55.63	33.07
49.31	0.00	51.43	0.13	53.55	0.35	55.67	33.21
49.35	0.00	51.47	0.13	53.59	0.55	55.71	33.35
49.39	0.00	51.51	0.13	53.63	0.81	55.75	33.48
49.43	0.00	51.55	0.13	53.67	1.11	55.79	33.62
49.47	0.00	51.59	0.14	53.71	1.45	55.83	33.76
49.51	0.00	51.63	0.14	53.75	1.82	55.87	33.89
49.55	0.00	51.67	0.14	53.79	2.22	55.91	34.03
49.59	0.00	51.71	0.14	53.83	2.65	55.95	34.16
49.63	0.00	51.75	0.14	53.87	3.10	55.99	<b>34.29</b>














# PROPOSED INDUSTRIAL DEVELOPMENT

## 70 & 80 CORPORATE DRIVE PORTSMOUTH, NEW HAMPSHIRE PROJECT NO: L-0700-13

MAY 21, 2018



LIST OF DRAWINGS		
SHEET NO.	SHEET TITLE	LAST REVISED
	COVER SHEET	05/21/2018
1 of 4	EXISTING CONDITIONS PLAN	08/03/2016
2 of 4	EXISTING CONDITIONS PLAN	08/03/2016
3 of 4	EXISTING CONDITIONS PLAN	08/03/2016
4 of 4	EXISTING CONDITIONS PLAN	08/03/2016
C-101	DEMOLITION PLAN	05/21/2018
C-102	DEMOLITION PLAN	05/21/2018
C-103	DEMOLITION PLAN	05/21/2018
C-104	OVERALL SITE PLAN	05/21/2018
C-105	SITE PLAN	05/21/2018
C-106	SITE PLAN	05/21/2018
C-107	SITE PLAN	05/21/2018
C-108	GRADING, DRAINAGE & EROSION CONTROL PLAN	05/21/2018
C-109	GRADING, DRAINAGE & EROSION CONTROL PLAN	05/21/2018
C-110	GRADING, DRAINAGE & EROSION CONTROL PLAN	05/21/2018
C-111	UTILITIES PLAN	05/21/2018
C-112	UTILITIES PLAN	05/21/2018
C-113	UTILITIES PLAN	05/21/2018
C-114	LANDSCAPE PLAN	05/21/2018
C-115	LANDSCAPE PLAN	05/21/2018
C-116	LANDSCAPE PLAN	05/21/2018
C-117	PHOTOMETRIC LIGHTING PLAN	05/21/2018
C-118	PHOTOMETRIC LIGHTING PLAN	05/21/2018
C-119	PHOTOMETRIC LIGHTING PLAN	05/21/2018
C-501	EROSION CONTROL NOTES & DETAILS SHEET	05/21/2018
C-502	DETAILS SHEET	05/21/2018
C-503	DETAILS SHEET	05/21/2018
C-504	DETAILS SHEET	05/21/2018
C-505	DETAILS SHEET	05/21/2018
C-506	DETAILS SHEET	05/21/2018
C-507	DETAILS SHEET	05/21/2018
C-508	DETAILS SHEET	05/21/2018
C-701	HODGSON BROOK GRADING, DRAINAGE & EROSION CONTROL PLAN	05/21/2018
C-702	HODGSON BROOK WETLAND PLANTING PLAN	05/21/2018
C-703	HODGSON BROOK DETAILS SHEET	05/21/2018



LOCATION MAP  
SCALE: 1" = 2,000'

- OWNER: PEASE DEVELOPMENT AUTHORITY  
55 INTERNATIONAL DRIVE  
PORTSMOUTH, NEW HAMPSHIRE 03801
- CLIENT: LONZA BIOLOGICS  
101 INTERNATIONAL DRIVE  
PORTSMOUTH, NH 03801
- CIVIL ENGINEER: **Tighe&Bond**  
Engineers | Environmental Specialists  
177 CORPORATE DRIVE  
PORTSMOUTH, NEW HAMPSHIRE 03801
- SURVEYOR: DOUCET SURVEY, INC.  
102 KENT PLACE  
NEWMARKET, NEW HAMPSHIRE 03857
- WETLAND SCIENTIST: GOVE ENVIRONMENTAL SERVICES, INC.  
8 CONTINENTAL DRIVE, UNIT H  
EXETER, NEW HAMPSHIRE 03833
- STREAM DESIGN CONSULTANT: STREAMWORKS, PLLC  
MADBURY, NEW HAMPSHIRE 03823

**COMPLETE SET 35 SHEETS**




DRAINAGE STRUCTURE TABLE			
CB #1013 RIM ELEV.=68.4' (1019) 18" HDPE INV.=64.4' (A) 18" HDPE INV.=64.4'	CBR #1324 RIM ELEV.=55.7' (A) 12" RCP INV.=52.3' (1325) 12" RCP INV.=51.9' (1305) 15" RCP INV.=51.9' (B) 22" RCP INV.=51.7'	CB #1461 RIM ELEV.=59.9' (1460) 12" RCP INV.=53.2'	CB #1732 RIM ELEV.=39.1' (1695) 10" RCP INV.=37.3'
CB #1019 RIM ELEV.=68.5' (A) 18" HDPE INV.=65.1' (1013) 18" HDPE INV.=64.7'	CB #1325 RIM ELEV.=55.7' (1399) 15" RCP INV.=51.9' (1324) 12" RCP INV.=51.8'	CB #1478 RIM ELEV.=54.2' (1515) 12" RCP INV.=47.2'	CBR #1733 RIM ELEV.=39.1' STRUCTURE DAMAGED
CB #1088 RIM ELEV.=66.6' (A) 6" HDPE INV.=62.0' (1111) 12" RCP INV.=61.6' (1095) 12" RCP INV.=61.6'	DMH #1338 RIM ELEV.=57.7' (SUMP)=49.9' (LARGE VAULT)	CB #1504 RIM ELEV.=48.9' (A) 12" RCP INV.=42.7' (1484) 12" RCP INV.=42.6'	DMH #1755 RIM ELEV.=42' (A) 24" RCP INV.=37.2' (B) 24" RCP INV.=37.1'
DMH #1095 RIM ELEV.=65.2' (1088) 12" RCP INV.=60.0' (1137) 12" RCP INV.=59.7'	CB #1345 RIM ELEV.=58.1' (1420) 12" RCP INV.=53.9'	CB #1515 RIM ELEV.=54.1' (1756) 12" RCP INV.=38.1' (A) 12" RCP INV.=33.5'	CB #1769 RIM ELEV.=42.5' (1769) 12" RCP INV.=39.2'
CB #1111 RIM ELEV.=66.8' (1088) 12" RCP INV.=61.9'	CB #1381 RIM ELEV.=57.2' (1212) 15" RCP INV.=54.3' (1311) 15" RCP INV.=54.4'	CB #1542 RIM ELEV.=44.4' (1651) 12" RCP INV.=41.0'	CB #1935 RIM ELEV.=49.7' NOT OPENED - SILT SOCK
CB #1137 RIM ELEV.=60.7' (1095) 12" RCP INV.=57.3' (1285) 15" RCP INV.=56.8' (1141) 15" RCP INV.=56.8'	CB #1399 RIM ELEV.=55.5' (1325) 15" RCP INV.=52.3'	CB #1570 RIM ELEV.=40.7' (A) 18" RCP INV.=36.2' (B) 18" RCP INV.=36.2'	CB #2031 RIM ELEV.=59.0' NOT OPENED - SILT SOCK
DMH #1141 RIM ELEV.=61.1' (1300) 12" RCP INV.=57.2' (1137) 15" RCP INV.=56.9' (1147) 15" RCP INV.=56.6' (A) 15" RCP INV.=56.4' (B) 18" ASB INV.=56.3'	DMH #1401 RIM ELEV.=58.3' NOT OPENED - OFF SITE	CB #1572 RIM ELEV.=42.2' (1611) 12" RCP INV.=38.2'	DMH #2142 RIM ELEV.=62.8' (A) 24" HDPE INV.=58.2' (B) 24" HDPE INV.=56.8'
CB #1147 RIM ELEV.=61.5' (A) 15" RCP INV.=57.2' (1141) 15" RCP INV.=57.1'	DMH #1408 RIM ELEV.=56.8' NOT OPENED - OFF SITE	CB #1580 RIM ELEV.=41.7' (1586) 15" RCP INV.=36.8'	CB #2152 RIM ELEV.=64.3' NOT OPENED - SILT SOCK
CB #1183 RIM ELEV.=60.1' (1212) 15" RCP INV.=55.7'	CB #1420 RIM ELEV.=58.1' (1345) 12" RCP INV.=54.4' (1421) 12" HDPE INV.=54.1'	CB #1586 RIM ELEV.=41.9' (1580) 15" RCP INV.=36.4' (A) 15" RCP INV.=36.6'	DMH #2153 RIM ELEV.=64.5' (SUMP) INV.=53.9' FULL OF WATER
CB #1212 RIM ELEV.=57.5' (1183) 15" RCP INV.=54.8' (1381) 15" RCP INV.=54.6'	DMH #1421 RIM ELEV.=57.4' (1420) 12" RCP INV.=54.3' SUMP=53.4' (FULL OF SILT)	CB #1611 RIM ELEV.=42.4' (1572) 12" RCP INV.=37.8' (A) 12" RCP INV.=37.5'	CB #2170 RIM ELEV.=65.7' NOT OPENED - SILT SOCK
CB #1255 RIM ELEV.=60.7' (1137) 15" RCP INV.=57.0'	DMH #1438 RIM ELEV.=50.2' (A) 12" RCP INV.=44.6' (1439) 12" RCP INV.=44.6' (B) UNK. CMP INV.=42.9' (C) UNK. CMP INV.=42.9'	CB #1651 RIM ELEV.=44.6' (1542) 12" RCP INV.=39.5' (A) 12" RCP INV.=39.5'	CBR #2327 RIM ELEV.=40.2' (A) 12" RCP INV.=38.3'
CBR #1305 RIM ELEV.=56.7' (1311) 12" RCP INV.=52.8' (A) 15" RCP INV.=52.7' (1324) 15" RCP INV.=52.7'	CBR #1439 RIM ELEV.=47.4' (1438) 12" RCP INV.=45.2'	CB #1678 RIM ELEV.=39.2' (TOP OF WATER) INV.=36.5' (A) 12" RCP INV.=35.4'	CBR #2329 RIM ELEV.=47.4' (A) 12" RCP INV.=42.0'
CB #1311 RIM ELEV.=57.1' (1381) 15" RCP INV.=53.4' (1305) 12" RCP INV.=53.0'	CBR #1444 RIM ELEV.=48.3' 12" HDPE INV.=46.4' (SUMP) INV.=42.8'	CB #1685 RIM ELEV.=39.2' (TOP OF WATER) INV.=36.6' (2330) 12" RCP INV.=36.4'	DMH #2330 RIM ELEV.=40.4' (1685) 12" RCP INV.=36.5' (A) 12" RCP INV.=36.3' (B) 15" RCP INV.=36.1'
	DMH #1460 RIM ELEV.=58' (1461) 12" RCP INV.=51.6' (1456) 12" RCP INV.=51.5' (A) 15" RCP INV.=50.7'	DMH #1695 RIM ELEV.=42.8' (1732) 10" RCP INV.=36.4' (A) 48" RCP INV.=35.9' (B) NOT MEASURED (RECESSED - LARGE VAULT)	DMH #2336 RIM ELEV.=39.7' (A) 18" RCP INV.=36.1' (B) 24" RCP INV.=35.4'


SEWER STRUCTURE TABLE	
SMH #1062 RIM ELEV.=69.8' (A) 6" CLAY INV.=63.9' (B) 6" CLAY INV.=63.7' (1067) 8" CLAY INV.=62.6'	SMH #1551 RIM ELEV.=43.6' (A) 8" PVC INV.=35.6' (B) 12" UNK. INV.=34.2' (C) 12" UNK. INV.=34.1'
SMH #1067 RIM ELEV.=68.6' (1062) 8" CLAY INV.=60.4' (2242) 8" UNK. INV.=60.3'	SMH #1691 RIM ELEV.=39.9' (1784) UNK. INV.=34.2' (1722) UNK. INV.=34.1'
SMH #1078 RIM ELEV.=69.0' COULD NOT OPEN	SMH #1722 RIM ELEV.=41.1' (A) 6" CLAY INV.=33.2' (1691) UNK. CLAY INV.=33.1'
SMH #1123 RIM ELEV.=64' (1295) 8" PVC INV.=55.8'	SMH #1784 RIM ELEV.=41.1' (1921) 10" UNK. INV.=35.4' (1691) 10" UNK. INV.=35.5'
SMH #1169 RIM ELEV.=65.2' (1184) 15" STEEL INV.=53.8' (A) 15" STEEL INV.=53.8'	SMH #1921 RIM ELEV.=44.8' (1953) UNK. INV.=37' (1784) UNK. INV.=36.9'
SMH #1184 RIM ELEV.=60.4' (1296) 8" CLAY INV.=54.2' (1217) 15" STEEL INV.=52.7' (1169) 15" STEEL INV.=52.7'	SMH #1953 RIM ELEV.=50.1' (A) 6" CLAY INV.=42.4' (2080) UNK. INV.=42.2' (1921) UNK. INV.=42.2'
SMH #1217 RIM ELEV.=57.9' (1184) 15" STEEL INV.=52.3' (1400) 15" STEEL INV.=52.2'	SMH #2080 RIM ELEV.=57.9' (A) 8" UNK. INV.=50.1' 2187" 8" UNK. INV.=50.1' (1953) 8" UNK. INV.=49.9'
SMH #1296 RIM ELEV.=63.7' (1123) 8" PVC INV.=55.5' (2326) 8" UNK. INV.=55.0' (1184) 8" UNK. INV.=55.0'	SMH #2187 RIM ELEV.=63' (A) 6" PVC INV.=54.9' (2242) 8" PVC INV.=54.9' (2080) 8" PVC INV.=54.9'
SMH #1400 RIM ELEV.=55.6' (1217) 15" ASB INV.=49.3' (1415) 15" ASB INV.=49.3'	SMH #2242 RIM ELEV.=65.0' (1067) 8" CLAY INV.=56.8' (2187) 8" CLAY INV.=57.0'
SMH #1415 RIM ELEV.=57.9' (A) 12" PVC INV.=48.3' (1400) 18" UNK. INV.=47.9' (1450) 18" PVC INV.=48.0'	SMH #2326 RIM ELEV.=68.1' (1078) 8" PVC INV.=62.2' (1296) 8" ASB INV.=62.1'
SMH #1450 RIM ELEV.=60.5' (1415) 18" PVC INV.=47.6' (1459) 18" PVC INV.=47.5'	SMH #2328 RIM ELEV.=43.1' (1551) 12" UNK. INV.=32.3' (A) 18" UNK. INV.=32.3'
SMH #1459 RIM ELEV.=58.8' (A) 8" PVC INV.=48.4' (1450) 18" PVC INV.=47.1' (B) 18" PVC INV.=47.1'	

- REFERENCE PLANS:
- "R.O.W. WORKSHEET, CORPORATE DRIVE PREPARED FOR PEASE DEVELOPMENT AUTHORITY" DATED DEC. 21, 1992 BY RICHARD D. BARTLETT & ASSOCIATES, INC. SHEETS 1 AND 2.
  - "PEASE A.F.B. / PORTSMOUTH, N.H. REPAVE BASE STREETS, PORTSMOUTH AVE, ROCKINGHAM AVE." DATED 7 DEC 82 BY STRATEGIC AIR COMMAND CIVIL ENGINEERING. SHEET 4 OF 5
  - "PORTSMOUTH AIR FORCE BASE, PORTSMOUTH, N.H. ROADS AND STORAGE AREA FY-56" DATED DEC 1955 BY WHITMAN & HOWARD ENGINEERS. INDEX PAGE AND SHEETS 2 - 5 OF 11.
  - "PEASE INTERNATIONAL TRADEPORT SUBDIVISION PLAT, INTERNATIONAL DRIVE LOTS BC11-001 & BC11-002, PORTSMOUTH, N.H." DATED FEBRUARY 5, 1993 BY RICHARD D. BARTLETT & ASSOCIATES INC. R.C.R.D. PLAN #022556.
  - "SUBDIVISION PLAN OF LAND FOR REDHOOK ALE BREWERY, INC. CORPORATE DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED DECEMBER 10, 1994 BY RICHARD P. MILLETTE AND ASSOCIATES. R.C.R.D. PLAN #0-23978.
  - "ALTA/ACSM LAND TITLE SURVEY FOR RESPOR, LLC, ONE INTERNATIONAL DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED FEBRUARY 27, 1998 BY MILLETTE, SPRAGUE & COLWELL, INC. R.C.R.D. PLAN #0-26125.
  - "FRANKLIN PIERCE COLLEGE, PEASE INTERNATIONAL TRADEPORT, 73 CORPORATE DRIVE, PORTSMOUTH, NH" DATED JANUARY 15, 1998 BY RONALD R. BURD. R.C.R.D. PLAN #0-26427.
  - "SUBDIVISION PLAN FOR LAND LEASED BY PEASE DEVELOPMENT AUTHORITY & KNOWN AS #119 INTERNATIONAL DRIVE LOCATED AT PEASE INTERNATIONAL TRADEPORT, PORTSMOUTH, N.H." DATED MARCH 1, 2000 BY KNIGHT HILL LAND SURVEYING SERVICES, INC. R.C.R.D. PLAN #0-28059.
  - "SUBDIVISION PLAT PREPARED FOR 80 CORPORATE DRIVE LLC C/O BOULOS PROPERTY MANAGEMENT, LOCATION CORPORATE & GOOSE BAY DRIVES, PEASE INTERNATIONAL TRADEPORT - PORTSMOUTH, NH" DATED APRIL 11, 2000 BY FWS LAND SURVEYING P.L.L.C. R.C.R.D. PLAN #0-28447.
  - "LEASE LINE REVISION PLAN FOR LONZA BIOLOGICS, INC. 101 INTERNATIONAL DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED FEB. 5, 2001 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #0-28955.
  - "LEASE LINE REVISION PLAN FOR LONZA BIOLOGICS, INC. 101 INTERNATIONAL DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED SEPT. 17, 2001 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #0-29538.
  - "SUBDIVISION PLAN OF LAND OF PEASE DEVELOPMENT AUTHORITY TO BE LEASED TO NORTHEAST REHABILITATION (A PORTION OF TAX MAP 303, LOT 6) 105 & 121 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH, NEW HAMPSHIRE" DATED NOV. 5, 2008 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #0-35869.
  - "CONDOMINIUM SITE & FLOOR PLAN PREPARED FOR PIONEER NEW HAMPSHIRE, LLC, LAND OF PEASE DEVELOPMENT AUTHORITY, TAX MAP PARCEL 305-3 (108, 110, 112 & 114 CORPORATE DRIVE) PORTSMOUTH, NEW HAMPSHIRE" DATED APRIL 12, 2013 BY FIELDSTONE LAND CONSULTANTS, P.L.L.C. SHEET 1 OF 5. R.C.R.D. PLAN #0-37765.
  - "SUBDIVISION PLAN FOR PEASE DEVELOPMENT AUTHORITY, (TAX MAP 303, LOT 4) 67 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH NEW HAMPSHIRE" DATED MAY 29, 2009 BY DOUCET SURVEY, INC. (NOT RECORDED)
  - "EXISTING CONDITIONS, BUILDING A, 80 CORPORATE DRIVE AND BUILDING B, 70 CORPORATE DRIVE, PORTSMOUTH, NH" DATED 4/14/2000 AND REVISED 6/05/2000 BY OPECHEE CONSTRUCTION CORPORATION. (NOT RECORDED)

- LEGEND
- EXISTING LEASE/R.O.W. LINES
  - CHAIN LINK FENCE
  - OVERHEAD WIRES
  - SEWER LINE
  - DRAIN LINE
  - GAS LINE
  - WATER LINE
  - UNDERGROUND ELECTRIC LINE
  - XS SEWER LINE PER REF. PLAN #15
  - XD DRAIN LINE PER REF. PLAN #15
  - XG GAS LINE PER REF. PLAN #15
  - XW WATER LINE PER REF. PLAN #15
  - -100 MAJOR CONTOUR LINE
  - -98 MINOR CONTOUR LINE
  - TREE LINE
  - EDGE OF WETLAND (SEE NOTE #6)
  - HISS LINE (SEE NOTE #6)
  - UTILITY POLE
  - SIGN
  - GRANITE BOUND FOUND
  - DRILL HOLE FOUND
  - IRON PIPE/ROD FOUND
  - 4"x4" GRANITE BOUND TO BE SET
  - 5/8" REBAR W/ ID CAP TO BE SET
  - BOLLARD
  - FIRE HYDRANT
  - WATER GATE VALVE
  - GAS GATE VALVE
  - PAD MOUNTED TRANSFORMER
  - ELECTRIC BOX
  - TELEPHONE BOX
  - UTILITY BOX
  - CABLE BOX
  - CATCH BASIN
  - CATCH BASIN
  - CATCH BASIN
  - DRAIN MANHOLE
  - FLARED END SECTION
  - ELECTRIC MANHOLE
  - TELEPHONE MANHOLE
  - SEWER MANHOLE
  - CLEANOUT
  - CATCH BASIN PER REF. PLAN #15
  - DRAIN MANHOLE PER REF. PLAN #15
  - SEWER MANHOLE PER REF. PLAN #15
  - HAND HOLE
  - WETLAND AREA
  - CONIFEROUS TREE
  - DECIDUOUS TREE
  - CONCRETE
  - RIP RAP
  - GRAVEL AREA
  - LEDGE OUTCROP
  - BOUND FOUND
  - D.H.F. DRILL HOLE FOUND
  - EP EDGE OF PAVEMENT
  - SWL SINGLE WHITE LINE
  - DYL DOUBLE YELLOW LINE
  - VGC VERTICAL GRANITE CURB
  - VGC HISS SOIL TYPE




- NOTES:
- REFERENCE: TAX MAP 305, LOT 1 PHYSICAL ADDRESS: 70 CORPORATE DRIVE TAX MAP 305, LOT 2 PHYSICAL ADDRESS: 80 CORPORATE DRIVE
  - TOTAL PARCEL AREA: TAX MAP 305, LOT 1: 443,578 SQ. FT. OR 10.183 AC. TAX MAP 305, LOT 2: 604,273 SQ. FT. OR 13.872 AC. TOTAL AREA: 1,047,851 SQ. FT. OR 24.055 AC.
  - OWNER OF RECORD: TAX MAP 305, LOTS 1 & 2 PEASE DEVELOPMENT AUTHORITY 55 INTERNATIONAL DRIVE PORTSMOUTH, NEW HAMPSHIRE 03801 R.C.R.D. BOOK 4227, PAGE 001
  - ZONE: AIRPORT, BUSINESS & COMMERCIAL (ABC)
  - FIELD SURVEY PERFORMED BY J.M.L., E.J.S., J.P.E., J.F.K., AND N.J.M. DURING NOVEMBER 2015 USING A TRIMBLE R8 SURVEY GRADE GPS UNIT AND A TRIMBLE S6 ROBOTIC TOTAL STATION WITH A TRIMBLE TSC3 DATA COLLECTOR.
  - JURISDICTIONAL WETLANDS DELINEATED BY GOVE ENVIRONMENTAL SERVICES, INC. DURING FALL 2014 IN ACCORDANCE WITH 1987 CORPS OF ENGINEERS WETLANDS DELINEATIONS MANUAL, TECHNICAL REPORT Y-87-1. HISS MAPPING COMPLETED BY GOVE ENVIRONMENTAL SERVICES DURING DECEMBER 2015.
  - FLOOD HAZARD ZONE: "X", PER FIRM MAP #33015C0260E, DATED MAY 17, 2005.
  - HORIZONTAL DATUM BASED ON NH STATE PLANE 2800(NAD83/86) PER REFERENCE PLANS #10, #11, & #12.
  - VERTICAL DATUM IS BASED ON NGVD29 PER REFERENCE PLANS #10, #11, & #12.
  - PROPER FIELD PROCEDURES WERE FOLLOWED IN ORDER TO GENERATE CONTOURS AT 2' INTERVALS. ANY MODIFICATION OF THIS INTERVAL WILL DIMINISH THE INTEGRITY OF THE DATA, AND DOUCET SURVEY, INC. WILL NOT BE RESPONSIBLE FOR ANY SUCH ALTERATION PERFORMED BY THE USER.
  - UNDERGROUND UTILITIES SHOWN HEREON ARE BASED ON OBSERVABLE PHYSICAL EVIDENCE AND PAINT MARKS FOUND ON-SITE. THE SITE WAS NOT MARKED FOR THE PURPOSES OF THIS SURVEY. SOME UTILITIES ARE SHOWN PER REFERENCE PLANS AS NOTED IN THE LEGEND.
  - THE ACCURACY OF MEASURED UTILITY INVERTS AND PIPE SIZES/TYPES IS SUBJECT TO NUMEROUS FIELD CONDITIONS, INCLUDING: THE ABILITY TO MAKE VISUAL OBSERVATIONS, DIRECT ACCESS TO THE VARIOUS ELEMENTS, MANHOLE CONFIGURATION, ETC.
  - THE INTENT OF THIS PLAN IS TO SHOW THE LOCATION OF BOUNDARIES IN ACCORDANCE WITH AND IN RELATION TO THE CURRENT LEGAL DESCRIPTION, AND IS NOT AN ATTEMPT TO DEFINE UNWRITTEN RIGHTS, DETERMINE THE EXTENT OF OWNERSHIP, OR DEFINE THE LIMITS OF TITLE.
  - TAX MAP 305, LOTS 1 & 2 ARE EITHER SUBJECT TO OR IN BENEFIT OF, BUT NOT LIMITED TO, THE FOLLOWING EASEMENTS/RIGHTS OF RECORD:
    - 50' WIDE ACCESS EASEMENT FOR THE BENEFIT OF LOT 305-2. (SHOWN PER REFERENCE PLAN #9)
    - APPROXIMATE LOCATION OF 20' WIDE LICENSE TO THE CITY OF PORTSMOUTH FOR THE PURPOSES OF MAINTAINING A DRAINAGE LINE. (SHOWN PER REFERENCE PLAN #9)
  - FINAL MONUMENTATION MAY BE DIFFERENT THAN THE PROPOSED MONUMENTATION SHOWN HEREON, DUE TO THE FACT THAT SITE CONDITIONS WILL DICTATE THE ACTUAL LOCATION AND TYPE OF MONUMENTS INSTALLED IN THE FIELD. PLEASE REFER TO EITHER THE "MONUMENTATION LOCATION PLAN" TO BE RECORDED OR CONTACT DOUCET SURVEY, INC. FOR CLARIFICATION OF MONUMENTS SET. (A RECORDED PLAN WILL BE PRODUCED AT THE DISCRETION OF DOUCET SURVEY, INC.)



EXISTING CONDITIONS PLAN  
FOR  
TIGHE & BOND AND LONZA  
LAND OF  
PEASE DEVELOPMENT AUTHORITY  
(TAX MAP 305, LOTS 1 & 2)  
GOOSE BAY DRIVE & CORPORATE DRIVE  
PORTSMOUTH, NEW HAMPSHIRE

DRAWN BY: K.C.W.	DATE: DEC. 23, 2015
CHECKED BY: J.A.G.	DRAWING NO.: 4375A
JOB NO.: 4375	SHEET 1 OF 4

**DOUCET SURVEY**  
Serving Your Professional Surveying & Mapping Needs  
102 Kent Place, Newmarket, NH 03857 (603) 659-6560  
10 Storers Street (RiverView Suite) Kennebunk, ME (207) 502-7005  
http://www.doucetsurvey.com



NO.	DATE	DESCRIPTION	BY
1	8/3/16	GENERAL EDITS AND ADDED WETLANDS BUFFER	J.A.G.

NOTE:  
ALL ELECTRIC, GAS, TEL. WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION. THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888-DIG-SAFE.



523BH

HIGH INTENSITY MAP SYMBOL 5	
DRAINAGE CLASS	
1. EXCESSIVELY DRAINED	
2. WELL DRAINED	
3. MODERATELY WELL DRAINED	
4. SOMEWHAT POORLY DRAINED	
5. POORLY DRAINED	
6. VERY POORLY DRAINED	
7. NOT DETERMINABLE	
PARENT MATERIAL 2	
1. GLACIOFLUVIAL	
2. GLACIAL TILL	
3. MARINE OR GLACIOLACUSTRINE VERY FINE SAND AND SILT	
4. MARINE OR GLACIOLACUSTRINE LOAMY/SANDY OVER SILT/CLAY	
5. MARINE OR GLACIOLACUSTRINE SILT AND CLAY	
6. EXCAVATED, REGRADED, OR FILLED	
7. ALLUVIAL DEPOSITS	
8. ORGANIC MATERIALS FRESH WATER	
9. ORGANIC MATERIALS TIDAL MARSH	
RESTRICTIVE FEATURES 3	
1. NONE	
2. BOULDERY, WITH MORE THAN 15% OF SURFACE COVERED	
3. MINERAL RESTRICTIVE LAYER(S) AREA PRESENT AT LESS THAN 40 IN. DEPTH.	
4. BEDROCK 0 IN. TO 20 IN. DEPTH.	
5. SUBJECT TO FLOODING	
6. DOES NOT MEET FILL STANDARDS.	
X. DEPTH TO BEDROCK VARIABLE, COMPLEX OF SOIL TYPES.	

HIGH INTENSITY MAP SYMBOL 523BH INDICATES A POORLY DRAINED GLACIAL TILL SOIL WITH A RESTRICTIVE FEATURE, ON A SLOPE OF 0 TO 8%

TAX MAP 303, LOT 2-1  
OPROCK PORTSMOUTH INTL FEE LLC  
C/O OCEAN PROPERTIES LTD  
1000 MARKET ST SUITE 300  
PORTSMOUTH, NH 03801  
R.C.R.D. BOOK 4831, PAGE 2677

TAX MAP 303, LOT 2-2  
RESPORT LLC  
1000 MARKET ST BLDG 1 STE 300  
PORTSMOUTH, NH 03801

TAX MAP 305, LOT 7  
PEASE DEVELOPMENT AUTHORITY  
55 INTERNATIONAL DRIVE  
PORTSMOUTH, NEW HAMPSHIRE 03801



TAX MAP 305, LOT 7-1  
UNIVERSITY SYSTEM OF NEW HAMPSHIRE  
COLLEGE FOR LIFELONG LEARNING  
51 INTERNATIONAL DRIVE  
PORTSMOUTH, NH 03801

TAX MAP 305, LOT 7-1  
CITY OF PORTSMOUTH  
1 JUNKINS AVE  
PORTSMOUTH, NH 03801

TAX MAP 303, LOT 3  
RED HOOK BREWERY INC  
C/O WIDMER BROTHERS BREWING CO  
929 NORTH RUSSELL ST.  
PORTLAND, OR 97227



TAX MAP 305, LOT 6  
LONZA BIOLOGICS INC.  
101 INTERNATIONAL DRIVE  
PORTSMOUTH, NH 03801

305-1  
443,578 Sq. Ft.  
10.18 Acres



EXISTING CONDITIONS PLAN  
FOR  
TIGHE & BOND AND LONZA  
LAND OF  
PEASE DEVELOPMENT AUTHORITY  
(TAX MAP 305, LOTS 1 & 2)  
GOOSE BAY DRIVE & CORPORATE DRIVE  
PORTSMOUTH, NEW HAMPSHIRE



DRAWN BY:	K.C.W.	DATE:	DEC. 23, 2015
CHECKED BY:	J.A.G.	DRAWING NO.:	4375A
JOB NO.:	4375	SHEET	2 OF 4



NOTE:  
ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION, THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH, CALL DIG-SAFE AT 1-888-DIG-SAFE.


NO.	DATE	DESCRIPTION	BY
1	8/3/16	GENERAL EDITS AND ADDED WETLANDS BUFFER	J.A.G.






TAX MAP 305, LOT 6  
LONZA BIOLOGICS INC.  
101 INTERNATIONAL DRIVE  
PORTSMOUTH, NH 03801

TAX MAP 303, LOT 4  
PEASE DEVELOPMENT AUTHORITY  
55 INTERNATIONAL DRIVE  
PORTSMOUTH, NEW HAMPSHIRE 03801




TAX MAP 303, LOT 7  
PEASE REHAB LLC  
C/O NORTHEAST REHAB  
70 BUTLER ST.  
SALEM, NH 03079




EXISTING CONDITIONS PLAN  
FOR  
TIGHE & BOND AND LONZA  
LAND OF  
PEASE DEVELOPMENT AUTHORITY  
(TAX MAP 305, LOTS 1 & 2)  
GOOSE BAY DRIVE & CORPORATE DRIVE  
PORTSMOUTH, NEW HAMPSHIRE

NO.	DATE	DESCRIPTION	BY
1	8/3/16	GENERAL EDITS AND ADDED WETLANDS BUFFER	J.A.G.




NOTE:  
ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION, THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888-DIG-SAFE.




DRAWN BY:	K.C.W.	DATE:	DEC. 23, 2015
CHECKED BY:	J.A.G.	DRAWING NO.:	4375A
JOB NO.:	4375	SHEET:	3 OF 4







**EXISTING CONDITIONS PLAN**  
 FOR  
**TIGHE & BOND AND LONZA**  
 LAND OF  
**PEASE DEVELOPMENT AUTHORITY**  
 (TAX MAP 305, LOTS 1 & 2)  
**GOOSE BAY DRIVE & CORPORATE DRIVE**  
 PORTSMOUTH, NEW HAMPSHIRE



DRAWN BY:	K.C.W.	DATE:	DEC. 23, 2015
CHECKED BY:	J.A.G.	DRAWING NO.:	4375A
JOB NO.:	4375	SHEET:	4 OF 4

**DOUCET SURVEY**  
 Serving Your Professional Surveying & Mapping Needs  
 162 Kent Place, Newmarket, NH 03857 (603) 659-6560  
 10 Storer Street (Riverview Suite) Kennebunk, ME (207) 502-7005  
<http://www.doucetsurvey.com>

TAX MAP 305, LOT 6  
 LONZA BIOLOGICS INC.  
 101 INTERNATIONAL DR  
 PORTSMOUTH, NH  
 03801

TAX MAP 305, LOT 4  
 119 INTERNATIONAL DRIVE LLC  
 CO-OWNER: KEYBANK REAL  
 ESTATE CAPITAL  
 ATTN: TAX DEPT  
 11501 OUTLOOK SUITE 300  
 OVERLAND PARK, KS 66211

TAX MAP 305, LOT 3-1  
 PIONEER NEW HAMPSHIRE LLC  
 340 CENTRAL AVE STE 202  
 DOVER, NH 03820  
 R.C.R.D. BOOK 3571, PAGE 1559

TAX MAP 305, LOT 3-2  
 PIONEER NEW HAMPSHIRE LLC  
 340 CENTRAL AVE STE 202  
 DOVER, NH 03820  
 R.C.R.D. BOOK 3571, PAGE 1559


TAX MAP 305, LOT 3-3  
 PIONEER NEW HAMPSHIRE LLC  
 340 CENTRAL AVE STE 202  
 DOVER, NH 03820  
 R.C.R.D. BOOK 3571, PAGE 1559

TAX MAP 305, LOT 3-4  
 NEXTERA ENERGY SEABROOK LLC  
 700 UNIVERSE BOULEVARD PSX/JB  
 JUNO BEACH, FL 33408  
 R.C.R.D. BOOK 5454, PAGE 2321

**NOTE:**  
 ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC  
 FASHION. THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK  
 WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE  
 SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE  
 LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888-DIG-SAFE.

NO.	DATE	DESCRIPTION	BY
1	8/3/16	GENERAL EDITS AND ADDED WETLANDS BUFFER	J.A.G.






**DEMOLITION NOTES:**

1. THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR THE ENGINEER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK.
2. ALL MATERIALS SCHEDULED TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTOR UNLESS OTHERWISE SPECIFIED. THE CONTRACTOR SHALL DISPOSE OF ALL MATERIALS OFF-SITE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCES AND CODES.
3. COORDINATE REMOVAL, RELOCATION, DISPOSAL OR SALVAGE OF UTILITIES WITH THE OWNER AND APPROPRIATE UTILITY COMPANY.
4. ANY EXISTING WORK OR PROPERTY DAMAGED OR DISRUPTED BY CONSTRUCTION/DEMOLITION ACTIVITIES SHALL BE REPLACED OR REPAIRED TO MATCH ORIGINAL EXISTING CONDITIONS BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
5. THE CONTRACTOR SHALL VERIFY LOCATION OF ALL EXISTING UTILITIES. CALL DIG SAFE AT LEAST 72 HOURS PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
6. SAWCUT AND REMOVE PAVEMENT ONE FOOT OFF PROPOSED EDGE OF PAVEMENT OR EXISTING CURB LINE IN ALL AREAS WHERE PAVEMENT TO BE REMOVED ABUTS EXISTING PAVEMENT OR CONCRETE TO REMAIN.
7. IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE THEMSELVES WITH THE CONDITIONS OF ALL OF THE PERMIT APPROVALS.
8. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ADDITIONAL PERMITS, NOTICES AND FEES NECESSARY TO COMPLETE THE WORK AND ARRANGE FOR AND PAY FOR NECESSARY INSPECTIONS AND APPROVALS FROM THE AUTHORITIES HAVING JURISDICTION.
9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION AND OFF-SITE DISPOSAL OF MATERIALS REQUIRED TO COMPLETE THE WORK, EXCEPT FOR WORK NOTED TO BE COMPLETED BY OTHERS.
10. UTILITIES SHALL BE TERMINATED AT THE MAIN LINE PER UTILITY COMPANY STANDARDS. THE CONTRACTOR SHALL REMOVE ALL ABANDONED UTILITIES LOCATED WITHIN THE LIMITS OF WORK. CONTRACTOR SHALL VERIFY ORIGIN OF ALL DRAINS AND UTILITIES PRIOR TO REMOVAL/TERMINATION TO DETERMINE IF DRAINS OR UTILITY IS ACTIVE, AND SERVICES ANY ON OR OFF-SITE STRUCTURE TO REMAIN. CONTRACTOR SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY SUCH UTILITY FOUND AND SHALL MAINTAIN THESE UTILITIES UNTIL PERMANENT SOLUTION IS IN PLACE.
11. PAVEMENT REMOVAL LIMITS ARE SHOWN FOR CONTRACTOR'S CONVENIENCE. ADDITIONAL PAVEMENT REMOVAL MAY BE REQUIRED DEPENDING ON THE CONTRACTOR'S OPERATION. CONTRACTOR TO VERIFY FULL LIMITS OF PAVEMENT REMOVAL PRIOR TO BID.
12. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL EXISTING STRUCTURES, CONCRETE PADS, UTILITIES AND PAVEMENT WITHIN THE WORK LIMITS SHOWN UNLESS SPECIFICALLY IDENTIFIED TO REMAIN. ITEMS TO BE REMOVED INCLUDE BUT ARE NOT LIMITED TO: CONCRETE, PAVEMENT, CURBS, LIGHTING, MANHOLES, CATCH BASINS, UNDER GROUND PIPING, POLES, SIGNS, FENCES, RAMPS, WALLS, BOLLARDS, TREES AND LANDSCAPING.
13. COORDINATE ALL WORK WITHIN THE PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH.
14. REMOVE TREES AND BRUSH AS REQUIRED FOR COMPLETION OF WORK. CONTRACTOR SHALL GRUB AND REMOVE ALL STUMPS WITHIN LIMITS OF WORK AND DISPOSE OF OFF SITE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.
15. CONTRACTOR SHALL PROTECT ALL PROPERTY MONUMENTATION THROUGHOUT DEMOLITION AND CONSTRUCTION OPERATIONS. SHOULD ANY MONUMENTATION BE DISTURBED BY THE CONTRACTOR, HE SHALL EMPLOY A LICENSED SURVEYOR TO REPLACE IT.
16. PROVIDE INLET PROTECTION BARRIERS AT ALL CATCH BASINS WITHIN CONSTRUCTION LIMITS AS WELL AS CATCH BASINS THAT MAY RECEIVE RUNOFF FROM CONSTRUCTION ACTIVITIES. INLET PROTECTION BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT. INLET PROTECTION BARRIERS SHALL BE "HIGH FLOW SILT SACK" BY ACF ENVIRONMENTAL OR APPROVED EQUAL. INSPECT BARRIERS WEEKLY AND AFTER EACH RAIN OF 0.25 INCHES OR GREATER. CONTRACTOR SHALL COMPLETE A MAINTENANCE INSPECTION REPORT AFTER EACH INSPECTION. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED.
17. THE CONTRACTOR SHALL PHASE DEMOLITION AND CONSTRUCTION AS REQUIRED TO PROVIDE CONTINUOUS SERVICE TO EXISTING BUSINESSES AND HOMES THROUGHOUT THE CONSTRUCTION PERIOD. EXISTING BUSINESS AND HOME SERVICES INCLUDE, BUT ARE NOT LIMITED TO ELECTRICAL COMMUNICATION, FIRE PROTECTION, DOMESTIC WATER AND SEWER SERVICES. TEMPORARY SERVICES, IF REQUIRED, SHALL COMPLY WITH ALL FEDERAL, STATE, LOCAL AND UTILITY COMPANY STANDARDS. CONTRACTOR SHALL PROVIDE DETAILED CONSTRUCTION SCHEDULE TO OWNER PRIOR TO ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
18. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO THE START OF ANY CLEARING OR DEMOLITION ACTIVITIES.
19. THE CONTRACTOR SHALL PAY ALL COSTS NECESSARY FOR TEMPORARY PARTITIONING, BARRICADING, FENCING, SECURITY AND SAFETY DEVICES REQUIRED FOR THE MAINTENANCE OF A CLEAN AND SAFE CONSTRUCTION SITE.
20. SAWCUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL UTILITIES TO BE REMOVED AND PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN.

**LEGEND**

- APPROXIMATE LIMIT OF PROPOSED SAW CUT
- ▨ APPROXIMATE LIMIT OF PROPOSED WETLAND IMPACT AREA
- ▧ APPROXIMATE LIMIT OF PROPOSED WETLAND BUFFER IMPACT AREA
- ▩ APPROXIMATE LIMIT OF PAVEMENT TO BE REMOVED
- TBR TO BE REMOVED
- BLDG BUILDING
- TYP TYPICAL
- COORD COORDINATE



**Proposed Industrial Development**

**Lonza Biologics**

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION





PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-101 to C-103.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**DEMOLITION PLAN**

SCALE: AS SHOWN

Last Save Date: May 30, 2018 12:13 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 10:18 AM Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion\wds\1278\013 Iron Parcel Redevelopment\Drawings\_Figures\AutoCAD\Sheet\0700-CD-101 to C-103.dwg Layout Tab: C-101





**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-101 to C-103.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**DEMOLITION PLAN**



SCALE: AS SHOWN

**C-102**

SEE SHEET C-101 FOR LEGEND AND DEMOLITION NOTES

Last Save Date: May 21, 2018 3:03 PM By: BCLARK  
Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
File Location: Z:\L0700\Lonza Biologics Expansion.was 12726.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-101 to C-103.dwg Layout Tab: C-102





**Proposed Industrial Development**


Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-101 to C-103.dwg  
DRAWN BY: NAH  
CHECKED BY: PMC  
APPROVED BY: BLM



DEMOLITION PLAN  
SCALE: AS SHOWN  
**C-103**



SEE SHEET C-101 FOR LEGEND AND DEMOLITION NOTES

Last Save Date: May 21, 2018 3:03 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion\18726\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-101 to C-103.dwg Layout Tab: C-103





**SITE DATA**  
LOCATION: TAX MAP 305, LOTS 1 & 2  
70 & 80 CORPORATE DRIVE  
PORTSMOUTH, NH  
TAX MAP 305, LOT 6  
101 INTERNATIONAL DRIVE  
PORTSMOUTH, NH  
ZONING DISTRICT: AIRPORT, BUSINESS & COMMERCIAL (ABC)

**DIMENSIONAL REQUIREMENTS:**




MINIMUM LOT AREA:	REQUIRED 5 AC	PROVIDED 43.4± AC
MINIMUM STREET FRONTAGE:	200 FT	1,038 FT
MINIMUM FRONT YARD SETBACK:	70 FT	70 FT
SIDE SETBACK:	30 FT	30 FT
REAR SETBACK:	50 FT	51 FT
MINIMUM OPEN SPACE:	25 %	41.7± %

MAXIMUM STRUCTURE HEIGHT SHALL NOT EXCEED FAA CRITERIA.

**PARKING REQUIREMENTS:**

REQUIRED PARKING  
2 SPACES PER 3 EMPLOYEES ON LARGEST SHIFT  
740 EXISTING EMPLOYEES 493 SPACES  
1000 ANTICIPATED EMPLOYEES 667 SPACES  
TOTAL REQUIRED: 1160 SPACES

PARKING PROVIDED  
EXISTING SPACES: 521 SPACES  
PROPOSED PARKING GARAGE #1: 325 SPACES  
PROPOSED PARKING GARAGE #2: 375 SPACES  
TOTAL: 1221 SPACES



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

**WETLAND & BUFFER IMPACT TABLE:**

	WETLAND	BUFFER
WETLAND IMPACT AREA #1:	17,628 SF	24,677 SF
WETLAND IMPACT AREA #2:	1,189 SF	NO BUFFER*
WETLAND IMPACT AREA #3:	20,204 SF	23,047 SF
WETLAND IMPACT AREA #4:	11,443 SF	19,128 SF
WETLAND IMPACT AREA #5:	5,091 SF	NO BUFFER*
<b>TOTAL IMPACT AREA:</b>	<b>55,555 SF</b>	<b>66,852 SF</b>

\*PER PDA REGULATIONS: WETLANDS LESS THAN 10,000 SF DO NOT HAVE A BUFFER.

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CS-104 to C-107.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		


OVERALL SITE PLAN

SCALE: AS SHOWN

**C-104**

Last Save Date: May 30, 2018 10:54 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 12769.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-104 to C-107.dwg Layout Tab: C-104








**SITE NOTES:**

1. STRIPE PARKING AREAS AS SHOWN, INCLUDING PARKING SPACES, STOP BARS, ADA SYMBOLS, PAINTED ISLANDS, CROSS WALKS, ARROWS, LEGENDS AND CENTERLINES (ALL MARKINGS EXCEPT CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING WHITE TRAFFIC PAINT. CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING YELLOW TRAFFIC PAINT. ALL TRAFFIC PAINT SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F").
2. ALL PAVEMENT MARKINGS AND SIGNS TO CONFORM TO "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", "STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS", AND THE AMERICANS WITH DISABILITIES ACT REQUIREMENTS, LATEST EDITIONS.
3. SEE DETAILS FOR PARKING STALL MARKINGS, ADA SYMBOLS, SIGNS AND SIGN POSTS.
4. CENTERLINES SHALL BE FOUR (4) INCH WIDE YELLOW LINES. STOP BARS SHALL BE EIGHTEEN (18) INCHES WIDE.
5. PAINTED ISLANDS SHALL BE FOUR (4) INCH WIDE DIAGONAL LINES AT 3'-0" O.C. BORDERED BY FOUR (4) INCH WIDE LINES.
6. THE CONTRACTOR SHALL EMPLOY A NEW HAMPSHIRE LICENSED ENGINEER/SURVEYOR TO DETERMINE ALL LINES AND GRADES.
7. CLEAN AND COAT VERTICAL FACE OF EXISTING PAVEMENT AT SAWCUT LINE WITH RS-1 EMULSION IMMEDIATELY PRIOR TO PLACING NEW BITUMINOUS CONCRETE.
8. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND/OR TOWN CODES & SPECIFICATIONS.
9. WORK WITHIN CORPORATE DRIVE AND GOOSE BAY DRIVE SHALL BE COORDINATED WITH CITY OF PORTSMOUTH.
10. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILE) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
11. CONTRACTOR SHALL COORDINATE WITH THE BUILDING DRAWINGS FOR ALL CONCRETE PADS & SIDEWALKS ADJACENT TO BUILDING.
12. ALL WORK SHALL CONFORM TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS, STANDARD SPECIFICATIONS.
13. CONTRACTOR TO PROVIDE BACKFILL AND COMPACTION AT CURB LINE AFTER CONCRETE FORMS FOR SIDEWALKS AND PADS HAVE BEEN STRIPPED. COORDINATE WITH BUILDING CONTRACTOR.
14. ALL LIGHT POLE BASES NOT PROTECTED BY A RAISED CURB SHALL BE PAINTED YELLOW.
15. ALL DIMENSIONS ARE TO THE FACE OF CURB UNLESS OTHERWISE NOTED.
16. UPON COMPLETION OF CONSTRUCTION AND PRIOR TO ISSUANCE OF CERTIFICATE OF OCCUPANCY AND RELEASE OF BOND, THE APPLICANT SHALL SUBMIT A LETTER TO THE PDA, SIGNED AND STAMPED BY A PROFESSIONAL ENGINEER, STATING CONSTRUCTION HAS BEEN COMPLETED IN CONFORMANCE WITH THE APPROVED PLANS.

**LEGEND**

- MATCH LINE
- - - PROPOSED PROPERTY LINE
- - - PROPOSED SETBACK LINE
- [Cross-hatched] APPROXIMATE LIMIT OF PROPOSED WETLAND IMPACT AREA
- [Stippled] APPROXIMATE LIMIT OF PROPOSED WETLAND BUFFER IMPACT AREA
- [Dotted] PROPOSED PAVEMENT SECTION
- [Solid] PROPOSED CONCRETE
- BLDG --- BUILDING
- TYP --- TYPICAL
- COORD --- COORDINATE
- 30'R --- PROPOSED CURB RADIUS
- VGC --- PROPOSED VERTICAL GRANITE CURB
- SGC --- PROPOSED SLOPED GRANITE CURB



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CS-104 to C-107.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**SITE PLAN**


SCALE: AS SHOWN

**C-105**



Last Save Date: May 30, 2018 10:54 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 127820\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-104 to C-107.dwg Layout Tab: C-105



Last Save Date: May 30, 2018 10:54 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 127670.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-104 to C-107.dwg Layout Tab: C-106



SEE SHEET C-105 FOR LEGEND AND SITE NOTES



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire



2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CS-104 to C-107.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

SITE PLAN

SCALE: AS SHOWN

C-106





**Proposed Industrial Development**


Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CS-104 to C-107.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

SITE PLAN  
SCALE: AS SHOWN  
**C-107**



SEE SHEET C-105 FOR LEGEND AND SITE NOTES

Last Save Date: May 30, 2018 10:54 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 1278P\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-104 to C-107.dwg Layout Tab: C-107



**DRAINAGE STRUCTURE TABLE**

FES100 RIM=46.61 INV.IN=43.00	PCB107 RIM=53.60 INV.OUT=46.66	PDMH101 RIM=52.32 INV.IN=46.30 INV.IN=46.30 INV.OUT=46.20	PDMH402 RIM=53.50 INV.IN=49.50 INV.OUT=49.40
FES101 RIM=-2.94 INV.IN=43.00	PCB108 RIM=53.60 INV.IN=46.55 INV.OUT=46.45	PDMH102 RIM=54.10 INV.IN=46.10 INV.OUT=46.00	PDMH403 RIM=50.50 INV.IN=46.70 INV.OUT=45.55
FES200 RIM=2.92 INV.IN=50.00	PCB109 RIM=49.30 INV.OUT=43.36	PDMH103 RIM=50.70 INV.IN=44.75 INV.IN=44.75 INV.OUT=44.65	POS100 RIM=46.17 INV.OUT=41.35
FES201 RIM=0.66 INV.IN=50.00	PCB110 RIM=49.30 INV.IN=43.25 INV.OUT=43.15	PDMH104 RIM=51.00 INV.IN=44.00 INV.IN=43.20 INV.OUT=43.10	POS200 RIM=55.50 INV.OUT=49.35
FES300 RIM=52.22 INV.IN=50.50	PCB200 RIM=59.81 INV.IN=49.80 INV.IN=49.80 INV.OUT=49.70	PDMH201 RIM=72.20 INV.IN=50.60 INV.OUT=50.50	POS300 RIM=55.50 INV.OUT=49.85
FES400 RIM=46.43 INV.IN=45.00	PCB201 RIM=57.00 INV.OUT=49.90	PDMH301 RIM=58.17 INV.IN=51.60 INV.OUT=51.50	PYD100 RIM=55.00 INV.OUT=50.15
FES401 RIM=-2.94 INV.IN=45.00	PCB202 RIM=61.62 INV.IN=50.60 INV.OUT=50.50	PDMH302 RIM=56.95 INV.IN=51.30 INV.IN=51.30 INV.OUT=51.20	PYD101 RIM=55.00 INV.IN=49.65 INV.OUT=49.55
HW100 RIM=43.47 INV.IN=41.20	PCB204 RIM=56.00 INV.OUT=50.80	PDMH303 RIM=62.51 INV.IN=50.90 INV.IN=50.90 INV.OUT=50.80	PYD102 RIM=55.00 INV.IN=49.15 INV.OUT=49.05
HW300 RIM=-2.75 INV.IN=47.00	PCB205 RIM=56.00 INV.OUT=51.00	PDMH304 RIM=57.00 INV.IN=49.45 INV.OUT=49.35	PYD103 RIM=59.00 INV.OUT=56.00
PCB100 RIM=54.00 INV.IN=47.10 INV.IN=47.10 INV.OUT=47.00	PCB206 RIM=55.75 INV.OUT=51.70	PDMH305 RIM=57.50 INV.IN=48.45 INV.OUT=48.35	PYD104 RIM=55.00 INV.IN=48.00 INV.OUT=47.90
PCB101 RIM=54.00 INV.IN=47.10 INV.IN=47.10 INV.OUT=47.00	PCB207 RIM=55.75 INV.OUT=51.45	PDMH306 RIM=57.30 INV.IN=47.55 INV.IN=47.55 INV.OUT=47.45	PYD105 RIM=51.00 INV.IN=45.70 INV.OUT=45.60
PCB102 RIM=51.20 INV.OUT=45.30	PCB302 RIM=56.00 INV.OUT=51.85	PDMH400 RIM=51.50 INV.IN=45.25 INV.OUT=45.15	PYD300 RIM=60.00 INV.OUT=53.90
PCB103 RIM=51.20 INV.IN=45.15 INV.IN=45.15 INV.OUT=45.05	PCB303 RIM=55.85 INV.OUT=51.60	PDMH401 RIM=55.00 INV.IN=50.80 INV.IN=48.70 INV.OUT=48.60	PYD301 RIM=61.00 INV.IN=53.65 INV.OUT=53.55
PCB104 RIM=50.30 INV.OUT=44.95	PCB304 RIM=55.25 INV.OUT=51.40		PYD400 RIM=55.00 INV.OUT=52.00
PCB105 RIM=49.50 INV.IN=43.95 INV.OUT=43.85	PCB400 RIM=50.60 INV.OUT=45.60		PYD401 RIM=55.00 INV.IN=51.55 INV.OUT=51.45
PCB106 RIM=49.40 INV.IN=44.50 INV.OUT=44.40			

**GRADING AND DRAINAGE NOTES:**

1. COMPACTION REQUIREMENTS:  
BELOW PAVED OR CONCRETE AREAS 95%  
TRENCH BEDDING MATERIAL AND SAND BLANKET BACKFILL 95%  
BELOW LOAM AND SEED AREAS 90%
- \* ALL PERCENTAGES OF COMPACTION SHALL BE OF THE MAXIMUM DRY DENSITY AT THE OPTIMUM MOISTURE CONTENT AS DETERMINED AND CONTROLLED IN ACCORDANCE WITH ASTM D-1557, METHOD C FIELD DENSITY TESTS SHALL BE MADE IN ACCORDANCE WITH ASTM D-1556 OR ASTM-2922.
2. ALL STORM DRAINAGE PIPES SHALL BE HIGH DENSITY POLYETHYLENE (HANCOR HI-Q, ADS N-12 OR APPROVED EQUAL) OR RCP CLASS IV, UNLESS OTHERWISE SPECIFIED.
3. SEE UTILITIES PLAN FOR ALL SITE UTILITY INFORMATION.
4. ADJUST ALL MANHOLES, CATCHBASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
5. CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE AND LAWN AREAS FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE BUILDING ENTRANCES, EXITS, RAMPS AND LOADING DOCK AREAS ADJACENT TO THE BUILDING.
6. CONTRACTOR SHALL THOROUGHLY CLEAN ALL CATCHBASINS AND DRAIN LINES, WITHIN THE LIMIT OF WORK, OF SEDIMENT IMMEDIATELY UPON COMPLETION OF CONSTRUCTION.
7. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND LOCAL CODES.
8. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED FERTILIZER AND MULCH.
9. ALL STORM DRAIN CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE NHDOT STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES, LATEST EDITION.
10. ALL PROPOSED CATCHBASINS SHALL BE EQUIPPED WITH OIL/GAS SEPARATOR HOODS AND 4' SUMPS.
11. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS AND CONSTRUCTION SPECIFICATIONS, LATEST REVISIONS.
12. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILE) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
13. SEE EXISTING CONDITIONS PLAN FOR BENCH MARK INFORMATION.



**EROSION CONTROL NOTES:**

1. INSTALL EROSION CONTROL BARRIERS AS SHOWN AS FIRST ORDER OF WORK.
2. SEE GENERAL EROSION CONTROL NOTES ON DETAIL SHEETS.
3. PROVIDE INLET PROTECTION AROUND ALL EXISTING AND PROPOSED CATCHBASIN INLETS WITHIN THE WORK LIMITS. MAINTAIN FOR THE DURATION OF THE PROJECT UNTIL PAVEMENT HAS BEEN INSTALLED.
4. INSTALL STABILIZED CONSTRUCTION ENTRANCES.
5. INSPECT INLET PROTECTION AND SILT FENCES DAILY AND AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS 1/3 THE FILTER HEIGHT.
6. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED, FERTILIZER AND MULCH.
7. CONSTRUCT EXCELSIOR MAT ON ALL SLOPES STEEPER THAN 3:1.
8. PRIOR TO ANY WORK OR SOIL DISTURBANCE COMMENCING ON THE SUBJECT PROPERTY, INCLUDING MOVING OF EARTH, THE APPLICANT SHALL INSTALL ALL EROSION AND SILTATION MITIGATION AND CONTROL MEASURES AS REQUIRED BY STATE AND LOCAL PERMITS AND APPROVALS.
9. CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST AND WIND EROSION THROUGHOUT THE CONSTRUCTION PERIOD. DUST CONTROL MEASURES SHALL INCLUDE, BUT NOT LIMITED TO, SPRINKLING WATER ON UNSTABLE SOILS SUBJECT TO ARID CONDITIONS.
10. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION.
11. ALL CATCHBASIN SUMPS AND PIPING SHALL BE THOROUGHLY CLEANED TO REMOVE ALL SEDIMENT AND DEBRIS AFTER THE PROJECT HAS BEEN PAVED.
12. TEMPORARY SOIL STOCKPILE SHALL BE SURROUNDED BY SILT FENCE AND SHALL BE STABILIZED BY TEMPORARY EROSION CONTROL SEEDING. STOCKPILE AREAS TO BE LOCATED AS FAR AS POSSIBLE FROM THE DELINEATED EDGE OF WETLAND.
13. SAFETY FENCING SHALL BE PROVIDED AROUND STOCKPILES OVER 10 FT.
14. CONCRETE TRUCKS WILL BE REQUIRED TO WASH OUT (IF NECESSARY) SHOOTS ONLY WITHIN AREAS WHERE CONCRETE HAS BEEN PLACED. NO OTHER WASH OUT WILL BE ALLOWED.

**LEGEND**

	MATCH LINE
	PROPOSED PROPERTY LINE
	PROPOSED CONTOUR LINE
	PROPOSED DRAIN LINE (TYP)
	PROPOSED SILT SOCK
	PROPOSED PAVEMENT SECTION
	PROPOSED CONCRETE
	BUILDING
	TYPICAL
	COORDINATE
	ROAD
	ROOF DRAIN
	INLET PROTECTION SILT SACK

Last Save Date: May 21, 2018 12:21 PM By: BCLARK  
 Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion\Drawings - Figures\AutoCAD\Sheet\0700-CG-108 to C-110.dwg Layout Tab: C-108



**Proposed Industrial Development**

Lonza Biologics



Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CG-108 to C-110.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

**GRADING, DRAINAGE & EROSION CONTROL PLAN**

SCALE: AS SHOWN





**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire


MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CG-108 to C-110.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

GRADING, DRAINAGE & EROSION CONTROL PLAN

SCALE: AS SHOWN






C-109



SEE SHEET C-108 FOR LEGEND GRADING, DRAINAGE & EROSION CONTROL NOTES, & DRAINAGE STRUCTURE TABLE

Last Save Date: May 21, 2018 12:21 PM By: BCLARK  
 Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700 Lonza Biologics Expansion.was 127626.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CG-108 to C-110.dwg Layout Tab: C-109





Last Save Date: May 21, 2018 12:21 PM By: BCLARK  
 Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
 Plot File Location: J:\L0700\Lonza Biologics Expansion.was 12769.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CG-108 to C-110.dwg Layout Tab: C-110

**Proposed Industrial Development**  
**Lonza Biologics**  
  
Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
 DATE: 04/03/2018  
 FILE: L0700-CG-108 to C-110.dwg  
 DRAWN BY: NAH  
 CHECKED: PMC  
 APPROVED: BLM

GRADING, DRAINAGE & EROSION CONTROL PLAN  
 SCALE: AS SHOWN

SEE SHEET C-108 FOR LEGEND GRADING, DRAINAGE & EROSION CONTROL NOTES, & DRAINAGE STRUCTURE TABLE






**LEGEND**


- MATCH LINE
- PW — PROPOSED WATER MAIN
- PS — PROPOSED SEWER MAIN
- DB — PROPOSED DUCT BANK
- NG — PROPOSED NATURAL GAS
- TC — PROPOSED TELECOMMUNICATIONS
- ⊕ PROPOSED WATER VALVE
- ▲ PROPOSED THRUST BLOCK
- ⊙ PROPOSED SEWER MANHOLE
- BLDG BUILDING
- TYP TYPICAL
- COORD COORDINATE

**UTILITY NOTES:**

1. THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR ENGINEER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES, AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK AT NO ADDITIONAL COST TO THE OWNER.
2. COORDINATE ALL UTILITY WORK WITH APPROPRIATE UTILITY COMPANY.  
 NATURAL GAS - UNITIL  
 WATER - CITY OF PORTSMOUTH DPW  
 SEWER - CITY OF PORTSMOUTH DPW  
 ELECTRIC - EVERSOURCE  
 COMMUNICATIONS - FAIRPOINT, COMCAST, FIRSTLIGHT
3. SEE EXISTING CONDITIONS PLAN FOR BENCHMARK INFORMATION.
4. SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR PROPOSED GRADING AND EROSION CONTROL MEASURES.
5. ALL WATER MAIN INSTALLATIONS SHALL BE CLASS 52, CEMENT LINED DUCTILE IRON PIPE.
6. ALL WATER MAIN INSTALLATIONS SHALL BE PRESSURE TESTED AND CHLORINATED AFTER CONSTRUCTION PRIOR TO ACTIVATING THE SYSTEM. CONTRACTOR SHALL COORDINATE CHLORINATION AND TESTING WITH THE CITY OF PORTSMOUTH WATER DEPARTMENT.
7. ALL SEWER PIPE SHALL BE FIBERGLASS REINFORCED PLASTIC UNLESS OTHERWISE STATED.
8. ALL WORK WITHIN PORTSMOUTH ROWS SHALL BE COORDINATED WITH CITY OF PORTSMOUTH.
9. CONTRACTOR SHALL MAINTAIN UTILITY SERVICES TO ABUTTING PROPERTIES THROUGHOUT CONSTRUCTION.
10. CONNECTIONS TO EXISTING WATER MAIN SHALL BE CONSTRUCTED TO CITY OF PORTSMOUTH STANDARDS.
11. EXISTING UTILITIES TO BE REMOVED SHALL BE CAPPED AT THE MAIN AND MEET THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS STANDARDS FOR CAPPING OF WATER AND SEWER SERVICES.
12. ALL ELECTRICAL MATERIAL WORKMANSHIP SHALL CONFORM TO THE NATIONAL ELECTRIC CODE, LATEST EDITION, AND ALL APPLICABLE STATE AND LOCAL CODES.
13. THE EXACT LOCATION OF NEW UTILITY SERVICES AND CONNECTIONS SHALL BE COORDINATED WITH THE BUILDING DRAWINGS AND THE UTILITY COMPANIES.
14. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
15. ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES TO FACILITATE PULLING CABLES.
16. THE CONTRACTOR SHALL OBTAIN, PAY FOR, AND COMPLY WITH ALL REQUIRED PERMITS, ARRANGE FOR ALL INSPECTIONS, AND SUBMIT COPIES OF ACCEPTANCE CERTIFICATES TO THE OWNER PRIOR TO THE COMPLETION OF THIS PROJECT.
17. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES, AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER INSTALLATION OF UTILITIES COMPLETE AND OPERATIONAL.
18. CONTRACTOR SHALL PROVIDE EXCAVATION, BEDDING, BACKFILL AND COMPACTION FOR NATURAL GAS SERVICES.
19. A 10-FOOT MINIMUM EDGE TO EDGE HORIZONTAL SEPARATION SHALL BE PROVIDED BETWEEN ALL WATER AND SANITARY SEWER LINES. AN 18-INCH MINIMUM OUTSIDE TO OUTSIDE VERTICAL SEPARATION SHALL BE PROVIDED AT ALL WATER/SANITARY SEWER CROSSINGS.
20. THE CONTRACTOR SHALL CONTACT "DIG-SAFE" 72 HOURS PRIOR TO COMMENCING CONSTRUCTION. THE CONTRACTOR SHALL HAVE THE "DIG-SAFE" NUMBER ON SITE AT ALL TIMES.
21. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILES) TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
22. SAWCUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN.
23. HYDRANTS, GATE VALVES, FITTINGS, ETC. SHALL MEET THE REQUIREMENTS OF THE CITY OF PORTSMOUTH.
24. COORDINATE TESTING OF SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH.
25. ALL SEWER PIPE WITH LESS THAN 4' OF COVER SHALL BE INSULATED.
26. CONTRACTOR SHALL COORDINATE ALL ELECTRIC WORK INCLUDING BUT NOT LIMITED TO: CONDUIT CONSTRUCTION, MANHOLE CONSTRUCTION, UTILITY POLE CONSTRUCTION, OVERHEAD WIRE RELOCATION, AND TRANSFORMER CONSTRUCTION WITH POWER COMPANY.
27. CONTRACTOR SHALL PHASE UTILITY CONSTRUCTION, PARTICULARLY WATER MAIN AND GAS MAIN CONSTRUCTION, AS TO MAINTAIN CONTINUOUS SERVICE TO ABUTTING PROPERTIES. CONTRACTOR SHALL COORDINATE TEMPORARY SERVICES TO ABUTTERS WITH THE UTILITY COMPANY AND AFFECTED ABUTTER.
28. SITE LIGHTING SPECIFICATIONS, CONDUIT LAYOUT AND CIRCUITRY FOR PROPOSED SITE LIGHTING AND SIGN ILLUMINATION SHALL BE PROVIDED BY THE PROJECT ELECTRICAL ENGINEER.
29. CONTRACTOR SHALL CONSTRUCT ALL UTILITIES AND DRAINS TO WITHIN 10' OF THE FOUNDATION WALLS AND CONNECT THESE TO SERVICE STUBS FROM THE BUILDING.
30. EXISTING SEWER MAIN AND STRUCTURES IN GOOSE BAY DRIVE ARE BASED ON A PROPOSED DESIGN BY UNDERWOOD ENGINEERS, DATED JULY 28, 2017, AND IS SLATED FOR CONSTRUCTION IN SPRING 2018. THE PROPOSED ON-SITE SEWER DESIGN ELEVATIONS BASED ON THE UNDERWOOD PLAN DURING CONSTRUCTION. THE CONTRACTOR SHALL COORDINATE SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH, AND VERIFY ALL INVERTS PRIOR TO CONSTRUCTION.
31. LOCATION SHOWN IS APPROXIMATE ONLY. FINAL DESIGN OF NATURAL GAS SERVICE TO BE COMPLETED BY UNITIL. WORK IN CORPORATE DRIVE MAY NEED TO BE COMPLETED IN CONJUNCTION WITH FUTURE RECONSTRUCTION OF CORPORATE DRIVE. COORDINATE WITH CITY OF PORTSMOUTH AND UNITIL.
32. LOCATION AND TYPE SHOWN IS APPROXIMATE ONLY. FINAL DESIGN OF ELECTRIC SERVICE AND ASSOCIATED INFRASTRUCTURE TO BE COMPLETED BY EVERSOURCE. WORK IN CORPORATE DRIVE MAY NEED TO BE COMPLETED IN CONJUNCTION WITH FUTURE RECONSTRUCTION OF CORPORATE DRIVE.



Last Save Date: May 28, 2018 11:28 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 1276\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CU-111 to C-113.dwg Layout Tab: C-111



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire




MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
 DATE: 04/03/2018  
 FILE: L0700-CU-111 to C-113.dwg  
 DRAWN BY: BCC  
 CHECKED: PMC  
 APPROVED: BLM









**Proposed Industrial Development**

Lonza Biologics


Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CU-111 to C-113.dwg		
DRAWN BY: BCC		
CHECKED: PMC		
APPROVED: BLM		

**UTILITIES PLAN**

SCALE: AS SHOWN


**C-113**



SEE SHEET C-111 FOR  
UTILITY NOTES AND LEGEND




Last Save Date: May 28, 2018 11:28 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 12720@0.13 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CU-111 to C-113.dwg Layout Tab: C-113





**LANDSCAPE NOTES:**

1. THE CONTRACTOR SHALL FURNISH AND PLANT ALL PLANTS IN QUANTITIES AS SHOWN ON THIS PLAN. NO SUBSTITUTIONS WILL BE PERMITTED UNLESS APPROVED BY OWNER. ALL PLANTS SHALL BE NURSERY GROWN.
2. ALL PLANTS SHALL BE NURSERY GROWN AND PLANTS AND WORKMANSHIP SHALL CONFORM TO THE AMERICAN ASSOCIATION OF NURSERYMEN STANDARDS, INCLUDING BUT NOT LIMITED TO SIZE, HEALTH, SHAPE, ETC., AND SHALL BE SUBJECT TO THE APPROVAL OF THE LANDSCAPE ARCHITECT PRIOR TO ARRIVAL ON-SITE AND AFTER PLANTING.
3. PLANT STOCK SHALL BE GROWN WITHIN THE HARDINESS ZONES 4 THRU 7 ESTABLISHED BY THE PLANT HARDINESS ZONE MAP, MISCELLANEOUS PUBLICATIONS NO. 814, AGRICULTURAL RESEARCH SERVICE, UNITED STATES DEPARTMENT AGRICULTURE, LATEST REVISION.
4. PLANT MATERIAL SHALL BARE THE SAME RELATIONSHIP TO FINISHED GRADE AS TO THE ORIGINAL PLANTING GRADE PRIOR TO DIGGING.
5. THE NUMBER OF EACH INDIVIDUAL PLANT TYPE AND SIZE PROVIDED IN THE PLANT LIST OR ON THE PLAN IS FOR THE CONTRACTOR'S CONVENIENCE ONLY. IF A DISCREPANCY EXISTS BETWEEN THE NUMBER OF PLANTS ON THE LABEL AND THE NUMBER OF SYMBOLS SHOWN ON THE DRAWINGS, THE GREATER NUMBER SHALL APPLY.
6. NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT THE PRIOR WRITTEN APPROVAL OF THE OWNER'S REPRESENTATIVE.
7. THE CONTRACTOR SHALL LOCATE, VERIFY AND MARK ALL EXISTING AND NEWLY INSTALLED UNDERGROUND UTILITIES PRIOR TO ANY LAWN WORK OR PLANTING. ANY CONFLICTS WHICH MIGHT OCCUR BETWEEN PLANTING AND UTILITIES SHALL IMMEDIATELY BE REPORTED TO THE OWNER SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
8. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED, SHALL RECEIVE SIX (6) INCHES OF LOAM AND SEED. NO FILL SHALL BE PLACED IN ANY WETLAND AREA.
9. THREE (3) INCH BARK MULCH IS TO BE USED AROUND THE TREE AND SHRUB PLANTING AS SPECIFIED IN THE DETAILS. WHERE BARK MULCH IS TO BE USED IN A CURBED ISLAND THE BARK MULCH SHALL MEET THE TOP INSIDE EDGE OF THE CURB. ALL OTHER AREAS SHALL RECEIVE SIX (6) INCHES OF LOAM AND SEED.
10. LANDSCAPING SHALL BE LOCATED WITHIN 150 FT OF EXTERIOR HOSE ATTACHMENT OR SHALL BE PROVIDED WITH AN IRRIGATION SYSTEM.
11. SEE PLANTING DETAILS AND SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
12. TREE STAKES SHALL REMAIN IN PLACE FOR NO LESS THAN 6 MONTHS AND NO MORE THAN 1 YEAR.
13. PLANTING SHALL BE COMPLETED FROM APRIL 15TH THROUGH OCTOBER 1ST. NO PLANTING DURING JULY AND AUGUST UNLESS SPECIAL PROVISIONS ARE MADE FOR DROUGHT.
14. PARKING AREA PLANTED ISLANDS TO HAVE MINIMUM OF 1'-0" TOPSOIL PLACED TO WITHIN 3 INCHES OF THE TOP OF CURB ELEVATION. REMOVE ALL CONSTRUCTION DEBRIS BEFORE PLACING TOPSOIL.
15. TREES SHALL BE PRUNED IN ACCORDANCE WITH THE LATEST EDITION OF ANSI A300 'TREES, SHRUBS AND OTHER WOOD PLANT MAINTENANCE STANDARD PRACTICES.
16. ALL PLANTS SHALL BE WATERED THOROUGHLY TWICE DURING THE FIRST 24 HOUR PERIOD AFTER PLANTING. ALL PLANTS SHALL BE WATERED WEEKLY, OR MORE OFTEN, IF NECESSARY DURING THE FIRST GROWING SEASON.
17. EXISTING TREES AND SHRUBS SHOWN ON THE PLAN ARE TO REMAIN UNDISTURBED. ALL EXISTING TREES AND SHRUBS SHOWN TO REMAIN ARE TO BE PROTECTED WITH A 4-FOOT SNOW FENCE PLACED AT THE DRIP LINE OF THE BRANCHES OR AT 8 FEET MINIMUM FROM THE TREE TRUNK. ANY EXISTING TREE OR SHRUB SHOWN TO REMAIN, WHICH IS REMOVED DURING CONSTRUCTION, SHALL BE REPLACED BY A TREE OF COMPARABLE SIZE AND SPECIES TREE OR SHRUB.
18. THE CONTRACTOR SHALL GUARANTEE ALL PLANTINGS TO BE IN GOOD HEALTHY, FLOURISHING AND ACCEPTABLE CONDITION FOR A PERIOD OF (1) YEAR BEGINNING AT THE DATE OF ACCEPTANCE OF SUBSTANTIAL COMPLETION. ALL GRASSES, TREES AND SHRUBS THAT, IN THE OPINION OF THE LANDSCAPE ARCHITECT, SHOW LESS THAN 80% HEALTHY GROWTH AT THE END OF ONE YEAR PERIOD SHALL BE REPLACED BY THE CONTRACTOR.
19. UPON EXPIRATION OF THE CONTRACTOR'S ONE YEAR GUARANTEE PERIOD, THE OWNER SHALL BE RESPONSIBLE FOR LANDSCAPE MAINTENANCE INCLUDING WATERING DURING PERIODS OF DROUGHT.
20. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL PLANTING AND LAWNS AGAINST DAMAGE FROM ONGOING CONSTRUCTION. THIS PROTECTION SHALL BEGIN AT THE TIME THE PLANT IS INSTALLED AND CONTINUE UNTIL THE FORMAL ACCEPTANCE OF ALL THE PLANTINGS.
21. PRE-PURCHASE PLANT MATERIAL AND ARRANGE FOR DELIVERY TO MEET PROJECT SCHEDULE AS REQUIRED IT MAY BE NECESSARY TO PRE-DIG CERTAIN SPECIES WELL IN ADVANCE OF ACTUAL PLANTING DATES.



Last Save Date: May 21, 2018 3:43 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 1278\013 Iron Parcel Redevelopment\Drawings\_Figures\AutoCAD\Sheet\0700-CL-114 to C-116.dwg Layout Tab: C-114

**Proposed Industrial Development**  
  
Lonza Biologics

Portsmouth,  
New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CL-114 to C-116.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

SEE SHEET C-116 FOR PLANT SCHEDULE















**Proposed Industrial Development**

Lonza Biologics


Portsmouth,  
New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CP-117 to C-119.dwg		
DRAWN BY: NAH		
CHECKED BY: PMC		
APPROVED BY: BLM		


**PHOTOMETRIC LIGHTING PLAN**

SCALE: AS SHOWN

**C-117**






Symbol	Qty	Label	Arrangement	Description
[Symbol]	1	S3	SINGLE	GLEON-AF-02-LED-E1-SL3/ SSS4A208FN1 (20' AFG)
[Symbol]	4	S4	SINGLE	GLEON-AF-02-LED-E1-SL4/ SSS4A208FN1 (20' AFG)
[Symbol]	7	W	SINGLE	GWC-AF-01-LED-E1-SL1/ WALL MTD 20' AFG
[Symbol]	4	W3	SINGLE	GWC-AF-02-LED-E1-SL3/ WALL MTD 20' AFG
[Symbol]	26	W4	SINGLE	GWC-AF-02-LED-E1-SL4/ WALL MTD 20' AFG



Last Save Date: May 30, 2018 10:20 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion wss 1276\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CP-117 to C-119.dwg Layout Tab: C-117





**Proposed Industrial Development**

Lonza Biologics


Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CP-117 to C-119.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

**PHOTOMETRIC LIGHTING PLAN**

SCALE: AS SHOWN




**C-118**



Symbol	Qty	Label	Arrangement	Description
[Symbol]	1	S3	SINGLE	GLEON-AF-02-LED-E1-SL3/ SSS4A208FN1 (20' AFG)
[Symbol]	4	S4	SINGLE	GLEON-AF-02-LED-E1-SL4/ SSS4A208FN1 (20' AFG)
[Symbol]	7	W	SINGLE	GWC-AF-01-LED-E1-SL3/ WALL MTD 20' AFG
[Symbol]	4	W3	SINGLE	GWC-AF-02-LED-E1-SL3/ WALL MTD 20' AFG
[Symbol]	26	W4	SINGLE	GWC-AF-02-LED-E1-SL4/ WALL MTD 20' AFG

Last Save Date: May 30, 2018 10:20 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: Z:\L0700\Lonza Biologics Expansion.was 127620.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CP-117 to C-119.dwg Layout Tab: C-118





**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CP-117 to C-119.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**PHOTOMETRIC LIGHTING PLAN**

SCALE: AS SHOWN

**C-119**



Symbol	Qty	Label	Arrangement	Description
[Symbol]	1	S3	SINGLE	GLEON-AP-02-LED-E1-SL3/ SS84A20SFN1 (20' AFG)
[Symbol]	4	S4	SINGLE	GLEON-AP-02-LED-E1-SL4/ SS84A20SFN1 (20' AFG)
[Symbol]	1	W	SINGLE	GWC-AP-01-LED-E1-SL3/ WALL MTD 20' AFG
[Symbol]	4	W3	SINGLE	GWC-AP-02-LED-E1-SL3/ WALL MTD 20' AFG
[Symbol]	26	W4	SINGLE	GWC-AP-02-LED-E1-SL4/ WALL MTD 20' AFG

Last Save Date: May 30, 2018 10:20 AM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: X:\L0700\Lonza Biologics Expansion.was 1276P.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CP-117 to C-119.dwg Layout Tab: C-119



**PROJECT NAME AND LOCATION**

LONZA BIOLOGICS 43°-04'-59.0"N  
70 & 80 CORPORATE DRIVE 70°-48'-09.7"W  
PORTSMOUTH, NH 03801

**DESCRIPTION**

THE PROJECT CONSISTS OF THE EXPANSION OF LONZA BIOLOGICS, WHICH INCLUDES THE CONSTRUCTION OF 3 PROPOSED BUILDINGS, 2 PARKING GARAGES AND ASSOCIATED SITE IMPROVEMENTS

**DISTURBED AREA**

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 23 ACRES.

**SOIL CHARACTERISTICS**

BASED ON THE HIGH INTENSITY SOIL SURVEY PREPARED BY GOVE ENVIRONMENTAL SERVICES, INC. IN DECEMBER 2015, THE SITE SOILS VARY FROM WELL DRAINED TO VERY POORLY DRAINED AND PRIMARILY CONSIST OF SOMEWHAT POORLY DRAINED SOILS.

**NAME OF RECEIVING WATERS**

THE STORM WATER RUNOFF WILL ULTIMATELY DISCHARGE INTO HODGSON BROOK

**SEQUENCE OF MAJOR ACTIVITIES**

- CUT AND CLEAR TREES.
- CONSTRUCT TEMPORARY AND PERMANENT SEDIMENT, EROSION AND DETENTION CONTROL FACILITIES. EROSION, SEDIMENT AND DETENTION MEASURES SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OPERATIONS THAT WILL INFLUENCE STORMWATER RUNOFF SUCH AS:
  - NEW CONSTRUCTION
  - DEVELOPMENT OF BORROW PIT AREAS
  - DISPOSAL OF SEDIMENT SOIL, STUMP AND OTHER SOLID WASTE
  - STREAM CHANNEL MODIFICATIONS
  - CONTROL OF DUST
  - CONSTRUCTION OF ACCESS ROAD
- NEARNESS OF CONSTRUCTION SITE TO RECEIVING WATERS
  - CONSTRUCTION DURING LATE WINTER AND EARLY SPRING
- ALL PERMANENT DITCHES, SWALES, DETENTION, RETENTION AND SEDIMENTATION BASINS TO BE STABILIZED USING THE VEGETATIVE AND NON-STRUCTURAL BMPS PRIOR TO DIRECTING RUNOFF TO THEM.
- CLEAR AND DISPOSE OF DEBRIS.
- CONSTRUCT TEMPORARY CULVERTS AND DIVERSION CHANNELS AS REQUIRED.
- GRADE AND GRAVEL ROADWAYS AND PARKING AREAS - ALL ROADS AND PARKING AREA SHALL BE STABILIZED IMMEDIATELY AFTER THEIR CONSTRUCTION.
- BEGIN PERMANENT AND TEMPORARY SEEDING AND MULCHING. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED IMMEDIATELY AFTER THEIR CONSTRUCTION.
- DAILY, OR AS REQUIRED, CONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, SILT FENCES, SEDIMENT TRAPS, ETC., MULCH AND SEED AS REQUIRED.
- FINISH PAVING ALL ROADWAYS AND PARKING LOTS.
- INSPECT AND MAINTAIN ALL EROSION AND SEDIMENT CONTROL MEASURES.
- COMPLETE PERMANENT SEEDING AND LANDSCAPING.
- REMOVE TRAPPED SEDIMENTS FROM COLLECTOR DEVICES AS APPROPRIATE AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES.

NOTE: THE CONSTRUCTION SEQUENCE MUST LIMIT THE DURATION AND AREA OF DISTURBANCE.

**CULVERTS:**

- ALL STOCKPILES SHOULD BE SURROUNDED WITH TEMPORARY EROSION CONTROL MEASURES PRIOR TO THE ONSET OF PRECIPITATION.
- PERIMETER BARRIERS SHOULD BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE INTEGRITY OF THE BARRIER SHOULD BE INSPECTED AT THE END OF EACH WORKING DAY.
- PROTECT ALL STOCKPILES FROM STORMWATER RUN-OFF USING TEMPORARY EROSION CONTROL MEASURES SUCH AS BERMS, SILT SOCK, OR OTHER APPROVED PRACTICE TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.

**OFF SITE VEHICLE TRACKING**

THE CONTRACTOR SHALL CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE(S) PRIOR TO ANY EXCAVATION ACTIVITIES.

**VEGETATION**

- TEMPORARY GRASS COVER
  - SEEDBED PREPARATION:
    - APPLY FERTILIZER AT THE RATE OF 600 POUNDS PER ACRE OF 10-10-10. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF THREE (3) TONS PER ACRE.
  - SEEDING:
    - UTILIZE ANNUAL RYE GRASS AT A RATE OF 40 LBS/ACRE.
    - WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF TWO (2) INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.
    - APPLY SEED UNIFORMLY BY HAND, CYCLOSEEDER, OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). HYDROSEEDINGS, WHICH INCLUDE MULCH, MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING.
- MAINTENANCE
  - TEMPORARY SEEDING SHALL BE PERIODICALLY INSPECTED. AT A MINIMUM, 95% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND OTHER TEMPORARY MEASURES USED IN THE INTERIM (MULCH, FILTER BARRIERS, CHECK DAMS, ETC.).

**VEGETATIVE PRACTICE**

- FOR PERMANENT MEASURES AND PLANTINGS.
  - LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF THREE (3) TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5.
  - FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 800 POUNDS PER ACRE OF 10-20-20 FERTILIZER.
  - SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN, AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE REQUIRED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4-1/2 POUNDS AND 5-1/2 POUNDS PER INCH OF WIDTH.
  - SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH.
  - HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AS INDICATED ABOVE.
  - THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED, AND ALL NOXIOUS WEEDS REMOVED.
  - THE CONTRACTOR SHALL PROTECT AND MAINTAIN THE SEEDED AREAS UNTIL ACCEPTED.
  - A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE APPLIED AT THE INDICATED RATE:
 

SEEDING RATE	
CREeping RED FESCUE	20 LBS/ACRE
TALL FESCUE	20 LBS/ACRE
REDTOP	2 LBS/ACRE

IN NO CASE SHALL THE WEED CONTENT EXCEED ONE (1) PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH STATE AND FEDERAL SEED LAWS. SEEDING SHALL BE DONE NO LATER THAN SEPTEMBER 15. IN NO CASE SHALL SEEDING TAKE PLACE OVER SNOW.
- DORMANT SEEDING (SEPTEMBER 15 TO FIRST SNOWFALL) FOLLOW PERMANENT MEASURES SLOPE, LIME, FERTILIZER AND GRADING REQUIREMENTS. APPLY SEED MIXTURE AT TWICE THE INDICATED RATE. APPLY MULCH AS INDICATED FOR PERMANENT MEASURES.

**CONCRETE WASHOUT AREA**

- THE FOLLOWING ARE THE ONLY NON-STORMWATER DISCHARGES ALLOWED. ALL OTHER NON-STORMWATER DISCHARGES ARE PROHIBITED ON SITE.
  - THE CONCRETE DELIVERY TRUCKS SHALL, WHENEVER POSSIBLE, USE WASHOUT FACILITIES AT THEIR OWN PLANT OR DISPATCH FACILITY.
  - IF IT IS NECESSARY, SITE CONTRACTOR SHALL DESIGNATE SPECIFIC WASHOUT AREAS AND DESIGN FACILITIES TO HANDLE ANTICIPATED WASHOUT WATER.
  - CONTRACTOR SHALL LOCATE WASHOUT AREAS AT LEAST 150 FEET AWAY FROM STORM DRAINS, SWALES AND SURFACE WATERS OR DELINEATED WETLANDS.
  - INSPECT WASHOUT FACILITIES DAILY TO DETECT LEAKS OR TEARS AND TO IDENTIFY WHEN MATERIALS NEED TO BE REMOVED.

**ALLOWABLE NON-STORMWATER DISCHARGES**

- DISCHARGES FROM FIRE-FIGHTING ACTIVITIES
- FIRE HYDRANT FLUSHINGS
- WATERS USED TO WASH VEHICLES WHERE DETERGENTS ARE NOT USED
- WATER USED TO CONTROL DUST
- POTABLE WATER INC. UNCONTAMINATED WATER LINE FLUSHINGS
- ROUTINE EXTERNAL BUILDING WASH DOWN -NO DETERGENTS
- PAVEMENT WASH WATERS -NO SPILLS OR DETERGENTS
- UNCONTAMINATED AIR CONDITIONING/COMPRESSOR CONDENSATE
- UNCONTAMINATED GROUND WATER OR SPRING WATER
- FOUNDATION OR FOOTING DRAINS -NOT CONTAMINATED
- UNCONTAMINATED EXCAVATION DEWATERING
- LANDSCAPE IRRIGATION

**WASTE DISPOSAL**

- WASTE MATERIALS
  - ALL WASTE MATERIALS SHALL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE SHALL BE DEPOSITED IN A DUMPSTER.
  - NO CONSTRUCTION WASTE MATERIALS SHALL BE BURIED ON SITE.
  - ALL PERSONNEL SHALL BE INSTRUCTED REGARDING THE CORRECT PROCEDURE FOR WASTE DISPOSAL BY THE SUPERINTENDENT.
- HAZARDOUS WASTE
  - ALL HAZARDOUS WASTE MATERIALS SHALL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER.
  - SITE PERSONNEL SHALL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTENDENT.
- SANITARY WASTE
  - ALL SANITARY WASTE SHALL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

**SPILL PREVENTION**

- CONTRACTOR SHALL BE FAMILIAR WITH SPILL PREVENTION MEASURES REQUIRED BY LOCAL, STATE AND FEDERAL AGENCIES. AT A MINIMUM, CONTRACTOR SHALL FOLLOW THE BEST MANAGEMENT SPILL PREVENTION PRACTICES OUTLINED BELOW.
- THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT SHALL BE USED TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING CONSTRUCTION TO STORMWATER RUNOFF:

- GOOD HOUSEKEEPING:
  - THE FOLLOWING GOOD HOUSEKEEPING PRACTICES SHALL BE FOLLOWED ON SITE DURING THE CONSTRUCTION PROJECT:
    - ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB SHALL BE STORED ON SITE.
    - ALL MATERIALS STORED ON SITE SHALL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR PROPER (ORIGINAL, IF POSSIBLE) CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE.
    - MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL SHALL BE FOLLOWED.
    - THE SITE SUPERINTENDENT SHALL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS.
    - SUBSTANCES SHALL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER.
    - WHENEVER POSSIBLE ALL OF A PRODUCT SHALL BE USED UP BEFORE DISPOSING OF THE CONTAINER.
  - HAZARDOUS PRODUCTS:
    - THE FOLLOWING PRACTICES SHALL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
      - PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT RESEALABLE.
      - ORIGINAL LABELS AND MATERIAL SAFETY DATA SHALL BE RETAINED FOR IMPORTANT PRODUCT INFORMATION.
      - SURPLUS PRODUCT THAT MUST BE DISPOSED OF SHALL BE DISCARDED ACCORDING TO THE MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL.
  - PRODUCT SPECIFICATION PRACTICES
    - THE FOLLOWING PRODUCT SPECIFIC PRACTICES SHALL BE FOLLOWED ON SITE:
      - PETROLEUM PRODUCTS:
        - ALL ON SITE VEHICLES SHALL BE MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO REDUCE LEAKAGE.
        - PETROLEUM PRODUCTS SHALL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE SHALL BE APPLIED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.
      - FERTILIZERS:
        - FERTILIZERS USED SHALL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS.
        - ONCE APPLIED FERTILIZER SHALL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO STORMWATER.
        - STORAGE SHALL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER SHALL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.
      - PAINTS:
        - ALL CONTAINERS SHALL BE TIGHTLY SEALED AND STORED WHEN NOT REQUIRED FOR USE.
        - EXCESS PAINT SHALL NOT BE DISCHARGED TO THE STORM SEWER SYSTEM.
        - EXCESS PAINT SHALL BE DISPOSED OF PROPERLY ACCORDING TO MANUFACTURER'S INSTRUCTIONS OR STATE AND LOCAL REGULATIONS.
  - SPILL CONTROL PRACTICES
    - IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION, THE FOLLOWING PRACTICES SHALL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP:
      - MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP SHALL BE CLEARLY POSTED AND SITE PERSONNEL SHALL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES.
      - MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP SHALL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS SHALL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS, RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE.
      - ALL SPILLS SHALL BE CLEANED UP IMMEDIATELY AFTER DISCOVERY.
      - THE SPILL AREA SHALL BE KEPT WELL VENTILATED AND PERSONNEL SHALL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A HAZARDOUS SUBSTANCE.
      - SPILLS OF TOXIC OR HAZARDOUS MATERIAL SHALL BE REPORTED TO THE APPROPRIATE LOCAL, STATE OR FEDERAL AGENCIES AS REQUIRED.
      - THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS SHALL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.
    - VEHICLE FUELING AND MAINTENANCE PRACTICE:
      - CONTRACTOR SHALL MAKE AN EFFORT TO PERFORM EQUIPMENT/VEHICAL FUELING AND MAINTENANCE AT AN OFF-SITE FACILITY.
      - CONTRACTOR SHALL PROVIDE AN ON-SITE FUELING AND MAINTENANCE AREA THAT IS CLEAN AND DRY.
      - IF POSSIBLE THE CONTRACTOR SHALL KEEP AREA COVERED.
      - CONTRACTOR SHALL KEEP A SPILL KIT AT THE FUELING AND MAINTENANCE AREA.
      - CONTRACTOR SHALL VEHICLES SHALL BE INSPECTED REGULARLY FOR LEAKS AND DAMAGE.
      - CONTRACTOR SHALL USE DRIP PANS, DRIP CLOTHS, OR ABSORBENT PADS WHEN REPLACING SPENT FLUID.

**EROSION CONTROL OBSERVATIONS AND MAINTENANCE PRACTICES**  
THIS PROJECT EXCEEDS ONE (1) ACRE OF DISTURBANCE AND THUS REQUIRES A SWPPP. THE SWPPP SHALL BE PREPARED BY THE ENGINEER (CONTRACTOR). THE CONTRACTOR SHALL BE FAMILIAR WITH THE SWPPP AND KEEP AN UPDATED COPY OF THE SWPPP ON SITE AT ALL TIMES.

THE FOLLOWING REPRESENTS THE GENERAL OBSERVATION AND REPORTING PRACTICES THAT SHALL BE FOLLOWED AS PART OF THIS PROJECT.


- OBSERVATIONS OF THE PROJECT FOR COMPLIANCE WITH THE SWPPP SHALL BE MADE BY THE ENGINEER (CONTRACTOR) AT LEAST ONCE A WEEK OR WITHIN 24 HOURS OF A STORM 0.25 INCHES OR GREATER.
- AN OBSERVATION REPORT SHALL BE MADE AFTER EACH OBSERVATION AND DISTRIBUTED TO THE ENGINEER, THE OWNER, AND THE CONTRACTOR.
- A REPRESENTATIVE OF THE SITE CONTRACTOR, SHALL BE RESPONSIBLE FOR MAINTENANCE AND REPAIR ACTIVITIES.
- IF A REPAIR IS NECESSARY, IT SHALL BE INITIATED WITHIN 24 HOURS OF REPORT.

**BLASTING NOTES**

- IF MORE THAN 5000 CUBIC YARDS ARE TO BE BLASTED A BLASTING PLAN SHALL BE PROVIDED. BLASTING PLAN SHALL INCLUDE:
  - LOCATION AND IDENTIFICATION OF DRINKING WATER WELLS LOCATED WITHIN 2000 FEET OF THE PROPOSED BLASTING ACTIVITIES.
  - A GROUNDWATER QUALITY SAMPLING PROGRAM, APPROVED BY NHDES PRIOR TO INITIATING BLASTING, TO MONITOR FOR NITRATE AND NITRITE EITHER IN THE DRINKING WATER SUPPLY WELLS OR IN OTHER WELLS THAT ARE REPRESENTATIVE OF THE DRINKING WATER SUPPLY WELLS IN THE AREA.
    - THE GROUNDWATER SAMPLING PROGRAM MUST BE IMPLEMENTED ONCE APPROVED BY NHDES.
- THE FOLLOWING BEST MANAGEMENT PROCEDURES FOR BLASTING SHALL BE COMPLIED WITH:
  - LOADING PRACTICES.
    - THE FOLLOWING BLASTHOLE LOADING PRACTICES TO MINIMIZE ENVIRONMENTAL EFFECTS SHALL BE FOLLOWED:
      - DRILLING LOGS SHALL BE MAINTAINED BY THE DRILLER AND COMMUNICATED DIRECTLY TO THE BLASTER. THE LOGS SHALL INDICATE DEPTHS AND LENGTHS OF VOIDS, CAVITIES, AND FAULT ZONES OR OTHER WEAK ZONES ENCOUNTERED AS WELL AS GROUNDWATER CONDITIONS.
      - EXPLOSIVE PRODUCTS SHALL BE MANAGED ON-SITE SO THAT THEY ARE EITHER USED IN THE BOREHOLE, RETURNED TO THE DELIVERY VEHICLE, OR PLACED IN SECURE CONTAINERS FOR OFF-SITE DISPOSAL.
      - SPILLAGE AROUND THE BOREHOLE SHALL EITHER BE PLACED IN THE BOREHOLE OR CLEANED UP AND RETURNED TO AN APPROPRIATE VEHICLE FOR HANDLING OR PLACEMENT IN SECURED CONTAINERS FOR OFF-SITE DISPOSAL.
      - LOADED EXPLOSIVES SHALL BE DETONATED AS SOON AS POSSIBLE AND SHALL NOT BE LEFT IN THE BLASTHOLES OVERNIGHT, UNLESS WEATHER OR OTHER SAFETY CONCERNS REASONABLY DICTATE THAT DETONATION SHOULD BE POSTPONED.
  - LOADING EQUIPMENT SHALL BE CLEANED IN AN AREA WHERE WASTEWATER CAN BE PROPERLY CONTAINED AND HANDLED IN A MANNER THAT PREVENTS RELEASE OF CONTAMINANTS TO THE ENVIRONMENT.
  - EXPLOSIVES SHALL BE LOADED TO MAINTAIN GOOD CONTINUITY IN THE COLUMN LOAD TO PROMOTE COMPLETE DETONATION. INDUSTRY ACCEPTED LOADING PRACTICES FOR PRIMING, STEMMING, DECKING AND COLUMN RISE NEED TO BE ATTENDED TO.
  - EXPLOSIVE SELECTION
    - THE FOLLOWING BMPS SHALL BE FOLLOWED TO REDUCE THE POTENTIAL FOR GROUNDWATER CONTAMINATION WHEN EXPLOSIVES ARE USED:
      - EXPLOSIVE PRODUCTS SHALL BE SELECTED THAT ARE APPROPRIATE FOR SITE CONDITIONS AND SAFE BLAST EXECUTION.
      - EXPLOSIVE PRODUCTS SHALL BE SELECTED THAT HAVE THE APPROPRIATE WATER RESISTANCE FOR THE SITE CONDITIONS PRESENT TO MINIMIZE THE POTENTIAL FOR HAZARDOUS EFFECT OF THE PRODUCT UPON GROUNDWATER.
  - PREVENTION OF MISFIRES. APPROPRIATE PRACTICES SHALL BE DEVELOPED AND IMPLEMENTED TO PREVENT MISFIRES.
  - MUCK PILE MANAGEMENT
    - MUCK PILES (THE BLASTED PIECES OF ROCK) AND ROCK PILES SHALL BE MANAGED IN A MANNER TO REDUCE THE POTENTIAL FOR CONTAMINATION BY IMPLEMENTING THE FOLLOWING MEASURES:
      - REMOVE THE MUCK PILE FROM THE BLAST AREA AS SOON AS REASONABLY POSSIBLE.
      - MANAGE THE INTERACTION OF BLASTED ROCK PILES AND STORMWATER TO PREVENT CONTAMINATION OF WATER SUPPLY WELLS OR SURFACE WATER.
  - SPILL PREVENTION MEASURES AND SPILL MITIGATION
    - SPILL PREVENTION AND SPILL MITIGATION MEASURES SHALL BE IMPLEMENTED TO PREVENT THE RELEASE OF FUEL AND OTHER RELATED SUBSTANCES TO THE ENVIRONMENT. THE MEASURES SHALL INCLUDE AT A MINIMUM:
      - THE FUEL STORAGE REQUIREMENTS SHALL INCLUDE:
        - STORAGE OF REGULATED SUBSTANCES ON AN IMPERVIOUS SURFACE;
        - SECURE STORAGE AREAS AGAINST UNAUTHORIZED ENTRY;
        - LABEL REGULATED CONTAINERS CLEARLY AND VISIBLY;
        - INSPECT STORAGE AREAS WEEKLY;
        - COVER REGULATED CONTAINERS IN OUTSIDE STORAGE AREAS;
        - WHEREVER POSSIBLE, KEEP REGULATED CONTAINERS THAT ARE STORED OUTSIDE MORE THAN 50 FEET FROM SURFACE WATER AND STORM DRAINS, 75 FEET FROM PRIVATE WELLS, AND 400 FEET FROM PUBLIC WELLS; AND
        - SECONDARY CONTAINMENT IS REQUIRED FOR CONTAINERS CONTAINING REGULATED SUBSTANCES STORED OUTSIDE, EXCEPT FOR ON PREMISE USE HEATING FUEL TANKS, OR ABOVEGROUND OR UNDERGROUND STORAGE TANKS OTHERWISE REGULATED.
      - THE FUEL HANDLING REQUIREMENTS SHALL INCLUDE:
        - EXCEPT WHEN IN USE, KEEP CONTAINERS CONTAINING REGULATED SUBSTANCES CLOSED AND SEALED;
        - PLACE DRIP PANS UNDER SPIGOTS, VALVES, AND PUMPS;
        - HAVE SPILL CONTROL AND CONTAINMENT EQUIPMENT READILY AVAILABLE IN ALL WORK AREAS;
        - USE FUNNELS AND DRIP PANS WHEN TRANSFERRING REGULATED SUBSTANCES;
        - PERFORM TRANSFERS OF REGULATED SUBSTANCES OVER AN IMPERVIOUS SURFACE.
    - THE TRAINING OF ON-SITE EMPLOYEES AND THE ON-SITE POSTING OF RELEASE RESPONSE INFORMATION DESCRIBING WHAT TO DO IN THE EVENT OF A SPILL OF REGULATED SUBSTANCES.
    - FUELING AND MAINTENANCE OF EXCAVATION, EARTHMOVING AND OTHER CONSTRUCTION RELATED EQUIPMENT SHALL COMPLY WITH THE REGULATIONS OF THE NEW HAMPSHIRE DEPARTMENT OF ENVIRONMENTAL SERVICES THESE REQUIREMENTS ARE SUMMARIZED IN WD-DWGB-22-6 BEST MANAGEMENT PRACTICES FOR FUELING AND MAINTENANCE OF EXCAVATION AND EARTHMOVING EQUIPMENT" OR ITS SUCCESSOR DOCUMENT. (SEE [HTTP://DES.NH.GOV/ORGANIZATION/COMMISSIONER/PIP/FACTSHEETS/DWGB/DOCUMENTS/DWGB-22-6.PDF](http://DES.NH.GOV/ORGANIZATION/COMMISSIONER/PIP/FACTSHEETS/DWGB/DOCUMENTS/DWGB-22-6.PDF))



Engineers | Environmental Specialists



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION

PROJECT NO:	L-0700-13
DATE:	04/03/2018
FILE:	L0700-CD-501 to C-508.dwg
DRAWN BY:	NAH
CHECKED:	PMC
APPROVED:	BLM


**EROSION CONTROL NOTES**

SCALE: AS SHOWN

C-501

Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: J:\L0700 Lonza Biologics Expansion.was 157629.013 From Parcel Redevelopment Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-501







- PAVEMENT MARKING NOTES:**
- ALL WORDS AND SYMBOLS SHALL BE RETROREFLECTIVE WHITE AND SHALL CONFORM TO THE LATEST VERSION OF THE MUTCD.
  - COMBINATION ARROWS MAY BE COMPRISED OF 2 SINGLE ARROWS (e.g. TURN AND THROUGH ARROWS). HOWEVER, THE SHAFTS OF THE ARROWS SHALL COINCIDE AS SHOWN.
  - PREFORMED SYMBOLS SHALL BE PRE-CUT BY THE MANUFACTURER.
  - WRONG-WAY ARROWS SHALL NOT BE SUBSTITUTED FOR THROUGH ARROWS.
  - ALL SYMBOLS SHALL BE CONSTRUCTED USING FAST DRYING TRAFFIC PAINT MEETING THE REQUIREMENTS OF AASHTO M248-TYPE F. PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER.

**PAVEMENT MARKINGS**  
NO SCALE







- CONTROL LANE GENERAL NOTES:**
- THIS DRAWING IS NOT TO BE USED FOR ELECTRICAL CIRCUITRY, REFER TO ELECTRICAL DRAWINGS.
  - DENOTES CONDUIT AND WIRE FOR POWER OR PULL WIRE FOR CONTROLS BY ELECTRICAL CONTRACTOR.
  - DENOTES CONDUIT AND WIRE BY ELECTRICAL CONTRACTOR.
  - C.O. (CONDUIT ONLY) DENOTES CONDUIT AND PULL WIRE.
  - STUB-UP CONDUIT 8" ABOVE TOP OF CONCRETE ISLAND PLUS 3'-0" OF WIRE FOR PARKING EQUIPMENT SUPPLIER.
  - ELECTRICAL CONTRACTOR SHALL VERIFY WITH PARKING EQUIPMENT SUPPLIER AS TO THE ACTUAL POWER REQUIREMENTS TO EACH LOCATION BEFORE START OF WORK.
  - ELECTRICAL CONTRACTOR SHALL VERIFY WITH INTERCOM SYSTEM SUPPLIER AS TO THE ACTUAL CONDUIT SIZE REQUIRED BEFORE START OF WORK.
  - CONCRETE CURBS SHALL BE 6" HIGH UNO.
  - FOR ADDITIONAL PARKING EQUIPMENT REQUIREMENTS, REFER TO SPECS.
  - COORDINATE WITH ELECTRICAL DRAWINGS.
- PARKING CONTROL EQUIPMENT LIST:**
- CONTROL LANE # 1 (E) or (X)
- 1A - ARMING LOOP DETECTOR ASSEMBLY
  - 1B - ENTRY/EXIT COLUMN UNLIMITED (See Detail)
  - 1C - TWO-WAY INTERCOM UNIT
  - 1D - BARRIER GATE (See Detail)
  - 1E - CLOSING LOOP DETECTOR ASSEMBLY
  - 1F - PROTECTION POST
  - 1G - INGROUND JUNCTION BOXES (8"x8"x4") FOR POWER & DATA
- LEGEND**
- ① 1" # C.O., ARCNET CABLE (DATA)
  - ② 22/4 CAT3, PVC (VOICE)
  - ③ 3/4" # C.O., 22/8 CABLE O.S., PVC (DATA)
  - ④ ONE (1) 115VAC, 20AMP CIRCUIT (POWER)






- NOTE:**
- THE LANES, ISLANDS, AND GATE CONTROL LOCATIONS SHOWN ON THE PLAN ARE FOR GRAPHICAL PURPOSES ONLY, AND ARE INTENDED TO GENERALLY CONVEY THE INTENT OF THE ACCESS CONTROL THAT IS DESIRED.
  - FINAL BARRIER GATE DESIGN AND PREFERRED VENDOR TO BE COORDINATED WITH LONZA PRIOR TO CONSTRUCTION.



- NOTES:**
- CONTAINMENT SHALL BE STRUCTURALLY SOUND AND LEAK FREE AND CONTAIN ALL LIQUID WASTES.
  - CONTAINMENT DEVICES MUST BE OF SUFFICIENT QUANTITY OR VOLUME TO COMPLETELY CONTAIN THE LIQUID WASTES GENERATED.
  - WASHOUT SHALL BE CLEANED OR NEW FACILITIES CONSTRUCTED AND READY TO USE ONCE WASHOUT IS 75% FULL.
  - WASHOUT AREA(S) SHALL BE INSTALLED IN A LOCATION EASILY ACCESSIBLE BY CONCRETE TRUCKS.
  - ONE OR MORE AREAS MAY BE INSTALLED ON THE CONSTRUCTION SITE AND MAY BE RELOCATED AS CONSTRUCTION PROGRESSES.
  - AT LEAST WEEKLY, REMOVE ACCUMULATION OF SAND AND AGGREGATE AND DISPOSE OF PROPERLY.



- NOTE:**
- FINAL PAVEMENT DESIGN TO BE BASED ON GEOTECH REPORT.
  - SEE GRADING, DRAINAGE AND EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.
  - A TACK COAT SHALL BE PLACED ON TOP OF BINDER COURSE PAVEMENT PRIOR TO PLACING WEARING COURSE.
  - CONTRACTOR SHALL HAVE THE OPTION OF RECLAIMING THE EXISTING PAVEMENT AND REMOVING THE MATERIAL, THEN REUSING THE RECLAIMED MATERIAL AS A PAVEMENT SUBBASE.
















**Proposed Industrial Development**  
Lonza Biologics

Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CD-501 to C-508.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: X:\L0700\Lonza Biologics Expansion\wbs\_157676\013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-502





**Proposed Industrial Development**  
**Lonza Biologics**  
  
Portsmouth, New Hampshire


MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-501 to C-508.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**DETAILS SHEET**  
SCALE: AS SHOWN  
**C-503**


Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: J:\L0700 Lonza Biologics Expansion.was 127629.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-503






- NOTE:**
- NUMBER, MATERIAL, AND SIZE OF UTILITY CONDUITS TO BE DETERMINED BY LOCAL UTILITY OR AS SHOWN ON ELECTRICAL DRAWINGS. CONTRACTOR TO PROVIDE ONE SPARE CONDUIT FOR EACH UTILITY TO BUILDING.
  - DIMENSIONS SHOWN REPRESENT OWNERS MINIMUM REQUIREMENTS. ACTUAL DIMENSIONS MAY BE GREATER BASED ON UTILITY COMPANY STANDARDS, BUT SHALL NOT BE LESS THAN THOSE SHOWN.
  - NO CONDUIT RUN SHALL EXCEED 360 DEGREES IN TOTAL BENDS.
  - A SUITABLE PULLING STRING, CAPABLE OF 200 POUNDS OF PULL, MUST BE INSTALLED IN THE CONDUIT BEFORE UTILITY COMPANY IS NOTIFIED TO INSTALL CABLE. THE STRING SHOULD BE BLOWN INTO THE CONDUIT AFTER THE RUN IS ASSEMBLED TO AVOID BONDING THE STRING TO THE CONDUIT.
  - UTILITY COMPANY MUST BE GIVEN THE OPPORTUNITY TO INSPECT THE CONDUIT PRIOR TO BACKFILL. THE CONTRACTOR IS RESPONSIBLE FOR ALL REPAIRS SHOULD THE UTILITY COMPANY BE UNABLE TO INSTALL ITS CABLE IN A SUITABLE MANNER.
  - ALL CONDUIT INSTALLATIONS MUST CONFORM TO THE CURRENT EDITION OF THE NATIONAL ELECTRIC SAFETY CODE, STATE AND LOCAL CODES AND ORDINANCES, AND, WHERE APPLICABLE, THE NATIONAL ELECTRIC CODE.
  - ALL 90° SWEEPS WILL BE MADE USING RIGID GALVANIZED STEEL. SWEEPS WITH A 36 TO 48 INCH RADIUS.
  - SAND BEDDING TO BE REPLACED WITH CONCRETE ENCASEMENT WHERE COVER IS LESS THAN 3 FEET, WHEN LOCATED BELOW PAVEMENT, OR WHERE SHOWN ON THE UTILITIES PLAN.

**ELECTRICAL AND COMMUNICATION CONDUIT**  
NO SCALE



- NOTE:**
- ALL SECTIONS SHALL BE CONCRETE CLASS AA(4000 PSI).
  - CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQ. IN. PER LINEAR FT. IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
  - THE TONGUE AND GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQ. IN. PER LINEAR FT.
  - RISERS OF 1', 2', 3' & 4' CAN BE USED TO REACH DESIRED DEPTH.
  - THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.
  - THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.


**4" DIAMETER CATCHBASIN**  
NO SCALE




**4" DIAMETER DRAIN MANHOLE**  
NO SCALE

- NOTES:**
- STONE SIZE AND MAT DIMENSIONS DETAILED ON PLANS.
  - STONE SHALL CONSIST OF SUB-ANGULAR FIELD STONE OR ROUGH UNHEWN QUARRY STONE OF APPROXIMATELY RECTANGULAR SHAPE. FLAT OR ROUND ROCKS ARE NOT ACCEPTABLE. THE STONE SHALL BE HARD AND OF SUCH QUALITY THAT IT WILL NOT DISINTEGRATE ON EXPOSURE TO WATER OR WEATHERING, BE CHEMICALLY STABLE AND IT SHALL BE SUITABLE IN ALL OTHER RESPECTS FOR THE PURPOSE INTENDED. THE BULK SPECIFIC GRAVITY (SATURATED SURFACE-DRY BASIS) OF THE INDIVIDUAL STONES SHALL BE AT LEAST 2.5.
  - THE STONE SHALL BE COMPOSED OF A WELL-GRADED MIXTURE DOWN TO THE ONE-INCH SIZE PARTICLE SUCH THAT 50 PERCENT OF THE MIXTURE BY WEIGHT BE LARGER THAN THE D50 SIZE SPECIFIED. A WELL-GRADED MIXTURE IS DEFINED AS A MIXTURE COMPOSED PRIMARILY OF THE LARGER STONE SIZE BUT WITH A SUFFICIENT MIXTURE OF OTHER SIZES TO FILL THE PROGRESSIVELY SMALLER VOIDS BETWEEN THE STONES. THE DIAMETER OF THE LARGEST STONE SIZE IN SUCH A MIXTURE SHALL BE 1.5 TIMES THE D50 SIZE.

**RIPRAP APRON DETAIL**  
NO SCALE




**PIPE TO MANHOLE JOINTS**  
NO SCALE




**SEWER MANHOLE JOINTS**  
NOT TO SCALE

- NOTES:**
- HORIZONTAL JOINTS BETWEEN THE SECTIONS OF PRECAST CONCRETE BARRELS SHALL BE PER CITY OF PORTSMOUTH DPW STANDARD AND SHALL BE SEALED FOR WATERTIGHTNESS USING A DOUBLE ROW ELASTOMERIC OR MASTIC-LIKE GASKET.
  - PIPE TO MANHOLE JOINTS SHALL BE PER CITY OF PORTSMOUTH DPW STANDARD.
  - FOR BITUMASTIC TYPE JOINTS THE AMOUNT OF SEALANT SHALL BE SUFFICIENT TO FILL AT LEAST 75% OF THE JOINT CAVITY.
  - ALL GASKETS, SEALANTS, MORTAR, ETC. SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS' WRITTEN INSTRUCTIONS.




**TYPICAL SECTION**  
NO SCALE




**SECTION A-A**  
NO SCALE

- NOTES:**
- INVERT AND SHELF TO BE PLACED AFTER EACH LEAKAGE TEST.
  - CARE SHALL BE TAKEN TO INSURE THAT THE BRICK INVERT IS A SMOOTH CONTINUATION OF THE SEWER INVERT.
  - INVERT BRICKS SHALL BE LAID ON EDGE.
  - BITUMINOUS WATERPROOF COATING TO BE APPLIED TO ENTIRE EXTERIOR OF MANHOLE.
  - FRAMES AND COVERS MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A 30-INCH CLEAR OPENING. A 3-INCH (MINIMUM HEIGHT) WORD "SEWER" SHALL BE PLAINLY CAST INTO THE CENTER OF EACH COVER.
  - HORIZONTAL JOINTS SHALL BE SEALED FOR WATER TIGHTNESS USING A DOUBLE ROW OF ELASTOMERIC OR MASTIC-LIKE SEALANT.
  - BARREL AND CONE SECTIONS SHALL BE PRECAST REINFORCED CONCRETE DESIGNED FOR H2O LOADING, AND CONFORMING TO ASTM C478-06.
  - MANHOLES SHALL BE LINED WITH CORROSION BARRIER TO PROTECT MANHOLE FROM SANITARY EFFLUENT. LINER SHALL BE COORDINATED WITH ENGINEER AND CITY OF PORTSMOUTH PRIOR TO CONSTRUCTION.


**SEWER MANHOLE**  
NO SCALE




**CLEAN-OUT**  
NO SCALE



**TYPICAL ELECTRIC MANHOLE**  
NO SCALE




**TYPICAL ELECTRIC MANHOLE**  
NO SCALE




**METAL FLARED END SECTION**  
NO SCALE

PIPE DIA.	METAL GAGE	DIMENSIONS				
		A (1" TOL.)	B (1" MAX. TOL.)	H (1" TOL.)	L (1" TOL.)	W (2" TOL.)
12"	16	6"	6"	6"	21"	24"
15"	16	7"	8"	6"	26"	30"
18"	16	8"	13"	6"	31"	36"
24"	16	10"	16"	6"	41"	48"
30"	14	12"	16"	8"	51"	60"
36"	14	14"	19"	9"	60"	72"
42"	12	16"	22"	11"	69"	84"
48"	12	18"	27"	12"	78"	90"


- NOTES:**
- END SECTION FOR 12" TO 30" DIA. PIPE IN ONE PIECE, FOR 36" TO 48" DIA. PIPE TO BE MADE FROM TWO SHEETS JOINED BY RIVETING OR BOLTING ON CENTER LINE.
  - CONNECTOR SECTION, CORNER PLATE AND TOE PLATE TO BE SAME THICKNESS AS END SECTION AND EACH TO BE GALVANIZED.



**UTILITY TRENCH**  
NO SCALE



**STORM DRAINAGE AND SANITARY SEWER PIPE**  
NO SCALE





**THRUST BLOCK DETAIL**  
NO SCALE

**TABLE 1: SQUARE FEET OF CONCRETE THRUST BLOCKING BEARING ON UNDISTURBED MATERIAL**

REACTION TYPE	PIPE SIZE			
	4"	6"	8"	12"
A 90°	0.89	2.19	3.82	11.14
B 180°	0.89	1.55	2.78	8.38
C 45°	0.48	1.19	2.12	6.02
D 22-1/2°	0.25	0.60	1.06	3.08
E 11-1/4°	0.13	0.30	0.54	1.54

**NOTES:**

- POUR THRUST BLOCKS AGAINST UNDISTURBED MATERIAL, WHERE TRENCH WALL HAS BEEN DISTURBED, EXCAVATE LOOSE MATERIAL AND EXTEND THRUST BLOCK TO UNDISTURBED MATERIAL. NO JOINTS SHALL BE COVERED WITH CONCRETE.
- ON BENDS AND TEES, EXTEND THRUST BLOCKS FULL LENGTH OF FITTING.
- PLACE BOARD IN FRONT OF ALL PLUGS BEFORE POURING THRUST BLOCKS.
- WHERE M.J. PIPE IS USED, M.J. PLUG WITH RETAINER GLAND MAY BE SUBSTITUTED FOR END BLOCKINGS.
- INSTALLATION AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE PER WATER DEPARTMENT STANDARDS.



**Proposed Industrial Development**  
**Lonza Biologics**  
Portsmouth, New Hampshire




MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-501 to C-508.dwg  
DRAWN BY: NAH  
CHECKED BY: PMC  
APPROVED BY: BLM

**DETAILS SHEET**  
SCALE: AS SHOWN  
**C-504**

Last Save Date: May 21, 2018 2:25 PM BY: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: J:\L0700 Lonza Biologics Expansion.was 12/26/013 Iron Parcel Redevelopment Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-504






**NOTES:**  
1. CORE MATERIAL SHALL MEET USGS CLASSIFICATION SC, SM, CL OR ML AND HAVE A MAXIMUM PARTICLE SIZE OF 3" AND A PERMEABILITY LESS THAN 0.00005 CM/S, AND MEET THE FOLLOWING GRADATION

SIEVE SIZE	PERCENT FINER BY WEIGHT
3 INCH	100
No. 200	50 - 100.


2. PIPE SHALL BE FULLY EMBEDDED IN CORE TO ELIMINATE SEEPAGE

**CLAY CORE BERM**  
NO SCALE




**NOTES:**  
1. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS FOR LOCATIONS AND ELEVATIONS.

**GRAVEL WETLAND SPILLWAY**  
NO SCALE



**NOTE:**  
SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEET C-110, FOR LOCATIONS AND ELEVATIONS.


**RIPRAP SPILLWAY**  
NO SCALE



**NOTES:**  
1. ALL SECTIONS SHALL BE 4,000 PSI CONCRETE (TYPE II CEMENT).  
2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER OF THE THIRD WALL.  
3. THE TONGUE OR THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.  
4. THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.  
5. ALL JOINTS ON THE STRUCTURE AND PIPING SHALL BE WATERTIGHT.


**OUTLET STRUCTURE**  
NO SCALE

**WEIR DETAIL**  
NO SCALE




**NOTES:**  
1. GRATE SHALL BE HAALA INDUSTRIES, INC. MC56X56 TOP MOUNT GRATE OR EQUAL.  
2. GRATE TO BE SECURED TO CONCRETE STRUCTURE.

**OVERFLOW GRATE**  
NO SCALE



**NOTES:**  
1. WETLAND SOIL SHALL BE A SANDY CLAY LOAM WITH A HYDRAULIC CONDUCTIVITY OF 0.1-0.01 FT/DAY. ORGANIC CONTENT SHALL BE GREATER THAN 15% BY VOLUME. CLAY CONTENT SHALL BE LESS THAN 15% BY VOLUME. THE MAXIMUM PARTICLE SIZE SHALL BE 3".  
2. INFILTRATION TESTING OF THE NATIVE SOILS AT THE SUBGRADE OF THE PROPOSED GRAVEL WETLAND SHALL OCCUR PRIOR TO THE INSTALLATION OF THE GRAVEL WETLAND AND SHALL BE COORDINATED WITH THE ENGINEER. IF THE NATIVE SOILS EXCEED A PERMEABILITY RATE OF 0.03FT/DAY THE SOILS SHOULD AMENDED OR LINER ADDED AS DETERMINED BY THE ENGINEER.  
3. PERFORATED RISERS SHALL HAVE VERTICAL SLOTS CUT INTO RISERS ABOVE GRADE MEASURING 3"x1/8".  
4. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEETS C-2A AND C-2B, FOR LOCATIONS AND ELEVATIONS.

**GRAVEL WETLAND SECTION A-A**  
NO SCALE



SPECIES	PLANT SIZE	QUANTITY/SPACING
NEW ENGLAND EROSION CONTROL/RESTORATION MIX OR EQUIVALENT		35LB/ACRE
"RED OSIER DOGWOOD" CORNUS SERICEA	2'-3'	8'-10' ON CENTER
"SILKY DOGWOOD" CORNUS AMMOMUM		
AND	2'-3'	8'-10' ON CENTER
"HIGHBUSH BLUEBERRY" VACCINIUM CORYBOSSUSUM		

Inspection/Maintenance	Frequency	Action
Monitor to ensure that Gravel Wetland functions effectively after storms	Four (4) times annually (quarterly) and after any rainfall event exceeding 2.5" in a 24-hr period	- Trash and debris to be removed - Any required maintenance shall be addressed - Inspect soil and repair eroded areas, especially on slopes. - Check inlets, outlets, and overflow spillway for blockage, structural integrity and evidence of erosion.
Inspect Vegetation	Annually	- Inspect the condition of all gravel wetland vegetation - Prune back overgrowth - Replace dead vegetation - Remove any invasive species - Coordinate with UNH Stormwater Center for further vegetation management guidelines
Inspect Drawdown Time - The system shall drawdown within 48-hours following a rainfall event.	Annually	- Hire qualified professional to assess the condition of the facility to determine measures required to restore the filtration function, including but not limited to removal of accumulated sediments or reconstruction of the filter.

**Proposed Industrial Development**  
  
Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO:	L-0700-13
DATE:	04/03/2018
FILE:	L0700-CD-501 to C-508.dwg
DRAWN BY:	NAH
CHECKED:	PMC
APPROVED:	BLM



DETAILS SHEET

SCALE: AS SHOWN

C-505

Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: J:\L0700\Lonza Biologics Expansion.was 127620.013 From Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-505






NOTES:  
1. CORE MATERIAL SHALL MEET USGS CLASSIFICATION SC, SM, CL OR ML AND HAVE A MAXIMUM PARTICLE SIZE OF 3" AND A PERMEABILITY LESS THAN 0.00005 CM/S, AND MEET THE FOLLOWING GRADATION

SIEVE SIZE	PERCENT FINER BY WEIGHT
3 INCH	100
No. 200	50 -100.


2. PIPE SHALL BE FULLY EMBEDDED IN CORE TO ELIMINATE SEEPAGE

**CLAY CORE BERM**  
NO SCALE



NOTES:  
1. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS FOR LOCATIONS AND ELEVATIONS.


**GRAVEL WETLAND SPILLWAY**  
NO SCALE



NOTES:  
1. WETLAND SOIL SHALL BE A SANDY CLAY LOAM WITH A HYDRAULIC CONDUCTIVITY OF 0.1-0.01 FT/DAY. ORGANIC CONTENT SHALL BE GREATER THAN 15% BY VOLUME. CLAY CONTENT SHALL BE LESS THAN 15% BY VOLUME. THE MAXIMUM PARTICLE SIZE SHALL BE 3".  
2. INFILTRATION TESTING OF THE NATIVE SOILS AT THE SUBGRADE OF THE PROPOSED GRAVEL WETLAND SHALL OCCUR PRIOR TO THE INSTALLATION OF THE GRAVEL WETLAND AND SHALL BE COORDINATED WITH THE ENGINEER. IF THE NATIVE SOILS EXCEED A PERMEABILITY RATE OF 0.03FT/DAY THE SOILS SHOULD AMENDED OR LINER ADDED AS DETERMINED BY THE ENGINEER.  
3. PERFORATED RISERS SHALL HAVE VERTICAL SLOTS CUT INTO RISERS ABOVE GRADE MEASURING 3"x1/8".  
4. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEETS C-2A AND C-2B, FOR LOCATIONS AND ELEVATIONS.

**GRAVEL WETLAND SECTION A-A**  
NO SCALE

Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
P&E File Location: \\L0700-CD-501 to C-508.dwg Layout: Tab: C-506




NOTES:  
1. ALL SECTIONS SHALL BE 4,000 PSI CONCRETE (TYPE II CEMENT).  
2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER OF THE THIRD WALL.  
3. THE TONGUE OR THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.  
4. THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.  
5. ALL JOINTS ON THE STRUCTURE AND PIPING SHALL BE WATERTIGHT.

**OUTLET STRUCTURE**  
NO SCALE

NOTES:  
1. GRATE SHALL BE HAALA INDUSTRIES, INC. MC56X56 TOP MOUNT GRATE OR EQUAL.  
2. GRATE TO BE SECURED TO CONCRETE STRUCTURE.

**OVERFLOW GRATE**  
NO SCALE



**GRAVEL WETLAND #2 PLANTING PLAN**  
SCALE: 1" = 20'

Gravel Wetland Inspection/Maintenance Requirements		
Inspection/Maintenance	Frequency	Action
Monitor to ensure that Gravel Wetland functions effectively after storms	Four (4) times annually (quarterly) and after any rainfall event exceeding 2.5" in a 24-hr period	- Trash and debris to be removed - Any required maintenance shall be addressed - Inspect soil and repair eroded areas, especially on slopes. - Check inlets, outlets, and overflow spillway for blockage, structural integrity and evidence of erosion.
Inspect Vegetation	Annually	- Inspect the condition of all gravel wetland vegetation - Prune back overgrowth - Replace dead vegetation - Remove any invasive species - Coordinate with UNH Stormwater Center for further vegetation management guidelines
Inspect Drawdown Time	Annually	- Hire qualified professional to assess the condition of the facility to determine measures required to restore the filtration function, including but not limited to removal of accumulated sediments or reconstruction of the filter.

GRAVEL WETLAND PLANTING PLAN		
SPECIES	PLANT SIZE	QUANTITY/SPACING
NEW ENGLAND EROSION CONTROL/RESTORATION MIX OR EQUIVALENT		35LB/ACRE
"RED OSIER DOGWOOD" CORNUS SERICEA	2'-3'	8'-10' ON CENTER
"SILKY DOGWOOD" CORNUS AMMOMUM		
AND	2'-3'	8'-10' ON CENTER
"Highbush Blueberry" VACCINIUM CORYBOSSUM		



**Proposed Industrial Development**  
  
Lonza Biologics  
  
Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-501 to C-508.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

**DETAILS SHEET**  
SCALE: AS SHOWN  
**C-506**






NOTES:  
1. CORE MATERIAL SHALL MEET USGS CLASSIFICATION SC, SM, CL OR ML AND HAVE A MAXIMUM PARTICLE SIZE OF 3" AND A PERMEABILITY LESS THAN 0.00005 CM/S, AND MEET THE FOLLOWING GRADATION

SIEVE SIZE	PERCENT FINER BY WEIGHT
3 INCH	100
No. 200	50 -100.


2. PIPE SHALL BE FULLY EMBEDDED IN CORE TO ELIMINATE SEEPAGE

**CLAY CORE BERM**  
NO SCALE



NOTES:  
1. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS FOR LOCATIONS AND ELEVATIONS.


**GRAVEL WETLAND SPILLWAY**  
NO SCALE



NOTES:  
1. WETLAND SOIL SHALL BE A SANDY CLAY LOAM WITH A HYDRAULIC CONDUCTIVITY OF 0.1-0.01 FT/DAY. ORGANIC CONTENT SHALL BE GREATER THAN 15% BY VOLUME. CLAY CONTENT SHALL BE LESS THAN 15% BY VOLUME. THE MAXIMUM PARTICLE SIZE SHALL BE 3".  
2. INFILTRATION TESTING OF THE NATIVE SOILS AT THE SUBGRADE OF THE PROPOSED GRAVEL WETLAND SHALL OCCUR PRIOR TO THE INSTALLATION OF THE GRAVEL WETLAND AND SHALL BE COORDINATED WITH THE ENGINEER. IF THE NATIVE SOILS EXCEED A PERMEABILITY RATE OF 0.03FT/DAY THE SOILS SHOULD AMENDED OR LINER ADDED AS DETERMINED BY THE ENGINEER.  
3. PERFORATED RISERS SHALL HAVE VERTICAL SLOTS CUT INTO RISERS ABOVE GRADE MEASURING 3"x1/8".  
4. SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEETS C-2A AND C-2B, FOR LOCATIONS AND ELEVATIONS.


**GRAVEL WETLAND SECTION A-A**  
NO SCALE

Last Save Date: May 21, 2018 2:25 PM By: BCLARK  
Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
File Location: J:\L0700\Lonza Biologics Expansion.was 12762013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CD-501 to C-508.dwg Layout Tab: C-507




NOTES:  
1. ALL SECTIONS SHALL BE 4,000 PSI CONCRETE (TYPE II CEMENT).  
2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER OF THE THIRD WALL.  
3. THE TONGUE OR THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.  
4. THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.  
5. ALL JOINTS ON THE STRUCTURE AND PIPING SHALL BE WATERTIGHT.

**OUTLET STRUCTURE**  
NO SCALE



NOTES:  
1. GRATE SHALL BE HAALA INDUSTRIES, INC. MC56X56 TOP MOUNT GRATE OR EQUAL.  
2. GRATE TO BE SECURED TO CONCRETE STRUCTURE.

**OVERFLOW GRATE**  
NO SCALE



**GRAVEL WETLAND #3 PLANTING PLAN**  
SCALE: 1" = 20'

Gravel Wetland Inspection/Maintenance Requirements		
Inspection/Maintenance	Frequency	Action
Monitor to ensure that Gravel Wetland functions effectively after storms	Four (4) times annually (quarterly) and after any rainfall event exceeding 2.5" in a 24-hr period	- Trash and debris to be removed - Any required maintenance shall be addressed - Inspect soil and repair eroded areas, especially on slopes. - Check inlets, outlets, and overflow spillway for blockage, structural integrity and evidence of erosion.
Inspect Vegetation	Annually	- Inspect the condition of all gravel wetland vegetation - Prune back overgrowth - Replace dead vegetation - Remove any invasive species - Coordinate with UNH Stormwater Center for further vegetation management guidelines
Inspect Drawdown Time	Annually	- Hire qualified professional to assess the condition of the facility to determine measures required to restore the filtration function, including but not limited to removal of accumulated sediments or reconstruction of the filter.

GRAVEL WETLAND PLANTING PLAN		
SPECIES	PLANT SIZE	QUANTITY/SPACING
NEW ENGLAND EROSION CONTROL/RESTORATION MIX OR EQUIVALENT		35LB/ACRE
"RED OSIER DOGWOOD" CORNUS SERICEA	2'-3'	8'-10' ON CENTER
"SILKY DOGWOOD" CORNUS AMMOMUM		
AND	2'-3'	8'-10' ON CENTER
"HIGHBUSH BLUEBERRY" VACCINIUM CORYBOSSUSUM		

**Proposed Industrial Development**  
  
Lonza Biologics


Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO: L-0700-13  
DATE: 04/03/2018  
FILE: L0700-CD-501 to C-508.dwg  
DRAWN BY: NAH  
CHECKED: PMC  
APPROVED: BLM

DETAILS SHEET  
SCALE: AS SHOWN  
**C-507**






NOTES:  
 1. CORE MATERIAL SHALL MEET USGS CLASSIFICATION SC, SM, CL OR ML AND HAVE A MAXIMUM PARTICLE SIZE OF 3" AND A PERMEABILITY LESS THAN 0.00005 CM/S, AND MEET THE FOLLOWING GRADATION

SIEVE SIZE	PERCENT FINER BY WEIGHT
3 INCH	100
No. 200	50 -100.


2. PIPE SHALL BE FULLY EMBEDDED IN CORE TO ELIMINATE SEEPAGE

**CLAY CORE BERM**  
NO SCALE



NOTE:  
 SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEET C-110, FOR LOCATIONS AND ELEVATIONS.

**RIPRAP SPILLWAY**  
NO SCALE



SECTION VIEW


FILTER MEDIA COMPOSITION:			
COMPONENT MATERIAL	PERCENT OF MIXTURE BY VOLUME	SIEVE NO.	GRADATION OF MATERIAL PERCENT PASSING
ASTM C-33 CONCRETE SAND	50-55	SEE NOTE #5	
LOAMY SAND TOPSOIL	20-30	200	15-25
MODERATELY FINE SHREDDED BARK OR WOOD FIBER MULCH	20-30	200	5 MAX.

NOTES:  
 1. BARK MULCH SHALL BE AGED A MINIMUM OF 12 MONTHS AND SHALL NOT FLOAT.  
 2. RAIN GARDENS SHALL NOT BE PLACED INTO SERVICE UNTIL THE PRACTICE HAS BEEN PLANTED AND ITS CONTRIBUTING AREAS HAVE BEEN FULLY STABILIZED.  
 3. DO NOT TRAFFIC EXPOSED SOIL SURFACES WITH CONSTRUCTION EQUIPMENT. CONTRACTOR SHALL KEEP ALL EXCAVATION EQUIPMENT OUTSIDE OF THE LIMIT OF THE RAIN GARDEN.  
 4. SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR LOCATIONS, LAYOUTS, AND ELEVATIONS.  
 5. THE SAND PORTION OF THE FILTER MEDIA SHALL MEET THE FOLLOWING GRADATION (ASTM C-33):



SIEVE SIZE	PERCENT PASSING
3/8"	100
#4	95-100
#8	80-100
#16	50-85
#30	25-60
#50	5-30
#100	0-10

**RAIN GARDEN**  
NO SCALE

RAINGARDEN PLANT SCHEDULE				
CODE	BOTANICAL NAME	COMMON NAME	SIZE	REMARKS
<b>TREES</b>				
BN	BETULA NIGRA	RIVER BIRCH	12 - 14' HT	B & B (CLUMP)
AC	AMALANCHIER CANADENSIS	SHADBLOW SERVICEBERRY	6 - 7' HT	B & B (CLUMP)
<b>SHRUBS</b>				
VD	VIBURNUM DENTATUM	ARROWWOOD VIBURNUM	5 GALLON	CONTAINER
CA	CLEATHERA ALNIFOLIA	SUMMERSWEET CLEATHERA	5 GALLON	CONTAINER
<b>PERENNIALS</b>				
PV	PANICUM VIRGATUM 'SHENANDOAH'	SHENANDOAH SWITCH GRASS	3 GALLON	CONTAINER
EM	EUPATORIUM MACULATUM	JOE PYE WEED	2 GALLON	CONTAINER
AI	ASCLEPIAS INCARNATA	MARSH MILKWEED	2 GALLON	CONTAINER
RG	RUDBECKIA 'GOLDSTURM'	GOLDSTURM BLACKEYED SUSAN	1 GALLON	CONTAINER
EP	ECHINACEA 'PURPUREA'	PURPLE CONEFLOWER	1 GALLON	CONTAINER



**RAIN GARDEN PLANTING PLAN**  
SCALE: 1" = 20'



**Proposed Industrial Development**

Lonza Biologics

Portsmouth,  
New Hampshire





2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CD-501 to C-508.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		

DETAILS SHEET

SCALE: AS SHOWN

**C-508**





**LEGEND**

	MATCH LINE
	EXISTING EDGE OF WETLAND
	EXISTING DRAIN LINE
	PROPOSED FINISHED GRADE
	PROPOSED STREAM BANK
	PROPOSED DRAIN LINE (TYP)
	SILT SOCK
	PROPOSED LIMIT OF C125 EROSION CONTROL BLANKET
	PROPOSED LIMIT OF C350 EROSION CONTROL BLANKET
	PROPOSED LIMIT OF GRAVEL STREAM BED
	PROPOSED LIMIT OF COIR MATTING
	PROPOSED RIPRAP
	PROPOSED LOG VANE TYPICAL

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CS-701 to C-703.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BCC		

**HODGSON BROOK GRADING, DRAINAGE & EROSION CONTROL PLAN**

SCALE: AS SHOWN

SEE SHEET C-108 FOR GRADING, DRAINAGE & EROSION CONTROL NOTES



**C-701**

Last Save Date: May 30, 2018 12:20 PM By: BCLARK  
 Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 1278.0013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-701 to C-703.dwg Layout Tab: C-701



**PLANTING NOTES:**



- THE CONTRACTOR SHALL FURNISH AND PLANT ALL PLANTS IN QUANTITIES AS SHOWN ON THIS PLAN. NO SUBSTITUTIONS WILL BE PERMITTED UNLESS APPROVED BY OWNER. ALL PLANTS SHALL BE NURSERY GROWN.
- ALL PLANTS SHALL BE NURSERY GROWN AND PLANTS AND WORKMANSHIP SHALL CONFORM TO THE AMERICAN ASSOCIATION OF NURSERYMEN STANDARDS, INCLUDING BUT NOT LIMITED TO SIZE, HEALTH, SHAPE, ETC., AND SHALL BE SUBJECT TO THE APPROVAL OF THE LANDSCAPE ARCHITECT PRIOR TO ARRIVAL ON-SITE AND AFTER PLANTING.
- PLANT STOCK SHALL BE GROWN WITHIN THE HARDINESS ZONES 4 THRU 7 ESTABLISHED BY THE PLANT HARDINESS ZONE MAP, MISCELLANEOUS PUBLICATIONS NO. 814, AGRICULTURAL RESEARCH SERVICE, UNITED STATES DEPARTMENT AGRICULTURE, LATEST REVISION.
- PLANT MATERIAL SHALL BEAR THE SAME RELATIONSHIP TO FINISHED GRADE AS TO THE ORIGINAL PLANTING GRADE PRIOR TO DIGGING.
- NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT THE PRIOR WRITTEN APPROVAL OF THE OWNER'S REPRESENTATIVE.
- THE CONTRACTOR SHALL LOCATE, VERIFY AND MARK ALL EXISTING AND NEWLY INSTALLED UNDERGROUND UTILITIES PRIOR TO ANY LAWN WORK OR PLANTING. ANY CONFLICTS WHICH MIGHT OCCUR BETWEEN PLANTING AND UTILITIES SHALL IMMEDIATELY BE REPORTED TO THE OWNER SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
- SEE PLANTING DETAILS AND SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
- PLANTING SHALL BE COMPLETED FROM APRIL 15TH THROUGH OCTOBER 1ST, WITH THE EXCEPTION OF THE WHIPS. WHIPS SHALL BE PLANTED DURING THE DORMANT SEASON, OCTOBER 1ST THROUGH DECEMBER 15TH AND/OR MARCH 15TH THROUGH APRIL 15TH. NO PLANTING DURING JULY AND AUGUST UNLESS SPECIAL PROVISIONS ARE MADE FOR DROUGHT, SUCH AS DAILY WATERING AS REQUIRED.
- ALL PLANTS SHALL BE WATERED THOROUGHLY TWICE DURING THE FIRST 24 HOUR PERIOD AFTER PLANTING. ALL PLANTS SHALL BE WATERED WEEKLY, OR MORE OFTEN, IF NECESSARY DURING THE FIRST GROWING SEASON.
- THE CONTRACTOR SHALL GUARANTEE ALL PLANTINGS TO BE IN GOOD, HEALTHY, FLOURISHING AND ACCEPTABLE CONDITION FOR A PERIOD OF (1) YEAR BEGINNING AT THE DATE OF ACCEPTANCE OF SUBSTANTIAL COMPLETION. ALL GRASSES, TREES AND SHRUBS THAT, IN THE OPINION OF THE LANDSCAPE ARCHITECT, SHOW LESS THAN 80% HEALTHY GROWTH AT THE END OF ONE YEAR PERIOD SHALL BE REPLACED BY THE CONTRACTOR.
- UPON EXPIRATION OF THE CONTRACTOR'S ONE YEAR GUARANTEE PERIOD, THE OWNER SHALL BE RESPONSIBLE FOR LANDSCAPE MAINTENANCE INCLUDING WATERING DURING PERIODS OF DROUGHT
- PRE-PURCHASE PLANT MATERIAL AND ARRANGE FOR DELIVERY TO MEET PROJECT SCHEDULE AS REQUIRED. IT MAY BE NECESSARY TO PRE-DIG CERTAIN SPECIES WELL IN ADVANCE OF ACTUAL PLANTING DATES.
- SCRUB/SHRUB FLOODPLAIN AND FLOODPLAIN WETLAND ZONES (AREA A) PLANTING SEQUENCE:
  - ONCE THE AREA HAS BEEN FULLY GRADED AND LOAMED, ENTIRE AREA SHALL BE SEEDED WITH "RIVERBANK STABILIZATION MIX" AT A RATE OF 1 POUND PER 2000 SF.
  - THE EROSION CONTROL BLANKET SHALL THEN BE INSTALLED AS SHOWN ON SHEET C-701 AND DETAIL SHEET C-502.
  - THE SHRUB PLANTINGS SHALL BE PLANTED ON 8' CENTERS IN LIKE GROUPS OF 3 TO 5, THROUGH THE EROSION CONTROL BLANKET.
- SLOPE STABILIZATION AREA (AREA B) PLANTING SEQUENCE:
  - ONCE THE AREA HAS BEEN FULLY GRADED AND LOAMED, ENTIRE AREA SHALL BE SEEDED WITH "RIVERBANK STABILIZATION MIX" AT A RATE OF 1 POUND PER 2000 SF.
  - THE EROSION CONTROL BLANKET SHALL THEN BE INSTALLED AS SHOWN ON SHEET C-701 AND DETAIL SHEET C-502.
  - THE SHRUB PLANTINGS SHALL BE PLANTED ON 6' CENTERS THROUGH THE EROSION CONTROL BLANKET.
- STREAM BANK MARGINS PLANTING SEQUENCE:
  - INSTALL COIR MATTING PER DETAILS SHEET C-703.
  - PLANT WHIPS (1/2" - 3/4" DIAMETER, 3 TO 4 FEET IN LENGTH) OF SILKY DOGWOOD AND RED-OSIER DOGWOOD ON THE UPWARD AND DOWNWARD SIDE OF COIR MATS, AT A MINIMUM OF 1 TO 2 FEET INTO THE SOIL SUBSTRATE.
- "RIVERBANK STABILIZATION MIX" SHALL CONSIST OF:
  - AGROSTIS STOLONIFERA (CREEPING BENT GRASS)
  - AGROSTIS ALBA (RED TOP)
  - FRAXINUS PENNSYLVANICA (GREEN ASH)
  - CORNUS STOLONIFERA (RED-OSIER DOGWOOD)
  - CORNUS AMOMUM (SILKY DOGWOOD)
  - ELYMUS RIPARIUS (RIVERBANK WILD RYE)
  - VIBURNUM RECOGNITUM (NORTHERN ARROWWOOD)
 AS SUPPLIED BY STONEY RIDGE ENVIRONMENTAL, LLC, ALTON, NH 603-776-0194, OR APPROVED EQUAL.



PLANT SCHEDULE			
SCIENTIFIC NAME	COMMON NAME	QUANTITY	SIZE/TYPE
AREA A			
CORNUS AMMOMUM	SILKY DOGWOOD	170	2-3' POTTED PLANTS
VIBURNUM RECOGNITUM	NORTHERN ARROWWOOD	170	2-3' POTTED PLANTS
AREA B			
CORNUS AMMOMUM	SILKY DOGWOOD	410	2-3' POTTED PLANTS
VIBURNUM RECOGNITUM	NORTHERN ARROWWOOD	410	2-3' POTTED PLANTS
STREAM BANK MARGIN			
CORNUS AMMOMUM	SILKY DOGWOOD	600	1/2" TO 3/4" WHIPS
CORNUS STOLONIFERA	RED-OSIER DOGWOOD	600	1/2" TO 3/4" WHIPS

START CONSTRUCTION AT END OF STREAM AND WORK UPSTREAM, COMPLETING THE ENTIRE LENGTH AND ALLOWING VEGETATION TO TAKE ROOT BEFORE OPENING UP TO FLOWS

SEE SHEET C-108 FOR GRADING, DRAINAGE & EROSION CONTROL NOTES



**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO: L-0700-13		
DATE: 04/03/2018		
FILE: L0700-CS-701 to C-703.dwg		
DRAWN BY: NAH		
CHECKED: PMC		
APPROVED: BLM		



**HODGSON BROOK WETLAND PLANTING PLAN**

SCALE: AS SHOWN

**C-702**


Last Save Date: May 30, 2018 12:20 PM By: BCLARK  
Plot Date: Wednesday, May 30, 2018 Plotted By: Benjamin Clark  
P&E File Location: J:\L0700 Lonza Biologics Expansion\w\1276\013 Prop Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\LO700-CS-701 to C-703.dwg Layout Tab: C-702






- NOTES:**
1. SEE WETLAND PLANTING PLAN SHEET C-702 FOR TYPE AND LOCATION OF PLANTS.
  2. SEE SHEET C-701 FOR EROSION CONTROL BLANKET TYPE AND LOCATION.
  3. ALL AREAS TO BE PLANTED SHALL ALSO RECEIVE 6" OF LOAM AND SEED. SEE WETLAND PLANTING SHEET C-702 PLAN FOR SEED MIX.

**TYPICAL RIFFLE CROSS-SECTION**  
NO SCALE




**SHRUB PLANTING**  
NO SCALE



- NOTES:**
1. PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER AND SEED.
  2. BEGIN AT THE TOP OF THE SLOPE, 36" OVER THE GRADE BREAK, BY ANCHORING THE BLANKET IN A 6" DEEP X 6" WIDE TRENCH WITH APPROXIMATELY 12" OF BLANKET EXTENDED BEYOND THE UPSLOPE PORTION OF THE TRENCH. ANCHOR THE BLANKET WITH A ROW OF TAPLES/STAPLES 12" APART IN THE BOTTOM OF THE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING. APPLY SEED TO COMPACTED SOIL AND FOLD REMAINING 12" PORTION OF BLANKET BACK OVER SEED AND COMPACTED SOIL. SECURE BLANKET OVER COMPACTED SOIL WITH A ROW OF STAPLES SPACED 12" APART ACROSS THE WIDTH OF THE BLANKET.
  3. ROLL THE BLANKETS DOWN THE SLOPE. ALL BLANKETS MUST BE SECURELY FASTENED TO THE SOIL SURFACE BY PLACING STAPLES IN APPROPRIATE LOCATIONS AS SHOWN ON THE STAPLE PATTERN GUIDE.
  4. STAPLE LENGTHS SHALL BE A MINIMUM OF 8 INCHES.

**EROSION CONTROL BLANKET FOR SLOPE PROTECTION**  
NO SCALE



- SINGLE LOG VANE CONSTRUCTION SEQUENCE:**
1. EXCAVATE A TRENCH FOR THE VANE.
  2. SET THE CROSS LOG.
  3. SET THE VANE LOG(S).
  4. PIN THE LOG VANE ARMS WITH 4' LONG, 1/2" REBAR HAMMERED INTO PRE-DRILLED HOLES (2" ON CENTER). HOLES ARE ANGLED OFF THE VERTICAL, ALTERNATING DIRECTION (UPSTREAM, DOWNSTREAM).
  5. EXCAVATE A TRENCH FOR THE GEOTEXTILE FABRIC ON THE UPSLOPE SIDE OF THE VANE. THE TRENCH SHALL BE AT LEAST 1.5' DEEP.
  6. ANCHORS SHALL BE CABLED TO THE LOGS BY >1/2" WIRE ROPE (CABLE), FASTENED WITH GRIPPLE CLIPS OR BOLTED CLAMPS.
  7. ANCHORS SHALL BE EITHER LARGE (>100LB) ROCK OR REBAR CROSSES (TWO PIECES OF 2' LENGTH, 1/2" REBAR FASTENED AT THEIR CENTERS).
  8. STAPLE OR NAIL THE GEOTEXTILE ON THE UPSLOPE SIDE OF THE LOG, JUST ABOVE MID-DIAMETER, FOR THE FULL LENGTH OF THE LOG. FOLD OVER THE GEOTEXTILE FABRIC ALONG NAIL LINE. THE STAPLES/NAIls SHALL BE AT LEAST 1' ON CENTERS OR CLOSER. THE STAPLE/ NAIL LENGTH SHOULD BE AT LEAST 1".
  9. BACKFILL THE UPSLOPE SIDE OF THE VANE.
  10. EXCAVATE A SILL TRENCH (MINIMUM LENGTH OF 3') AT THE BANK-END OF THE LOG; EITHER A STONE SILL WITH MINIMUM DEPTH OF 2' OR A GEOTEXTILE SILL - TWO PARALLEL TRENCHES WITH A MINIMUM DEPTH OF 2'.
  11. CONSTRUCT THE SILL: PLACE >1" SIZE STONES IN TRENCH, COVER WITH GEOTEXTILE (MIRAFI N140 OR APPROVED EQUAL), BACKFILL; OR PLACE GEOTEXTILE IN PARALLEL TRENCHES, COVERING A MOUND BETWEEN THEM, AND BACKFILL.
  12. WEAVE ONE CONTINUOUS GEOTEXTILE ALONG VANE AND SILL.

- GENERAL NOTES:**
1. CROSS LOGS SHALL BE A MINIMUM OF 8" IN DIAMETER. VANE ARM LOGS SHALL BE A MINIMUM OF 6" IN DIAMETER. ALL LOGS SHOULD BE RELATIVELY STRAIGHT AND, OF A HARDWOOD, HEMLOCK, OR LARCH SPECIES.
  2. CROSS LOGS SHALL BE A MINIMUM OF 8' IN LENGTH AND BE PINNED EVERY 2'. VANE ARM LOGS SHALL BE A MINIMUM OF 7', AND PINNED EVERY 2'.
  3. VANE ARM LOGS SHALL BE BURIED INTO THE BANK A MINIMUM OF 2', WHERE THEY SHALL BE KEYED INTO THE BANK WITH A SILL OF A MINIMUM LENGTH OF 3'.
  4. NAIL FILTER FABRIC (MIRAFI 140N OR APPROVED EQUAL) ON TOP OF FOOTER LOG USING 3" 10d GALVANIZED COMMON NAIL OR SIMILAR AT 1' INTERVALS ALONG THE LOG. FOLD OVER THE FILTER FABRIC ALONG THE NAIL LINE.
  5. SET THE ELEVATION OF THE TOP OF THE CROSS LOG TO THE DESIGNED THALWEG (CENTERLINE) ELEVATION OF THE STREAMBED.
  6. THE CROSS NOTCH CAN BE FORMED BY MAKING CUTS 1"-2" APART WITH A CHAINSAW, THEN KNOCKING OUT THE SECTIONS WITH A CHISEL AND HAMMER.
  7. THE ANGLE OF THE CROSS NOTCH SHALL MATCH THE ANGLE BETWEEN THE VANE ARMS AND THE STREAM BANK.
  8. SCOUR POOLS SHALL BE OVER DUG BY ~1.4x THE RIFFLE DEPTH, OR ABOUT 1' - 1.25' DEEP.

**LOG CROSS VANE**  
NO SCALE

**Proposed Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

MARK	DATE	DESCRIPTION
2	5/21/2018	TAC SUBMISSION
1	4/3/2018	TAC WS SUBMISSION

PROJECT NO:	L-0700-13
DATE:	04/03/2018
FILE:	L0700-CS-701 to C-703.dwg
DRAWN BY:	NAH
CHECKED:	PMC
APPROVED:	BLM

**HODGSON BROOK DETAILS SHEET**

SCALE: AS SHOWN

**C-703**

Last Save Date: May 17, 2018 8:41 AM By: BCLARK  
 Plot Date: Monday, May 21, 2018 Plotted By: Benjamin Clark  
 P&E File Location: J:\L0700\Lonza Biologics Expansion.was 127670.013 Iron Parcel Redevelopment\Drawings - Figures\AutoCAD\Sheet\L0700-CS-701 to C-703.dwg Layout Tab: C-703