
PROPOSED INDUSTRIAL DEVELOPMENT


70 & 80 CORPORATE DRIVE PORTSMOUTH, NEW HAMPSHIRE PROJECT NO: L-0700-13 APRIL 3, 2018

REVISED: AUGUST 21, 2018

LIST OF DRAWINGS		
SHEET NO.	SHEET TITLE	LAST REVISED
	COVER SHEET	08/21/2018
1 of 4	EXISTING CONDITIONS PLAN	08/16/2018
2 of 4	EXISTING CONDITIONS PLAN	08/16/2018
3 of 4	EXISTING CONDITIONS PLAN	08/16/2018
4 of 4	EXISTING CONDITIONS PLAN	08/16/2018
1 of 2	SUBDIVISION PLAN	04/16/2018
2 of 2	SUBDIVISION PLAN	04/16/2018
C-101	DEMOLITION PLAN	08/21/2018
C-102	DEMOLITION PLAN	08/21/2018
C-103	DEMOLITION PLAN	08/21/2018
C-104	OVERALL SITE PLAN	08/21/2018
C-105	SITE PLAN	08/21/2018
C-106	SITE PLAN	08/21/2018
C-107	SITE PLAN	08/21/2018
C-108	GRADING, DRAINAGE & EROSION CONTROL PLAN	08/21/2018
C-109	GRADING, DRAINAGE & EROSION CONTROL PLAN	08/21/2018
C-110	GRADING, DRAINAGE & EROSION CONTROL PLAN	08/21/2018
C-111	UTILITIES PLAN	08/21/2018
C-112	UTILITIES PLAN	08/21/2018
C-113	UTILITIES PLAN	08/21/2018
C-114	LANDSCAPE PLAN	08/21/2018
C-115	LANDSCAPE PLAN	08/21/2018
C-116	LANDSCAPE PLAN	08/21/2018
C-117	PHOTOMETRIC LIGHTING PLAN	08/21/2018
C-118	PHOTOMETRIC LIGHTING PLAN	08/21/2018
C-119	PHOTOMETRIC LIGHTING PLAN	08/21/2018
C-501	EROSION CONTROL NOTES & DETAILS SHEET	08/21/2018
C-502	DETAILS SHEET	08/21/2018
C-503	DETAILS SHEET	08/21/2018
C-504	DETAILS SHEET	08/21/2018
C-505	DETAILS SHEET	08/21/2018
C-506	DETAILS SHEET	08/21/2018
C-507	DETAILS SHEET	08/21/2018
C-508	DETAILS SHEET	08/21/2018
C-509	DETAILS SHEET	08/21/2018
C-701	HODGSON BROOK GRADING, DRAINAGE & EROSION CONTROL PLAN	08/21/2018
C-702	HODGSON BROOK WETLAND PLANTING PLAN	08/21/2018
C-703	HODGSON BROOK DETAILS SHEET	08/21/2018
ASK-001	SITE PLAN - PERSPECTIVE	08/09/2018
ASK-002	BUILDING 1 CONCEPT PLANS	07/12/2018



LOCATION MAP
SCALE: 1" = 2,000'



STREAM DESIGN CONSULTANT:

PEASE DEVELOPMENT AUTHORITY

55 INTERNATIONAL DRIVE

PORTSMOUTH, NEW HAMPSHIRE 03801

CLIENT: LONZA BIOLOGICS

101 INTERNATIONAL DRIVE PORTSMOUTH, NH 03801

CIVIL ENGINEER: Tighe&Bond
Engineers | Environmental Specialists

Engineers | Environmental Specialists

177 CORPORATE DRIVE

PORTSMOUTH, NEW HAMPSHIRE 03801

SURVEYOR: DOUCET SURVEY, INC.

102 KENT PLACE

NEWMARKET, NEW HAMPSHIRE 03857

WETLAND SCIENTIST: GOVE ENVIRONMENTAL SERVICES, INC.

8 CONTINENTAL DRIVE, UNIT H EXETER, NEW HAMPSHIRE 03833

STREAMWORKS, PLLC

MADBURY, NEW HAMPSHIRE 03823



OWNER:

COMPLETE SET 40 SHEETS


CB #1013	CBR #1324	CB #1461	CB #1732
" RIM ELEV.=68.4'	" RIM ELEV.=55.7'	" RIM ELEV.=57.9'	RIM ELEV.=39.1'
(1019) 18" HDPE INV.=64.4"	(A) 12" RCP INV.=52.3'	(1460) 12" RCP INV.=53.2"	(1695) 10" RCP INV.=37.3
(A) 18" HDPE INV.=64.4'	(1325) 12" RCP INV.=51.9"		
	(1305) 15" RCP INV.=51.9'	CB #1478	CBR #1733
CB #1019	(B) 22" RCP INV.=51.7"	RIM ELEV.=54.2'	RIM ELEV.=39.1'
RIM ELEV.=68.5'		(1515) 12" RCP INV.=47.2"	STRUCTURE DAMAGED
(A) 18" HDPE INV.=65.1'	CB #1325		
(1013) 18" HDPE INV.=64.7"	RIM ELEV.=55.7'	CB #1484	DMH #1755
	(1399) 15" RCP INV.=51.9"	RIM ELEV.=49.0'	RIM ELEV.=42'
CB #1088	(1324) 12" RCP INV.=51.8'	BROKEN GRATE - NOT OPENED	(A) 24" RCP INV.=37.2"
RIM ELEV.=66.6'			(B) 24" RCP INV.=37.1'
(A) 6" HDPE INV.=62.0'	DMH #1338	CB #1504	
(1111) 12" RCP INV.=61.6"	RIM ELEV.=57.7'	RIM ELEV.=48.9'	CB #1756
(1095) 12" RCP INV.=61.6'	(SUMP)=49.9' (LARGE VAULT)	(A) 12" RCP INV.=42.7' (1484) 12" RCP INV.=42.6'	RIM ELEV.=42.5' (1769) 12" RCP INV.=39.2
DMH #1095	CB #1345		
RIM ELEV.=65.2'	RIM ELEV.=58.1'	CB #1515	CB #1769
(1088) 12" RCP INV.=60.0"	(1420) 12" RCP INV.=53.9"	RIM ELEV.=54.1'	RIM ELEV.=42.5'
(1137) 12" RCP INV.=59.7"		BROKEN GRATE - NOT OPENED	(1756) 12" RCP INV.=38.1
	CB #1381		(A) 12" RCP INV.=33.5"
CB #1111	RIM ELEV.=57.2'	CB #1542	
RIM ELEV.=66.8'	(1212) 15" RCP INV.=54.3'	RIM ELEV.=44.4	CB #1935
(1088) 12" RCP INV.=61.9"	(1311) 15" RCP INV.=54.4"	(1651) 12" RCP INV.=41.0'	RIM ELEV.=49.7'
			NOT OPENED - SILT SOCK
CB #1137	CB #1399	CB #1570	OD #80074
RIM ELEV.=60.7'	RIM ELEV.=55.5'	RIM ELEV.=40.7'	CB #2031
(1095) 12" RCP INV.=57.3'	(1325) 15" RCP INV.=52.3"	(A) 18" RCP INV.=36.2'	RIM ELEV.=59.0'
(1285) 15" RCP INV.=56.8'	DMH #1401	(B) 18" RCP INV.=36.2'	NOT OPENED - SILT SOCK
(1141) 15" RCP INV.=56.8'	DMH #1401	CB #1572	DMH #2142
DMH #1141	RIM ELEV.=58.3' NOT OPENED — OFF SITE	CB #15/2 RIM ELEV.=42.2'	RIM ELEV.=62.8'
RIM ELEV.=61.1'	HOT OF LINED - OFF SHE	(1611) 12" RCP INV.=38.2'	(A) 24" HDPE INV.=58.2'
(1300) 12" RCP INV.=57.2'	DMH #1408	(.5) 12 // // // // // // // // // // // // //	(B) 24" HDPE INV.=56.8'
(1137) 15" RCP INV.=56.9'	RIM ELEV.=56.8'	CB #1580	\-\/ = \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
(1147) 15" RCP INV.=56.6'	NOT OPENED - OFF SITE	RIM ELEV.=41.7'	CB #2152
(A) 15" RCP INV.=56.4'	HOT OF LINED - OFF SHE	(1586) 15" RCP INV.=36.8'	RIM ELEV.=64.3'
(B) 18" ASB INV.=56.3'	CB #1420)/ .5 No. 1111-0010	NOT OPENED - SILT SOCK
week more worseout absolute the fitter.	RIM ELEV.=58.1'	CB #1586	
CB #1147	(1345) 12" RCP INV.=54.4'	RIM ELEV.=41.9'	DMH #2153
RIM ELEV.=61.5'	(1421) 12" HDPE INV.=54.1'	(1580) 15" RCP INV.=36.4"	RIM ELEV.=64.5'
(A) 15" RCP INV.=57.2'	FFA 10	(A) 15" RCP INV.=36.6'	(SUMP) INV.=53.9'
(1141) 15" RCP INV.=57.1'	DMH #1421		FULL OF WATER
NO.	RIM ELEV.=57.4'	CB #1611	
CB #1183	(1420) 12" RCP INV.=54.3'	RIM ELEV.=42.4'	CB #2170
RIM ELEV.=60.1'	SUMP=53.4' (FULL OF SILT)	(1572) 12" RCP INV.=37.8'	RIM ELEV.=65.7'
(1212) 15" RCP INV.=55.7'		(A) 12" RCP INV.=37.5'	NOT OPENED - SILT SOCK
	DMH #1438		
CB #1212	RIM ELEV.=50.2'	CB #1651	CB #2246
RIM ELEV.=57.5'	(A) 12" RCP INV.=44.6"	RIM ELEV.=44.6'	RIM ELEV.=65.5'
(1183) 15" RCP INV.=54.8"	(1439) 12" RCP INV.=44.6'	(1542) 12" RCP INV.=39.5"	NOT OPENED - SILT SOCK
(1381) 15" RCP INV.=54.6'	(B) UNK. CMP INV.=42.9'	(A) 12" RCP INV.=39.5'	
	(C) UNK. CMP INV.=42.9'	2000 4000000	CBR #2327
CB #1285		CB #1678	RIM ELEV.=40.2'
RIM ELEV.=60.7'	CBR #1439	RIM ELEV.=39.2'	(A) 12" RCP INV.=38.3'
(1137) 15" RCP INV.=57.0'	RIM ELEV.=47.4'	(TOP OF WATER) INV.=36.5'	a de la constante de la consta
ODD 144757	(1438) 12" RCP INV.=45.2'	(A) 12" RCP INV.=35.4'	CBR #2329
CBR #1305	000 11444	OD #4605	RIM ELEV.=47.4'
RIM ELEV.=56.7'	CBR #1444	CB #1685	(A) 12" RCP INV.=42.0'
(1311) 12" RCP INV.=52.8'	RIM ELEV.=48.3'	RIM ELEV.=39.2'	SILT=41.9'
(A) 15" RCP INV.=52.7'	12" HDPE INV.=46.4'	(TOP OF WATER) INV.=36.6'	DMI #0770
(1324) 15" RCP INV.=52.7'	(SUMP) INV.=42.8'	(2330) 12" RCP INV.=36.4"	DMH #2330
CD #1314	CD MAEC	DML #1605	RIM ELEV.=40.4'
CB #1311	CB #1456	DMH #1695	(1685) 12" RCP INV.=36.5
RIM ELEV.=57.1'	RIM ELEV.=58.1'	RIM ELEV.=42.8'	(A) 12" RCP INV.=36.3'
(1381) 15" RCP INV.=53.4'	(1460) 12" RCP INV.=52.5'	(1732) 10" RCP INV.=36.4'	(B) 15" RCP INV.=36.1'
(1305) 12" RCP INV.=53.0'	DMH #1460	(A) 48" RCP INV.=35.9'	UMI TOSSE
	DMH #1460	(B) NOT MEASURED	DMH #2336
	RIM ELEV.=58'	(RECESSED — LARGE VAULT)	RIM ELEV.=39.7' (A) 18" PCP INV -36.1'
	(1461) 12" RCP INV.=51.6"		(A) 18" RCP INV.=36.1' (B) 24" RCP INV.=35.4'
	(1456) 12" RCP INV.=51.5'		

SMH #1062	SMH #1551
RIM ELEV.=69.8'	RIM ELEV.=43.6'
(A) 6" CLAY INV.=63.9'	(A) 8" PVC INV.=35.6'
(B) 6" CLAY INV.=63.7'	(B) 12" UNK. INV.=34.2'
(1067) 8" CLAY INV.=62.6'	(C) 12" UNK. INV.=34.1'
(1007) 0 0211 111102.0	(6) 12 5111. 111151.1
SMH #1067	SMH #1691
RIM ELEV.=68.6'	RIM ELEV.=39.9'
(1062) 8" CLAY INV.=60.4'	(1784) UNK. INV.=34.2'
(2242) 8" UNK. INV.=60.3"	(1722) UNK. INV.=34.1'
SMH #1078	SMH #1722
RIM ELEV.=69.0'	RIM ELEV.=41.1'
COULD NOT OPEN	(A) 6" CLAY INV.=33.2'
	(1691) UNK. CLAY INV.=3
SMH #1123	
RIM ELEV.=64'	SMH #1784
(1295) 8" PVC INV.=55.8'	RIM ELEV.=41.1'
	(1921) 10" UNK. INV.=35.
SMH #1169	(1691) 10" UNK. INV.=35.
RIM ELEV.=65.2'	The state of the s
(1184) 15" STEEL INV.=53.8'	SMH #1921
(A) 15" STEEL INV.=53.8'	RIM ELEV.=44.8'
V-7 .5 57222 111100.0	(1953) UNK. INV.=37'
SMH #1184	
	(1784) UNK. INV.=36.9'
RIM ELEV.=60.4'	CMU MAGEZ
(1296) 8" CLAY INV.=54.2'	SMH #1953
(1217) 15" STEEL INV.=52.7'	RIM ELEV.=50.1'
(1169) 15" STEEL INV.=52.7"	(A) 6" CLAY INV.=42.4"
	(2080) UNK. INV.=42.2'
SMH #1217	(1921) UNK. INV.=42.2'
RIM ELEV.=57.9'	
(1184) 15" STEEL INV.=52.3'	SMH #2080
(1400) 15" STEEL INV.=52.2'	RIM ELEV.=57.9'
	(A) 8" UNK. INV.=50.1"
SMH #1296	2187) 8" UNK. INV.=50.
RIM ELEV.=63.7'	(1953) 8" UNK. INV.=49.9
(1123) 8" PVC INV.=55.5'	250 2
(2326) 8" UNK. INV.=55.0'	SMH #2187
(1184) 8" UNK. INV.=55.0'	RIM ELEV.=63'
	(A) 6" PVC INV.=54.9'
SMH #1400	(2242) 8" PVC INV.=54.9
	NE 8
RIM ELEV.=55.6'	(2080) 8" PVC INV.=54.9
(1217) 15" ASB INV.=49.3'	
(1415) 15" ASB INV.=49.3'	SMH #2242
	RIM ELEV.=65.0'
SMH #1415	(1067) 8" CLAY INV.=56.
RIM ELEV.=57.9'	(2187) 8" CLAY INV.=57.
(A) 12" PVC INV.=48.3'	
(1400) 18" UNK. INV.=47.9"	SMH #2326
(1450) 18" PVC INV.=48.0'	RIM ELEV.=68.1'
	(1078) 8" PVC INV.=62.2
SMH #1450	(1296) 8" ASB INV.=62.1
RIM ELEV.=60.5'	Victory & Committee of the
(1415) 18" PVC INV.=47.6'	SMH #2328
(1459) 18" PVC INV.=47.5'	RIM ELEV.=43.1'
(1705) 10 F VO INV.=47.0	
CMLL HARC	(1551) 12" UNK INV.=32.3
SMH #1459	(A) 18" UNK INV.=32.3'
RIM ELEV.=58.8'	
(A) 8" PVC INV.=48.4'	
(1450) 18" PVC INV.=47.1'	

PURSUANT TO RSA 676:18, III:

I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN.

I CERTIFY THAT THIS SURVEY AND PLAN WERE PREPARED BY ME OR BY THOSE UNDER MY DIRECT SUPERVISION AND FALLS UNDER THE URBAN SURVEY CLASSIFICATION OF THE NH CODE OF ADMINISTRATIVE RULES OF THE BOARD OF LICENSURE FOR LAND SURVEYORS. I CERTIFY THAT THIS SURVEY WAS MADE ON THE GROUND AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. RANDOM TRAVERSE SURVEY BY TOTAL STATION, WITH A PRECISION GREATER THAN 1:15,000.



THE CERTIFICATIONS SHOWN HEREON ARE INTENDED TO MEET REGISTRY OF DEED REQUIREMENTS AND ARE NOT A CERTIFICATION TO TITLE OR OWNERSHIP OF PROPERTY SHOWN. OWNERS OF ADJOINING PROPERTIES ARE ACCORDING TO CURRENT TOWN ASSESSORS RECORDS.

REFERENCE PLANS:

- 1. "R.O.W. WORKSHEET, CORPORATE DRIVE PREPARED FOR PEASE DEVELOPMENT AUTHORITY" DATED DEC. 21, 1992 BY RICHARD D. BARTLETT & ASSOCIATES, INC. SHEETS 1 AND 2.
- 2. "PEASE A.F.B. / PORTSMOUTH, N.H. REPAVE BASE STREETS, PORTSMOUTH AVE, ROCKINGHAM AVE." DATED 7 DEC 82 BY STRATETIC AIR COMMAND CIVIL ENGINEERING. SHEET 4 OF 5
- 3. "PORTSMOUTH AIR FORCE BASE, PORTSMOUTH, N.H. ROADS AND STORAGE AREA FY-56" DATED DEC 1955 BY WHITMAN & HOWARD ENGINEERS. INDEX PAGE AND SHEETS 2 - 5 OF 11.
- 4. "PEASE INTERNATIONAL TRADEPORT SUBDIVISION PLAT, INTERNATIONAL DRIVE LOTS BC11-001 & BC11-002, PORTSMOUTH, N.H." DATED FEBRUARY 5, 1993 BY RICHARD D. BARTLETT & ASSOCIATES INC. R.C.R.D. PLAN #D22536.
- 5. "SUBDIVISION PLAN OF LAND FOR REDHOOK ALE BREWERY, INC. CORPORATE DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED DECEMBER 10, 1994 BY RICHARD P. MILLETTE AND ASSOCIATES. R.C.R.D. PLAN #D-23978.
- 6. "ALTA/ACSM LAND TITLE SURVEY FOR RESPORT, LLC, ONE INTERNATIONAL DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED FEBRUARY 27, 1998 BY MILLETTE, SPRAGUE & COLWELL, INC. R.C.R.D. PLAN #D-26125.
- 7. "FRANKLIN PIERCE COLLEGE, PEASE INTERNATIONAL TRADEPORT, 73 CORPORATE DRIVE, PORTSMOUTH, NH" DATED JANUARY 15, 1998 BY RONALD R. BURD. R.C.R.D. PLAN #D-26427.
- 8. "SUBDIVISION PLAN FOR LAND LEASED BY PEASE DEVELOPMENT AUTHORITY & KNOWN AS #119 INTERNATIONAL DRIVE LOCATED AT PEASE INTERNATIONAL TRADEPORT, PORTSMOUTH, N.H." DATED MARCH 1, 2000 BY KNIGHT HILL LAND SURVEYING SERVICES, INC. R.C.R.D. PLAN
- 9. "SUBDIVISION PLAT PREPARED FOR 80 CORPORATE DRIVE LLC C/O BOULOS PROPERTY MANAGEMENT, LOCATION CORPORATE & GOOSE BAY DRIVES, PEASE INTERNATIONAL TRADEPORT -PORTSMOUTH, NH" DATED APRIL 11, 2000 BY FWS LAND SURVEYING P.L.L.C. R.C.R.D. PLAN
- 10. "LEASE LINE REVISION PLAN FOR LONZA BIOLOGICS, INC. 101 INTERNATIONAL DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED FEB. 5, 2001 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #D-28955.
- 11. "LEASE LINE REVISION PLAN FOR LONZA BIOLOGICS, INC. 101 INTERNATIONAL DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED SEPT. 17, 2001 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #D-29538. NOTES:
- 12. "SUBDIVISION PLAN OF LAND OF PEASE DEVELOPMENT AUTHORITY TO BE LEASED TO NORTHEAST 1. REFERENCE: REHABILITATION (A PORTION OF TAX MAP 303, LOT 6) 105 & 121 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH, NEW HAMPSHIRE" DATED NOV. 5, 2008 BY DOUCET SURVEY, INC. R.C.R.D. PLAN #D-35869.
- 13. "CONDOMINIUM SITE & FLOOR PLAN PREPARED FOR PIONEER NEW HAMPSHIRE, LLC, LAND OF PEASE DEVELOPMENT AUTHORITY, TAX MAP PARCEL 305-3 (108, 110, 112 & 114 CORPORATE DRIVE) PORTSMOUTH, NEW HAMPSHIRE" DATED APRIL 12, 2013 BY FIELDSTONE LAND CONSULTANTS, PLLC. SHEET 1 OF 5. R.C.R.D. PLAN #D-37765.
- 14. "SUBDIVISION PLAN FOR PEASE DEVELOPMENT AUTHORITY, (TAX MAP 303, LOT 4) 67 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH NEW HAMPSHIRE" DATED MAY 29, 2009 BY DOUCET SURVEY, INC. (NOT RECORDED)
- 15. "EXISTING CONDITIONS, BUILDING A, 80 CORPORATE DRIVE AND BUILDING B, 70 CORPORATE DRIVE, PORTSMOUTH, NH" DATED 4/14/2000 AND REVISED 6/05/2000 BY OPECHEE CONSTRUCTION CORPORATION. (NOT RECORDED)

LEGEND

EXISTING LEASE/R.O.W. LINES ---- O --- O -- CHAIN LINK FENCE OHW OVERHEAD WIRES ------ \$ ------ SEWER LINE ---- D ----- DRAIN LINE ----- G ------ GAS LINE ----- W ----- WATER LINE ----- E ------ UNDERGROUND ELECTRIC LINE SEWER LINE PER REF. PLAN #15 - DRAIN LINE PER REF. PLAN #15 — 100— MAJOR CONTOUR LINE - - - 98 - - - MINOR CONTOUR LINE . TREE LINE — · · — · · — EDGE OF WETLAND (SEE NOTE #6) ---- HISS LINE (SEE NOTE #6) UTILITY POLE GRANITE BOUND FOUND DRILL HOLE FOUND IRON PIPE/ROD FOUND 4"X4" GRANITE BOUND TO BE SET 5/8" REBAR W/ ID CAP TO BE SET BOLLARD FIRE HYDRANT WATER GATE VALVE GAS GATE VALVE PAD MOUNTED TRANSFORMER ELECTRIC BOX TELEPHONE BOX UTILITY BOX CABLE BOX CATCH BASIN CATCH BASIN CATCH BASIN DRAIN MANHOLE FLARED END SECTION ELECTRIC MANHOLE TELEPHONE MANHOLE SEWER MANHOLE CATCH BASIN PER REF. PLAN #15 DRAIN MANHOLE PER REF. PLAN #15 SEWER MANHOLE PER REF. PLAN #15 HAND HOLE WETLAND AREA CONIFEROUS TREE DECIDUOUS TREE CONCRETE RIP RAP GRAVEL AREA LEDGE OUTCROP BOUND FOUND BND. FND.

> DRILL HOLE FOUND EDGE OF PAVEMENT

SINGLE WHITE LINE

HISS SOIL TYPE


DOUBLE YELLOW LINE

VERTICAL GRANITE CURB

D.H.F.

EP

SWL DYL



Location Map (n.t.s.

TAX MAP 305, LOT 1 PHYSICAL ADDRESS: 70 CORPORATE DRIVE TAX MAP 305, LOT 2 PHYSICAL ADDRESS: 80 CORPORATE DRIVE

2. TOTAL PARCEL AREA:

OWNER OF RECORD:

TAX MAP 305, LOT 1: 443,578 SQ. FT. OR 10.183 AC. TAX MAP 305, LOT 2: 604,273 SQ. FT. OR 13.872 AC. TOTAL AREA: 1,047,851 SQ. FT. OR 24.055 AC.

TAX MAP 305, LOTS 1 & 2

PEASE DEVELOPMENT AUTHORITY 55 INTERNATIONAL DRIVE PORTSMOUTH, NEW HAMPSHIRE 03801 R.C.R.D. BOOK 4227, PAGE 001

- 4. ZONE: AIRPORT, BUSINESS & COMMERCIAL (ABC)
- 5. FIELD SURVEY PERFORMED BY J.M.L, E.J.S., J.P.E., J.F.K., AND N.J.M. DURING NOVEMBER 2015 USING A TRIMBLE R8 SURVEY GRADE GPS UNIT AND A TRIMBLE S6 ROBOTIC TOTAL STATION WITH A TRIMBLE TSC3
- 6. JURISDICTIONAL WETLANDS DELINEATED BY GOVE ENVIRONMENTAL SERVICES, INC. DURING FALL 2014 IN ACCORDANCE WITH 1987 CORPS OF ENGINEERS WETLANDS DELINEATIONS MANUAL, TECHNICAL REPORT Y-87-1. HISS/SITE SPECIFIC SOILS MAPPING COMPLETED BY GOVE ENVIRONMENTAL SERVICES DURING DECEMBER 2015.
- 7. FLOOD HAZARD ZONE: "X", PER FIRM MAP #33015C0260E, DATED MAY 17, 2005.
- 8. HORIZONTAL DATUM BASED ON NH STATE PLANE 2800(NAD83/86) PER REFERENCE PLANS #10, #11, & #12.
- 9. VERTICAL DATUM IS BASED ON NGVD29 PER REFERENCE PLANS #10, #11, & #12.
- 10. PROPER FIELD PROCEDURES WERE FOLLOWED IN ORDER TO GENERATE CONTOURS AT 2' INTERVALS. ANY MODIFICATION OF THIS INTERVAL WILL DIMINISH THE INTEGRITY OF THE DATA, AND DOUCET SURVEY, INC. WILL NOT BE RESPONSIBLE FOR ANY SUCH ALTERATION PERFORMED BY THE USER.
- 11. UNDERGROUND UTILITIES SHOWN HEREON ARE BASED ON OBSERVABLE PHYSICAL EVIDENCE AND PAINT MARKS FOUND ON-SITE. THE SITE WAS NOT MARKED FOR THE PURPOSES OF THIS SURVEY. SOME UTILITIES ARE SHOWN PER REFERENCE PLANS AS NOTED IN THE LEGEND.
- 12. THE ACCURACY OF MEASURED UTILITY INVERTS AND PIPE SIZES/TYPES IS SUBJECT TO NUMEROUS FIELD CONDITIONS, INCLUDING; THE ABILITY TO MAKE VISUAL OBSERVATIONS, DIRECT ACCESS TO THE VARIOUS ELEMENTS, MANHOLE CONFIGURATION, ETC.
- 13. THE INTENT OF THIS PLAN IS TO SHOW THE LOCATION OF BOUNDARIES IN ACCORDANCE WITH AND IN RELATION TO THE CURRENT LEGAL DESCRIPTION, AND IS NOT AN ATTEMPT TO DEFINE UNWRITTEN RIGHTS, DETERMINE THE EXTENT OF OWNERSHIP, OR DEFINE THE LIMITS OF TITLE.
- 14. TAX MAP 305, LOTS 1 & 2 ARE EITHER SUBJECT TO OR IN BENEFIT OF, BUT NOT LIMITED TO, THE FOLLOWING EASEMENTS/RIGHTS OF RECORD:
- 14.A. 50' WIDE ACCESS EASEMENT FOR THE BENEFIT OF LOT 305-2. (SHOWN PER REFERENCE PLAN #9) 14.B. APPROXIMATE LOCATION OF 20' WIDE LICENSE TO THE CITY OF PORTSMOUTH FOR THE PURPOSES OF MAINTAINING A DRAINAGE LINE. (SHOWN PER REFERENCE PLAN #9)
- 15. FINAL MONUMENTATION MAY BE DIFFERENT THAN THE PROPOSED MONUMENTATION SHOWN HEREON, DUE TO THE FACT THAT SITE CONDITIONS WILL DICTATE THE ACTUAL LOCATION AND TYPE OF MONUMENTS INSTALLED IN THE FIELD. PLEASE REFER TO EITHER THE "MONUMENTATION LOCATION PLAN" TO BE RECORDED OR CONTACT DOUCET SURVEY, INC. FOR CLARIFICATION OF MONUMENTS SET. (A RECORDED PLAN WILL BE PRODUCED AT THE DISCRETION OF DOUCET SURVEY, INC.).




EXISTING CONDITIONS PLAN FOR TIGHE & BOND AND LONZA LAND OF

PEASE DEVELOPMENT AUTHORITY (TAX MAP 305, LOTS 1 & 2)

GOOSE BAY DRIVE & CORPORATE DRIVE PORTSMOUTH, NEW HAMPSHIRE

DEC. 23, 2015 DRAWN BY: J. A. G. CHECKED BY:







DESCRIPTION


NO. DATE


ALL ELECTRIC, GAS, TEL. WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC J.A.G. FASHION, THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE BY LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888-DIG-SAFE.





FILE NAME: C:\Users\Jeff\appdata\local\temp\AcPublish_8524\4375A.dwg LAYOUT NAME: DSI 22X34 (1) PLOTTED: Thursday, August 16, 2018 - 3:18pr











DRAWN BY: W.D.C.	DATE: APRIL 16, 2018
J.A.G. CHECKED BY:	DRAWING NO.: 5518A
5518 JOB NO.:	1 2 SHEET OF

http://www.doucetsurvey.com

NOTES:

1. REFERENCE:

TAX MAP 305, LOTS 5 & 6 PHYSICAL ADDRESS: 101 INTERNATIONAL DRIVE

2. PROPOSED LEASE AREA:

TAX MAP 305, LOT 6: 1,889,305 SQ. FT. OR 43.37 AC.

3. OWNER OF RECORD:

PEASE DEVELOPMENT AUTHORITY
55 INTERNATIONAL DRIVE

OWNER OF RECORD

PORTSMOUTH, NEW HAMPSHIRE 03801 R.C.R.D. BOOK 4227, PAGE 001

4. LESSEE OF RECORD:

TAX MAP 305. LOTS 5 & 6
LONZA BIOLOGICS, INC.
101 INTERNATIONAL DRIVE
PORTSMOUTH, NEW HAMPSHIRE 03801
R.C.R.D. BOOK 3015, PAGE 2559
(LEASE EXTENSIONS AND MODIFICATIONS
HAVE NOT BEEN RECORDED, BUT HAVE
BEEN PROVIDED BY THE LESSEE)
SEE REFERENCE PLAN 10

5. ZONE: AIRPORT, BUSINESS, AND COMMERCIAL (ABC) DIMENSIONAL REQUIREMENTS:

MINIMUM LOT AREA 217,800 sq.ft. OR 5.0 AC. MINIMUM STREET FRONTAGE 200 ft.

FRONT YARD SETBACK 70 ft.
SIDE SETBACK 30 ft.
REAR SETBACK 50 ft.
MINIMUM OPEN SPACE 25 %

MAXIMUM STRUCTURE HEIGHT SHALL NOT EXCEED FAA CRITERIA

WETLAND BUFFER

25 ft. (PER PDA REGULATIONS: WETLANDS LESS THAN 1/4 ACRE DO NOT HAVE A BUFFER)

ZONING INFORMATION LISTED HEREON WAS PROVIDED BY TIGHE & BOND. ADDITIONAL REGULATIONS APPLY, AND REFERENCE IS HEREBY MADE TO THE EFFECTIVE ZONING ORDINANCE. THE LAND OWNER IS RESPONSIBLE FOR COMPLYING WITH ALL APPLICABLE MUNICIPAL, STATE, AND FEDERAL REGULATIONS.

- 6. FIELD SURVEY PERFORMED BY B.T. & J.C.M. DURING MARCH 2018 USING A TRIMBLE S6 ROBOTIC TOTAL STATION WITH A TRIMBLE TSC3 DATA COLLECTOR. TRAVERSE ADJUSTMENT BASED ON LEAST SQUARE ANALYSIS.
- 7. FLOOD HAZARD ZONE: "X", PER FIRM MAP #33015C0260E, DATED MAY 17, 2005.
- 8. HORIZONTAL DATUM BASED ON NH STATE PLANE 2800(NAD83/86) PER REFERENCE PLANS 10, 11, & 12.
- 9. THE INTENT OF THIS PLAN IS TO SHOW THE LOCATION OF BOUNDARIES IN ACCORDANCE WITH AND IN RELATION TO THE CURRENT LEGAL DESCRIPTION, AND IS NOT AN ATTEMPT TO DEFINE UNWRITTEN RIGHTS, DETERMINE THE EXTENT OF OWNERSHIP, OR DEFINE THE LIMITS OF TITLE.
- 10. TAX MAP 305, LOTS 1 & 2 ARE EITHER SUBJECT TO OR IN BENEFIT OF, BUT NOT LIMITED TO, THE
- FOLLOWING EASEMENTS/RIGHTS OF RECORD:

 10.A. 50' WIDE ACCESS EASEMENT FOR THE BENEFIT OF LOT 305-2. (SHOWN PER REFERENCE PLAN 9)

 10.B. APPROXIMATE LOCATION OF 20' WIDE LICENSE TO THE CITY OF PORTSMOUTH FOR THE PURPOSES OF MAINTAINING A DRAINAGE LINE. (SHOWN PER REFERENCE PLAN 9)
- 11. TAX MAP 305, LOTS 5 & 6 ARE EITHER SUBJECT TO OR IN BENEFIT OF, BUT NOT LIMITED TO, THE
- FOLLOWING EASEMENTS/RIGHTS OF RECORD:
 11.A. 15' WIDE DRAINAGE EASEMENT. (SHOWN PER REFERENCE PLAN 10)
- 11.A. 15 WIDE DRAINAGE EASEMENT. (SHOWN PER REFERENCE FLAN 10)
- 12. FINAL MONUMENTATION MAY BE DIFFERENT THAN THE PROPOSED MONUMENTATION SHOWN HEREON, DUE TO THE FACT THAT SITE CONDITIONS WILL DICTATE THE ACTUAL LOCATION AND TYPE OF MONUMENTS INSTALLED IN THE FIELD. PLEASE REFER TO EITHER THE "MONUMENTATION LOCATION PLAN" TO BE RECORDED OR CONTACT DOUCET SURVEY, INC. FOR CLARIFICATION OF MONUMENTS SET. (A RECORDED PLAN WILL BE PRODUCED AT THE DISCRETION OF DOUCET SURVEY, INC.).
- 13. IMPROVEMENTS SHOWN HEREON ARE APPROXIMATE.
- 14. REGARDING THE PORTION GOOSE BAY DRIVE TO BECOME PART OF THE PROPOSED LEASE AREA:

 14.A. THE PEASE DEVELOPMENT AUTHORITY REPORTS THAT THE OWNERSHIP UNDERLYING ROADWAYS WITHIN

 THE TRADEPORT REMAINS VESTED IN THE PEASE DEVELOPMENT AUTHORITY.
- 14.B. THE PEASE DEVELOPMENT AUTHORITY REPORTS THAT THERE ARE UNDERLYING BLANKET UTILITY EASEMENTS ON LANDS IN THEIR OWNERSHIP. THIS MAY INCLUDE, BUT NOT BE LIMITED TO BURIED OR OVERHEAD ELECTRIC, TELECOMMUNICATIONS, GAS, WATER, AND SEWER.
- 15. THE APPLICANT WILL BE REQUESTING THE FOLLOWING WAIVER FROM THE CITY OF PORTSMOUTH PLANNING BOARD REGARDING SECTION IV; 3; I. CUL—DE—SACS:
- 15.A. MAXIMUM LENGTH OF CUL—DE—SAC OF 500'
 15.B. MINIMUM RADIUS OF CUL—DE—SAC PAVEMENT OF 50'

REFERENCE PLANS:

- 1. "R.O.W. WORKSHEET, CORPORATE DRIVE PREPARED FOR PEASE DEVELOPMENT AUTHORITY" DATED DEC. 21, 1992 BY RICHARD D. BARTLETT & ASSOCIATES, INC. SHEETS 1 AND 2. (NOT RECORDED)
- 2. "PEASE A.F.B. / PORTSMOUTH, N.H. REPAVE BASE STREETS, PORTSMOUTH AVE, ROCKINGHAM AVE."
 DATED 7 DEC 82 BY STRATETIC AIR COMMAND CIVIL ENGINEERING. SHEET 4 OF 5. (NOT RECORDED)
- 3. "PORTSMOUTH AIR FORCE BASE, PORTSMOUTH, N.H. ROADS AND STORAGE AREA FY-56" DATED DEC 1955 BY WHITMAN & HOWARD ENGINEERS. INDEX PAGE AND SHEETS 2 5 OF 11. (NOT RECORDED)
- 4. "PEASE INTERNATIONAL TRADEPORT SUBDIVISION PLAT, INTERNATIONAL DRIVE LOTS BC11-001 & BC11-002, PORTSMOUTH, N.H." DATED FEBRUARY 5, 1993 BY RICHARD D. BARTLETT & ASSOCIATES INC. R.C.R.D. PLAN D-22536.
- 5. "SUBDIVISION PLAN OF LAND FOR REDHOOK ALE BREWERY, INC. CORPORATE DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED DECEMBER 10, 1994 BY RICHARD P. MILLETTE AND ASSOCIATES. R.C.R.D. PLAN D-23978.
- 6. "ALTA/ACSM LAND TITLE SURVEY FOR RESPORT, LLC, ONE INTERNATIONAL DRIVE, COUNTY OF ROCKINGHAM, PORTSMOUTH, N.H." DATED FEBRUARY 27, 1998 BY MILLETTE, SPRAGUE & COLWELL, INC. R.C.R.D. PLAN D-26125.
- 7. "FRANKLIN PIERCE COLLEGE, PEASE INTERNATIONAL TRADEPORT, 73 CORPORATE DRIVE, PORTSMOUTH, NH" DATED JANUARY 15, 1998 BY RONALD R. BURD. R.C.R.D. PLAN D-26427.
- 8. "SUBDIVISION PLAN FOR LAND LEASED BY PEASE DEVELOPMENT AUTHORITY & KNOWN AS 119 INTERNATIONAL DRIVE LOCATED AT PEASE INTERNATIONAL TRADEPORT, PORTSMOUTH, N.H." DATED MARCH 1, 2000 BY KNIGHT HILL LAND SURVEYING SERVICES, INC. R.C.R.D. PLAN D-28059.
- 9. "SUBDIVISION PLAT PREPARED FOR 80 CORPORATE DRIVE LLC C/O BOULOS PROPERTY MANAGEMENT, LOCATION CORPORATE & GOOSE BAY DRIVES, PEASE INTERNATIONAL TRADEPORT PORTSMOUTH, NH" DATED APRIL 11, 2000 BY FWS LAND SURVEYING P.L.L.C. R.C.R.D. PLAN D-28447.
- 10. "LEASE LINE REVISION PLAN FOR LONZA BIOLOGICS, INC. 101 INTERNATIONAL DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED SEPT. 17, 2001 BY DOUCET SURVEY, INC. R.C.R.D. PLAN D-29538.


- 11. "SUBDIVISION PLAN OF LAND OF PEASE DEVELOPMENT AUTHORITY TO BE LEASED TO NORTHEAST REHABILITATION (A PORTION OF TAX MAP 303, LOT 6) 105 & 121 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH, NEW HAMPSHIRE" DATED NOV. 5, 2008 BY DOUCET SURVEY, INC. P. C. P.D. PLAN D. 35869
- 12. "CONDOMINIUM SITE & FLOOR PLAN PREPARED FOR PIONEER NEW HAMPSHIRE, LLC, LAND OF PEASE DEVELOPMENT AUTHORITY, TAX MAP PARCEL 305—3 (108, 110, 112 & 114 CORPORATE DRIVE) PORTSMOUTH, NEW HAMPSHIRE" DATED APRIL 12, 2013 BY FIELDSTONE LAND CONSULTANTS, PLLC. SHEET 1 OF 5. R.C.R.D. PLAN D—37765.
- 13. "SUBDIVISION PLAN FOR PEASE DEVELOPMENT AUTHORITY, (TAX MAP 303, LOT 4) 67 CORPORATE DRIVE, PEASE TRADEPORT, PORTSMOUTH NEW HAMPSHIRE" DATED MAY 29, 2009 BY DOUCET SURVEY, INC. (NOT RECORDED)
- 14. "EXISTING CONDITIONS, BUILDING A, 80 CORPORATE DRIVE AND BUILDING B, 70 CORPORATE DRIVE, PORTSMOUTH, NH" DATED 4/14/2000 AND REVISED 6/05/2000 BY OPECHEE CONSTRUCTION CORPORATION. (NOT RECORDED)
- 15. "EXISTING CONDITIONS PLAN FOR TIGHE & BOND AND LONZA, LAND OF PEASE DEVELOPMENT AUTHORITY, (TAX MAP 305, LOTS 1 & 2), GOOSE BAY DRIVE & CORPORATE DRIVE, PORTSMOUTH, NEW HAMPSHIRE" DATED DECEMBER 23, 2015 BY DOUCET SURVEY, INC. (NOT RECORDED)
- 16. "119 INTERNATIONAL DRIVE CONDOMINIUM, CONDOMINIUM SITE PLAN, FOR PROPERTY OWNED BY PEASE DEVELOPMENT AUTHORITY, LEASED TO 119 INTERNATIONAL DRIVE, LLC, KNOWN AS PORTSMOUTH TAX MAP 305, LOT 4, PORTSMOUTH, NH" DATED OCT. 10, 2017 BY KNIGHT HILL LAND SURVEYING SERVICES, INC. R.C.R.D. PLAN 40449
- 17. "ALTA/NSPS LAND TITLE SURVEY FOR 130 INTERNATIONAL DRIVE, LLC AND PEASE DEVELOPMENT AUTHORITY, 130 INTERNATIONAL DRIVE, PORTSMOUTH, NH" DATED JULY 2017 AND REVISED THROUGH 8/9/17 BY DOUCET SURVEY, INC. (NOT RECORDED)
- 18. "ALTA/ACSM LAND TITLE SURVEY FOR 100 INTERNATIONAL DRIVE, LLC, 100 INTERNATIONAL DRIVE, PEASE INTERNATIONAL TRADEPORT, PORTSMOUTH, NH" DATED MARCH 30, 2006 BY DOUCET SURVEY, INC. (NOT RECORDED)

SUBDIVISION PLAN FOR LONZA BIOLOGICS, INC. AND

THE PEASE DEVELOPMENT AUTHORITY

TAX MAP 305 LOTS 1, 2, 5 & 6 AND

GOOSE BAY DRIVE
INTERNATIONAL DRIVE - CORPORATE DRIVE
GOOSE BAY DRIVE
PORTSMOUTH, NEW HAMPSHIRE



I CERTIFY THAT THIS SURVEY AND PLAN WERE PREPARED BY
ME OR BY THOSE UNDER MY DIRECT SUPERVISION AND FALLS
UNDER THE URBAN SURVEY CLASSIFICATION OF THE NH CODE
OF ADMINISTRATIVE RULES OF THE BOARD OF LICENSURE FOR
LAND SURVEYORS. I CERTIFY THAT THIS SURVEY WAS MADE ON
THE GROUND AND IS CORRECT TO THE BEST OF MY KNOWLEDGE
AND BELIEF. RANDOM TRAVERSE SURVEY BY TOTAL STATION.

WITH A PRECISION GREATER THAN 1:15,000.

LL.S. #964

GOLDKNOPF

THE CERTIFICATIONS SHOWN HEREON ARE INTENDED TO MEET REGISTRY OF DEED REQUIREMENTS AND ARE NOT A CERTIFICATION TO TITLE OR OWNERSHIP OF PROPERTY SHOWN. OWNERS OF ADJOINING PROPERTIES ARE ACCORDING TO CURRENT TOWN ASSESSORS RECORDS.

NO. DATE DESCRIPTION BY

DRAWN BY: W.D.C. DATE: APRIL 16, 2018


CHECKED BY: J.A.G. DRAWING NO.:


5518

SHEET OF



102 Kent Place, Newmarket, NH 03857 (603) 659-6560
2 Commerce Drive (Suite 202) Bedford, NH 03110 (603) 614-4060
10 Storer Street (Riverview Suite) Kennebunk, ME (207) 502-7005
http://www.doucetsurvey.com





Proposed **Industrial Development**

Lonza Biologics


New Hampshire


D	8/21/2018	REVISED TAC SUBMISSION
C	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
ARK	DATE	DESCRIPTION
ROJECT NO:		L-0700-013
ΛTF:		04/03/2018


04/03/2018 FILE: L0700-CD-101 to C-103.dwg NAH PMC BLM


DEMOLITION PLAN

AS SHOWN












D	8/21/2018	REVISED TAC SUBMISSION	
С	6/18/2018	NHDES AOT SUBMISSION	
В	5/21/2018	TAC SUBMISSION	
Α	4/3/2018	TAC WS SUBMISSION	
MARK	DATE	DESCRIPTION	
PROJEC	PROJECT NO: L-0700-013		
DATE: 04/03/2018			
FILE: L0700-CS-104 to C-107.dwg			













D	8/21/2018	REVISED TAC SUBMISSION
C	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
ARK	DATE	DESCRIPTION
ROJECT NO:		L-0700-013









D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO:		L-0700-013








Engineers | Environmental Specialists





Proposed **Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire


D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO:		L-0700-013


04/03/2018 FILE: L0700-CL-114 to C-116.dwg


LANDSCAPE PLAN

AS SHOWN


CHECKED: APPROVED:








D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
DDOJECT NO:		1_0700_013





PROJECT OWNER: PEASE DEVELOPMENT AUTHORITY 55 INTERNATIONAL DRIVE

PORTSMOUTH, NH 03801 PROJECT APPLICANT: LONZA BIOLOGICS

101 INTERNATIONAL DRIVE PORTSMOUTH, NH 03801 PROJECT ADDRESS: 70 & 80 CORPORATE DRIVE PORTSMOUTH, NH 03801

PROJECT LATITUDE: 43°-04'-59.0"N PROJECT LONGITUDE: 71°-48'-09.7"W

PROJECT DESCRIPTION

THE PROJECT CONSISTS OF THE EXPANSION OF LONZA BIOLOGICS, WHICH INCLUDES THE CONSTRUCTION OF 3 PROPOSED BUILDINGS, 2 PARKING GARAGES AND ASSOCIATED SITE

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 23 ACRES.

SOIL CHARACTERISTICS

BASED ON THE HIGH INTENSITY SOIL SURVEY PREPARED BY GOVE ENVIRONMENTAL SERVICES, INC. IN DECEMBER 2015, THE SITE SOILS VARY FROM WELL DRAINED TO VERY POORLY DRAINED AND PRIMARILY CONSIST OF SOMEWHAT POORLY DRAINED SOILS.

NAME OF RECEIVING WATERS

THE STORM WATER RUNOFF WILL ULTIMATELY DISCHARGE INTO HODGSON BROOK

CONSTRUCTION SEQUENCE OF MAJOR ACTIVITIES: CUT AND CLEAR TREES

- CONSTRUCT TEMPORARY AND PERMANENT SEDIMENT, EROSION AND DETENTION CONTROL FACILITIES. EROSION, SEDIMENT AND DETENTION MEASURES SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OPERATIONS THAT WILL INFLUENCE STORMWATER RUNOFF SUCH
 - NEW CONSTRUCTION
 - CONTROL OF DUST
 - NEARNESS OF CONSTRUCTION SITE TO RECEIVING WATERS
- CONSTRUCTION DURING LATE WINTER AND EARLY SPRING ALL PERMANENT DITCHES, SWALES, DETENTION, RETENTION AND SEDIMENTATION BASINS TO BE STABILIZED USING THE VEGETATIVE AND NON-STRUCTURAL BMPS PRIOR TO DIRECTING RUNOFF TO THEM.
- CLEAR AND DISPOSE OF DEBRIS
- CONSTRUCT TEMPORARY CULVERTS AND DIVERSION CHANNELS AS REQUIRED
- GRADE AND GRAVEL ROADWAYS AND PARKING AREAS ALL ROADS AND PARKING AREA SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
- BEGIN PERMANENT AND TEMPORARY SEEDING AND MULCHING. ALL CUT AND FILL SLOPES
- SHALL BE SEEDED AND MULCHED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. DAILY, OR AS REQUIRED, CONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, PERIMETER
- EROSION CONTROL MEASURES, SEDIMENT TRAPS, ETC., MULCH AND SEED AS REQUIRED. SEDIMENT TRAPS AND/OR BASINS SHALL BE USED AS NECESSARY TO CONTAIN RUNOFF UNTIL SOILS ARE STABILIZED.
- 0. FINISH PAVING ALL ROADWAYS AND PARKING LOTS.
- 11. INSPECT AND MAINTAIN ALL EROSION AND SEDIMENT CONTROL MEASURES.
- COMPLETE PERMANENT SEEDING AND LANDSCAPING.
- 3. REMOVE TRAPPED SEDIMENTS FROM COLLECTOR DEVICES AS APPROPRIATE AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES.

SPECIAL CONSTRUCTION NOTES:

- THE CONSTRUCTION SEQUENCE MUST LIMIT THE DURATION AND AREA OF DISTURBANCE. THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND
- INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

- ALL EROSION CONTROL MEASURES AND PRACTICES SHALL CONFORM TO THE "NEV HAMPSHIRE STORMWATER MANUAL VOLUME 3: EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION" PREPARED BY THE NHDES.
- PRIOR TO ANY WORK OR SOIL DISTURBANCE, CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR EROSION CONTROL MEASURES AS REQUIRED IN THE PROJECT MANUAL.
- CONTRACTOR SHALL INSTALL TEMPORARY EROSION CONTROL BARRIERS, INCLUDING HAY BALES, SILT FENCES, MULCH BERMS, SILT SACKS AND SILT SOCKS AS SHOWN IN THESE DRAWINGS AS THE FIRST ORDER OF WORK.
- SILT SACK INLET PROTECTION SHALL BE INSTALLED IN ALL EXISTING AND PROPOSED CATCH BASIN INLETS WITHIN THE WORK LIMITS AND BE MAINTAINED FOR THE DURATION OF THE PROJECT.

PERIMETER CONTROLS INCLUDING SILT FENCES, MULCH BERM, SILT SOCK, AND/OR HAY

- BALE BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT UNTIL NON-PAVED AREAS HAVE BEEN STABILIZED. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION
- CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION. ALL DISTURBED AREAS NOT OTHERWISE BEING TREATED SHALL RECEIVE 6" LOAM, SEED
- AND FERTILIZER. INSPECT ALL INLET PROTECTION AND PERIMETER CONTROLS WEEKLY AND AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS 1/3 THE FILTER
- CONSTRUCT EROSION CONTROL BLANKETS ON ALL SLOPES STEEPER THAN 3:1.

- AN AREA SHALL BE CONSIDERED STABLE WHEN ONE OF THE FOLLOWING HAS OCCURRED:
- A. BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED; B. A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED;
- C. A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED;
- D. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.; E. IN AREAS TO BE PAVED, "STABLE" MEANS THAT BASE COURSE GRAVELS MEETING THE REQUIREMENTS OF NHDOT STANDARD FOR ROAD AND BRIDGE CONSTRUCTION, 2016,
- ITEM 304.2 HAVE BEEN INSTALLED. WINTER STABILIZATION PRACTICES:
- A. ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE
- OF THAW OR SPRING MELT EVENTS; ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS
- AFTER NOVEMBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOW AFTER EACH STORM EVENT;
- STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES, AND DISTURBED AREAS, WHERE CONSTRUCTION ACTIVITY SHALL NOT OCCUR FOR MORE THAN TWENTY-ONE (21) CALENDAR DAYS BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR TEMPORARILY CEASED IN THAT AREA. STABILIZATION MEASURES TO BE **USED INCLUDE:**
- A. TEMPORARY SEEDING;
- B. MULCHING.

- 4. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
- WHEN CONSTRUCTION ACTIVITY PERMANENTLY OR TEMPORARILY CEASES WITHIN 100 FEET OF NEARBY SURFACE WATERS OR DELINEATED WETLANDS, THE AREA SHALL BE STABILIZED WITHIN SEVEN (7) DAYS OR PRIOR TO A RAIN EVENT. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN AN THESE AREAS, SILT FENCES, MULCH BERMS, HAY BALE BARRIERS AND ANY EARTH/DIKES SHALL BE REMOVED ONCE PERMANENT MEASURES ARE
- 6. DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STABILIZED CHANNELS WHERE POSSIBLE. SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILT FENCES, MULCH BERMS, HAY BALE BARRIERS, OR SILT SOCKS. ALL STORM DRAIN BASIN INLETS SHALL BE PROVIDED WITH FLARED END SECTIONS AND TRASH RACKS. THE SITE SHALL BE STABILIZED FOR THE WINTER BY NOVEMBER 15.

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST THROUGHOUT THE
- 2. DUST CONTROL METHODS SHALL INCLUDE, BUT BE NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY
- 3. DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ABUTTING AREAS.

- 1. LOCATE STOCKPILES A MINIMUM OF 50 FEET AWAY FROM CATCH BASINS, SWALES, AND
- 2. ALL STOCKPILES SHOULD BE SURROUNDED WITH TEMPORARY EROSION CONTROL
- MEASURES PRIOR TO THE ONSET OF PRECIPITATION. 3. PERIMETER BARRIERS SHOULD BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE
- INTEGRITY OF THE BARRIER SHOULD BE INSPECTED AT THE END OF EACH WORKING DAY. 4. PROTECT ALL STOCKPILES FROM STORMWATER RUN-OFF USING TEMPORARY EROSION CONTROL MEASURES SUCH AS BERMS, SILT SOCK, OR OTHER APPROVED PRACTICE TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.

1. THE CONTRACTOR SHALL CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE(S) PRIOR TO ANY EXCAVATION ACTIVITIES.

- TEMPORARY GRASS COVER A. SEEDBED PREPARATION:
 - a. APPLY FERTILIZER AT THE RATE OF 600 POUNDS PER ACRE OF 10-10-10. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF THREE (3) TONS PER ACRE;
- B. SEEDING: a. UTILIZE ANNUAL RYE GRASS AT A RATE OF 40 LBS/ACRE;
- b. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF TWO (2) INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED;
- c. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). HYDROSEEDINGS, WHICH INCLUDE MULCH, MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING
- C. MAINTENANCE:
- a. TEMPORARY SEEDING SHALL BE PERIODICALLY INSPECTED. AT A MINIMUM, 95% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND OTHER TEMPORARY MEASURES USED IN THE INTERIM (MULCH, FILTER BARRIERS, CHECK DAMS, ETC.).
- 2. VEGETATIVE PRACTICE:
- A. FOR PERMANENT MEASURES AND PLANTINGS:
- a. LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF THREE (3) TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5;
- b. FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 800 POUNDS PER ACRE OF 10-20-20 FERTILIZER;
- c. SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN, AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE REQUIRED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4-1/2 POUNDS AND 5-1/2 POUNDS PER INCH OF WIDTH;
- d. SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH;
- e. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AS INDICATED ABOVE;
- f. THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED, AND ALL NOXIOUS WEEDS REMOVED;
- q. THE CONTRACTOR SHALL PROTECT AND MAINTAIN THE SEEDED AREAS UNTIL ACCEPTED;
- h. A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE APPLIED AT THE INDICATED RATE:
 - APPLICATION RATE CREEPING RED FESCUE 20 LBS/ACRE TALL FESCUE 20 LBS/ACRE
- 2 LBS/ACRE REDTOP IN NO CASE SHALL THE WEED CONTENT EXCEED ONE (1) PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH STATE AND FEDERAL SEED LAWS. SEEDING SHALL BE DONE NO LATER THAN SEPTEMBER 15. IN NO CASE SHALL SEEDING TAKE PLACE OVER SNOW.
- 3. DORMANT SEEDING (SEPTEMBER 15 TO FIRST SNOWFALL): A. FOLLOW PERMANENT MEASURES SLOPE, LIME, FERTILIZER AND GRADING REQUIREMENTS. APPLY SEED MIXTURE AT TWICE THE INDICATED RATE. APPLY MULCH AS
- **CONCRETE WASHOUT AREA:**
- THE FOLLOWING ARE THE ONLY NON-STORMWATER DISCHARGES ALLOWED. ALL OTHER NON-STORMWATER DISCHARGES ARE PROHIBITED ON SITE:
- A. THE CONCRETE DELIVERY TRUCKS SHALL, WHENEVER POSSIBLE, USE WASHOUT FACILITIES AT THEIR OWN PLANT OR DISPATCH FACILITY; B. IF IT IS NECESSARY, SITE CONTRACTOR SHALL DESIGNATE SPECIFIC WASHOUT AREAS
- AND DESIGN FACILITIES TO HANDLE ANTICIPATED WASHOUT WATER; C. CONTRACTOR SHALL LOCATE WASHOUT AREAS AT LEAST 150 FEET AWAY FROM STORM
- DRAINS, SWALES AND SURFACE WATERS OR DELINEATED WETLANDS; D. INSPECT WASHOUT FACILITIES DAILY TO DETECT LEAKS OR TEARS AND TO IDENTIFY WHEN MATERIALS NEED TO BE REMOVED.

ALLOWABLE NON-STORMWATER DISCHARGES:

INDICATED FOR PERMANENT MEASURES.

- .. FIRE-FIGHTING ACTIVITIES;
- FIRE HYDRANT FLUSHING;
- 3. WATERS USED TO WASH VEHICLES WHERE DETERGENTS ARE NOT USED;

10. FOUNDATION OR FOOTING DRAINS WHICH ARE UNCONTAMINATED;

- WATER USED TO CONTROL DUST;
- POTABLE WATER INCLUDING UNCONTAMINATED WATER LINE FLUSHING; ROUTINE EXTERNAL BUILDING WASH DOWN WHERE DETERGENTS ARE NOT USED;
- 7. PAVEMENT WASH WATERS WHERE DETERGENTS ARE NOT USED;
- 8. UNCONTAMINATED AIR CONDITIONING/COMPRESSOR CONDENSATION; UNCONTAMINATED GROUND WATER OR SPRING WATER;
- 11. UNCONTAMINATED EXCAVATION DEWATERING;

12. LANDSCAPE IRRIGATION.

DEPOSITED IN A DUMPSTER;

- I. WASTE MATERIAL A. ALL WASTE MATERIALS SHALL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES, ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE SHALL BE
- B. NO CONSTRUCTION WASTE MATERIALS SHALL BE BURIED ON SITE; C. ALL PERSONNEL SHALL BE INSTRUCTED REGARDING THE CORRECT PROCEDURE FOR WASTE DISPOSAL BY THE SUPERINTENDENT.
- HAZARDOUS WASTE: A. ALL HAZARDOUS WASTE MATERIALS SHALL BE DISPOSED OF IN THE MANNER SPECIFIED
- BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER; B. SITE PERSONNEL SHALL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTENDENT
- SANITARY WASTE: A. ALL SANITARY WASTE SHALL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

- CONTRACTOR SHALL BE FAMILIAR WITH SPILL PREVENTION MEASURES REQUIRED BY LOCAL, STATE AND FEDERAL AGENCIES. AT A MINIMUM, CONTRACTOR SHALL FOLLOW THE BEST MANAGEMENT SPILL PREVENTION PRACTICES OUTLINED BELOW.
- 2. THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT SHALL BE USED TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING CONSTRUCTION TO STORMWATER RUNOFF:
- A. GOOD HOUSEKEEPING THE FOLLOWING GOOD HOUSEKEEPING PRACTICE SHALL BE FOLLOWED ON SITE DURING CONSTRUCTION:
- a. ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB SHALL BE STORED ON b. ALL MATERIALS STORED ON SITE SHALL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR PROPER (ORIGINAL IF POSSIBLE) CONTAINERS AND, IF POSSIBLE, UNDER A
- ROOF OR OTHER ENCLOSURE; c. MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL SHALL BE FOLLOWED;
- d. THE SITE SUPERINTENDENT SHALL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS
- e. SUBSTANCES SHALL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER
- WHENEVER POSSIBLE ALL OF A PRODUCT SHALL BE USED UP BEFORE DISPOSING OF
- HAZARDOUS PRODUCTS THE FOLLOWING PRACTICES SHALL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
- g. PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT
- h. ORIGINAL LABELS AND MATERIAL SAFETY DATA SHALL BE RETAINED FOR IMPORTANT PRODUCT INFORMATION; i. SURPLUS PRODUCT THAT MUST BE DISPOSED OF SHALL BE DISCARDED ACCORDING
- TO THE MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL C. PRODUCT SPECIFIC PRACTICES - THE FOLLOWING PRODUCT SPECIFIC PRACTICES SHALL
- BE FOLLOWED ON SITE: a. PETROLEUM PRODUCTS:

ALL ON SITE VEHICLES SHALL BE MONITORED FOR LEAKS AND RECEIVE REGULAR

- PREVENTIVE MAINTENANCE TO REDUCE LEAKAGE; PETROLEUM PRODUCTS SHALL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE SHALL BE APPLIED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS
- b. FERTILIZERS: FERTILIZERS USED SHALL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS;
- ONCE APPLIED FERTILIZER SHALL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO STORMWATER:
- STORAGE SHALL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER SHALL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.
- ALL CONTAINERS SHALL BE TIGHTLY SEALED AND STORED WHEN NOT REQUIRED
- EXCESS PAINT SHALL NOT BE DISCHARGED TO THE STORM SEWER SYSTEM • EXCESS PAINT SHALL BE DISPOSED OF PROPERLY ACCORDING TO MANUFACTURER'S INSTRUCTIONS OR STATE AND LOCAL REGULATIONS. D. SPILL CONTROL PRACTICES - IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL
- MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION, THE FOLLOWING PRACTICES SHALL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP: a. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP SHALL BE CLEARLY POSTED AND SITE PERSONNEL SHALL BE MADE AWARE OF THE PROCEDURES AND THE
- LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES; b. MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP SHALL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS SHALL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS, RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE;
- c. ALL SPILLS SHALL BE CLEANED UP IMMEDIATELY AFTER DISCOVERY; d. THE SPILL AREA SHALL BE KEPT WELL VENTILATED AND PERSONNEL SHALL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A
- e. SPILLS OF TOXIC OR HAZARDOUS MATERIAL SHALL BE REPORTED TO THE
- APPROPRIATE LOCAL, STATE OR FEDERAL AGENCIES AS REQUIRED; f. THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS SHALL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.
- E. VEHICLE FUELING AND MAINTENANCE PRACTICE: a. CONTRACTOR SHALL MAKE AN EFFORT TO PERFORM EQUIPTMENT/VEHICAL FUELING
- AND MAINTENANCE AT AN OFF-SITE FACILITY; b. CONTRACTOR SHALL PROVIDE AN ON-SITE FUELING AND MAINTENANCE AREA THAT IS
- c. IF POSSIBLE THE CONTRACTOR SHALL KEEP AREA COVERED;
- d. CONTRACTOR SHALL KEEP A SPILL KIT AT THE FUELING AND MAINTENANCE AREA;
- e. CONTRACTOR SHALL REGULARLY INSPECT VEHICLES FOR LEAKS AND DAMAGE; f. CONTRACTOR SHALL USE DRIP PANS, DRIP CLOTHS, OR ABSORBENT PADS WHEN

EROSION CONTROL OBSERVATIONS AND MAINTENANCE PRACTICES

HAZARDOUS SUBSTANCE;

REPLACING SPENT FLUID.

THIS PROJECT EXCEEDS ONE (1) ACRE OF DISTURBANCE AND THUS REQUIRES A SWPPP. THE SWPPP SHALL BE PREPARED BY THE CONTRACTOR. THE CONTRACTOR SHALL BE FAMILIAR WITH THE SWPPP AND KEEP AN UPDATED COPY OF THE SWPPP ONSITE AT ALL TIMES.

- THE FOLLOWING REPRESENTS THE GENERAL OBSERVATION AND REPORTING PRACTICES THAT SHALL BE FOLLOWED AS PART OF THIS PROJECT: 1. OBSERVATIONS OF THE PROJECT FOR COMPLIANCE WITH THE SWPPP SHALL BE MADE BY THE CONTRACTOR AT LEAST ONCE A WEEK OR WITHIN 24 HOURS OF A STORM 0.25 INCHES
- OR GREATER; 2. AN OBSERVATION REPORT SHALL BE MADE AFTER EACH OBSERVATION AND DISTRIBUTED TO THE ENGINEER, THE OWNER, AND THE CONTRACTOR;

3. A REPRESENTATIVE OF THE SITE CONTRACTOR, SHALL BE RESPONSIBLE FOR MAINTENANCE


AND REPAIR ACTIVITIES; 4. IF A REPAIR IS NECESSARY, IT SHALL BE INITIATED WITHIN 24 HOURS OF REPORT.

→ FLOW 7 + + + + - PERFORATED DIKE, IF RISER IF NECESSARY, WEIR OR -USING PIPE TO DIVERT EMBANKMENT IF OUTLET **USING STONE** FLOW INTO EXCAVATION FOR TRAP OUTLET OR PIPE REQUIRED STORAGE OUTLET 3:1 MAX. SLOPE SIDE SLOPES TO BE STABILIZED

THE TRAP SHALL BE INSTALLED AS CLOSE TO THE DISTURBED AREA AS POSSIBLE. THE MAXIMUM CONTRIBUTING AREA TO A SINGLE TRAP SHALL BE LESS THAN 5 ACRES. THE MINIMUM VOLUME OF THE TRAP SHALL BE 3,600 CUBIC FEET OF STORAGE FOR EACH


- ACRE OF DRAINAGE AREA. TRAP OUTLET SHALL BE MINIMUM OF ONE FOOT BELOW THE CREST OF THE TRAP. TRAP SHALL DISCHARGE TO A STABILIZED AREA.
 - TRAP SHALL BE CLEANED WHEN 50 PERCENT OF THE ORIGINAL VOLUME IS FILLED. MATERIALS REMOVED FROM THE TRAP SHALL BE PROPERLY DISPOSED OF AND STABILIZED.

SEDIMENT TRAP NO SCALE




1. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OF SEDIMENT FROM THE SITE. WHEN WASHING IS REQUIRED, IT SHALL BE DONE SO RUNOFF DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING STORM DRAINS, DITCHES, OR WATERWAYS

STABILIZED CONSTRUCTION ENTRANCE



SILT SOCK NO SCALE

WITH...



Proposea **Industrial** Development

Lonza Biologics

Portsmouth, New Hampshire


D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION

L-0700-013 04/03/2018 NAH


EROSION CONTROL NOTES


AS SHOWN

SCALE:



ROJECT NO: FILE: L0700-CD-501 to C-508.dwg DRAWN BY CHECKED: PMC APPROVED: BLM





TYPICAL PARKING EQUIPMENT DETAILS


CONST. R7-8 & R7-8b SIGNS 4' HANDICAP GRAPHIC -(SEE SITE PLAN & SIGN LEGEND SYMBOL (SEE DETAIL) AND SIGN POST DETAIL) SYMBOL TO BE INSTALLED— 4" WIDE PAINTED ON BLUE NON-SKID WHITE LINES (TYP) BACKGROUND PAINTED ISLAND TYPICAL SPACE HANDICAP SPACE 8' MIN. VAN ACCESSIBLE


1. ALL PAINT SHALL BE FAST DRYING TRAFFIC PAINT, MEETING THE REQUIREMENTS OF AASHTO M248-TYPE F. PAINT SHALL BE APPLIED AS SPECIFIED BY MANUFACTURER.

2. SYMBOLS & PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT AND LOCAL AND STATE REQUIREMENTS. 3. FINISH PAVEMENT GRADES AT ALL HANDICAP ACCESSIBLE STALLS AND PAINTED

ACCESS AISLES SHALL NOT EXCEED 2% IN ANY DIRECTION.


STALL STRIPING-SINGLE STRIPE NO SCALE





Proposed **Industrial Development**

Lonza Biologics



-WEED BARRIER FABRIC (MIRAFI

←3" BARK MULCH

MIRASCAPE OR APPROVED EQUAL)

DO NOT ENTER R5-1 30"X30" WHITE ON RED

RESERVED PARKING R7-8 12"X18"

BLUE AND GREEN ON WHITE

EMERGENCY AND AUTHORIZED VEHICLES ONLY 12"X18" **BLACK ON**

WHITE LENGTH: AS REQUIRED WEIGHT PER LINEAR FOOT: 2.50 LBS (MIN.)

AN APPROVED MEDIUM GREEN BAKED ON OR ALL FABRICATION SHALL BE COMPLETE BEFORE PAINTING.

STEEL: SHALL CONFORM TO ASTM A-499 (GRADE

HOLES: 3/8" DIAMETER, 1" C-C FULL LENGTH

60) OR ASSTM A-576 (GRADE 1070 - 1080) FINISH: SHALL BE PAINTED WITH TWO COATS OF DRIED, PAINT OF WEATHER RESISTANT QUALITY. ALL SIGNS TO BE INSTALLED AS INDICATED IN THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.

> SIGN LEGEND & SIGN POST NO SCALE

ACCESSIBLE

R7-8A

6"X12"

BLUE AND

GREEN ON

WHITE


R1-1

30"X30"


WHITE ON RED

3-1/8"

SECTION A-A



-BARK MULCH 3" ABOVE CURB (ON WEED BARRIER FABRIC) DON NOT PLACE ANY BARK MULCH AGAINS THE SHRUB TRUNK _3" BARK MULCH ON WEED BARRIER FABRIC (MIRAFI MIRASCAPE OR APPROVED EQUAL) -PLANTING SOIL MIX: DECIDUOUS- FOUR PARTS TOPSOIL & ONE PART MANURE PLANTING SOIL MIX-**EVERGREEN- FOUR PARTS** TO TOP OF CURB TOPSOIL & ONE PART PEAT HUMUS -WIDTH OF PIT SHALL BE 3 TIMES THE WIDTH OF ROOT BALL (5' MIN IN LEDGE)(SCARIFY AND CURB-\ SLOPE SIDES OF PIT) BITUMINOUS-CONCRETE **PAVEMENT** SUBGRADE 6" MIN. IN EARTH UNTIE BURLAP & ROLL 18" MIN. IN LEDGE BACK 1/3 OF ROOT BALL. IF PLASTIC TAMPED PLANTING MIX-BURLAP IS USED, CONTAINER GROWN NURSERY DUG REMOVE COMPLTELY BALL & BURLAP REMOVE CONTAINER CURBED ISLAND → LAWN CONDITION CONDITION SHRUB PLANTING PLANT AT SAME DEPTH AS PREVIOUSLY PLANTED, OR NO SCALE WITHIN 2" ABOVE.



DECIDUOUS TREE PLANTING

PLANT AT SAME DEPTH AS PREVIOUSLY PLANTED OR WITHIN 2" ABOVE.

NO SCALE

—3" BARK MULCH ON WEED BARK MULCH 3" ABOVE— BARRIER FABRIC (MIRAFI CURB (ON WEED MIRASCAPE OR APPROVED BARRIER FABRIC) DO EQUAL) NOT PLACE ANY BARK MULCH AGAINST TREE —WIDTH OF PIT SHALL TRUNK BE 3 TIMES WIDTH OF ROOT BALL (10' MIN IN LEDGE)(SCARIFY AND SLOPE SIDES OF PIT) PLANTING SOIL MIX— PLANTING SOIL TO TOP OF CURB MIX - FOUR PARTS TOP SOIL & ONE PART PEAT HUMUS BITUMINOUS-CONCRETE -3" EARTH PAVEMENT SAUCER 12" MIN. IN EARTH 24" MIN. IN LEDGE -TAMPED PLANTING MIX EXISTING SUBGRADE— -UNTIE BURLAP & ROLL BACK FROM TOP 1/3 OF ROOT BALL. IF PLASTIC BURLAP IS USED, REMOVE COMPLETELY.

CURBED ISLAND CONDITION - LAWN CONDITION

PLANT AT SAME DEPTH AS PREVIOUSLY PLANTED IN NURSERY, OR WITHIN 2" ABOVE.

> EVERGREEN TREE PLANTING NO SCALE

Portsmouth,


SCALE:

New Hampshire

D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJECT NO:		L-0700-013
DATE:		04/03/2018
FILE: L0700-CD-501 to C-508.dwg		
DRAWN BY:		NAH
CHECKED:		PMC
APPROVED:		BLM

DETAILS SHEET


AS SHOWN




- ALL SECTIONS SHALL BE CONCRETE CLASS AA(4000 psi).
- CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQ.IN. PER LINEAR FT. IN ALL SECTIONS AND SHALL
- BE PLACED IN THE CENTER THIRD OF THE WALL. THE TONGUE AND GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL
- REINFORCEMENT EQUAL TO 0.12 SQ. IN. PER LINEAR FT. RISERS OF 1', 2', 3' & 4' CAN BE USED TO REACH DESIRED DEPTH
- THE STRUCTURES SHALL BE DESIGNED FOR H20 LOADING.
- FITTING FRAME TO GRADE MAY BE DONE WITH PREFABRICATED ADJUSTMENT RINGS OR CLAY BRICKS (2
- CONE SECTIONS MAY BE EITHER CONCENTRIC OR ECCENTRIC, OR FLAT SLAB TOPS MAY BE USED WHERE PIPE WOULD OTHERWISE ENTER INTO THE CONE SECTION OF THE STRUCTURE AND WHERE PERMITTED.
- PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING. OUTSIDE EDGES OF PIPES SHALL PROJECT NO MORE THAN 3" BEYOND INSIDE WALL OF STRUCTURE.
- 10. PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS. 11. THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.

4' DIAMETER CATCHBASIN

12. "ELIMINATOR" OIL/WATER SEPARATOR SHALL BE INSTALLED TIGHT TO INSIDE OF CATCHBASIN.



THE STONE SHALL BE COMPOSED OF A WELL-GRADED MIXTURE DOWN TO THE ONE-INCH THE D50 SIZE SPECIFIED. A WELL-GRADED MIXTURE IS DEFINED AS A MIXTURE COMPOSED PRIMARILY OF THE LARGER STONE SIZE BUT WITH A SUFFICIENT MIXTURE OF OTHER SIZES LARGEST STONE SIZE IN SUCH A MIXTURE SHALL BE 1.5 TIMES THE D50 SIZE.



NOTES:

- 1. ALL SECTIONS SHALL BE 4,000 PSI CONCRETE.
- 2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
- 3. THE TONGUE AND THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL
- REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.

<u>PLAN</u>

10"

10"

15"

18"

12"

25"

6.5"

6.5"

6.5"

6.5"

8.6"

8.6"

25"

25"

32"

36"

58"

58"

29"

29"

35"

45"

63"

63"

DIA.

12"

15"

18"

24"

30"

36"

6.5"

6.5"

7.5"

7.5"

7.5"

7.5"

- 4. THE STRUCTURES SHALL BE DESIGNED FOR H20 LOADING.
- CONSTRUCT CRUSHED STONE BEDDING AND BACKFILL UNDER (6" MINIMUM THICKNESS)
- THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.
- 7. PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING. 8. OUTSIDE EDGES OF PIPES SHALL PROJECT NO MORE THAN 3" BEYOND INSIDE WALL OF STRUCTURE.
- 9. PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS.
- 10. ALL STRUCTURES WITH MULTIPLE PIPES SHALL HAVE A MINIMUM OF 12" OF INSIDE SURFACE BETWEEN HOLES, NO MORE THAN 75% OF A HORIZNTAL CROSS SECTION SHALL BE HOLES, AND THERE SHALL BE NO HOLES CLOSER THAN 3" TO JOINTS.

4' DIAMETER DRAIN MANHOLE NO SCALE

SPACERS

-POLYETHYLENE THREADED ROD WITH WING NUTS AND




PLATE /

TOE PLATE

END SECTIONS MANUFACTURED BY

COLUMBUS, OHIO. END SECTIONS TO BE

WELDED TO PIPE AS PER MANUFACTURER'S

ADVANCED DRAINAGE SYSTEMS,


HDPE END SECTION

NO SCALE

RECOMMENDATIONS.

SECTION A-A

ELEVATION




- 1. ALL CATCH BASIN OUTLETS TO HAVE "ELIMINATOR" OIL AND FLOATING DEBRIS TRAP MANUFACTURED BY
- KLEANSTREAM (NO EQUAL) INSTALL DEBRIS TRAP TIGHT TO INSIDE OF STRUCTURE.

3. 1/4" HOLE SHALL BE DRILLED IN

TOP OF DEBRIS TRAP

"ELIMINATOR" OIL FLOATING DEBRIS TRAP

NO SCALE



-SQUARE

FRAME **BLOCKS**

> 1. CRUSHED STONE BEDDING AND BACKFILL FOR FULL WIDTH OF THE TRENCH FROM 6" BELOW PIPE IN EARTH AND 12" BELOW PIPE IN ROCK UP TO 6" ABOVE TOP OF PIPE.

2. ALL UTILITIES SHALL BE INSTALLED PER THE INDIVIDUAL UTILITY COMPANY STANDARDS. COORDINATE ALL INSTALLATIONS WITH INDIVIDUAL UTILITY COMPANIES AND THE CITY OF PORTSMOUTH.

> STORM DRAIN TRENCH NO SCALE

-WATER MAIN, SIZE VARIES (TYP.) CONCRETE THRUST BLOCK (TYP.) UNDISTURBED-EARTH (TYP.)

TEST PRESSURE = 200psi	SQUARE FEET OF CONCRETE THRUST BLOCKING BEARING ON UNDISTURBED MATERIAL					
	REACTION	EACTION PIPE SIZE				
	TYPE	4"	6"	8"	10"	12"
	A 90°	0.89	2.19	3.82	11.14	17.24
	В 180°	0.65	1.55	2.78	8.38	12.00
	C 45°	0.48	1.19	2.12	6.02	9.32
	D 22-1/2°	0.25	0.60	1.06	3.08	4.74
	E 11-1/4°	0.13	0.30	0.54	1.54	2.38

- 1. POUR THRUST BLOCKS AGAINST UNDISTURBED MATERIAL, WHERE TRENCH WALL HAS BEEN DISTURBED, EXCAVATE LOOSE MATERIAL AND EXTEND THRUST BLOCK TO UNDISTURBED MATERIAL. NO JOINTS SHALL BE COVERED WITH CONCRETE.
- 2. ON BENDS AND TEES, EXTEND THRUST BLOCKS FULL LENGTH OF FITTING.
- 3. PLACE BOARD IN FRONT OF ALL PLUGS BEFORE POURING THRUST BLOCKS.
- 4. WHERE M.J. PIPE IS USED, M.J. PLUG WITH RETAINER GLAND MAY BE SUBSTITUTED FOR END BLOCKINGS. 5. INSTALLATION AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE WITH TOWN OF EXETER WATER DEPARTMENT STANDARDS.

THRUST BLOCKING DETAIL

NO SCALE

Proposed **Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

D	8/21/2018	REVISED TAC SUBMISSION	
С	6/18/2018	NHDES AOT SUBMISSION	
В	5/21/2018	TAC SUBMISSION	
Α	4/3/2018	TAC WS SUBMISSION	
MARK	DATE	DESCRIPTION	

L-0700-013 PROJECT NO: 04/03/2018 FILE: L0700-CD-501 to C-508.dwg DRAWN BY NAH CHECKED: PMC


DETAILS SHEETS

BLM

APPROVED:


SCALE: AS SHOWN

C-504



SIZE PARTICLE SUCH THAT 50 PERCENT OF THE MIXTURE BY WEIGHT SHALL BE LARGER THAN TO FILL THE PROGRESSIVELY SMALLER VOIDS BETWEEN THE STONES. THE DIAMETER OF THE


RIP-RAP APRON DETAIL





<u>IOTES:</u>

- 1. INVERT AND SHELF TO BE PLACED AFTER EACH LEAKAGE TEST.
- 2. CARE SHALL BE TAKEN TO INSURE THAT THE BRICK INVERT IS A SMOOTH CONTINUATION OF THE SEWER INVERT.
- 3. INVERT BRICKS SHALL BE LAID ON EDGE.
- 4. BITUMINOUS WATERPROOF COATING TO BE APPLIED TO ENTIRE EXTERIOR OF MANHOLE.
 5. FRAMES AND COVERS: MANHOLE FRAMES AND COVERS WITHIN CITY RIGHT OF WAY SHALL BE CITY STANDARD HINGE COVERS
- MANUFACTURED BY EJ. FRAMES AND COVERS WILL BE PURCHASED FROM THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS. ALL OTHER MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A 30-INCH CLEAR OPENING. A 3-INCH (MINIMUM HEIGHT) WORD "SEWER" SHALL BE PLAINLY CAST INTO THE CENTER OF EACH COVER.
- 6. HORIZONTAL JOINTS SHALL BE SEALED FOR WATER TIGHTNESS USING A DOUBLE ROW OF ELASTOMERIC OR MASTIC-LIKE SEALANT.7. BARREL AND CONE SECTIONS SHALL BE PRECAST REINFORCED CONCRETE DESIGNED FOR H20 LOADING, AND CONFORMING TO ASTM C478-06.

SEWER MANHOLE NO SCALE








TYPICAL SEWER TRENCH



Lonza Biologics

Portsmouth,

New Hampshire



NO SCALE

D 8/21/2018 REVISED TAC SUBMISSION
C 6/18/2018 NHDES AOT SUBMISSION
B 5/21/2018 TAC SUBMISSION
A 4/3/2018 TAC WS SUBMISSION

 A
 4/3/2018
 TAC WS SUBMISSION

 MARK
 DATE
 DESCRIPTION

 PROJECT NO:
 L-0700-013

 DATE:
 04/03/2018

 FILE:
 L0700-CD-501 to C-508.dwg

 DRAWN BY:
 NAH

CHECKED:

APPROVED:

DETAILS SHEETS

PMC

BLM

SCALE: AS SHOWN

C-505

MANUFACTURERS' WRITTEN INSTRUCTIONS.

MANHOLE JOINTS


NO SCALE

3. FOR BITUMASTIC TYPE JOINTS THE AMOUNT OF SEALANT SHALL BE SUFFICIENT TO FILL AT

4. ALL GASKETS, SEALANTS, MORTAR, ETC. SHALL BE INSTALLED IN ACCORDANCE WITH

PIPE TO MANHOLE JOINTS SHALL BE PER TOWN OF EXETER STANDARD.

LEAST 75% OF THE JOINT CAVITY.




PIPE IN EARTH AND 12" BELOW PIPE IN ROCK UP TO 12" ABOVE TOP OF PIPE.


GAS TRENCH

NO SCALE

2. GAS SHALL BE INSTALLED PER UNITIL STANDARDS. COORDINATE ALL

INSTALLATIONS WITH UNITIL AND THE CITY OF PORTSMOUTH.






NOTE:


1. SAND BEDDING AND BACKFILL FOR FULL WIDTH OF THE TRENCH FROM 6" BELOW PIPE IN EARTH AND 12" BELOW PIPE IN ROCK UP TO 12" ABOVE TOP OF PIPE.

2. WATER MAIN SHALL BE INSTALLED PER CITY OF PORTSMOUTH STANDARDS.

COORDINATE ALL INSTALLATIONS WITH THE CITY OF PORTSMOUTH.

WATER TRENCH NO SCALE





NOTES:


- 1. NUMBER, MATERIAL, AND SIZE OF UTILITY CONDUITS TO BE DETERMINED BY LOCAL UTILITY OR AS SHOWN ON ELECTRICAL DRAWINGS. CONTRACTOR TO PROVIDE ONE SPARE CONDUIT FOR EACH UTILITY TO BUILDING.
- 2. DIMENSIONS SHOWN REPRESENT OWNERS MINIMUM REQUIREMENTS. ACTUAL DIMENSIONS MAY BE GREATER BASED ON UTILITY COMPANY STANDARDS, BUT SHALL NOT BE LESS THAN THOSE SHOWN.
- NO CONDUIT RUN SHALL EXCEED 360 DEGREES IN TOTAL BENDS.
 A SUITABLE PULLING STRING, CAPABLE OF 200 POUNDS OF PULL, MUST BE INSTALLED IN THE CONDUIT BEFORE UTILITY COMPANY IS NOTIFIED TO INSTALL CABLE. THE STRING SHOULD BE BLOWN INTO THE
- 5. UTILITY COMPANY MUST BE GIVEN THE OPPORTUNITY TO INSPECT THE CONDUIT PRIOR TO BACKFILL. THE CONTRACTOR IS RESPONSIBLE FOR ALL REPAIRS SHOULD THE UTILITY COMPANY BE UNABLE TO INSTALL ITS CABLE IN A SUITABLE MANNER.


CONDUIT AFTER THE RUN IS ASSEMBLED TO AVOID BONDING THE STRING TO THE CONDUIT.

- 6. ALL CONDUIT INSTALLATIONS MUST CONFORM TO THE CURRENT EDITION OF THE NATIONAL ELECTRIC SAFETY CODE, STATE AND LOCAL CODES AND ORDINANCES, AND, WHERE APPLICABLE, THE NATIONAL ELECTRIC CODE
- 7. ALL 90° SWEEPS WILL BE MADE USING RIGID GALVANIZED STEEL. SWEEPS WITH A 36 TO 48 INCH
- SAND BEDDING TO BE REPLACED WITH CONCRETE ENCASEMENT WHERE COVER IS LESS THAN 3 FEET, WHEN LOCATED BELOW PAVEMENT, OR WHERE SHOWN ON THE UTILITIES PLAN.

ELECTRICAL AND COMMUNICATION CONDUIT

NO SCALE





NOTES:


1. DIMENSIONS SHOWN REPRESENT TYPICAL REQUIREMENTS.
MANHOLE LOCATIONS AND REQUIREMENTS SHALL BE
COORDINATED WITH EVERSOURCE PRIOR TO CONSTRUCTION
2. CONCRETE MINIMUM STRENGTH - 5,000 PSI @ 28 DAYS
3. STEEL REINFORCEMENT - ASTM A615, GRADE 60, 1" MIN. COVER
4. DESIGNED FOR HS20-44 LOADING

SWITCH GEAR PAD AND MANHOLE

NO SCALE

5. EXTERIOR COATING PROVIDED





Proposed Industrial Development

Lonza Biologics

Portsmouth, New Hampshire

D	8/21/2018	REVISED TAC SUBMISSION	
С	6/18/2018	NHDES AOT SUBMISSION	
В	5/21/2018	TAC SUBMISSION	
Α	4/3/2018	TAC WS SUBMISSION	
MARK DATE		DESCRIPTION	
PROJECT NO:		L-0700-013	

PROJECT NO: L-0700-013

DATE: 04/03/2018

FILE: L0700-CD-501 to C-508.dwg

DRAWN BY: NAH


CHECKED: PMC


BLM


DETAILS SHEETS


SCALE: AS SHOWN

APPROVED:









Proposed **Industrial Development**

Lonza Biologics

Portsmouth, New Hampshire

	- COORDINATE WITH UNH STORMWATER			
	CENTER FOR FURTHER VEGETATION MANAGEMENT GUIDELINES			
		D	8/21/2018	REVISED TAC SUBMISSION
	- HIRE QUALIFIED PROFESSIONAL TO ASSESS THE CONDITION OF THE FACILITY TO DETERMINE MEASURES REQUIRED TO RESTORE THE FILTRATION FUNCTION, INCLUDING BUT NOT LIMITED TO REMOVAL OF ACCUMULATED SEDIMENTS OR	С	6/18/2018	NHDES AOT SUBMISSION
		В	5/21/2018	TAC SUBMISSION
		Α	4/3/2018	TAC WS SUBMISSION
	RECONSTRUCTION OF THE FILTER.		DATE	DESCRIPTION
		PROJE	CT NO:	L-0700-013
		DATE:		04/03/2018

FILE: L0700-CD-501 to C-508.dwg

NAH

PMC

BLM

AS SHOWN

DRAWN BY:

HECKED:

PPROVED:

SCALE:

GRATE IN BELL OF PIPE

8'-10' ON CENTER

TRASH AND DEBRIS TO BE REMOVED

ANY REQUIRED MAINTENANCE SHALL BE

INSPECT SOIL AND REPAIR ERODED AREAS,

CHECK INLETS, OUTLETS, AND OVERFLOW

INSPECT THE CONDITION OF ALL GRAVEL

SPILLWAY FOR BLOCKAGE, STRUCTURAL

INTEGRITY AND EVIDENCE OF EROSION.

2'-3'

GRAVEL WETLAND INSPECTION / MAINTENANCE REQUIREMENTS

ADDRESSED

SPECIALLY ON SLOPES.

WETLAND VEGETATION

PRUNE BACK OVERGROWTH

REPLACE DEAD VEGETATION

REMOVE ANY INVASIVE SPECIES

FREQUENCY

FOUR (4) TIMES

ANY RAINFALL

ANNUALLY

EXCEEDING 2.5" IN

A 24-HR PERIOD

1. 8" GRAVEL WETLAND GRATES SHALL NEENAH R-4350-1 GRATE OR EQUAL

NEENAH R-4350 SERIES GRATE

CLETHERA ALNIFOLIA

"SILKY DOGWOOD"

CORNUS AMMOMUM

"HIGHBUSH BLUEBERRY"

"HERITAGE RIVER BIRCH"

BETULA NIGRA "HERITAGE"

MONITOR TO ENSURE ANNUALLY (QUARTE

THAT GRAVEL WETLAND RLY) AND AFTER

INSPECT VEGETATION ANNUALLY

FUNCTIONS

STORMS

EFFECTIVELY AFTER

INSPECT DRAWDOWN

THE SYSTEM SHALL


48-HOURS FOLLOWING

DRAWDOWN WITHIN

A RAINFALL EVENT.

VACCINUM CORYBOSSUSUM

DETAILS SHEETS




NOTES: 1. CORE MATERIAL SHALL MEET USGS CLASSIFICATION SC, SM, CL OR ML AND HAVE A MAXIMUM PARTICLE SIZE OF 3" AND A PERMEABILITY LESS THAN 0.000005 CM/S, AND MEET THE FOLLOWING GRADATION


PERCENT FINER BY WEIGHT SIEVE SIZE 3 INCH 100

No. 200 50 -100.

2. PIPE SHALL BE FULLY EMBEDDED IN CORE TO ELIMINATE SEEPAGE

CLAY CORE BERM NO SCALE






NO SCALE

NOTE: SEE GRADING, DRAINAGE & EROSION CONTROL PLANS, SHEET C-110, FOR LOCATIONS AND ELEVATIONS. RIPRAP OVERFLOW SPILLWAY

	RAINGARDEN PLANT SCHEDULE				
CODE	BOTANICAL NAME	COMMON NAME	SIZE	REMARKS	
TREES					
BN	BETULA NIGRA	RIVER BIRCH	12 - 14' HT	B & B (CLUMP)	
AC	AMALANCHIER CANADENSIS	SHADBLOW SERVICEBERRY	6 - 7' HT	B & B (CLUMP)	
SHRUBS	SHRUBS				
VD	VIBURNUM DENTATUM	ARROWWOOD VIBURNUM	5 GALLON	CONTAINER	
CA	CLETHERA ALNIFOLIA	SUMMERSWEET CLETHERA	5 GALLON	CONTAINER	
PERENN	PERENNIALS				
PV	PANICUM VIRGATUM 'SHENANDOAH'	SHENANDOAH SWITCH GRASS	3 GALLON	CONTAINER	
EM	EUPATORIUM MACULATUM	JOE PYE WEED	2 GALLON	CONTAINER	
AI	ASCLEPIAS INCARNATA	MARSH MILKWEED	2 GALLON	CONTAINER	
RG	RUDBECKIA 'GOLDSTURM'	GOLDSTURM BLACKEYED SUSAN	1 GALLON	CONTAINER	
EP	ECHINACEA 'PURPUREA'	PURPLE CONEFLOWER	1 GALLON	CONTAINER	




	FILTER MEDIA COMPOSIT	TON:	
COMPONENT MATERIAL	PERCENT OF MIXTURE	<u>GRADATI</u>	ON OF MATERIAL
	BY VOLUME	SIEVE NO.	PERCENT PASSING
ASTM C-33 CONCRETE SAND	50-55	SEE N	OTE #5
LOAMY SAND TOPSOIL	20-30	200	15-25
MODERATELY FINE SHREDDED	20-30	200	5 MAX.
BARK OR WOOD FIBER MULCH			

- 1. RAIN GARDENS SHALL NOT BE PLACED INTO SERVICE UNTIL THE PRACTICE HAS BEEN PLANTED AND ITS CONTRIBUTING AREAS HAVE BEEN FULLY STABILIZED.
- 2. DO NOT TRAFFIC EXPOSED SOIL SURFACES WITH CONSTRUCTION EQUIPMENT. CONTRACTOR SHALL KEEP ALL EXCAVATION EQUIPMENT OUTSIDE OF THE LIMIT OF THE RAIN GARDEN.
- SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR LOCATIONS, LAYOUTS, AND ELEVATIONS.
 THE SAND PORTION OF THE FILTER MEDIA SHALL MEET THE FOLLOWING GRADATION (ASTM C-33):
 SIEVE SIZE PERCENT PASSING

3/8" 100	
5/0	
#4 95-100	
#8 80-100	
#16 50-85	
#30 25-60	
<i>#</i> 50 5-30	
#100 0-10	

RAIN GARDEN NO SCALE



Proposed Industrial Development

Lonza Biologics

Portsmouth, New Hampshire

D	8/21/2018	REVISED TAC SUBMISSION	
С	6/18/2018	NHDES AOT SUBMISSION	
В	5/21/2018	TAC SUBMISSION	
Α	4/3/2018	TAC WS SUBMISSION	
MARK	DATE	DESCRIPTION	
PROJECT NO: L-0700-013			
DATE: 04/03/2018			
FILE: L0700-CD-501 to C-508.dwg			

CHECKED: PMC APPROVED: BLM


AS SHOWN


DETAILS SHEETS

NAH

DRAWN BY:

SCALE:





PROPOSED LOG VANE

CONSTRUCT

CONST

CONSTRUCTION SEQUENCE:


THIS STREAM RESTORATION IS A PART OF A LARGER DEVELOPMENT PROJECT AS A WHOLE, THE CONSTRUCTION SEQUENCE BELOW DETAILS ONLY ACTIVITIES PERTAINING TO THE STREAM CORRIDOR. IT DOES NOT INCLUDE ACTIVITIES THAT MIGHT USUALLY BE INCLUDED IN SUCH A SEQUENCE, SUCH AS (BUT NOT LIMITED TO) CLEARING AND GRUBBING, CONSTRUCTION LAYOUT, TRAFFIC CONTROL, EROSION CONTROL, AND MATERIAL DISPOSAL. THE SEQUENCE IS SUBJECT TO CHANGE TO INTEGRATE FLUIDLY WITH THE ENTIRE PROJECT, AND MAY CHANGE TO THE DESIRES OF THE CONTRACTOR, AS THEY SEE BEST FIT. CONTRACTOR SHALL SUBMIT A DETAILED CONSTRUCTION SEQUENCE PRIOR TO CONSTRUCTION TO BE REVIEWED AND APPROVED BY THE DESIGN ENGINEER. THIS CONSTRUCTION SEQUENCE ASSUMES THAT THE EXISTING DRAINAGE INFRASTRUCTURE IS TO REMAIN IN PLACE UNTIL THE STREAM IS BUILT.

STREAM CORRIDOR CONSTRUCTION SEQUENCE:

- 1. EXCAVATE AND GRADE THE STREAM CORRIDOR, FROM THE TOP OF THE VALLEY, DOWN TO THE TOP OF THE FLOODPLAIN AND INTO THE CENTER OF THE CORRIDOR, LEAVING AN ACCESS RAMP AT THE START AND END OF THE PROJECT. IF REQUIRED, THE GRADE MAY BE SET LOWER TO ALLOW FOR BACKFILLING OF LOAM, SHOULD THE EXISTING EARTH BE OF POOR MATERIAL. DO NOT OVER-COMPACT FLOODPLAIN OR VALLEY SLOPES; COMPACT ONLY BY TRACK-WALKING OR APPLYING PRESSURE WITH THE BUCKET OF THE EXCAVATOR. THE FLOODPLAIN AND SLOPES SHOULD BE LEFT ROUGH, TO ALLOW SEED TO GROW MORE EASILY. LEAVE AN ACCESS PATH ALONG THE TOP OF THE VALLEY TO ONE OR BOTH SIDES, TO ALLOW FOR THE TRANSPORT AND TEMPORARY STAGING OF IN- STREAM MATERIALS AND MOVEMENT OF HEAVY EQUIPMENT. THIS MAY ALSO BE DONE BY USING THE UPSTREAM ACCESS RAMP TO DELIVER MATERIALS BEHIND THE EXCAVATOR, USING THE CORRIDOR AS THE PATH. THIS IS NOT PREFERRED, SINCE OVER-COMPACTION IS LIKELY TO OCCUR RESULTING FROM THE EXCESSIVE USE.
- 2.BECAUSE THE CONSTRUCTION WILL BE PERFORMED IN THE DRY, CONSTRUCTION WILL START AT THE DOWNSTREAM END OF THE RESTORED HODGSON BROOK. STARTING AT THE DOWNSTREAM END OF THE STREAM, BEGIN BY EXCAVATING THE POOL WHICH WILL REDIRECT WATER INTO THE EXISTING CULVERTS BELOW GOOSE BAY DRIVE FROM UPSTREAM OF THE POOL. WORKING FROM UPSTREAM OF THE SECTION UNDER CONSTRUCTION, BEGIN THE FINE GRADING OF THE STREAM CHANNEL. THIS MAY BE DONE BY OVER-EXCAVATING THE CHANNEL AND BANKS, THEN INSTALLING THE COMPOST LOG ROLL STREAM BANKS. INITIALLY THE BED SLOPE OF THE STREAM IS GRADED UNIFORM, AND THEN RIFFLES AND POOLS GRADED NEAR THE FINISHING STEPS. THE LOWER COMPOST LOG SHOULD SIT BELOW THE THALWEG OF THE STREAM, AND ONCE SET IN PLACE AT THE CORRECT ELEVATION, MAY HAVE FILL PLACED BEHIND THE ROLLS. THE STREAM CHANNEL SHOULD THEN BE BACKFILLED AT THE RIFFLES AND POOLS WITH APPROPRIATELY GRADED MATERIAL, LEAVING THE POOLS AS DEEPER FEATURES IN THE STREAM CHANNEL. AS CONSTRUCTION CONTINUES UPSTREAM, MERGING THE COMPOST LOG ROLLS SHOULD BE DONE SUCH THAT THE UPSTREAM-MOST END OF THE ROLLS IS CURLED OUT FROM THE BANK, SUCH THAT THE NEXT UPSTREAM ROLLS MAY BE PLACED LINEARLY INTO THE BANK, AND FLOWS WILL BE DIRECTED AS TO NOT CAUSE EROSION OR AVULSION BETWEEN THE ROLLS (SHIPLAPPED CONSTRUCTION). EXTRA HEAVY ATTACHMENT (CONNECTIONS) OF THE ROLLS AT THESE LOCATIONS SHOULD BE PERFORMED WITH BIODEGRADABLE MATERIALS. WHILE CONSTRUCTION CONTINUES, BACKFILLING OF ANY FLOODPLAIN LOAM - SHOULD IT BE DEEMED NECESSARY - SHOULD BE PERFORMED TO THE FINAL GRADE OF THE FLOODPLAIN. CONSTRUCT IN-STREAM STRUCTURES (LOG CROSS VANES) AS THEY ARE REACHED, AS WELL AS FLOODPLAIN SILLS. ADDITIONAL FLOODPLAIN FEATURES MAY BE CONSTRUCTED AT THIS TIME, SUCH AS HABITAT LOGS AND BOULDERS, TREE STANDS, AND VERNAL POOLS (ALL OPTIONAL, BUT RECOMMENDED). CONSTRUCTION MATERIALS MAY BE PROVIDED ON-DEMAND USING THE ACCESS PATH ALONG THE TOP OF THE VALLEY. MATERIALS (LOGS, REBAR, GEOTEXTILE, RIFFLE MATERIAL, COMPOST ROLLS, ETC.) MAY BE SET OUTSIDE THE STREAM CORRIDOR, AND GATHERED BY THE EXCAVATOR FROM INSIDE THE CORRIDOR, OR LESS PREFERABLY, PLACED BEHIND THE EXCAVATOR IN THE CORRIDOR. ALL FINE GRADING AND STRUCTURES SHOULD BE CHECKED FOR ELEVATIONS AND GEOMORPHIC METRICS BEFORE STARTING THE NEXT UPSTREAM SECTION.
- 3. SEED AND MULCH THE CORRIDOR AND TOP OF VALLEY WITH THE TEMPORARY STABILIZATION SEED MIX (PREFERABLY A CONSERVATION MIX WITH AT LEAST 10% WILDFLOWER SEEDS, THOUGH MAY BE OF A PERENNIAL RYEGRASS). SEED TO THE AMOUNTS AS SPECIFIED BY THE SEED MANUFACTURER WITH GREATER APPLICATION ON THE STEEPER VALLEY SLOPES AND MULCH WITH WOOD CHIPS (90% GROUND COVERAGE) OR STRAW (TO A DEPTH OF 1 INCH). WATER AS SPECIFIED BY THE SEED MANUFACTURER, IF DROUGHT PERSISTS LONGER THAN THE RECOMMENDED WATERING RATE. ALLOW THE GRASS TO GROW TO A HEIGHT OF 2 INCHES BEFORE PROCEEDING TO THE NEXT STEP. IF ANY BARE PATCHES EXIST, RESEED AND MULCH TO ENSURE STABILIZATION. THIS STEP MAY BE PERFORMED AS A SECTION OF STREAM IS CONSTRUCTED, WHICH MAY REDUCE THE OVERALL CONSTRUCTION DURATION, THOUGH IT MAY COME AT A COST OF INCREASED WATERING EFFORT.
- 4.WHEN ALL PREVIOUS STEPS HAVE BEEN COMPLETED, THE STREAM SHOULD BE OPENED UP TO FLOWS. FIRST, THE EXISTING DRAINAGE CULVERT AT THE DOWNSTREAM END SHOULD BE EXCAVATED AND REMOVED. GRADE AND TEMPORARILY STABILIZE THE INCOMING FLOWS TO THE DOWNSTREAM POOL. PROCEED TO THE INLET TO THE STREAM AND CONSTRUCT (IF NOT ALREADY DONE IN STEP 2) THE INLET POOL AND GRADING. FLOWS MAY THEN BE DIRECTED INTO THE STREAM CHANNEL, IN A MANNER THAT SHALL BE DETERMINED IN THE FIELD, BASED ON THE MANNER IN WHICH THE INCOMING CULVERT AND UPSTREAM INFRASTRUCTURE IS BEING CONSTRUCTED. ALLOWING INCOMING FLOWS TO THE STREAM MAY BE PERFORMED CONCURRENTLY WITH THAT OF THE OUTLET, PROVIDED THE CONTRACTOR HAS THE LABOR AND EQUIPMENT AVAILABLE. HOWEVER, CAUTION SHOULD BE EXERCISED TO ENSURE THAT FLOWS ARE ABLE TO EXIT THE CORRIDOR FULLY AND APPROPRIATELY, TO PREVENT DAMAGE AND/OR FLOODING TO THE SITE.
- 5. WITH THE STREAM NOW CARRYING FLOWS, THE ENTIRE SITE SHOULD BE SEEDED AND PLANTED AS SPECIFIED IN THE PLANTING PLAN. THIS MAY BE DONE COMPLETELY OR PARTIALLY AS CONSTRUCTION OF THE STREAM TAKES PLACE. AT THIS POINT THE TEMPORARY STABILIZATION GRASS SHOULD HAVE TAKEN HOLD ENOUGH TO PROVIDE SOME COVER FOR SEEDS, AND KEEP IN MOISTURE DURING THE DAY. THIS STEP SHOULD ONLY BE DONE DURING A GROWING SEASON AND NOT IN MID-SUMMER OR WINTER, TO HELP ENSURE PLANTING SUCCESS. THIS STEP MAY BE DONE AFTER STEP 6, IF CONSTRUCTION ENDS BEFORE A PLANTING SEASON IS SET TO BEGIN. THIS STEP SHOULD BE PERFORMED WHEN THE APPROPRIATE EQUIPMENT IS AVAILABLE. THIS MAY HELP EXPEDITE THE PROCESS, RATHER THAN PERFORMING IT ALL COMPLETELY BY HAND.
- 6.FINALLY, MONITORING DEVICES AND COMPONENTS SHOULD BE INSTALLED, MEASUREMENTS RECORDED, AND INSTRUMENTS CALIBRATED AS NECESSARY. PLEASE REFER TO THE MONITORING PLAN SECTION OF THIS REPORT FOR MORE DETAILS ON THE MONITORING METHODS AND SCHEDULES.

SEE SHEET C-108 FOR GRADING, DRAINAGE & EROSION CONTROL NOTES





Proposed Industrial Development

Lonza Biologics

Portsmouth, New Hampshire


D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION


OJECT NO:	L-0700-013
TE:	04/03/2018
E: L0700-CS-701 to	C-703.dwg
AWN BY:	NAH
ECKED:	PMC

HODGSON BROOK GRADING, DRAINAGE & EROSION CONTROL PLAN

SCALE: AS SHOWN

APPROVED:





PLANTING NOTES:

- 1. THE CONTRACTOR SHALL FURNISH AND PLANT ALL PLANTS IN QUANTITIES AS SHOWN ON TH PLAN. NO SUBSTITUTIONS WILL BE PERMITTED UNLESS APPROVED BY OWNER. ALL PLANTS SHALL BE NURSERY GROWN.
- 2. ALL PLANTS SHALL BE NURSERY GROWN AND PLANTS AND WORKMANSHIP SHALL CONFORM TO THE AMERICAN ASSOCIATION OF NURSERYMEN STANDARDS, INCLUDING BUT NOT LIMITED TO SIZE, HEALTH, SHAPE, ETC., AND SHALL BE SUBJECT TO THE APPROVAL OF THE LANDSCAPE ARCHITECT PRIOR TO ARRIVAL ON-SITE AND AFTER PLANTING.
- 3. PLANT STOCK SHALL BE GROWN WITHIN THE HARDINESS ZONES 4 THRU 7 ESTABLISHED BY THE PLANT HARDINESS ZONE MAP, MISCELLANEOUS PUBLICATIONS NO. 814, AGRICULTURAL RESEARCH SERVICE, UNITED STATES DEPARTMENT AGRICULTURE, LATEST REVISION.
- 4. PLANT MATERIAL SHALL BEAR THE SAME RELATIONSHIP TO FINISHED GRADE AS TO THE ORIGINAL PLANTING GRADE PRIOR TO DIGGING.
- 5. NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT THE PRIOR WRITTEN APPROVAL OF THE OWNER'S REPRESENTATIVE.
- THE CONTRACTOR SHALL LOCATE, VERIFY AND MARK ALL EXISTING AND NEWLY INSTALLED UNDERGROUND UTILITIES PRIOR TO ANY LAWN WORK OR PLANTING. ANY CONFLICTS WHICH MIGHT OCCUR BETWEEN PLANTING AND UTILITIES SHALL IMMEDIATELY BE REPORTED TO THE OWNER SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
- 7. SEE PLANTING DETAILS AND SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
- 8. PLANTING SHALL BE COMPLETED FROM APRIL 15TH THROUGH OCTOBER 1ST, WITH THE EXCEPTION OF THE WHIPS. WHIPS SHALL BE PLANTED DURING THE DORMANT SEASON, OCTOBER 1ST THROUGH DECEMBER 15TH AND/OR MARCH 15TH THROUGH APRIL 15TH. NO PLANTING DURING JULY AND AUGUST UNLESS SPECIAL PROVISIONS ARE MADE FOR DROUGHT, SUCH AS DAILY WATERING AS REQUIRED.
- 9. ALL PLANTS SHALL BE WATERED THOROUGHLY TWICE DURING THE FIRST 24 HOUR PERIOD AFTER PLANTING. ALL PLANTS SHALL BE WATERED WEEKLY, OR MORE OFTEN, IF NECESSARY DURING THE FIRST GROWING SEASON.
- 10. THE CONTRACTOR SHALL GUARANTEE ALL PLANTINGS TO BE IN GOOD, HEALTHY, FLOURISHING AND ACCEPTABLE CONDITION FOR A PERIOD OF (1) YEAR BEGINNING AT THE DATE OF ACCEPTANCE OF SUBSTANTIAL COMPLETION. ALL GRASSES, TREES AND SHRUBS THAT, IN THE OPINION OF THE LANDSCAPE ARCHITECT, SHOW LESS THAN 80% HEALTHY GROWTH AT THE END OF ONE YEAR PERIOD SHALL BE REPLACED BY THE CONTRACTOR.
- 11. UPON EXPIRATION OF THE CONTRACTOR'S ONE YEAR GUARANTEE PERIOD, THE OWNER SHALL BE RESPONSIBLE FOR LANDSCAPE MAINTENANCE INCLUDING WATERING DURING PERIODS OF
- 12. PRE-PURCHASE PLANT MATERIAL AND ARRANGE FOR DELIVERY TO MEET PROJECT SCHEDULE AS REQUIRED. IT MAY BE NECESSARY TO PRE-DIG CERTAIN SPECIES WELL IN ADVANCE OF ACTUAL PLANTING DATES.
- 13. THE STREAM CORRIDOR HAS TWO DISTINCT ZONES FOR PLANTING: THE FLOODPLAIN (ZONE 1) AND THE UPLAND, OR VALLEY SLOPES (ZONE 2). THE TWO ZONES WERE BROKEN DOWN EVEN FURTHER, WITH EACH ZONE HAVING A LOWER AND AN UPPER PART (1L, 1U; 2L, 2U). FURTHERMORE, ZONE 1L CONTAINS AN ADDITIONAL SUB-ZONE THAT REFERS TO THE STREAM BANKS, JUST UP ONTO THE TOP OF THE BANKS. THIS SUB-ZONE CONTAINS TWO SECTIONS, ONE ALONG THE OUTER BANK OF EACH BEND, AND THE OTHER CONTAINING ALL THE OTHER BANKS (INNER BEND AND RIFFLES). THE OUTER BANK OF EACH POOL IS REFERRED TO AS ZONE 1LP, AND THE OTHER BANKS ARE IN ZONE 1LB. SEE SHEET C-703 FOR DETAILED ZONE PLAN.
- 14. SCRUB/SHRUB FLOODPLAIN AND FLOODPLAIN WETLAND ZONES (ZONE 1) PLANTING
- a. ONCE THE AREA HAS BEEN FULLY GRADED AND LOAMED, ENTIRE AREA SHALL BE SEEDED WITH "RIVERBANK STABILIZATION MIX" AT A RATE OF 1 POUND PER 2000 SF.
- b. THE EROSION CONTROL BLANKET SHALL THEN BE INSTALLED AS SHOWN ON SHEET C-701 AND DETAIL SHEET C-502.
- c. THE SHRUB PLANTINGS SHALL BE PLANTED ON 8' CENTERS IN LIKE GROUPS OF 3 TO 5, THROUGH THE EROSION CONTROL BLANKET.

14. SLOPE STABILIZATION AREA (ZONE 2) PLANTING SEQUENCE:


- a. ONCE THE AREA HAS BEEN FULLY GRADED AND LOAMED, ENTIRE AREA SHALL BE SEEDED WITH "RIVERBANK STABILIZATION MIX" AT A RATE OF 1 POUND PER 2000 SF.
- b. THE EROSION CONTROL BLANKET SHALL THEN BE INSTALLED AS SHOWN ON SHEET C-701 AND DETAIL SHEET C-502.
- c. THE SHRUB PLANTINGS SHALL BE PLANTED ON 6' CENTERS THROUGH THE EROSION CONTROL BLANKET.
- 15. STREAM BANK MARGINS PLANTING SEQUENCE:
- a. INSTALL COIR MATTING PER DETAILS SHEET C-703.
- b. PLANT WHIPS (1/2" 3/4" DIAMETER, 3 TO 4 FEET IN LENGTH) OF SILKY DOGWOOD AND RED-OSIER DOGWOOD ON THE UPWARD AND DOWNWARD SIDE OF COIR MATS, AT A MINIMUM OF 1 TO 2 FEET INTO THE SOIL SUBSTRATE.
- 16. "RIVERBANK STABILIZATION MIX" SHALL CONSIST OF:
- a. AGROSTIS STOLONIFERA (CREEPING BENT GRASS)
- b. AGROSTIS ALBA (RED TOP)
- c. FRAXINUS PENNSYLVANICA (GREEN ASH)
- d. CORNUS STOLONIFERA (RED-OSIER DOGWOOD)
- e. CORNUS AMOMUM (SILKY DOGWOOD) f. ELYMUS RIPARIUS (RIVERBANK WILD RYE)
- a. VIBURNUM RECOGNITUM (NORTHERN ARROWWOOD)
- AS SUPPLIED BY STONEY RIDGE ENVIRONMENTAL, LLC,

ALTON, NH 603-776-0194, OR APPROVED EQUAL

ORDERING ANY SUCH SEED MIX.


17. THE FINAL SPECIES USED IN CONSTRUCTION OF THE SITE MAY NOT BE LIMITED TO THOSE LISTED, ANY OTHER SPECIES WILL BE REVIEWED AND APPROVED BY THE ENGINEER BEFORE BEING ORDERED, OR PLACED IN THE FIELD. THIS IS ESPECIALLY TRUE OF ANY SEED MIX THAT MAY BE USED AT THE SITE; THE SELECTED MIX (MIXES) THAT THE CONTRACTOR SHALL USE SHOULD BE REVIEWED AND APPROVED BY THE ENGINEER BEFORE PLACEMENT, OR BEFORE

LEGEND



SEE SHEET C-108 FOR GRADING, DRAINAGE & EROSION CONTROL NOTES







GRAPHIC SCALE

Lonza Biologics

Portsmouth, New Hampshire

D	8/21/2018	REVISED TAC SUBMISSION
С	6/18/2018	NHDES AOT SUBMISSION
В	5/21/2018	TAC SUBMISSION
Α	4/3/2018	TAC WS SUBMISSION
MARK	DATE	DESCRIPTION
PROJE	CT NO:	L-0700-013
DATE:		04/03/2018

APPROVED: HODGSON BROOK WETLAND

PLANTING PLAN

NAH


PMC

SCALE: AS SHOWN

FILE: L0700-CS-701 to C-703.dwg

DRAWN BY

CHECKED:



TYPICAL RIFFLE CROSS-SECTION NO SCALE

> PLANTING SOIL MIX TO TOP OF CURB-

BITUMINOUS

CONCRETE

PAVEMENT-

6" MIN. IN EARTH

18" MIN. IN LEDGE T

CONTAINER GROWN NURSERY DUG

REMOVE CONTAINER | BALL & BURLAP


NOTE: PLANT AT SAME DEPTH AS PREVIOUSLY PLANTED, OR WITHIN 2" ABOVE.


SHRUB PLANTING

NO SCALE

CURBED ISLAND CONDITION ← LAWN CONDITION

CURB-






PLANTING ZONES DETAIL

SINGLE LOG VANE CONSTRUCTION SEQUENCE: EXCAVATE A TRENCH FOR THE VANE. 2. SET THE CROSS LOG SET THE VANE LOG(S).

- 4. PIN THE LOG VANE ARMS WITH 4' LONG, ½" REBAR HAMMERED INTO PRE-DRILLED HOLES (2ft ON CENTER). HOLES ARE ANGLED OFF THE VERTICAL, ALTERNATING DIRECTION (UPSTREAM, DOWNSTREAM).
- 5. EXCAVATE A TRENCH FOR THE GEOTEXTILE FABRIC ON THE UPSTREAM SIDE OF THE VANE. THE TRENCH SHALL BE AT LEAST 1.5' DEEP.
- 6. ANCHORS SHALL BE CABLED TO THE LOGS BY > 1/3" WIRE ROPE (CABLE), FASTENED WITH GRIPPLE CLIPS OR
- BOLTED CLAMPS. 7. ANCHORS SHALL BE EITHER LARGE (>100LB) ROCK OR REBAR CROSSES (TWO PIECES OF 2' LENTH, ½" REBAR FASTENED AT THEIR CENTERS).
- 8. STAPLE OR NAIL THE GEOTEXTILE ON THE UPSTREAM SIDE OF THE LOG, JUST ABOVE MID-DIAMETER, FOR THE FULL LENGTH OF THE LOG. FOLD OVER THE GEOTEXTILE FABRIC ALONG NAIL LINE. THE STAPLES/NAILS SHALL BE AT LEAST 1' ON CENTERS OR CLOSER. THE STAPLE/ NAIL LENGTH SHOULD BE AT LEAST 1".
- 9. BACKFILL THE UPSTREAM SIDE OF THE VANE.
- TRENCH, COVER WITH GEOTEXTILE (MIRAFI N140 OR APPROVED EQUAL), BACKFILL; OR PLACE GEOTEXTILE IN PARALLEL TRENCHES, COVERING A MOUND BETWEEN
- 12. WEAVE ONE CONTINUOUS GEOTEXTILE ALONG VANE AND SILL.



PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER AND SEED.


BEGIN AT THE TOP OF THE SLOPE, 36" OVER THE GRADE BREAK, BY ANCHORING THE BLANKET IN A 6" DEEP X 6" WIDE TRENCH WITH APPROXIMATELY 12" OF THE BLANKET WITH A ROW OF TAPLES/STAKES 12" APART IN THE BOTTOM OF THE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING. APPLY SEED TO COMPACTED SOIL AND FOLD REMAINING 12" PORTION OF BLANKET BACK OVER SEED AND COMPACTED SOIL. SECURE BLANKET OVER COMPACTED SOIL WITH A ROW OF STAPLES SPACED 12" APART ACROSS THE WIDTH OF THE


ROLL THE BLANKETS DOWN THE SLOPE. ALL BLANKETS MUST BE SECURELY FASTENED TO THE SOIL SURFACE BY PLACING STAPLES IN APPROPRIATE LOCATIONS AS SHOWN ON THE STAPLE PATTERN GUIDE.

4. STAPLE LENGTHS SHALL BE A MINIMUM OF 8 INCHES.

BLANKET.

EROSION CONTROL BLANKET FOR SLOPE PROTECTION





FOLD OVER THE FILTER FABRIC ALONG THE NAIL LINE.

10. EXCAVATE A SILL TRENCH (MINIMUM LENGTH OF 3') AT THE BANK-END OF THE LOG; EITHER A STONE SILL WITH MINIMUM DEPTH OF 2' OR A GEOTEXTILE SILL - TWO PARALLEL TRENCHES WITH A MINIMUM DEPTH OF 2'. 11. CONSTRUCT THE SILL: PLACE >1' SIZE STONES IN

THEM, AND BACKFILL.

CROSS LOGS SHALL BE A MINIMUM OF 8" IN DIAMETER. VANE ARM LOGS SHALL BE A MINIMUM OF 6" IN DIAMETER. ALL LOGS SHOULD BE RELATIVELY STRAIGHT AND, OF A HARDWOOD, HEMLOCK, OR LARCH SPECIES.

2. CROSS LOGS SHALL BE A MINIMUM OF 8' IN LENGTH AND BE PINNED EVERY 2'. VANE ARM LOGS SHALL BE A MINIMUM OF 7', AND PINNED EVERY 2'. 3. VANE ARM LOGS SHALL BE BURIED INTO THE BANK A MINIMUM OF 2', WHERE THEY SHALL BE KEYED INTO THE BANK WITH A SILL OF A MINIMUM LENGTH OF 3'.

4. NAIL FILTER FABRIC (MIRAFI 140N OR APPROVED EQUAL) ON TOP OF FOOTER LOG USING 3" 10d GALVANIZED COMMON NAIL OR SIMILAR AT 1' INTERVALS ALONG THE LOG.

SET THE ELEVATION OF THE TOP OF THE CROSS LOG TO THE DESIGNED THALWEG (CENTERLINE) ELEVATION OF THE STREAMBED. 6. THE CROSS NOTCH CAN BE FORMED BY MAKING CUTS 1"-2" APART WITH A CHAINSAW, THEN KNOCKING OUT THE SECTIONS WITH A CHISEL AND HAMMER.

7. THE ANGLE OF THE CROSS NOTCH SHALL MATCH THE ANGLE BETWEEN THE VANE ARMS AND THE STREAM BANK. 8. SCOUR POOLS SHALL BE OVER DUG BY ~1.4x THE RIFFLE DEPTH, OR ABOUT 1' - 1.25' DEEP.

> LOG CROSS VANE NO SCALE

Proposed

Industrial

Development

Lonza Biologics

D	8/21/2018	REVISED TAC SUBMISSION		
С	6/18/2018	NHDES AOT SUBMISSION		
В	5/21/2018	TAC SUBMISSION		
Α	4/3/2018	TAC WS SUBMISSION		
MARK	DATE	DESCRIPTION		
PROJE	CT NO:	L-0700-013		
DATE:		04/03/2018		

APPROVED: BLM **HODGSON BROOK**

DETAILS SHEET

NAH


PMC

SCALE: AS SHOWN

FILE: L0700-CS-701 to C-703.dwg

DRAWN BY

CHECKED:



LEGEND


PHASE 1 (3-5 YEARS)

PHASE 2 (5-10 YEARS)

PHASE 3 (10-15 YEARS)



ASK-001 NONE ASK-001 NONE



09 AUG

ASK-001

DATE: REVISION A

SITE PLAN -

PERSPECTIVE

Lonza

LONZA

BIOLOGICS

PORTSMOUTH, NEW HAMPSHIRE MAD18221.01

IRON PARCEL

ips

PERSPECTIVE VIEW


NONE

ASK-001 1" = 100'-0"


8/13/2018 2:38:03 PM

Parcel_scaban85DQ5.nt


3rd Floor @ 60'-0"




3rd Floor Intermediate @ 75'-0"




Penthouse @ 90'-0"




2nd Floor @ 30'-0"



2nd Floor Intermediate @ 45'-0"



1st Floor @ 0'-0"



1st Floor Intermediate @ 15'-0"

MANUFACTURING PENTHOUSE @90'-0" UTILITIES WAREHOUSE OFFICE THIRD FLOOR INTERMEDIATE @75'-0" ASSEMBLY THIRD FLOOR @60'-0" SECOND FLOOR INTERMEDIATE @45'-0" SECOND FLOOR @30'-0" FIRST FLOOR INTERMEDIATE @15'-0" FIRST FLOOR @0'-0"

AXONOMETRIC VIEW

			Building			
Floor		Area	Building 1	Building 2	Building 3	Site Total
_		First Floor Total	137,840	160,000	62,000	359,840
1 Area		Manufacturing	61,700	70,000		131,700
		Lab/Office	12,000	20,000		32,000
	rea	Circulation	19,210	16,000		
	ا	Warehouse	17,000	12,000		
		Support Utility	27,930	42,000	62,000	131,930
	_					
2 Prea		Second Floor Total	137,840	160,000	62,000	359,840
		Manufacturing	79,900	90,000	62,000	231,900
	е <u></u>	Lab/Office	12,000	20,000		32,000
	_ا <u>د</u>	Warehouse	3,480	3,600		7,080
	~∟	Circulation	19,170	16,000		35,170
	_	Support Utility	23,290	30,400		53,690
Area		Third Floor Total	155,040	160,000	62,000	377,040
		Manufacturing	97,100	90,000	62,000	249,100
	eg –	Lab/Office	12,000	20,000	di-	32,000
	Ar	Circulation	17,740	16,000		33,740
		Support Utility	28,200	34,000		62,200





IRON PARCEL

PORTSMOUTH, NH MAD18221.01

BUILDING 1 CONCEPT **PLANS**

ASK-002

12-JUL-2018



5.3 Facility Design—Building Renderings



Image 5.10 – Facility Rendering

5.3 Facility Design—Building Renderings



Image 5.11 – Facility Rendering

