

July 29, 2019 File No. 04.0190892.00

City of Portsmouth
Planning Board
Attn: Dexter Legg, Chairman
1 Junkins Ave, 3<sup>rd</sup> Floor
Portsmouth, New Hampshire 03801

Re: Conditional Use Permit Application
City of Portsmouth Proposed Multi-Purpose Recreational Fields
680 Peverly Hill Road (Tax Map 254, Lot 8)

Portsmouth, New Hampshire

Dear Chairman Legg:

This letter transmits a Conditional Use Permit Application on behalf of the City of Portsmouth (the City), for the construction of three multi-purpose recreational fields and associated parking, as well as the construction of a new transfer station and related upgrades adjacent to the existing City of Portsmouth Public Works facility located at 680 Peverly Hill Road (i.e., the Site) (see attached **Locus Plan**). On behalf of the City, GZA GeoEnvironmental, Inc. (GZA) is requesting consideration of a Conditional Use Permit application for permanent impacts within wetlands and wetland buffers within the City of Portsmouth.

The proposed project involves the construction of three multi-purpose recreational fields and associated parking on the western portion of the Site. In addition, the City is proposing to construct a new transfer station and associated upgrades adjacent to the existing City or Portsmouth Public Works facility on the eastern portion of the Site. The Site is an old quarry and was extensively re-graded as part of gravel pit reclamation in the 1990s.

Before prioritizing this Site, the City completed an extensive recreational needs assessment (see Comprehensive Recreation Needs Study dated 5/17/10 prepared by The Architectural Team, Inc., Ballard\*King & Associates Ltd., Barker Rinker Seacat Architecture, and Copley Wolff Design Group). This assessment determined a need for additional fields due to the City's growing population and the City's 2025 Master Plan goal to increase recreational opportunities to the public. Currently, the City does not have adequate field space dedicated to non-school sports, and there is a shortage of fields available for existing leagues. At least 14-16 groups compete for field time primarily from spring to late fall with activities occurring from March to mid-November. During June 2019, over 2,000 players spanning 60-64 individual teams required space on the existing limited field space. Currently, these teams

----


ENVIRONMENTAL

COLOGICAL

WATER

CONSTRUCTION MANAGEMENT

5 Commerce Park North Suite 201 Bedford, NH 03110 T: 603.623.3600 F: 603.624.9463 www.gza.com





require space in Greenland, Newington, Rye, and New Castle, to supplement field space available in Portsmouth. The Recreational Needs Study recommended the construction of three multi-purpose fields to address current and future demands for recreational field space.

As part of the comprehensive recreational needs study, five potential parcels were identified as candidates for the proposed construction of multi-purpose recreational fields (see Figure 5, Alternative Site Analysis). Two parcels were reviewed at municipal hearings and were denied due to abutter input. The other two parcels are either too distant from existing sports facilities, would not support multiple recreational fields, or were not owned/available to the City. The construction of all three proposed fields in one location provides key efficiencies and improved logistics for City residents. Often, multiple members of a family are involved in sports, and the presence of multiple fields optimizes operations and limits excessive trips to attend games. The current proposed Site is the only remaining candidate available to construct three multi-purpose fields at one Site.


In addition, the City is proposing to construct a new transfer station in the eastern portion of the Site adjacent to the existing City of Portsmouth Public Works facility. The solid waste transfer/recycling facility is being developed to significantly increase efficiencies in the hauling of solid waste and recyclables from the City's solid waste management program. Currently, the City operates a curbside collection system for both household/business solid waste and recyclables and drives the materials to remote disposal or processing facilities in relatively small packers that collect the material. The facility is required to meet the current and projected demand for solid waste processing. The Site is zoned for Municipal uses, and therefore is ideal for accommodating both multi-purpose recreational fields and a new transfer station.

The team completed a field walk with the New Hampshire Department of Environmental Services (NHDES) on March 29, 2019 and a pre-application meeting with the NHDES, U.S. Army Corps of Engineers, United States Environmental Protection Agency, and New Hampshire Natural Heritage Bureau on April 30, 2019. Since the original concept was developed, the proposed wetland impacts have been reduced from approximately 83,929 square feet (sq. ft.) to 57,512 sq. ft. In addition, direct impacts have been avoided in Wetland 1, a natural wetland with the highest functions and values on Site. Direct impacts have been avoided in Wetlands 2 and 3 which are also natural wetland systems (see Existing Conditions Overview). The proposed project includes unavoidable impacts within 100-foot wetland buffer areas totaling approximately 436,119 sq. ft. However, as previously mentioned, majority of impacts to wetlands and wetland buffers are to previous man-made sedimentation ponds, ditches, treatment swales, and previously altered buffers.

GZA coordinated a review with the New Hampshire Natural Heritage Bureau (NHB). Through coordination with the NHB, it was determined that there are no anticipated impacts to exemplary natural communicates located off-Site as a result of the proposed project.

In accordance with the City of Portsmouth Zoning Ordinance, Article 10, section 10.1017.50, a Conditional Use Permit may be issued by the Planning Board for any proposed development other than installation of utilities within a right-of-way, as long as the project meets the following criteria;

A. **The land is reasonably suited to the use, activity or alteration**. The Site is an old quarry area and is zoned as a Municipal lot. The Site can accommodate multiple fields, is located in close proximity to schools, and is owned by the City. In addition, the proposed project avoids direct impact to natural wetlands and is adjacent to an existing passive recreational area to the west.





The Site is also surrounded by parcels zoned as Industrial and Mixed Residential. In 2010 the City completed a detailed recreational needs assessment which determined a need for additional fields due to the City's growing population and the City's 2025 Master Plan to increase recreational opportunities to the public. The City study further identified five potential parcels for the proposed recreational fields, including the current Site. Two other project parcels were deemed unsuitable after public input. The others do not support multiple recreational fields, or were not owned by the City.

The proposed transfer station on the eastern side of the Site is suitable for this parcel of land as the Site is zoned as a Municipal lot which can accommodate a transfer station. In addition, the Site is adjacent to the existing public works facility. The transfer station only proposes impacts to created treatment swales and ditches, and does not propose impacts to natural wetlands or unaltered buffers.

- B. There is no alternative location outside the wetland buffer that is feasible and reasonable for the proposed use, activity or alteration. There are nine wetlands located on Site. Of these nine wetlands, three are natural and six were previously excavated for quarry activities or were graded as part of final reclamation of the Site, and are not considered natural wetlands. The proposed project has been redesigned to reduce overall direct wetland impacts from 83,929 sq. ft. to 57,512 sq. ft. In addition, direct impacts to natural wetlands were avoided entirely through careful site design. The proposed transfer station on the eastern portion of the Site will impact wetland buffers of previously excavated wetlands and will not impact wetland buffers of natural wetlands.
- C. There will be no adverse impact on the wetland functional values of the site or surrounding properties. The natural wetlands, including Wetlands 1, 2 and 3, are located in the western portion of the Site. Wetland impacts to natural wetland have been avoided as a result of the proposed project. The three natural wetlands located on Site provide the highest wetland functions and values, including groundwater recharge/discharge, floodflow alteration, sediment and toxicant retention, nutrient removal, wildlife habitat, educational/scientific value, and specifically production export, sediment/shoreline stabilization, recreational function, visual quality and uniqueness value in Wetland 1. Since wetland impacts were avoided in the three previously listed natural wetlands, it is not anticipated that there will be adverse impacts on the wetland functions and values on natural wetlands as a result of the proposed project. The remaining wetlands, which were excavated for quarry activities or were graded as part of final reclamation of the Site, primarily offer sediment/toxicant retention function. However, a portion of Wetland 9 containing a large detention pond is not proposed to be impacted as a result of the project and will retain primary sediment/toxicant retention capability. In addition, the project includes a landscaping plan and an in-lieu fee mitigation payment for unavoidable impacts to wetlands.
- D. Alteration of the natural vegetative state or managed woodland will occur only to the extent necessary to achieve construction goals. The existing Site is primarily cleared as a result of prior quarrying and grading activities. In addition, existing natural vegetation in Wetlands 1, 2 and 3 are not proposed to be impacted. As a result, disturbance to natural vegetation will only occur to the extent necessary for the proposed project within the prior quarried and disturbed portion of the Site.
- E. The proposed alternative with the least adverse impact to areas and environments under the jurisdiction of this Section. As previously mentioned, through careful site design and meetings with the project team, the proposed impacts have been reduced from 83,929 sq. ft. to 57,512 sq. ft. in prior excavated wetlands. Impacts to natural wetlands have been avoided and functions and values of natural wetlands will not be



adversely impacted. In addition, the proposed project offers redevelopment and repurposing of an old quarry site. As a result, this is the least impacting alternative to the Site.

F. Any area within the vegetated buffer strip will be returned to a natural state to the extent feasible. Impacts to wetland vegetative buffer strips have been minimized to the greatest extent feasible through project design and meetings with the project team. Impacts to natural wetlands have been avoided, and majority of impacts to wetland buffers and vegetated buffer strips are associated with wetlands previously excavated for quarry activities or were graded as part of final reclamation of the Site. Limited impact within the vegetated buffer strip of natural wetlands was necessary due to lot size and shape restrictions, recreational field size requirements, and proximity of proposed recreational fields to wetlands on Site. However, as previously mentioned, wetland impacts to natural wetlands were avoided entirely through site plan revisions and meetings with the project team, and impacts to vegetated buffer strips associated with natural wetlands have been minimized and avoided to the greatest extent.

As part of the proposed project, best management practices and design considerations have been implemented to minimize and protect existing natural resource features including the following;

#### 1. Landscape Plantings


The project includes an extensive planting plan comprised of native and naturalized species including balsam fir (Abies balsamea), western red cedar (Thuja plicata), Eastern white pine (Pinus strobus), gray birch (Betula populifolia), flowering dogwood (Cornus florida), and American basswood (Tilia americana) (see Figure 4 – Plans by CMA Engineers, Inc.). These plantings will enhance visual aesthetics and provide wildlife habitat components. The plantings will provide nesting and feeding locations to common songbirds including song sparrow (Melospiza melodia), mockingbird (Mimus polyglottos), and black-capped chickadee (Poecile atricapillus) which occur on Site.

#### 2. Modern Stormwater Treatment

The existing, excavated manmade wetlands on Site are remnants of prior quarry activities and are isolated from natural wetlands. In addition, these wetlands provide low functional benefits and minimal stormwater treatment. The project proposes the creation of modern, state-of-the-practice stormwater management facilities which will meet NHDES and Alteration of Terrain permit requirements. Proposed stormwater management features will provide high pollutant removal efficiencies for TSS, zinc, phosphorus and nitrogen. Stormwater treatment features throughout the Site will include subsurface storage facilities, subsurface gravel wetland features, and vegetative swales and forebays.

The three proposed recreational fields will provide infiltration of precipitation comparable to permeable pavement in terms of performance. A subsurface storage facility will be located under the north side of the fields which will provide treatment to stormwater from the fields, as well as groundwater recharge and peak flow attenuation.

Stormwater runoff associated with proposed parking areas and accessways for the three recreational fields will be pretreated in a vegetative swale and forebay prior to receiving primary treatment in proposed subsurface gravel wetland stormwater features.





Stormwater runoff associated with the proposed transfer station will primarily flow through underground treatment facilities for treatment prior to being recharged to groundwater or discharged. Additional runoff from pavement and gravel areas will be pre-treated by sediment forebays and treated by a vegetated infiltration basin before being discharged to surface waters.

#### 3. Invasive Species Management

Several invasive plant species including phragmites (*Phragmites australis*), reed canary grass (*Phalaris arundinacea*), autumn olive (*Elaeagnus umbellata*), multiflora rose (*Rosa multiflora*), oriental bittersweet (*Celastrus orbiculatus*), and glossy buckthorn (*Frangula alnus*) have been observed on Site. During construction, the project will implement practices to control the spread of invasive plants within the work limits of the project. Invasive plants that are excavated for construction will be managed in accordance with "Best Management Practices for the Control of Invasive and Noxious Plant Species," dated 2018, prepared by the New Hampshire Department of Transportation. The contractor will be required to develop a site-specific Invasive Species Management Plan.

#### 4. Mitigation

The project includes mitigation for permanent wetland impacts exceeding the 10,000 sq. ft. threshold for State and federal wetland mitigation. As required, GZA completed a pre-application meeting with the NHDES, NHFG, the Environmental Protection Agency (EPA), and the USACE on April 30, 2019 to review project details and proposed mitigation. As a result of the NHDES pre-application meeting on April 30, 2019, and preliminary coordination with the City of Portsmouth, the project includes a mitigation package including an in-lieu fee payment to the Aquatic Resource Mitigation (ARM) Fund of \$205,024.44. In-lieu fee payments to the ARM fund can be applied for by towns and other local agencies to fund wetland restoration, creation, and preservation projects within the same watershed where impacts occurred.

James Long, CWS, CSS

Consultant/Reviewer

Please feel free to contact us with any questions.

Very truly yours,

GZA GEOENVIRONMENTAL, INC.

Tracy Tarr, CWS, CWB, CESSWI

**Associate Principal** 

Deborah M. Zarta Gier, CNRP

ebouch U. Java

Principal

TLT/DMZ/JHL:kr

\gzabedford\jobs\04jobs\0190800s\04.0190892.00\work\local permitting\portsmouth cup\draft portsmouth athletic fields cup application 072319 dmz.docx

Attachments: Owner Authorization






Photo Log List of Abutters

Figure 1 – Locus Plan

Figure 2 – Wildlife Action Plan Overlay

Figure 3 – Existing Conditions Overlay

Figure 4 – Plans by CMA Engineers, Inc.


Table 1 – Wetland and Buffer Area Analysis

Table 2 - Wetland and Buffer Impact Analysis



### Owner - Letter of Authorization

hereby authorize CMA Engineers, I Conditional Use Permit Application transfer station on Tax Map 254, Lo	resentative of the City of Portsmouth, Inc. and GZA GeoEnvironmental, Inc. to n for the construction of recreational athlet 8 within the Wetlands Protection area. That this does not incur any costs on my be	prepare and submit a etic fields and a new his shall include any
Signature	Print Name	7/17// Date//
Witness Witness	Print Name	7 23 19 Date 1





Photograph No. 1: Looking northerly into Vernal Pool A within Wetland 1. There are no proposed wetland impacts to Wetland 1.



Photograph No. 2: Looking into Wetland 1. There are no proposed wetland impacts to Wetland 1.



Photograph No. 3: Looking westerly at intermittent channel within Wetland 1. There are no proposed wetland impacts to Wetland 1.



Photograph No. 4: Looking easterly at Vernal Pool B within Wetland 1.



Photograph No. 5: Looking northerly at Wetland 2 adjacent to the existing access road. There are no proposed wetland impacts to Wetland 2.



Photograph No. 6: Looking northerly at Wetland 3. There are no proposed wetland impacts to Wetland 3.



Photograph No. 7: Looking northerly at Wetland 4 primarily dominated by Phgramites (*Phragmites australis*).



Photograph No. 8: Looking northwesterly at Wetland 5 adjacent to Pike Industries to the north.



Photograph No. 9: Looking northerly at Wetland 6 (treatment swale).



Photograph No. 10: Looking southeasterly at Wetland 7 (ditch).



Photograph No. 11: Looking southwesterly at Wetland 8 in the foreground and Wetland 9 in the background.



Photograph No. 12: Looking easterly at Wetland 9 (stormwater treatment facility).





# City of Portsmouth Multi-Purpose Recreational Fields Project City of Portsmouth Conditional Use permit Abutters List Portsmouth, New Hampshire

#### **Wetland Scientist**

GZA GeoEnvironmental, Inc. Attn: Tracy Tarr, CWS, CWB, CESSWI 5 Commerce Park North, Suite 201 Bedford, NH 03110

#### **Engineer**

Weston and Sampson 55 Walkers Brook Drive, Suite 100 Reading, MA 01867

#### Tax Map 252-2-12

One Hundred West LLC 100 West Road Portsmouth, NH 03801

#### Tax Map 266-4

Foundation for Seacoast Health 100 Campus Drive, Suite 1 Portsmouth, NH 03801

#### Tax Map 267-19

Two Hundred Seventy West Condo Mastercard 270 West Road Portsmouth, NH 03801

#### Tax Map 267-23

Engel Family Trust C/O Robert Engel, Trustee PO Box 6070 Manchester, NH 03108

# Owner/Applicant Tax Map 254-8

City of Portsmouth
1 Junkins Avenue
Portsmouth, NH 03801

#### Tax Map 252-2-10

JMK Realty LLC PO Box 971 Portsmouth, NH 03802

#### Tax Map 252-2-14

Litchfield Portsmouth LLC C/O Eaton Partners, Inc. 175 Canal Street, Suite 401 Manchester, NH 03101

#### Tax Map 266-1

Ricci Construction Co, Inc. 225 Banfield Road Portsmouth, NH 03801

#### Tax Map 266-5

Hope for Tomorrow Foundation 1 Stoneridge Drive Rye, NH 03870

#### Tax Map 267-20

Harvey Propco LLC 1400 Main Street Waltham, MA 02451

#### **Engineer**

CMA Engineers 1 Sundial Avenue Suite 510N Manchester, NH 03103

#### Tax Map 252-2-11

HEG West Road LLC 2 International Way Lawrence, MA 01843

#### Tax Map 254-7

Pike Industries 3 Eastgate Park Road Belmont, NH 03220

#### Tax Map 266-3


Andrew and Carol Ann Croteau 285 Banfield Road Portsmouth, NH 03801


#### Tax Map 267-17

Graywolf Properties 1 Libbey Lane Rye, NH 03870


#### Tax Map 267-22

200 West Road LLC 210 Commerce Way Portsmouth, NH 03801




















# City of Portsmouth, New Hampshire Department of Public Works Multi-purpose Recreation Fields 680 Peverly Hill Road

# Agency Review Plans - July 2019


# Sheet Index (PERMIT PLANS)



Prepared For:

City of Portsmouth
Department of Public Works
680 Peverly Hill Road
Portsmouth, New Hampshire 03801

Prepared By:








CIVIL/ENVIRONMENTAL/STRUCTURAL

Portsmouth, NH Manchester, NH 603/431-6196 603/627-0708 207/541-4223

c m a e n g i n e e r s . c o m

427 Main Street, Suite 400, Worcester, MA (978) 977-0110 (800) 726-7766 (Sampson) www.westonandsampson.com



# **General Construction Notes:**

- 1. All work shall be in conformance with current Cith of Portsmouth and current NHDOT Standard Specifications and details.
- 2. The Contractor shall be solely responsible for construction means, methods, techniques, and procedures, and for safety precautions and programs in connection with all work included under this contract, including compliance with all applicable OSHA regulations. The Drawings do not include necessary components for construction safety. The Contractor shall be solely responsible for providing and maintaining all safety barriers, warning flashers, etc., as required by the conduct of the work for the protection of workers and non— workers alike. The Owner and Engineer will periodically review construction for compliance with the plans and specifications; such review does not imply approval of methods of construction.
- 3. The Contractor shall provide staging areas as required for staging, processing, and stock pile area as necessary. The Contractor shall prepare the area as necessary and install all erosion control devices to meet NHDES—WT standards. The Contractor shall stockpile, handle and transport materials to preserve their quality and fitness for the work. Materials shall also be stored to facilitate inspection and may be subject to inspection and retesting before incorporation in the work. Private property shall not be used for storage purposes without written permission of the property owner. If requested, copies of such written permission shall be furnished to the Owner. After completion of construction, the contractor shall return the staging area to preexisting conditions to the satisfaction of the property owner and the City.
- 4. Existing conditions survey and topography provided by JAMES VERRA & ASSOCIATES, INC. in January 2018. Bench marks and horizontal control points for the Contractor to lay out the work have been established and are shown on the Plans.
- 5. The Contractor shall perform all required layout and developing as—built documentation work with competent, qualified personnel in a manner consistent with the current survey/layout practices and acceptable to the Engineer. No separate payment for this work will be made. The Contractor shall provide the engineer with qualified persons to assist in this checking as needed and on request of the engineer. The Contractor shall perform all necessary layout work in order to construct all elements of the project as shown on the plans and specified in the contract. This work shall include, but shall not be limited to, stakeout necessary to establish lines and grades as earthwork operations progress; stakeout, layout and elevations as required for installing drain lines, sewer, water lines, and other items included in the work.
- 6. The Contractor is solely responsible for the accuracy of the work. The Engineer may check all or any portion of the layout, stake—out made by the Contractor. Any necessary correction to the work shall be made immediately by the contractor. Such checking by the engineer will not relieve the contractor of any responsibilities for the accuracy or completeness of the work. No claim will be considered because of alleged inaccuracies unless the contractor notifies the Engineer thereof in writing immediately upon discovery of the alleged inaccuracies and affords the Engineer opportunity to check or verify the control in question.
- 7. The Contractor shall be responsible for the preservation of all bench marks and control points. If any of the control points are disturbed by the Contractor during the construction, the Contractor shall replace them at no expense to the owner. Damaged or destroyed points, bench marks or stakes or any reference points damaged or made inaccessible by the progress of the construction shall be replaced or transferred by the Contractor, subject to verification by the engineer. Replacement of any layout points shall be performed by or under the direction of a NH licensed land surveyor.
- 8. Apparent edge of right—of—way based on the existing conditions survey. Perform all work within the existing right—of—way or acquired temporary right of entry limits.
- 9. The Contractor shall protect private property and shall take all necessary measures and precautions to avoid damage to existing trees, shrubs, lawns, plantings, etc. This protection will include the trimming of trees prior to construction if necessary. The Contractor shall be responsible for repairs/replacement of all damaged items.
- 10. The Contractor shall plan and perform test pit excavation well in advance of commencing construction and ordering materials to allow time to review actual conditions encountered. Test pits not specifically identified, shall be excavated by the Contractor at the direction of the Engineer.
- 11. All excavations shall be thoroughly secured on a daily basis by the Contractor at the completion of construction operations in the immediate area.
- 12. All drainage structures to be abandoned in place shall have the cone removed and be filled with gravel. The material shall be compacted in layers not exceeding 12 inches of compacted thickness. All connections shall be plugged with a cement concrete masonry plug at the pipe locations.
- 13. Plugging existing pipes with brick and mortar shall be considered subsidiary to the drainage work.
- 14. Pipe connections to replacement structures are subsidiary to the structure.
- 15. All proposed and existing drainage and sanitary sewer structure rim and pipe invert elevations are to be field verified by the contractor and accepted by the engineer.
- 16. The Contractor shall set all manhole frames and covers and catch basin grates and water valve covers to be flush with the base pavement grades, then raised to 1/8" to 1/4" below final pavement elevations during installation of the final wearing coarse.
- 17. The Contractor shall be responsible for removal and relocation of all signs that conflict with the work (incidental to construction). Any signs damaged during construction shall be replaced at no additional cost to the Owner.
- 18. Final location of traffic signs and supports as shown in the plans shall be field—confirmed by the Contractor and accepted by the Engineer prior to installation.
- 19. Remove topsoil for its total depth within the limits of the slope lines. unless otherwise directed, stockpile topsoil and use it on this project as needed.
- 20. All disturbed areas not designated to be paved or landscaped otherwise shall have loam borrow placed and seeded.

  The loam borrow shall have a minimum depth of 4" and shall be placed flush with the top of adjacent curbing, edging, pavement millings, back of sidewalk or other paved edge.
- 21. The contractor shall be responsible for the site restoration and clean up upon completion of the project.

# **Existing Utility Notes:**

- 1. The Contractor shall verify all existing utility locations, public or private, shown or not shown, on these plans prior to construction. The engineer shall be notified in writing of any utilities found interfering with the proposed construction and appropriate remedial action shall be taken before proceeding with the work. The Contractor shall notify Dig—Safe at 1—800—225—4977 and Portsmouth DPW (to locate water, sewer & drains) at least 72 hours prior to beginning work to confirm the location of underground utilities.
- 2. The Contractor is responsible for the location, protection and repair (if damaged) of all existing utility mains and services. The locations of known gas, water, and sewer mains shown on these drawings are approximate. Existing gas, water, and sewer service laterals may not be shown and the Contractor should anticipate their existence. The Contractor should consider conflicts, hand excavation, and decrease in production when preparing their bid.

## **Permit Notes**

- 1. The Contractor shall be responsible for obtaining all other construction permits, local and state, as well as from public utilities, including but not limited to a right—of—way trench permit from the Portsmouth DPW.
- 2. The Contractor shall prepare a project specific Stormwater Pollution Prevention Plan (SWPPP) and obtain an EPA Construction General Permit.

# **Disposal of Surplus Material**

- 1. Unsuitable materials and boulders/rock/stones as defined by the specifications which are not acceptable as fill material shall be removed from the site. All pavement and subgrade soils removed during construction to achieve proposed grades shall become property of the Contractor. Disposal is the Contractor's responsibility.
- 2. Unless requested by the City, all frames, covers, grates, valves and valve boxes, and curbing to be removed during the project shall become the property of the Contractor. All pavement, concrete and subgrade soils removed during construction to achieve proposed grades shall become the property of the Contractor. All sidewalk pavement, sidewalk brick, concrete or brick structures, sewer manholes, drainage, water and sewer pipe to be removed/demolished shall become the property of the Contractor.
- 3. If Asbestos Cement (AC) pipe is encountered, all work shall be done in accordance with Env—A 1800 Asbestos Management and Control. If the AC pipe is broken or requires cutting or breaking, a licensed abatement contractor must complete this work and properly bag and dispose of the pipe materials. All disposal shall be done in accordance with Env—A 1800 and Env—Sw 901. The Contractor shall be responsible for removing and disposing asbestos cement pipe, including service connections, within the limits of trench excavation. The Contractor shall maintain water service to users through the use of temporary bypass piping and valves.
- 4. Removal of existing drainage and sanitary sewer structures and pipe shall be subsidiary to proposed work items when the existing drainage and sewer items are located within the trench limits of the proposed drainage items as specified in Section 206 of the NHDOT standard specification.

## **Boring Notes**

- 1. Borings indicated on the plans were made by S.W. Cole Engineering, Inc in November 2018. Blow counts shown are the number of blows required to drive a 2" O.D. standard split spoon sampler 6" using a 140 lb weight falling 30".
- 2. Borings are for design purposes showing conditions at boring points only, and do not necessarily indicate material to be encountered during construction.
- 3. Water levels indicate thus were measured at the time of exploration. The water levels encountered during construction may vary consducted due to prevailing climate, rainfall, or other factors.
- 4. The Geotechnical investigation report is provided as an appendix to the contract documents.

# **Construction Traffic Management & Signing Notes**

- 1. Two weeks prior to beginning work, the Contractor shall submit a Work Plan for the sequencing of the project and management of traffic in accordance with Section 01570. Plan shall include locations of construction signage, variable message boards, and provisions for temporary accessible pedestrian routes.
- 2. All traffic control devices shall conform with Sections 618 and 619 of the NHDOT Standard Specifications, the current editions of the MUTCD including all revisions, and the State of NH DOT Traffic Control Handbook.
- 3. The Contractor shall exercise caution and comply with all applicable traffic laws and regulations in the execution of work. The Contractor is to coordinate all work with the Cith of Portsmouth Public Works, Fire and Police Departments and Engineer at least 14 days prior to implementing any temporary road closures or temporary detours.
- 4. All costs for traffic control devices including placement, relocation, maintenance, and removal of signs shall be included in the Contractor's bid.
- 5. The Contractor is to furnish and place three portable message boards at the project site (location designated by City) at least 7 days in advance of any work for advance public notification. The message board shall remain active during the construction period.
- 6. All permanent construction signing and warning devices shall be supplied, erected, maintained, and removed by the Contractor. Placement of permanent construction signs shall be coordinated with the Engineer and Public Works staff. The contractor shall bear all expense of maintaining the section of road undergoing improvement including all temporary approaches or crossings and intersections with trails, roads, streets, businesses, parking lots, residences, garages, farms, and other features as may be necessary.
- 7. Access to existing drives shall be maintained at all times. In the event that major work must be done at drives that precludes full access, the Contractor is to coordinate the work with the Owners and the Engineer 24 hours in advance to minimize inconveniences.
- 8. Unless otherwise approved, the Contractor shall maintain a minimum of 14—feet of roadway access at all times to accommodate through traffic and local emergency access. Emergency vehicles shall be given priority.
- 9. All road openings shall be backfilled at the end of each work day to ensure safe vehicular and pedestrian travel. The Contractor shall maintain two lanes of traffic at the end of each work day. Plating trenches overnight is not allowed without prior City approval.
- 10. Dust control operations shall be provided throughout the duration of the project, incidental to the work.

## Sanitary Sewer Notes


- 1. All sewer mains and fittings shall conform to ASTM D-3034 and shall be PVC SDR 35. Pipe and pipe fittings between manholes are to be of the same manufacturer. Joint compression rings shall be of an oil resistant rubber type or flexible elastomeric seals conforming to ASTM D-3212. Manufacturer's certificate of compliance shall be furnished to the City prior to installation.
- 2. Pipe Lengths shown on plans are horizontal lengths, measured from inside of manhole wall (2 feet from MH center for 4' diameter MH) to inside of manhole wall.
- 3. Sewer mains and services constructed above or without adequate separation from water mains shall be constructed of pressure class pipe (ductile iron (conforming to ANSI/AWWA C150/A21.50) or C900 PVC) for a minimum distance of 9 feet each side of the crossing. Joints shall be water pressure rated with zero leakage when tested at 25 pounds per square inch for gravity sewers and 1½ times working pressure for force mains, and joints shall not be located within 9 feet of the crossing point. Adequate separation is defined as 10 feet of horizontal separation and 18 inches vertical separation below the water main. If the minimum 18—inch vertical separation is not achievable, a waiver from NHDES is required.
- 4. All pipe utilizing bell and spigot joints shall be laid with the spigot end downstream. Bells will not be permitted in structures.
- 5. Green detectable "sewer" tape shall be installed in the sewer trench on top of the 12—inch sand blanket on all sanitary sewer mains and services.
- 6. Sewer service laterals are to be 6" SDR 35 pipe. Sewer Service shall be constructed at a 1% minimum slope (1/8 inch per foot) unless otherwise approved by the Engineer (10% maximum).
- 7. Sewer services will not be allowed to have more than two angle points, or a total angular deviation of 180 degrees, unless a variance is granted by the City.
- 8. Service laterals shall not connect to manholes unless specified on plans.
- 9. Sewer service laterals shall be designed for a minimum of 4 feet of cover at the building. Insulation will be required should the sanitary sewer lateral be less than the required 4 feet deep (6 feet in paved areas).

## **Water Notes**

- 1. All materials and workmanship shall be in conformance with the Cith of Portsmouth's Construction Standards and Details and NH DES Env—DW 404. The more stringent regulation shall apply.
- 2. All water mains shall be Class 52 Cement Lined (CL) Ductile Iron Pipe and pipe shall meet, or exceed, current AWWA C151 specifications for ductile iron water pipe.
- 3. Water Mains and services shall have a minimum cover of 5'. Where top of water main is less than 5'-0" below finished grade, the Contractor shall install rigid insulation in conformance with the typical water trench detail.
- 4. All water mains shall be encased in polyethylene encasement (polywrap). See specification section 02611W.
- 5. At pipe crossings, one full length of water pipe shall be located so both joints will be as far from the sewer/drain pipe as possible. Special structural supports for the water and sewer pipes may be required.
- 6. All materials coming in physical contact with drinking water must be certified to meet the ANSI/NSF Standard 61 by either the Underwriters Labs (UL) or the National Sanitation Foundation (NSF).
- 7. Disinfection and testing of water lines shall be done in accordance with Cith of Portsmouth and current AWWA
- 8. All existing water pipe identified to be abandoned shall be capped at all exposed ends and abandoned in place unless removal is required because of other interferences (incidental).
- 9. The contractor shall use restraint systems on all valves and fittings unless otherwise noted on the plans.
- 10. All gate valves shall have restrained mechanical joints and shall open left.
- 11. Existing curb box and/or other castings disturbed or relocated by construction activities shall be adjusted to match final grade, unless otherwise directed by the Engineer (subsidiary).
- 12. Where water main is less than 4'-0" horizontally from a structure, the contractor shall install 2 inches of rigid insulation along the side wall of the water main trench a minimum of 10'-0" horizontally beyond the centerline of the structure in both directions to protect the water main from freezing.
- 13. Maintain a minimum of 10 feet horizontal distance between water main and sewer piping. Notify Engineers if any discrepancy.
- 14. Existing fire hydrants shall be removed, decommissioned below grade, and delivered to a location specified by the City.
- 15. The Contractor shall install the Water Service Connections (including service saddles if required, live taps, corporations, curb stop, curb box, and PE water service pipe with tracer wire at the size specified in the service schedule) and connect the existing water service to the new curb box. The new service shall be connected to the existing service pipe past the curb stop unless the existing water service pipe is galvanized cast iron, galvanized steel or lead; in this case, the Contractor shall notify the City and Engineer.

				I
URAL				
NH Portland, ME	7	CONSERVATION COMMISSION SUBMISSION	07/24/2019 JFM	JFI
201741-4220	1	TAC WORK SESSION SUBMISSION	07/09/2019 JFH	JFI
rs.com	no.	revision	date	by

ENGINEERS	CIVIL/ENVIRONMENTAL/STRUCTURAL	Portsmouth, NH Manchester, NH Portlar 603/431-6196 603/627-0708 207/54	c m a e n g i n e e r s . c
MILLE	OF NE	EW HAMP	



				ĺ
		Notes		-
scale:	208	Recreation Fields	1	
	1119 NOTES.dwg	680 Peverly Hill Road	10°	of
approved b	file name:			
AGL	1119	Multi-purpose Recreation Fields	G	
drawn by:	project no:	Department of Public Works		
	July 2019	. :		et:
iq pəubisəp	date:	City of Portsmouth New Hampshire		she


PERMIT PLANS

ABBREVIAT	TIONS:			GENERAL S'	YMBOLS:
ABBREV. @	<b>MEANING</b> AT	<b>ABBREV.</b> STD	<b>MEANING</b> SINGLE TILE DUCT	<u>EXISTING</u>	UTILITY POLE & GUY WIRE
ABD ABAN	ABANDONED ABANDON IN PLACE	STY SW	STORY SIDEWALK	UPL CP JA	UTILITY POLE W/ LIGHT LIGHT POLE
ACP	ASBESTOS CEMENT PIPE	T&B.	TOP AND BOTTOM	₩B □ ⊗	MAILBOX VENT PIPE
ADD'L APPROX	ADDITIONAL APPROXIMATE	TBC TCC	TOP BACK OF CURB TRAFFIC CONTROL CABINET		SIGNS (TWO POSTS)
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS	TD TEL	TELEDUCT TELEPHONE CONDUIT/DUCT BANK	<ul><li></li></ul>	GRANITE BOUND FOUND DRILL HOLE FOUND
BTM BH	BOTTOM BRADLEY HEAD	TH TL	TOP OF HATCH TRAFFIC LIGHT CONDUIT	0	IRON PIPE/ROD FOUND METAL POST
BIT BLDG	BITUMINOUS CONCRETE BUILDING	TOH	TOP OF HOOD	Δ	GRANITE OR CONC. POST
BMP	BUILDING MONITORING POINT	TOW TRAF	TOP OF WALL Traffic conduit	çço GG	FIRE HYDRANT GAS GATE VALVE
BOW BR	BOTTOM OF WALL BRICK	TS TYP	TRAFFIC SIGNAL TYPICAL	WG °	WATER GATE VALVE
CB C.B.	CATCH BASIN CONCRETE BOUND	UMP UNK	UTILITY MONITORING POINT UNKNOWN	cs E	WATER CURB STOP VALVE ELECTRIC BOX
CBCI CC	CATCH BASIN WITH CURB INLET CAST—IN—PLACE CONCRETE	UP	UTILITY POLE	СВ	CATCH BASIN
CEM	CEMENT CLEAR	VC VERT	VITRIFIED CLAY VERTICAL	DMH O EMH	DRAIN MANHOLE ELECTRIC MANHOLE
CL Q	CENTER LINE	VGC W	VERTICAL GRANITE CURB WATER	™ <b>(W)</b>	TELEPHONE MANHOLE WATER MANHOLE
CLF CI	CHAIN LINK FENCE CAST IRON	W/ WC	WITH WYE CONNECTION	SMH (M)	SEWER MANHOLE MANHOLE
CICL CIP	CAST IRON CEMENT—LINED CAST IN PLACE	WIP	WROUGHT IRON PIPE	⊕ 6	BUSH/SHRUB
C.O. CONC	CLEAN OUT CONCRETE	WM WMH	WATER METER WATER MANHOLE	M	TREE STUMP
CONN	CONNECTION	WFLG	WETLAND FLAG		CONIFEROUS TREE
COR CP	CORNER CONCRETE PIPE				DECIDUOUS TREE
CMP CSE	CORRUGATED METAL PIPE COBBLE STONE EDGE			<b>9</b>	ROCK
D DEPT	DRAIN DEPARTMENT			± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ±	BORING
DH	DRILL HOLE DUCTILE IRON			WF# 🛆	WETLAND WETLAND FLAG
DI DIA	DIAMETER			\til\til\til\til\til\til\til\til\til\til	SPOT LIGHT GUY WIRE
DICL DIA	DUCTILE IRON CEMENT—LINED DIAMETER				EDGE OF PAVEMENT STOCKADE FENCE
DISCH DMH	DISCHARGE DRAIN MANHOLE			×335.2	EROSION CONTROL FIBER ROLL SPOT ELEVATION
DLY DT	DOUBLE SOLID YELLOW LINE DRAIN TILE			x335.2	City LAYOUT LINE
DWG	DRAWING			s	OVERHEAD WIRES SEWER LINE
EA EF	EACH EACH FACE			d	DRAIN LINE GAS LINE
EM E-VAULT	ELECTRIC METER ELECTRIC—VAULT			— w —	WATER SERVICE UNDERGROUND UNDERGROUND ELECTRIC LINE
EL, ELEV ELEC, E	ELEVATION ELECTRIC			—— uge —— ——— — —	APPROX. ABUTTERS
EOP	EDGE OF PAVEMENT EXISTING				LOT LINE SHRUB LINE
EXIST ESHWL	EXIST. SEASONAL HIGH WATER			·~~~~~	TREE LINE STONE WALL
F&C	LEVEL FRAME AND COVER			0 0	GUARDRAIL MAJOR CONTOUR LINE
FA FD	FIRE ALARM FLOOR DRAIN				MINOR CONTOUR LINE
FED FH	FEDERAL FIRE HYDRANT				EASEMENT LINE WETLAND LINE
FM FND	FORCE MAIN FOUND			W	STATE HIGHWAY LAYOUT LINE WATER MAIN
FP FT	FLAG POLE				BOLLARD SLOPE LINE
GM	FOOT GAS METER				CONSTRUCTION BASELINE THRUST BLOCK
GRAN HDPE	GRANITE HIGH DENSITY POLYETHYLENE				THINGST BEGON
HH HORIZ	HAND HOLE HORIZONTAL				
HYD H/C	HYDRANT HANDICAP				
INV	INVERT				
IN IP	INCHES IRON PIPE				
L MBOX	LEAVE MAIL BOX				
MHB MHW	MASS HIGHWAY BOUND MEAN HIGH WATER				
MIN MON	MINIMUM MONUMENT				
NIC	NOT IN CONTRACT				
NO, # NTS	NUMBER NOT TO SCALE				
PB PC	PULL BOX PRECAST CONCRETE				
PCCP	PRESTRESSED CONCRETE CYLINDER PIPE				
PCI PERF	PIT CAST IRON PEFORATED				
PM PNS	PARKING METER PIPE NOT SEEN				
PROP PSI	PROPOSED  POUNDS PER SQUARE INCH				
PVC	POLYVINYL CHLORIDE				
R REC	REMOVE/RELOCATE RECORD INFORMATION				
REINF RES	REINFORCEMENT REVERE EXTENSION SEWER				
RET RCP	RETAIN REINFORCED CONCRETE PIPE				
RS	RECEIVING SHAFT				
ROW SB	RIGHT-OF-WAY STREET LIGHT BASE				
S.B. SD	STONE BOUND STORM DRAIN				
SF SGC	FIRE SERVICE SLOPED GRANITE CURB				
SLCC SMH	STREET LIGHT CONTROL CABINET SEWER MANHOLE				
SPEC	SPECIFICATION				
SWL SQ	SINGLE WHITE LINE SQUARE				
S ST	SANITARY SEWER STEEL				

ENERAL	SYMBOLS:	
<u>EXISTING</u>		PROPOSED
UP. -O- UPL	UTILITY POLE & GUY WIRE	Q
UPL LP ** MB	UTILITY POLE W/ LIGHT LIGHT POLE	*
	MAILBOX	0
⊗ 	VENT PIPE SIGNS (TWO POSTS)	<del>- o -</del>
•	GRANITE BOUND FOUND	•
<ul><li>O</li></ul>	DRILL HOLE FOUND IRON PIPE/ROD FOUND	
	METAL POST	
Φ.	GRANITE OR CONC. POST FIRE HYDRANT	
GG GG	GAS GATE VALVE	₩.
WG o	WATER GATE VALVE	<b>1</b> 000 × 1000 ×
CS °	WATER CURB STOP	1,50
CB	VALVE ELECTRIC BOX	
DMH O	CATCH BASIN DRAIN MANHOLE	
EMH O	ELECTRIC MANHOLE	
TMH	TELEPHONE MANHOLE WATER MANHOLE	
SMH	SEWER MANHOLE	S
₩ <b>₩</b>	MANHOLE BUSH/SHRUB	
M	TREE STUMP	
	CONIFEROUS TREE	
0	DECIDUOUS TREE	
ව වි	ROCK	
₿ ₩	BORING	
WF# 🛆	WETLAND WETLAND FLAG	
111	SPOT LIGHT	
<del></del>	GUY WIRE — EDGE OF PAVEMENT	
	STOCKADE FENCE	
×335.2	EROSION CONTROL FIBER ROLL SPOT ELEVATION	131.75'
	— City LAYOUT LINE	•
s	— OVERHEAD WIRES — SEWER LINE	
d	- DRAIN LINE	
	— GAS LINE — WATER SERVICE UNDERGROUND	—— PWS ——
uge	UNDERGROUND ELECTRIC LINE	
	— APPROX. ABUTTERS — LOT LINE	
	SHRUB LINE	
	TREE LINE STONE WALL	· · · · · · · · · · · · · · · · · · ·
0 0	— GUARDRAIL	0
	MAJOR CONTOUR LINE MINOR CONTOUR LINE	
	EASEMENT LINE	
	— WETLAND LINE — STATE HIGHWAY LAYOUT LINE	
w	— WATER MAIN	PW
	BOLLARD SLOPE LINE	<del> </del>
	CONSTRUCTION BASELINE	302+00
	THRUST BLOCK	

			1	Ŧ				
						JFK	JFK	by
						07/24/2019 JFK	07/09/2019 JFK	date
						CONSERVATION COMMISSION SUBMISSION	TAC WORK SESSION SUBMISSION	revision
						7	1	no.
ENGINEERS  CIVIL/ENVIRONMENTAL/STRUCTURAL  Portsmouth, NH Manchester, NH Portland, ME 603/431-6196 603/627-0708 207/541-4223  C m a e n g i n e e r s . c o m								
JOSEPH H. KIEFFNER NO. 5517 CENSE ON AL EMILITING								
designed by:		drawn by:	AGL	approved by:		scale:		
date:	July 2019	project no:	6111	file name:	1119 NOTES.dwg	SC		
٩								

drawing no. **G-102** sheet: ---- of ----



# ABUTTERS LIST

MAP-LOT	OWNER OF RECORD	<u>DEED REFERENCE</u>
252-2-10 252-2-11	JMK REALTY LLC, PO BOX 971, PORTSMOUTH, NH 03802 HEG WEST ROAD LLC, 2 INTERNATIONAL WAY, LAWRENCE, MA 01843 60 WEST RD, PORTSMOUTH, NH 03801	3656/744 5835/67
252-2-12 252-2-14	ONE HUNDRED WEST LLC, 100 WEST RD, PORTSMOUTH, NH 03801 LITCHFIELD PORTSMOUTH LLC C/O EATON PARTNERS INC, 175 CANAL ST STE 401, MANCHESTER, NH 03101	3589/1427 4800/1185
252-3 52-4 & 252-5 253-4 253-5 253-5-1 254-7 254-8-1	LIGHTHOUSE MANUFACTURING LLC, 25 SOUTH SATELLITE RD, SOUTH WINDSOR, CT 06074 4 AMIGOS LLC, 321 LAFAYETTE RD, HAMPTON, NH 03842 DPH REALTY LLC, 30 MIRONA RD EXT, PORTSMOUTH, NH 03801 GERALD W. & TERESA M. REYNOLDS, 164 MASON RD, MILTON, NH 03851 BOURAS GROUP LLC, 10 MIRONA RD, PORTSMOUTH, NH 03801 PIKE INDUSTRIES, INC., 3 EASTGATE PARK RD, BELMONT, NH 03220 MCM ACQUISTION 2017 LLC ATTN: TAX DEPT NH22094—A, 8051 CONGRESS AVE, BOCA RATON, FL 33487—1307	N/A N/A N/A N/A N/A 3192/1085 N/A
266-1	RICCI CONSTRUCTION CO., INC., 225 BANFIELD RD, PORTSMOUTH, NH 03801	2527/322
266-3 266-4	ANDREW R. & CAROL ANN CROTEAU, 285 BANFIELD RD, PORTSMOUTH, NH 03801 FOUNDATION FOR SEACOAST HEALTH, 100 CAMPUS DR SUITE 1, PORTSMOUTH, NH 03801	2274/1868 3276/2980 & 3259/2178
266–5 267–17–1	HOPE FOR TOMORROW FOUNDATION, 1 STONERIDGE DR, RYE, NH 03870 300 WEST RD LLC, 300 WEST ROAD UNIT #1, PORTSMOUTH, NH 03801	5783/602 4453/1140
267-17-2 267-17-3 267-17-4	GRAYWOLF PROPERTIES LLC, 1 LIBBEY LN, RYE, NH 03870 GRAYWOLF PROPERTIES LLC, 1 LIBBEY LN, RYE, NH 03870 GRAYWOLF PROPERTIES LLC, 1 LIBBEY LN, RYE, NH 03870	4397/2371 4439/1934 4397/2371
267-19-1 267-19-2	BBJ PROPERTIES, INC., 38 RAINBOW LN, SANFORD, ME 04073 PETER PARADIS, 481 DENNETT ST, PORTSMOUTH, NH 03801	3396/126 3090/1083
267-19-3 267-19-4	KEVIN J. DUPLISEA, 270 WEST RD #3, PORTSMOUTH, NH 03801 WEST ROAD EQUIPMENT LLC, 270 WEST RD UNIT 4A, PORTSMOUTH, NH 03801	5564/2186 5059/2202
267-20 267-21 267-21	HARVEY PROPCO LLC, 1400 MAIN ST, WALTHAM, MA 02451 P A M REALTY TRUST C/O CP MANAGEMENT, INC., 11 COURT ST. SUITE 100, EXETER, NH 03833 STERLING REALTY, INC., 143 PINELOCH DR, PORTLAND, ME 04103	5660/1693 4438/828 2762/2839
267-22 267-23 273-5	MICRONICS, INC., 200 WEST RD, PORTSMOUTH, NH 03801 ENGEL FAMILY TRUST, ROBERT ENGEL TRUSTEE, PO BOX 6070, MANCHESTER, NH 03108 BELLWOOD ASSOCIATES LTD PARTNERSHIP C/O FESTIVAL FUN PARK PROPERTY TAX SERVICES	5423/2254 3459/1842 3471/2972
= 7 0 0	DO DOV 547405 DALLAC TV 75754	01,1,20,2

#### NOTES:

PO BOX 543185, DALLAS, TX 75354

- 2. THE RELATIVE ERROR OF CLOSURE WAS LESS THAN 1 FOOT IN 15,000 FEET.
- 3. THIS PLAN IS BASED ON A FIELD SURVEY, INFORMATION FROM PLANS OF RECORD AND AERIAL MAPPING BY EASTERN TOPOGRAPHICS. PRIMARY BM: CITY CONTROL POINT "INDU" HORIZONTAL DATUM: NAD 1983 (1986 CONTROL ADJUSTMENT) VERTICAL DATUM: NAVD 1988
- 4. THE LOCATION OF ALL UNDERGROUND UTILITIES SHOWN HEREON ARE APPROXIMATE AND ARE BASED UPON THE FIELD LOCATION OF ALL VISIBLE STRUCTURES (IE CATCH BASINS, MANHOLES, WATER GATES ETC.) AND INFORMATION COMPILED FROM PLANS PROVIDED BY UTILITY COMPANIES AND GOVERNMENTAL AGENCIES. ALL CONTRACTORS SHOULD NOTIFY, IN WRITING, SAID AGENCIES PRIOR TO ANY EXCAVATION WORK AND CALL DIG—SAFE @ 1—888—DIG—SAFE.
- 5. THE SUBJECT TRACTS LIE IN ZONE X (UNSHADED), AREAS DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN, AS SHOWN ON FLOOD INSURANCE MAP NO. 33015CO270E, EFFECTIVE DATE MAY 17, 2005, BY FEMA.
- 6. PARCEL 254-8 AND A PORTION OF PARCEL 266-4 ARE SUBJECT TO A RESTRICTIVE COVENANT AGREEMENT BETWEEN JOHN IAFOLLA CO., INC. & PIKE INDUSTRIES, INC., SEE RCRD BOOK 3192, PAGE 1088, BOOK 3193, PAGE 2059 AND BOOK 3198, PAGE 853.
- 7. WETLANDS DELINEATION 10/2018 BY GZA ENVIRONMENTAL.
- 8. ENGINEER OR CONTRACTOR TO VERIFY SITE BENCHMARKS BY LEVELING BETWEEN 2 BENCHMARKS PRIOR TO THE SETTING OR ESTABLISHMENT OF ANY GRADES/ELEVATIONS. DISCREPANCIES ARE TO BE REPORTED TO JAMES VERRA AND ASSOC., INC.

# WETLAND DELINEATION NOTES:

- 1. JURISDICTIONAL WETLANDS WERE DELINEATED BY GZA GEOENVIRONMENTAL, INC. (GZA) ON OCTOBER 19 AND 22, 2018, AND APRIL 24, 2019, IN ACCORDANCE WITH THE 1987 U.S. ARMY CORPS OF ENGINEERS' (ACOE) "WETLANDS DELINEATION MANUAL," TECHNICAL REPORT Y-87-1 AND THE "REGIONAL SUPPLEMENT TO THE CORPS OF ENGINEERS WETLAND DELINEATION MANUAL, NORTHCENTRAL AND NORTHEAST REGION." JANUARY 2012.
- 2. GZA EVALUATED WETLANDS AS POTENTIAL VERNAL POOLS ON APRIL 24, 2019 IN ACCORDANCE WITH THE NH CODE OF ADMINISTRATIVE RULES (ENV-WT 101.75, 101.86, 101.106) AND THE MANUAL "IDENTIFICATION AND DOCUMENTATION OF VERNAL POOLS IN NEW HAMPSHIRE, NEW HAMPSHIRE FISH AND GAME DEPARTMENT, NONGAME AND ENDANGERED WILDLIFE PROGRAM. 2004.
- 3. GZA PERFORMED A WETLANDS FUNCTIONS AND VALUES ASSESSMENT ON OCTOBER 19 AND 22, 2018, AND APRIL 24, 2019, IN ACCORDANCE WITH THE ACOE'S "HIGHWAY METHODOLOGY WORKBOOK SUPPLEMENT," SEPTEMBER 1999, AND CLASSIFIED WETLANDS IN ACCORDANCE WITH THE "CLASSIFICATION OF WETLANDS AND DEEPWATER HABITATS OF THE UNITED STATES" (FEDERAL GEOGRAPHIC DATA COMMITTEE, 2013).

## WETLAND STANDARDS:

FEDERAL GEOGRAPHIC DATA COMMITTEE. 2013. CLASSIFICATION OF WETLANDS AND DEEPWATER HABITATS OF THE

UNITED STATES. FGDC-STD-004-2013. SECOND EDITION. WETLANDS SUBCOMMITTEE, FEDERAL GEOGRAPHIC DATA COMMITTEE AND U.S. FISH AND WILDLIFE SERVICE, WASHINGTON,

LICHVAR, R.W., D.L. BANKS, W.N. KIRCHNER, AND N.C. MELVIN. 2016. THE NATIONAL WETLAND PLANT LIST: 2016 WETLAND RATINGS. PHYTONEURON 2016—30: 1—17. PUBLISHED 28 APRIL 2016. ISSN 2153 733X


## WETLAND STANDARDS (CONTINUED):

NEW ENGLAND HYDRIC SOILS TECHNICAL COMMITTEE. 2019. VERSION 4. FIELD INDICATORS FOR IDENTIFYING HYDRIC SOILS IN NEW ENGLAND, INTERSTATE WATER POLLUTION CONTROL COMMISSION, LOWELL, MASSACHUSETTS.

U.S. ARMY CORPS OF ENGINEERS, ENVIRONMENTAL LABORATORY. 1987. CORPS OF ENGINEERS WETLANDS DELINEATION MANUAL, TECHNICAL REPORT Y-87-1, U.S. ARMY ENGINEER WATERWAYS EXPERIMENT STATION, VICKSBURG, MISSISSIPPI.

U.S. ARMY CORPS OF ENGINEERS. 2012. REGIONAL SUPPLEMENT TO THE CORPS OF ENGINEERS WETLAND DELINEATION MANUAL: NORTHCENTRAL AND NORTHEAST REGION, ED. J. S. WAKELY, R. W. LICHVAR, AND C. V. NOBLE. ERDC/EL TR-12-1. VICKSBURY, MS: U.S. ARMY ENGINEER RESEARCH AND DEVELOPMENT CENTER.

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCE CONSERVATION SERVICE, 2018. FIELD INDICATORS OF HYDRIC SOILS IN THE UNITED STATES, VERSION 8.2. L.M. VASILAS, G.W. HURT, AND J.F. BERKOWITZ (EDS.). USDA, NRCS, IN COOPERATION WITH THE NATIONAL TECHNICAL COMMITTEE FOR HYDRIC SOILS.




## REFERENCE PLANS:

- AMENDED SITE PLAN, PROPERTY OF MICRONICS INC, 200 WEST ROAD, PORTSMOUTH, N.H., DATED 12/30/2014, RCRD PLAN D-38846.
- 2. LOT LINE REVISION PLAN, 755 BANFIELD ROAD REALTY, LLC, CONSTITUTION AVENUE, PORTSMOUTH, N.H., REVISED TO 11/28/2011, RCRD PLAN D-37091.
- DRAINAGE EASEMENT PLAN OVER LAND OF BELLWOOD ASSOCIATES LIMITED PARTNERSHIP, CAMPUS DRIVE, PORTSMOUTH, N.H., DATED 7/30/2007, RCRD PLAN D-35073.
- 4. ACTIVITY AND USE RESTRICTION EASEMENT PLAN FOR PORTSMOUTH DEPARTMENT OF PUBLIC WORKS, 680 PEVERLY HILL ROAD, PORTSMOUTH, N.H., REVISED TO 9/13/2006, RCRD PLAN D-34222.
- 5. LATTICE TOWER EASEMENT PLAN, PEVERLY HILL ROAD, PORTSMOUTH, N.H., FOR MESSAGE CENTER MANAGEMENT, REVISED TO 4/16/2002, RCRD PLAN D-30056.
- 6. FOUNDATION FOR SEACOAST HEALTH, PORTSMOUTH, N.H., LOT LINE ADJUSTMENT, JOHN IAFOLLA COMPANY, INC. AND CITY OF PORTSMOUTH, REVISED TO 4/14/1998, RCRD PLAN D-26202.
- 7. SUBDIVISION & LOT LINE RELOCATION PLAN FOR PIKE INDUSTRIES, INC. & JOHN IAFOLLA COMPANY, INC, PEVERLY HILL ROAD/ BANFIELD ROAD, PORTSMOUTH, N.H., REVISED TO 11/21/1997, RCRD PLAN D-26136.
- 8. SUBDIVISION PLAN FOR JOHN IAFOLLA COMPANY, INC., PEVERLY HILL ROAD/ BANFIELD ROAD, PORTSMOUTH, N.H., REVISED TO 11/20/1996, RCRD PLAN D-25124.
- 9. LOT LINE ELIMINATION PLAN FOR BELLWOOD ASSOCIATES LIMITED PARTNERSHIP, LAFAYETTE ROAD/ CONSTITUTION AVENUE, PORTSMOUTH, N.H., DATED 9/3/1991, RCRD PLAN D-21288.
- 10. PLAN OF DRAINAGE EASEMENT FOR LAFAYETTE WEST CORP & FFP INTERIM PARTNERS, WEST ROAD, PORTSMOUTH, N.H., REVISED TO 3/28/1989, RCRD PLAN D-22902.
- 11. SUBDIVISION PLAN, LINCOLN AND MARY HANSCOM, PORTSMOUTH, N.H., DATED 1/1983, RCRD PLAN D-11441.
- 12. LOT LINE REVISION PLAN, CAMPUS DRIVE, BANFIELD & PEVERLY HILL ROADS, PORTSMOUTH, N.H., FOR CITY OF PORTSMOUTH, N.H. & FOUNDATION FOR SEACOAST HEALTH, REVISED TO 12/14/2016, RCRD PLAN D-39897.

							by
							date
							revision
					, ME	4223	m no.
		HIRAI	i i		NH Portland, ME		ers.co
	RS	JENTAL /STRUCT			Manchester, NH		c m a e n g i n e e r s . c o m
CM	ENGINEERS	GIVII /ENVIBONMENTAI /STBLICTUBAI			Portsmouth, NH Manchester, NH Portland, ME	003/43 1-0 130	c m a e n
designed by:	drawn by:	AGL	approved by:	-	je:	,009	= 300′
date: July 2019	project no:	1119	file name:	1119 ECP.dwg	scale:	300,	Scale: 1" = 300'
of Portsmouth, New Hampshire	ublic Works	Ilti-nurnose Recreation Fields				ditions Plan	
City of Portsmouth,	Department of Public Works	Multi-numose Re	Stood Ball	680 Peverly Hill Road		Existing Conditions Plan	
City of Portsmouth,	Department of Pu	dra	wing	g n		Existing Con	

M:\CADD\PROJECTS\1119 Portsmouth Athletic fields\Production\1119 ECP.dwg Date Plotted: Jul 23, 2019 - 4:46pm Plotted By: JKIEFFNER



# 254-8-1ASPHALT CELL TOWER PAVEMENT ELECTRICAL EQUIPMENT TELEPHONE-\_\_\_\_\_D ~ VAULT CATV VAULT APPROXIMATE LOCATION OF UTILITIES EASEMENT PER RCRD D-30056ALSO SEE 3739/1560 254-8 252-2-10 252-2-11

## DRAIN & SEWER TABLE

RIM EL= 49.52 (1) INV IN 15"HDPE= 42.40 (2) INV OUT 15"HDPE= 42.30

DMH B

DMH C

RIM EL= 46.87 (1) INV IN 12"HDPE= 43.10 (2) INV IN 12"HDPE= 43.37 (3) INV OUT 15"HDPE= 43.67

CB 44

RIM EL= 45.55

CB 53 RIM EL= 46.69 (1) INV OUT 12"HDPE= 43.35

CB 54 RIM EL= 44.37 (1) INV IN 15"HDPE= 41.26 (2) INV IN 12"HDPE= 41.19 (3) INV OUT 18"HDPE= 41.10

CB 55 RIM EL= 49.67 (1) INV OUT 12"HDPE= 43.00

CB 56

RIM EL= 47.97 (1) INV OUT 12"HDPE= 44.05

RIM EL= 27.63 (1) INV IN 24"HDPE= 23.81 (2) INV OUT 24"HDPE= 23.73

CB A

RIM EL= 27.41 (1) INV IN 24"HDPE= 23.43 (2) INV OUT 24"HDPE= 23.41

CB C RIM EL= 27.22 (1) INV IN 24"HDPE= 23.24 (2) INV OUT 24"HDPE= 23.26

SMH 5557 RIM EL= 52.36 (1) INV IN 4"PVC FM=  $48.1\pm$ (2) INV OUT 8"PVC= 47.7±


\mht2\MHT-Projects\CADD\PROJECTS\1119 Portsmouth Athletic fields\Production\1119 ECP.dwg Date Plotted: Jul 23, 2019 - 7:55am Plotted By: SFORTIER

INV OUT 18"HDPE= 40.0± (1) INV IN 18"HDPE= 40.39 (2) INV IN 15"HDPE= 39.73 INV OUT 18"HDPE= 39.65 (3) INV OUT 18"HDPE= 40.08 BRICK WEIR FLOW LINE FOR (4) = 41.23INV OUT 24"RCP= 33.54 (4) INV OUT 18"HDPE= 40.24 INV C2 INV OUT 24"RCP= 33.56 DMH B & DMH C ARE VORTECHNICS DRAINAGE TREATMENT STRUCTURES INV IN = 22.31RIM EL= 48.99INV E RIM EL= 49.03INV OUT= 21.90 TRAPEZOIDAL WEIR EL= 41.73
(1) INV OUT 18"HDPE= 39.88 INV OUT 24"HDPE= 23.06 DROP INLET 1 CONCRETE COVER EL= 51.58 INV IN 24"HDPE= 23.89 2 SIDE INLETS 0.85 W X 0.70 H INV H (PERFORATED PIPE) INLET EL= 50.71 INV OUT 6"HDPE= 24.52 (1) INV OUT 18"HDPE= 46.26 INV I (PERFORATED PIPE) INV IN 6"HDPE= 30.63 INV IN 15"HDPE= 31.83 INV IN 15"HDPE= 31.78 INV K1 INV OUT 15"HDPE= 30.66 INV K2 INV OUT 15"HDPE= 30.90

INV IN 18"HDPE= 45.26 INV IN 18"HDPE= 45.23 INV IN 18"HDPE= 45.23 INV O (UNDERDRAIN) INV OUT 4"PVC= 46.05 INV P (UNDERDRAIN) 54"W X 42"H ARCHED CMP INV OUT 4"PVC= 46.15 INV Q1 INV OUT 18"HDPE= 44.90 54"W X 42"H ARCHED CMP INV Q2 INV OUT 18"HDPE= 44.92 INV Q3 INV OUT 18"HDPE= 44.84 INV R1 INV OUT 36"CMP= 27.33 INV R2 INV OUT 36"CMP= 27.32 INV S1 INV IN 36"CMP= 30.68 INV S2 INV IN 36"CMP= 30.64 INV T1 INV IN 24"RCP= 35.22 INV T2 INV IN 24"RCP= 35.47 INV IN 12"HDPE= 41.23 INV OUT 18"HDPE= 45.80

INV M (UNDERDRAIN)

INV OUT 4"PVC= 46.63



# TBM TABLE

WESTERLY CORNER OF CONCRETE TRANSFORMER PAD EL= 49.68

BOLT W/ "X" CUT HYDRANT TOP FLANGE EL= 48.63

TBM 3 BOLT W/ "X" CUT HYDRANT TOP FLANGE EL= 53.92

TBM 4 SURVEY SPIKE SET IN BASE 30" PINE EL= 42.40 (0.5' ABOVE GROUND)

TBM 5 MARKED BOLT HYDRANT LOWER FLANGE EL= 52.07

CHISELLED SQUARE FOUND IN LEDGE OUTCROP EL= 40.09 (AT GROUND EL.)

SPIKE FOUND IN BASE 30" PINE EL= 37.19 (0.5' ABOVE GROUND)

IRON PIPE BOUND as DESCRIBED WOOD HUB DRILL HOLE . CHAIN LINK FENCE ..WOOD FENCE **—** - - - - - .... ..GUARD RAIL \_\_\_\_\_\_... .WOOD FENCE POST ∅.... ..BARBED WIRE FENCE — *x* — ..... 110-5 . TAX SHEET — LOT NUMBER RCRD . ROCKINGHAM COUNTY REGISTRY OF DEEDS EOP.. ..EDGE OF PAVEMENT SGC.. SLOPED FACED GRANITE CURB VGC... ..VERTICAL FACED GRANITE CURB RWBL. .MODULAR BLOCK RETAINING WALL RWC... ..CONCRETE RETAINING WALL RWM... .MORTARED RETAINING WALL RWS.... ..STONE RETAINING WALL ⊕... .BOLLARD <del>。</del> .. .DOUBLE POST SIGN SIGNAL JUNCTION BOX ..LIGHT POLE . ELECTRICAL CONDUIT .PAD MOUNTED TRANSFORMER .ELECTRICAL PANEL .ELECTRICAL BOX ..ELECTRIC METER .TELEPHONE MANHOLE .GAS VALVE .WATER GATE VALVE .HYDRANT .CATCH BASIN .CATCH BASIN ..DRAIN MANHOLE .SEWER MANHOLE TREE LINE ~~... ..BRUSH LINE .CONIFEROUS TREE .DECIDUOUS TREE . WATER LINE - w - .... SEWER LINE -s - ....DRAIN LINE -D- ...... . GAS LINE — G — ...... FORCE MAIN — *FM* — —UGC— . UNDERGROUND COMMUNICATIONS .. UNDERGROUND ELECTRIC —UGE— .BORING .TEST PIT . CEMENT CONCRETE . CRUSHED STONE 20209... **...** . RETAINING WALL ...LANDSCAPED AREA

..SPOT GRADE

LEGEND:

 $\infty$ 


<u>LA</u> .....


×12.5....


STONE WALL


. IRON ROD


City of Portsmouth, New Hampshire  July 2019  Department of Public Works  Project no. 1119  AGL  Multi-purpose Recreation Fields  Residued by: 1119  AGL  Civil-Environmental/Structural.  Augusting Conditions Plan					date
City of Portsmouth, New Hampshire  Department of Public Works    Condition					
City of Portsmouth, New Hampshire  Department of Public Works  Multi-purpose Recreation Fields  Scale: 17 = 20'  Gate: July 2019  Integration Grawn bands  AGL  AGL  AGL  AGL  AGL  AGL  AGL  AG	CMA	ENGINEERS	(	Fortsmouth, NH Manchester, NH Portland, ME 603/431-6196 603/627-0708 207/541-4223	
City of Portsmouth, New Hampshire  Department of Public Works  Multi-purpose Recreation Fields  Sealer  Existing Conditions Plan  Scaler	designed by:	drawn by: AGL	approved by:	0	= 20′
drawing no. V-203	date: July 2019	project no: 1119	file name: 1119 ECP.dwg	scal	
V-203	City of Portsmouth, New Hampshire	Department of Public Works		Existing Conditions Plan	
·			_		



















































NOTE: 1. REFUSALS NOT ENCOUNTERED DURING SUBSURFACE EXPLORATIONS WERE ASSUMED TO BE AT THE BOTTOM OF THE EXPLORATION.

- 2. LINES REPRESENTING THE WATER SURFACE AND REFUSAL PROFILES WERE INTERPOLATED BETWEEN BORINGS AND TEST PITS. ACTUAL FIELD ELEVATIONS MAY VARY.
- 3. SHWL DATA NOT MEASURED AT PIEZOMETERS/BORINGS WAS ASSUMED TO BE 1 FOOT BELOW EG AT THE LIMITS OF DELINEATED WETLANDS AND INTERPOLATED IN BETWEEN. ACTUAL FIELD ELEVATIONS MAY VARY.


		19 JFK	19 JFK	by
		07/24/2019 JFK	07/09/2019 JFK	date
		CONSERVATION COMMISSION SUBMISSION	TAC WORK SESSION SUBMISSION	revision
		7	1	no.
	TURAL	, NH Portland, ME	20134-14223	ers.com

ENGIN	CIVIL/ENVIR	Portsmouth 603/431-6	ه 2
THE POOR OF THE PROPERTY OF TH	JOSE H KIEFF	HAMOSHINE - RITER - RI	P


designed by: 	drawn by: AGL	approved by:	scale: 20' 40' Scale: 1" = 20'
date: July 2019	project no: 1119	file name: 1119 Field Site Sections.d/vg	SC3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
City of Portsmouth, New Hampshire	Department of Public Works	1089 1089	Recreation Fields Site Sections - Phase 1
		wing no.	2
sheet:		of	



								date b
								revision
		ENGINEERS	CIVII /ENVIBONMENTAI /STBIICTIIBAI		Dortzes NI Mascachar NI Dortzes ME	603/431-6196 603/627-0708 207/541-4223		c m a e n g i n e e r s . c o m
designed by:	-	drawn by:	AGL	approved by:				
date:	July 2019	project no:	1119	file name:		scale:		
City of Portsmouth. New Hampshire		Department of Public Works	Multi-nurpose Recreation Fields	680 Deverty Hill Road	DOOT EVELLY LITTINGED		Storm Water Sections & Details	
				wing		 1		



Not to Scale




AT A DEPTH SUCH THAT THE CROWN OF

THE CULVERT IS AT LEAST 2' BELOW GRADE


Typical Drainage Pipe

Not to Scale



### Stone Outlet Protection

Not to Scale



NOTES:

1. HORIZONTAL JOINTS BETWEEN
SECTIONS OF PRECAST CONCRETE
BARRELS SHALL BE OF A TYPE
APPROVED BY THE ENGINEER, WHICH
SHALL, IN GENERAL, DEPEND FOR
WATERTIGHTNESS UPON AN
ELASTOMERIC OR MASTIC—LIKE
GASKET.

2. PIPE-TO-MANHOLE JOINTS SHALL BE ONLY AS APPROVED BY THE ENGINEER AND IN GENERAL WILL DEPEND FOR WATERTIGHTNESS UPON EITHER AN APPROVED NON-SHRINKING MORTAR OR ELASTOMERIC SEALANT.

3. FOR BITUMASTIC TYPE JOINTS, THE AMOUNT OF SEALANT SHALL BE SUFFICIENT TO FILL AT LEAST 75% OF THE JOINT CAVITY. APPROVED BITUMASTIC SEALANTS INCLUDE RAM-NEK, KENT SEAL NO. 2, EZ OR FQUAL.

4. THE TONGUE OR THE GROOVE OF THE JOINT OF THE WALL SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQ.IN. PER LINEAR FOOT.

5. ECCENTRIC CONES SHALL BE USED WHEN DEPTH TO CROWN OF SHALLOWEST PIPE EXCEEDS 30". RISERS OF 12", 36" AND 48" CAN BE USED TO REACH THE DESIRED DEPTH.

6. MANHOLE COVERS TO BE NHDOT TYPE B GRAY IRON.


7. ROOF LATERALS TO TIE INTO MANHOLE 4' MIN BELOW GRADE.

### **Drain Manhole**

Not to Scale


designed by: 	drawn by:	AGL	approved by:	-	scale:	
даге. July 2019	project no:	1119	file name:	1119 DETAILS.dwg	208	
City of Portsmouth, New Hampshire	Department of Public Works	Multi-purpose Recreation Fields		680 Peverly Hill Road	Drainage Details	
	(			ng no. -9(		
sheet:				of		

Portland, ME 207/541-4223




### "Silt Sack" Sediment Control Device for Inlet Protection


#### Not to Scale




### **Temporary Tree Protection**

Not to Scale









- 1. PLACE CRUSHED STONE TO WITHIN 6" OF TOP OF DRAINAGE WAY.
- 2. FOR ACTIVE DRAINAGE OUTFLOW CHECK DAMS SHALL BE PLACED IN SERIES ALONG FLOW LINE TO RETAIN SEDIMENTS.

### Stone Check Dam

Not to Scale






### **Erosion Control Notes:**

- 1. PERIMETER CONTROLS TO BE INSTALLED PRIOR TO EARTH MOVING OPERATIONS
- 2. PRIOR TO CONSTRUCTION AND THEREAFTER EROSION CONTROL MEASURES ARE TO BE IMPLEMENTED AS NOTED. PONDS AND SWALES SHALL BE INSTALLED EARLY ON IN THE CONSTRUCTION SEQUENCE (BEFORE ROUGH GRADING THE SITE).
- 3. THE SMALLEST PRACTICAL AREA OF LAND SHOULD BE EXPOSED AT ANY ONE TIME DURING DEVELOPMENT. WHEN LAND IS EXPOSED DURING DEVELOPMENT, THE EXPOSURE SHOULD BE KEPT TO THE SHORTEST PRACTICAL PERIOD OF TIME. LAND SHOULD NOT BE LEFT EXPOSED DURING THE WINTER MONTHS.
- 4. CATCH BASIN INSERTS, MIRAFI DANDY SACK OR EQUAL, SHALL BE INSTALLED AND MAINTAINED AT CATCH BASINS UNTIL PAVEMENT IS INSTALLED. SEDIMENT AND DEBRIS SHALL BE REMOVED FOLLOWING EACH STORM EVENT.
- 5. ALL DISTURBED AREAS AND SIDE SLOPES WHICH ARE FINISH GRADED WITH NO FURTHER CONSTRUCTION TO TAKE PLACE SHALL BE SEEDED AND MULCHED. ALL DISTURBED AREAS OUTSIDE LIMITS OF BUILDING, AND PAVEMENT SHALL BE STABILIZED WITH LOAM AND SEED. ALL SEED, LIME AND FERTILIZER PROGRAMS SHALL CONFORM TO ALL APPLICABLE SECTIONS OF THE SPECIFICATIONS.
- 6. ANY DISTURBED AREAS WHICH ARE TO BE LEFT TEMPORARILY, OR LONGER THAN TWO WEEKS AND WHICH WILL BE RE-GRADED LATER DURING CONSTRUCTION, SHALL BE TEMPORARILY SEEDED AND MACHINE STRAW MULCHED AT A RATE OF 1.5 TONS/ACRE.
- 7. AVOID USE OF UNDISTURBED AREAS WHEREVER POSSIBLE DURING CONSTRUCTION. CONSTRUCTION TRAFFIC SHALL TRAVEL THE ROADBEDS OF EXISTING AND FUTURE ROADS AND SHALL BE LIMITED TO WITHIN THE LIMITS OF CONSTRUCTION NOTED ON THE PLANS.
- 8. SILT FENCES SHALL BE MINIMUM OF 36 INCHES HIGH WITH THE BOTTOM OF THE CLOTH KEYED INTO THE GROUND (SEE DETAIL). POSTS SHALL BE OF WOOD OR STEEL. SILT FENCE SHALL BE INSTALLED & MAINTAINED AS NEEDED TO PREVENT SEDIMENT FROM LEAVING THE CONSTRUCTION SITE. ADDITIONAL SILT FENCE MAY BE ADDED AS REQUIRED BY THE ENGINEER PRIOR TO ANY ON-SITE GRADING OR DISTURBANCE OF EXISTING SURFACE MATERIAL. IT SHOULD BE MAINTAINED DURING AND AFTER DEVELOPMENT TO REMOVE SEDIMENT FROM RUNOFF WATER AND FROM LAND UNDERGOING DEVELOPMENT. WHERE POSSIBLE NATURAL DRAINAGE WAYS SHOULD BE UTILIZED AND LEFT OPEN TO REMOVE CLEAN EXCESS SURFACE WATER. THE SILT FENCE IS TO BE MAINTAINED AND CLEANED UNTIL ALL SLOPES HAVE A HEALTHY STAND OF GRASS.
- 9. EROSION CONTROL DEVICES SHOWN REPRESENT MINIMUM MEASURES REQUIRED FOR EROSION CONTROL. THE CONTRACTOR SHALL TAKE ANY AND ALL NECESSARY MEASURES TO PREVENT TRANSPORTATION OF SEDIMENT BEYOND THE WORK AREA.
- 10. ALL SWALES SHALL BE STABILIZED PRIOR TO DIRECTING FLOW TO THEM.
- 11. AFTER ALL DISTURBED AREAS HAVE BEEN STABILIZED, THE TEMPORARY EROSION CONTROL MEASURES ARE TO BE REMOVED AND ACCUMULATED SEDIMENT DISPOSED OFF IN A LOCATION DESIGNATED BY THE OWNER.
- 12. WITHIN THE NEW HAMPSHIRE DEPARTMENT OF ENVIRONMENTAL SERVICES COMPREHENSIVE SHORELAND PROTECTION ACT 250' BUFFER, ONLY LOW PHOSPHATE, SLOW RELEASE NITROGEN FERTILIZER OR LIMESTONE, MAY BE USED ON LAWNS OR AREAS WITH GRASS.
- 13. ALL ROADWAYS AND PARKING LOTS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
- 14. ALL CUT AND FILL SLOPES SHALL BE SEEDED/LOAMED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
- 15. ALL EROSION CONTROLS SHALL BE INSPECTED WEEKLY AND AFTER EVERY 0.5" OF RAINFALL.
- 16. THE SMALLEST PRACTICAL AREA SHALL BE DISTURBED DURING CONSTRUCTION, BUT IN NO CASE SHALL EXCEED 5 ACRES AT ANY ONE TIME BEFORE DISTURBED AREAS ARE STABILIZED.
- 17. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:
  - BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED - A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED
- A MINIMUM OF 3" OF NO-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED
- 18. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
- 19. TEMPORARY SEEDING (IF USED) SHALL BE PERENNIAL RYE GRASS, SPREAD 0.7LB/1000 SQ. FT.

### 20. WINTER CONSTRUCTION NOTES

- ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS;
- ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS;

  — AFTER NOVEMBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE
- WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM




**Dewatering Basin (Section)** Not to Scale


sheet: ---- of ----

C-903

Recreation Fields erly Hill Road

**Erosion Control Fiber Roll** Not to Scale





### PARALLEL CURB RAMP DETAIL

### THE ORDER OF PREFERENCE FOR LOCATION OF CORNER RAMPS:

- 1. TWO SEPARATE RAMPS LOCATED ON TANGENT SIDEWALK AREA IMMEDIATELY OUTSIDE OF CORNER RADIUS.
- 2. TWO SEPARATE RAMPS SEPARATED BY 5' MINIMUM AS SHOWN ABOVE.
- 3. SINGLE RAMP SERVING TWO CROSSWALKS.

#### GENERAL NOTES

- 1. THE MAXIMUM RUNNING SLOPE OF ANY SIDEWALK CURB RAMP IS 12:1, THE MAXIMUM CROSS SLOPE IS 2%. THE SLOPE OF THE LANDING SHALL NOT EXCEED 2% IN ANY DIRECTION. RAMP RUNNING SLOPE EXCEPTION: A GREATER THAN 8.33% RAMP RUNNING GRADE IS ALLOWED WHERE THE THE ROADWAY AND THE SIDEWALK(S) ARE PARALLEL AND VERY CLOSE TOGETHER, WITH THE SAME GRADE, AND USING A GRADE OF 8.33% WOULD RESULT IN A RAMP LENGTH LONGER THAN 15'. IN THOSE CIRCUMSTANCES USE A MAXIMUM RAMP LENGTH OF 15' AND THE ALLOWABLE RUNNING SLOPE OF THE RAMP(S) IS GREATER THAN 8.33%
- 2. TRANSITIONS SHALL BE FLUSH AND FREE OF ABRUPT CHANGES. ROADWAY SHOULDER SLOPES ADJOINING SIDEWALK CURB RAMPS SHALL BE A MAXIMUM OF 5% (FULL WIDTH) FOR A DISTANCE OF 2 FT. FROM THE ROADWAY CURB LINE.
- 3. INTERCEPT DRAINAGE ALONG THE CURB IN ADVANCE OF SIDEWALK CURB RAMPS OR LANDINGS. CATCH BASINS, MANHOLES, ETC. SHALL NOT BE LOCATED IN, OR AT THE BASE OF, SIDEWALK CURB RAMPS OR LANDINGS.
- 4. THE BOTTOM OF THE SIDEWALK CURB RAMP OR LANDING, EXCLUSIVE OF THE FLARED SIDES, SHALL BE WHOLLY CONTAINED WITHIN THE CROSSWALK MARKINGS.
- 5. THE SURFACE OF A PERPENDICULAR SIDEWALK CURB RAMP OR THE LANDING OF A PARALLEL SIDEWALK CURB RAMP SHALL CONTRAST VISUALLY WITH THE ADJOINING SIDEWALK SURFACE, EITHER ASPHALT/LIGHT—COLORED CONCRETE OR LIGHT—COLORED CONCRETE/DARK—STAINED CONCRETE. THE CONCRETE SURFACE SHALL BE SLIP RESISTANT.
- 6. DETECTABLE WARNING PANELS SHALL BE THE FULL WIDTH OF THE LANDING, BLENDED TRANSITION, OR CURB RAMP THEY ARE A PART OF AND SHALL BE A MINIMUM OF 2 FEET IN DEPTH. THE ROWS OF TRUNCATED DOMES SHALL BE ALIGNED PERPENDICULAR TO THE GRADE BREAK BETWEEN THE RAMP, BLENDED TRANSITION, OR LANDING AND THE STREET.



BLENDED TRANSITIONS HAVE A RUNNING SLOPE GREATER THAN 2% BUT LESS THAN 5%. CURB RAMPS HAVE A RUNNING SLOPE OF 5% MIN. TO 8.33% MAX. SIDEWALK, BLENDED TRANSITIONS, AND CURB RAMPS HAVE A MAX. CROSS SLOPE OF 2%.

CORNER PARALLEL RAMP DETAIL

BE PERPENDICULAR TO THE DIRECTION OF TRAVEL.

IF IT IS NECESSARY TO USE SIDEWALK WIDTHS 5'-0" OR LESS. PROVIDE A WIDENE

ALL GRADE BREAKS BETWEEN LANDINGS, RAMPS, AND BLENDED TRANSITIONS SHALL

IF IT IS NECESSARY TO USE SIDEWALK WIDTHS 5'-0" OR LESS, PROVIDE A WIDENED AREA A MINIMUM OF 5'-0" WIDE BY 5'-0" LONG SPACED AT INTERVALS OF 200' MAXIMUM TO ALLOW FOR USERS TO PASS EACH OTHER.

PROVIDE DETECTABLE WARNING SURFACES ANYTIME THAT A CURB RAMP, BLENDED TRANSITION, OR LANDING CONNECTS TO A STREET. PLACEMENT FOR DETECTABLE WARNING SURFACES ARE AS FOLLOWS:

#### PERPENDICULAR CURB RAMPS:

WHERE BOTH ENDS OF THE BOTTOM GRADE ARE LESS THAN 5'- 0" FROM THE BACK OF THE CURB, LOCATE THE DETECTABLE WARNING PANELS ON THE RAMP SURFACE AT THE BOTTOM OF THE RAMP. WHERE EITHER END OF THE BOTTOM GRADE IS GREATER THAN 5'-0" FROM THE BACK OF THE CURB, LOCATE THE DETECTABLE WARNINGS AT THE BOTTOM OF THE LANDING.

#### PARALLEL CURB RAMPS:


LOCATE THE DETECTABLE WARNING SURFACES AT THE BACK OF THE CURB ALONG THE EDGE OF THE LANDING.


### FOR BLENDED TRANSITIONS AND LANDINGS:


LOCATE THE DETECTABLE WARNING SURFACES AT THE BACK OF THE CURB.

# Sidewalk & Curb Ramp Details

Not to Scale









### Typical Vertical Granite Curb/Bituminous Sidewalk

Not to Scale



## Porous Pavement Path


Not to Scale



Typical Guardrail


Not to Scale

							revision
							no.
CMA	ENGINEERS	CIVII /ENVIBONMENTAI /STBLICTI IBAI			Portsmouth, NH Manchester, NH Portland, ME		c m a e n g i n e e r s . c o m
designed by:	drawn by:	AGL	approved by:				
				,	scale:		
date: July 2019	project no:	1119	file name:	1119 DETAILS.dwg			
City of Portsmouth, New Hampshire	Department of Public Works	Multi-purpose Recreation Fields		680 Peverly Hill Road		Miscellaneous Details	
City of P							
City of P		dra C	wing <b>-</b> 9	g no	5		



### Typical Water Main Trench

### Not to Scale




- 1. INSULATION TO BE USED WHERE VERTICAL PIPE SEPARATION IS 24" OR LESS AND HORIZONTAL SEPARATION WITH A SEWER MANHOLE OR OTHER OPEN STRUCTURE IS 6' OR LESS.
- 2. INSTALL VERTICAL MJ BENDS WITH RESTRAINED JOINT FITTINGS OR SWEEP PIPE WITHIN THE SPECIFICATION LIMITS IF NECESSARY TO ADJUST WATER MAIN PROFILE TO GAIN MINIMUM VERTICAL SEPARATION ABOVE SEWER.
- 2" OF INSULATION TO BE USED AROUND WATER SERVICE CONNECTIONS WHERE PIPE CROSSINGS OCCUR.
- WHERE WATER MAIN CROSSES SEWER AT 45° TO 90° PROVIDE MAXIMUM SPACING OF PIPE JOINTS FROM CROSSING LOCATION FOR BOTH WATER MAIN AND SEWER PIPE.

#### INDICATOR POST LIMIT OF PAY ITEM 3'-0: MIN. FROM APPROXIMATE LOCATION SHOWN ON DETAIL DRAWING EXACT LOCATION TO MARIES, SEE PLAN - MUELLER HYDRANT BE INDICATED BY THE OWNER/ENGINEER IN ADVANCE OF CONSTRUCTION IN FIELD -PROVIDE EXTENSIONS REQUIRED TO MEET PROPOSED GRADES (INCIDENTAL TO HYDRANT PAY ITEM) FINISH GROUND 6"DIA¬ -PLACE 2 LAYERS OF POLY AGAINST SURFACE HYDRANT SHOE BEFORE PLACING ADJUSTABLE VALVE THRUST BLOCK BOX WITH FLANGED -INSTALL THRUST BLOCK WITH 10 S.F. TOP SECTION BEARING AREA (MINIMUM) AGAINST UNDISTURBED SOIL -SET HYDRANT ON FLAT STONE CONCRETE THRUST -BLOCK 6" GATE VALVE $-2'\times2'\times3'$ 3/4"CRUSHED STONE BASE MJ HYDRANT CONSTRAINED - HYDRANT DRAIN HOLES ANCHORING TEE JOINT SHALL BE PLUGGED FLANGE-TO-FLANGE

FINISHED GRADE

## Hydrant Assembly

#### Not to Scale




<u>PLAN</u>

**SECTION** 

**ALL BENDS** 

## Water/Utility Crossing

### Not to Scale



VERTICAL BENDS Thrust Blocks

Not to Scale

**ELEVATION** 

NOTES:

1. Thrust blocks shall be precast concrete, except thrust blocks for vertical bends can be CIP concrete.

-I/UNDISTURBED

<u>PLAN</u>

**SECTION** 

TEE OR TAPPING SLEEVE


2. The minimum bearing areas shown above are based on a system pressure of 100 PSI. If the system pressure is above 100 psi, increase the noted areas proportional to the actual system pressure. For example, if the actual system pressure is 160 psi, multiply the above values by 160%.

3. Place thrust blocks such that the length (L) of the block is approximately twice as long as the depth (D). 4. Place thrust blocks against undisturbed soil. 5. Place thrust blocks along the full length of the fitting

- to maximize bearing area.

  5. Place 2 layers of polyethylene or roofing paper around fittings prior to placement of the concrete to create a bond break & protect the bolts.
- 6. Place a solid concrete block between cap/plugs and
- 7. Place a 12" long steel horseshoe—shaped pickup hook in all plug and cap thrust blocks. Diameter of hook
- shall be a minimum of 5/8". 8. Use of thrust blocks does not eliminate the
- requirement of retainer glands. Thrust blocks are required on all fittings. 10. Coat all threaded rods, nuts, and bolts with

bituminous paint. 11. Place anti-seize lubricant on all bolts.




- NOTES:

  1. VALVE BOXES SHALL BE HEAVY PATTERN CAST IRON, TWO PIECE, SLIP TYPE, 5—INCH DIAMETER SHAFT WITH EXTENSION PIECES TO ALLOW SUFFICIENT COVER.
- 2. THE UPPER SECTION OF THE BOX SHALL BE TOP-FLANGE TYPE TO PREVENT SETTLEMENT. 3. THE LOWER SECTION SHALL BE BELLED-TYPE TO ENCLOSE THE OPERATING NUT OF THE VALVE. 4. THE COVER SHALL BE CAST IRON WITH THE WORD "WATER" PLAINLY CAST THEREON.
- 5. GATE VALVES SHALL OPEN LEFT.

### Valve & Valve Box Detail

#### Not to Scale



NOTES:

1. JOINT RESTRAINT IS
REQUIRED AT ALL FITTINGS PER THE ABOVE TABLE.

VALVE	RESTRAINED JOINTS
IN LINE VALVES	BELL RESTRT'S REQUIRED 1 JOINT EACH SIDE/VALVE
FITTING	RESTRAINED JOINTS
22.5° BEND	1 EACH SIDE
45° BEND	1 EACH SIDE
90° BEND	2 EACH SIDE

1 EA SIDE/RUN 2 ON BRANCH

Recreation I erly Hill Roac

C-906

---- of ----

sheet:

### Joint Restraint Detail

### Not to Scale

# THRUST BLOCK SCHEDULE

MINIMUM BEARING AREA (SQUARE FEET)										
		PIPE SIZE								
Nominal Dia. (in)	4	6	8	10	12	16	20	24		
Tees, Caps, Plugs, & Tapping Sleeves	1.05	2.32	4.15	6.37	9.15	16.23	25.44	36.58		
90 Degree Bends	1.48	3.29	5.86	9.01	12.93	22.96	35.97	51.73		
45 Degree Bends	0.80	1.78	3.17	4.88	7.00	12.42	19.47	28.00		
22-1/2 Degree Bends	0.41	0.91	1.62	2.49	3.57	6.33	9.92	14.27		
11-1/4 Degree Bends	0.21	0.46	0.81	1.25	1.79	3.18	4.99	7.17		
System Pressure: 100psi Safety Factor: 1.5 Soil Bearing Capacity: 2,000psf										

## Water Service Installation

COPPER CRIMP OR SPLIT BOLT CONNECTOR.

Not to Scale

INSERT STAINLESS STEEL STIFFENERES REQUIRES ON ALL FLEXIBLE PLASTIC CONNECTIONS.

6. TRACER WIRE (#10 INSULATED) SHALL BE PLACED ALONG THE SERVICE LINE AND SHALL BE A CONTINOUS


CONNECT CURB STOP TO EXISTING SERVICE AT PROPERTY LINE OR AT LOCATION APPROVED BY THE


LENGTH (WITHOUT SPLICES), EXCEPT FOR THE SPLICE AT THE STOP BOX, WHICH SHALL BE MADE WITH A


MAINS/SERVICES, PROVIDE RIGID INSULATION ON TWO SIDES OF SERVICE PIPE.


PRESSURE TEST, DISINFECT, AND FLUSH ALL WATER SERVICE CONNECTIONS.


ENGINEER (NO COUPLING WITHOUT APPROVAL OF ENGINEER).













- NOTES:
  1. 24" MIN SUMP IS REQUIRED AT ALL AREA DRAINS WITHIN THE
- SYNTHETIC TURF FIELD. 2. GRATES AND/OR COVERS SHALL BE 24" ROUND AT THE LOCATIONS INDICATED ON THE GRADING PLAN.




SCALE: N.T.S.







SYNTHETIC TURF FIELD SCALE: NTS



1. FLAT DRAIN TO BE DIRECTLY CONNECTED TO PERIMETER DRAIN. PROVIDE MANUFACTURED FITTINGS TO MAKE THE CONNECTION AS REQUIRED AND APPROVED BY THE OWNERS REPRESENTATIVE. 2. CONCRETE CURB TO BE 4,500 PSI AT 28 DAYS (AIR CONTENT 6% +/- 1%) (COARSE AGGREGATE ASTM C-33 SIZE #57)

COLLECTOR DRAIN SCALE: NTS

City of Portsmouth, New Hampshire  Department of Public Works  Inle name:  Multi-purpose Recreation Fields  Scale:  Additional distance of Public Works  Multi-purpose Recreation Fields  It or - Drainage Details of Post Control (1909) 726-7766  DETAILS								no.
date:			CIVIL / ENVIRONMENTAL ENGINEERS	Portsmouth, NH Manchester, NH Portland, Maine	8		(978) 977-0110 (800) 726-7766	(Sampson) www.westonandsampson.com
date: - project no: - file name: L7.01- Drainage Detail:								
City of Portsmouth, New Hampshire Department of Public Works Multi-purpose Recreation Fields 680 Peverly Hill Road Recreation Fields DETAILS	designed by: -	drawn by:	-	approved by:		. 9 6		
						.alaus		

\wse03.local\WSE\Projects\NH\Portsmouth, NH\Community Fields\CADART\L7.01- Drainage Details.dwg Date Plotted: Jul 02, 2019 - 12:58pm Plotted By: ANDRIKOSE



Table 1
Wetland and Wetland Buffer Area Analysis

Town	Wetland ID	Classification	Wetland Area (SF)	Wetland Area (Acres)	Buffer Area (SF)	Buffer Area (Acres)	Buffer Setback (ft)
Portsmouth	Wetland 1	PFO1/4E, R4SB	835,599	19.18			100
Portsmouth	Wetland 2	PFO1/4E	126,106	2.89			100
Portsmouth	Wetland 3	PFO1E	347	0.01			100
Portsmouth	Wetland 4	PEM1Ex	24,687	0.57		46.84	100
Portsmouth	Wetland 5	PEM1Ex	11,146	0.26	2,040,239		100
Portsmouth	Wetland 6	PEM1Ex	9,610	0.22			100
Portsmouth	Wetland 7	PEM1Ex	497	0.01			100
Portsmouth	Wetland 8	PEM1Ex	1,619	0.04			100
Portsmouth	Wetland 9	PUBx, PEM1Ex	200,800	4.61			100
Total	•		1,210,411	27.79	2,040,239	46.84	



Table 2
Wetland and Buffer Impact Analysis

Town	Wetland ID	Classification	Permanent Wetland Impact (SF)	Permanent Prime Wetland Buffer Impact (SF)
Portsmouth	Wetland 1	PFO1/4E, R4SB	-	
Portsmouth	Wetland 2	PFO1/4E	-	
Portsmouth	Wetland 3	PFO1E	-	
Portsmouth	Wetland 4	PEM1Ex	24,699	
Portsmouth	Wetland 5	PEM1Ex	11,246	436,119
Portsmouth	Wetland 6	PEM1Ex	9,637	
Portsmouth	Wetland 7	PEM1Ex	497	
Portsmouth	Wetland 8	PEM1Ex	1,646	
Portsmouth	Wetland 9	PUBx, PEM1Ex	9,787	
Total			57,512	436,119