### RFP#16-18 FOUNDRY PLACE PARKING GARAGE PERCENT FOR ART PROJECT PORTSMOUTH, NH November 28, 2017

#### Addendum#1

This Addendum forms part of the original document marked: RFP#16-18 Foundry Place Parking Garage Percent for Art Project.

1) The following questions regarding specific space available for art work at the Foundry Place Garage have been asked, and in response the City has provided annotated floor plan(s) that provide answers to these questions.

Q: Could you perhaps highlight on the floor plan(s) where the long blank interior wall that could be used for art is located?

A: See attached annotated plan(s).

Q: If there are additional walls that would contain a decent amount of blank space, could those be highlighted (drawings A101 through A106)?A: See attached annotated plan(s)

A: See attached annotated plan(s).

Q: What is the finish of the wall, and what are the dimensions - both width and height?

A: See attached annotated plan(s).

Q: On any of these walls, including the ones highlighted on the attached plans, could you call out where any interior signage such as floor numbers, exit signs, etc. would be? A: See attached annotated plan(s).


Q: Is there a cutoff date for questions to be submitted? A: No


Artists are not limited to the locations specified in this addendum (attached annotated plans) for their art. These locations are provided in response to the questions asked as part of this addendum.

Respondents are to acknowledge this addendum within their proposal. Failure to do so may subject a respondent to disqualification.

End of Addendum #1

Continue below for the plans.






7/28/2017 3:34:01 PM

### POTENTIAL ART LOCATIONS FOUNDRY PLACE PARKING GARAGE PORTSMOUTH NH





- MOUNTING DETAILS.

CONSIDERATIONS					
LOCATIONS	ELECTRICITY EASILY AVAILABLE	STRUCTURAL CONSIDERATION	WIND LOAD CONSIDERATION	MOUNTING RESTRICTIONS	COMMENTS
1. TOP OF FLEX SPACE ROOF					
2. SHEAR WALLS					
3. GROUND SURFACE					
4. ROUNDABOUT CENTER					OVERALL DIAMETER OF PROPOSED INSTALLATION MUST NOT INTERFERE W/ FIRETRUCK TURNING RADIUS.
5. ENTIRE ELEVATION					SHOULD NOT PROJECT MORE THAN 4" FROM BUILDING FACE.
6. STAIR TOWER (INTERIOR)					
7. TOWER TOPS					
8. FIN SURFACE					
9. ELEVATOR SURFACE (INT.)					MINIMAL IMPACT ALLOWED PER FIRE DEPT. & STATE ELEVATOR INSPECTOR GUIDELINES. GRAPHIC ONLY.
10. LIGHT WALL (INT.)					
11. BACKSIDE OF FLEX SPACE (INT.)					
12. UPPER WALL SURFACE OF TOWERS (INT.)					
13. STAIR B LANDING WALLS (INT.)	0				
14. PORTSMOUTH LETTER LOCATIONS					REQUIRES HIGH LEVEL OF COORDINATIONS FOR MOUNTING LARGE INSTALLATION.





LIGHT WALL IMAGES





## GENERAL SHEET NOTES

- 1. ALL EXTERIOR COLUMNS, WALL PANELS, AND SPANDRELS (INCLUDING GRADE SPANDRELS) ARE TO HAVE AN ARCHITECTURAL CONCRETE MIX DESIGN. THE "ARCHITECTURAL PRECAST" MIX IS TO MATCH ARCHITECTS SAMPLE.
- SEE SHEET A-501 AND 502 FOR FINISH OF EXTERIOR PRECAST ELEMENTS.
- 3. CURTAINWALL MULLIONS ALIGNED TO PRECAST REVEALS
- SHALL BE FIELD MEASURED FOR COORDINATION.4. SEE CIVIL DRAWING FOR SITE GRADES AT PERIMETER OF
- STRUCTURE. 5. RECESSED JUNCTION BOXES IN FACE OF EXTERIOR
- PANELS TO BE CAST-IN AT PREFABRICATION PLANT. SEE ELEC. DRAWINGS
- 6. RECESSED JUNCTION BOX FOR DECORATIVE LIGHTING 3' FROM GRID LINE
- CURTAIN WALL AND STOREFRONT GLAZING AT STAIR TOWERS TO BE 1/4" CLEAR TEMPERED GLASS.
- STOREFRONT GLAZING AT FLEX SPACE TO BE 1" TEMPERED INSULATED GLASS.

### LEGEND

ARCH P/C COLOR 1
ARCH P/C COLOR 2
ARCH P/C COLOR 3
ARCH P/C COLOR 4





POTENTIAL ART LOCATIONS FOUNDRY PLACE PARKING GARAGE

PORTSMOUTH NH



CONSIDERATIONS					
LOCATIONS	ELECTRICITY EASILY AVAILABLE	STRUCTURAL CONSIDERATION	WIND LOAD CONSIDERATION	MOUNTING RESTRICTIONS	COMMENTS
1. TOP OF FLEX SPACE ROOF					
2. SHEAR WALLS					
3. GROUND SURFACE					
4. ROUNDABOUT CENTER					OVERALL DIAMETER OF PROPOSED INSTALLATION MUST NOT INTERFERE W/ FIRETRUCK TURNING RADIUS.
5. ENTIRE ELEVATION					SHOULD NOT PROJECT MORE THAN 4" FROM BUILDING FACE.
6. STAIR TOWER (INTERIOR)					
7. TOWER TOPS					
8. FIN SURFACE					
9. ELEVATOR SURFACE (INT.)					MINIMAL IMPACT ALLOWED PER FIRE DEPT. & STATE ELEVATOR INSPECTOR GUIDELINES. GRAPHIC ONLY.
10. LIGHT WALL (INT.)					
11. BACKSIDE OF FLEX SPACE (INT.)					
12. UPPER WALL SURFACE OF TOWERS (INT.)					
13. STAIR B LANDING WALLS (INT.)					
14. PORTSMOUTH LETTER LOCATIONS					REQUIRES HIGH LEVEL OF COORDINATIONS FOR MOUNTING LARGE INSTALLATION.

2 A-440

EXTRUDED ALUMINUM PLATE FABRICATED "GEARS" (ALT: 6" SURFACE FRP SCULPTURAL "GEARS" FEATURE) SECURE TO PRECAST SPANDRELS WITH CONCEALED PIN-TYPE SUPPORTS. AVOID LOWER 1'-6" OF SPANDRELS FOR SUPPORTS. PROVIDE WEEP HOLES AS NECESSARY (TYP)

SIXTH TIER EL 69' - 4"

FIFTH TIER EL 58' - 0"

FOURTH TIER EL 46' - 8"

HIRD TIER EL 35'-4"

SECOND TIER EL 24' - 0"

GROUND TIER EL 12' - 0"

JUNCTION BOX SEE NOTE 1

- OVERHEAD CLEARANCE SIGN, TYP.



## GENERAL SHEET NOTES


- 1. ALL EXTERIOR COLUMNS, WALL PANELS, AND SPANDRELS (INCLUDING GRADE SPANDRELS) ARE TO HAVE AN ARCHITECTURAL CONCRETE MIX DESIGN. THE "ARCHITECTURAL PRECAST" MIX IS TO MATCH ARCHITECTS
- SAMPLE. 2. SEE SHEET A-501 AND 502 FOR FINISH OF EXTERIOR
- PRECAST ELEMENTS.
  3. CURTAINWALL MULLIONS ALIGNED TO PRECAST REVEALS
- SHALL BE FIELD MEASURED FOR COORDINATION.
  4. SEE CIVIL DRAWING FOR SITE GRADES AT PERIMETER OF
- STRUCTURE. 5. RECESSED JUNCTION BOXES IN FACE OF EXTERIOR
- PANELS TO BE CAST-IN AT PREFABRICATION PLANT. SEE ELEC. DRAWINGS
- RECESSED JUNCTION BOX FOR DECORATIVE LIGHTING 3' FROM GRID LINE
- CURTAIN WALL AND STOREFRONT GLAZING AT STAIR TOWERS TO BE 1/4" CLEAR TEMPERED GLASS.
- STOREFRONT GLAZING AT FLEX SPACE TO BE 1" TEMPERED INSULATED GLASS.


## LEGEND






ARCH P/C COLOR 4







POTENTIAL ART LOCATIONS FOUNDRY PLACE PARKING GARAGE PORTSMOUTH NH **ELEVATION - WEST** 

# NORTH ELEVATION

CONSIDERATIONS					
LOCATIONS	ELECTRICITY EASILY AVAILABLE	STRUCTURAL CONSIDERATION	WIND LOAD CONSIDERATION	MOUNTING RESTRICTIONS	COMMENTS
1. TOP OF FLEX SPACE ROOF					
2. SHEAR WALLS					
3. GROUND SURFACE					
4. ROUNDABOUT CENTER					OVERALL DIAMETER OF PROPOSED INSTALLATION MUST NOT INTERFERE W/ FIRETRUCK TURNING RADIUS.
5. ENTIRE ELEVATION					SHOULD NOT PROJECT MORE THAN 4" FROM BUILDING FACE.
6. STAIR TOWER (INTERIOR)					
7. TOWER TOPS					
8. FIN SURFACE					
9. ELEVATOR SURFACE (INT.)					MINIMAL IMPACT ALLOWED PER FIRE DEPT. & STATE ELEVATOR INSPECTOR GUIDELINES. GRAPHIC ONLY.
10. LIGHT WALL (INT.)					
11. BACKSIDE OF FLEX SPACE (INT.)					
12. UPPER WALL SURFACE OF TOWERS (INT.)					
13. STAIR B LANDING WALLS (INT.)					
14. PORTSMOUTH LETTER LOCATIONS					REQUIRES HIGH LEVEL OF COORDINATIONS FOR MOUNTING LARGE INSTALLATION.



### 21 NOVEMBER 2017