

April 5, 2021

Mr. Peter Stith, AICP Principal Planner Planning Departmen City of Portsmouth One Junkins Avenue Portsmouth, NH 03801

RE: Conditional Use Permit approval and Site Plan Review approval for property located at 1400 Lafayette Road, Peverly Hill Road and 721 Peverly Hill Road (PU# LU-20-12)

Subject: Approval Expiration and Extension Request

Dear Mr. Stith:

The above referenced project was approved by the Planning Board on April 30, 2020. On behalf of the applicant, 4 Amigos, LLC, we hereby request a one (1) year extension of said approval in accordance with Section 2.14 of the Site Review Regulations.

The applicant has been working diligently on the Conditions (precedent) of Approval, as well as the final architectural plans for submission of a building permit application. A time extension is required due to the economic impact associated with the COVID-19 pandemic. We are optimistic that this situation will change in the near future and we can obtain a building permit to proceed with construction.

It is our opinion that there is no material change that has taken place at the project site which would affect the site plan as previously approved. Please contact our office if you have any questions or need any additional information in order for the Planning Board to act on this request.

Thank you for your consideration.

Very Truly Yours,

**GREENMAN-PEDERSEN, INC.** 

Frank C. Monteiro, PE

**Director of Land Development** 

Frank C Monteiro, VP

cc: Mr. Rick Green - 4 Amigos, LLC

CR MAX-0458519.00



#### CITY OF PORTSMOUTH

Planning Department 1 Junkins Avenue Portsmouth, New Hampshire 03801

(603) 610-7216

#### **PLANNING BOARD**

May 4, 2020

Rick Green 4 Amigos, LLC 321 Lafayette Road, Unit D Hampton, NH 03842

RE: Conditional Use Permit approval and Site Plan Review approval for property located at 1400 Lafayette Road, Peverly Hill Road and 721 Peverly Hill Road

Dear Mr. Green:

The Planning Board, at its regularly scheduled meeting of Thursday, April 30, 2020, considered your application for Conditional Use Permit approval for a Development Site according to the requirements of Section 10.5B40 of the Zoning Ordinance and Site Plan Review approval for the construction of a 53-unit Garden and Townhouse Style residential development consisting of 6 structures with a combined total footprint of 37,775 +/- s.f. and 122,000 +/- GFA with associated grading, lighting, utilities, stormwater management, landscape improvements and community space. Said property is shown on Assessor Map 252 Lots 7, 4 & 5 and lies within the Gateway Neighborhood Mixed Use Center (G2) District. As a result of said consideration, the Board voted to as follows:

- 1) To find that the application meets the requirements of Section 10.5B43.10 and to grant the Conditional Use Permit for a Development Site;
- 2) To grant Site Plan Review Approval with the following stipulations:
- 2.1) Conditions precedent (to be completed prior to building permit issuance):
- a) Water service design shall be reviewed and approved by the Portsmouth Water Department;
- b) Applicant shall confirm with Eversource that both poles proposed to have service drops are able to provide them. Plan revisions shall be reviewed and approved by Portsmouth DPW, as required;
- c) Applicant shall coordinate addressing and numbering of the buildings with Portsmouth DPW and Fire Department. Proposed sign locations shall be added to the plan set and separate sign permits may be required;
- d) Owner shall provide an access easement to the City for water valve access and leak

detection. The easement shall be reviewed and approved by the Planning and Legal Departments prior to acceptance by the City Council;

- e) Owner shall provide a sidewalk public access easement to the City subject to review and approval by the Planning and Legal Departments prior to acceptance by City Council;
- f) The site plan and any easement plans and deeds shall be reviewed for pre-approval by the Rockingham County Registry of Deeds and subsequently recorded or as deemed appropriate by the Planning Department;
- g) Plans shall be updated to include signage prohibiting truck traffic from entering the development from Peverly Hill Road;
- h) The applicant shall document the condition, verify ownership, and provide or produce any easements and agreements pertaining to the access and maintenance of sewer lines that cross the property to the satisfaction of the Department of Public Works;
- i) Applicant shall coordinate with COAST to determine if an additional bus stop can be located along Route 1 or Peverly Hill Road to serve the development.

#### 2.2) Conditions subsequent (to be completed subsequent to building permit issuance):

- a) The applicant shall design and construct a pedestrian crossing of Peverly Hill Road at the West Road intersection, along with an pedestrian activated signal. Plans shall be reviewed and approved by DPW;
- b) The applicant shall provide engineered plans for a sidewalk along Peverly Hill Road between West Road and the Market Basket driveway for future construction by the City. Plans shall be reviewed and approved by DPW;
- c) The applicant shall replace the water main in Peverly Hill Road as required per Portsmouth DPW requirements;
- d) The Engineer of Record shall submit a written report (with photographs and engineer stamp) certifying that the stormwater infrastructure was constructed according to the approved plans and specifications and will meet the design performance;
- e) All utilities being installed shall be witnessed by a third party inspection company to be determined by the City.

The Board's decision may be appealed up to thirty (30) days after the vote. Any action taken by the applicant pursuant to the Board's decision during this appeal period shall be at the applicant's risk. Please contact the Planning Department for more details about the appeals process.

This site plan approval shall not be effective until a site plan agreement has been signed satisfying the requirements of Section 2.12 of the City's Site Review Approval Regulations.

Unless otherwise indicated above, applicant is responsible for applying for and securing a building permit from the Inspection Department prior to starting any project work.

The Planning Director must certify that all stipulations of approval have been completed prior to issuance of a building permit unless otherwise indicated above.

This site plan approval shall expire unless a building permit is issued within a period of one (1) year from the date granted by the Planning Board unless an extension is granted by the Planning Board in accordance with Section 2.14 of the Site Review Regulations.

The minutes and audio recording of this meeting are available by contacting the Planning Department.

Very truly yours,

Dexter R. Legg, Chairman of the Planning Board

cc: Robert Marsilia, Chief Building Inspector Rosann Maurice-Lentz, City Assessor

Peter H. Rice, Director of Public Works

Robert White, GPI, Inc.

# SITE DEVELOPMENT PLANS


for

TAX MAP 252 LOTS 4, 5 & 9 1400 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE 03801

Prepared for:

4 AMIGOS, LLC

321D LAFAYETTE ROAD HAMPTON, NEW HAMPSHIRE 03842



#### LOCATION MAP NOT TO SCALE

## **INDEX TO DRAWINGS**

- **TITLE SHEET**
- **EXISTING CONDITIONS PLAN**
- **DEMOLITION PLAN**
- SITE OVERVIEW PLAN
- SITE PLAN
- **GRADING & DRAINAGE PLAN**
- **UTILITY PLAN**
- **EROSION & SEDIMENT CONTROL PLAN**
- LANDSCAPE PLAN
- LANDSCAPE DETAILS
- **DETAIL SHEET** 11.
- **DETAIL SHEET**
- **DETAIL SHEET**
- **DETAIL SHEET**
- **DETAIL SHEET**
- 1 OF 1. SEWER PLAN & PROFILE (P&P) 1 OF 1. COMMUNITY SPACE OVERVIEW PLAN
- 1 OF 1. LIGHTING PLAN (CREE)
- 1 OF 1. BUILDING A CONCEPT (A-1.A)
- 1 OF 1. BUILDING A PLANS (A-2.A)
- 1 OF 1. BUILDING B TYPICAL UNIT (A-1.B)
- 1 OF 1. BUILDING B PLANS AND ELEV. (A-2.B)
- 1 OF 1. BUILDING C CONCEPT PLANS (A-1.C)
- 1 OF 1. BUILDING C RENDER CONCEPTS (A-2.C)

2	REV SHEETS 3-11, P&P - A-2.C	СМТ	3/9/20
1,	REV SHEETS 3-9, P&P, A-1.C	СМТ	2/20/20
NO.	DESCRIPTION	BY	DATE

**ENGINEER:** 

FRANK C. MONTEIRO, PE 44 STILES ROAD, SUITE ONE

GREENMAN-PEDERSEN, INC. (GPI)

MICHAEL J KEANE ARCHITECTS PLLC

JOEL A. CONNOLLY, LLS 44 STILES ROAD, SUITE ONE SALEM, NH 03079

(603) 893-0720

(603) 893-0720

MICAHEL KEANE 101 KENT PLACE

(603) 292-1400

NEWMARKET, NH 03857


ARCHITECT:

**REVISIONS** TITLE SHEET

ASSESSORS MAP 252 - LOTS 4, 5 & 9 1400 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE PREPARED FOR:

4 AMIGOS, LLC 321 LAFAYETTE ROAD UNIT D HAMPTON, NEW HAMPSHIRE 03842

CITY OF PORTSMOUTH PLANNING BOARD





**GPINET.COM** 


Greenman-Pedersen, Inc. 44 Stiles Road Suite One


Salem, NH 03079


DATE: JANUARY 20, 2020 SCALE: NONE DRAWN BY: CHECKED BY: PROJECT NO. SHEET NO. 1 OF 15 CMT 458219


**CHAIRPERSON** 


DATE














LOCATION MAP (NOT TO SCALE)

- 1) ALL SITE DRAINAGE PIPE SHALL BE CORRUGATED HIGH-DENSITY POLYETHYLENE PIPE WITH STANDARD JOINTS, DUAL-WALL, SMOOTH INTERIOR AS MANUFACTURED BY ADS, INC., OR APPROVED EQUAL, UNLESS OTHERWISE
- 2) ALL ROOF DRAIN PIPE SHALL BE MINIMUM 6" PVC(SDR-35).
- 3) ELEVATIONS ARE BASED ON NAVD 1988 DATUM.
- 4) ALL PROPOSED ELEVATIONS AS SHOWN ARE BOTTOM OF CURB ELEVATIONS, UNLESS OTHERWISE NOTED.
- 5) ANY UTILITY FIELD ADJUSTMENTS SHALL BE APPROVED BY THE LOCAL AUTHORITIES AND THE DEVELOPER
- 6) THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE ONLY. THE CONTRACTOR IS TO VERIFY EXACT LOCATION PRIOR TO CONSTRUCTION. THE CONTRACTOR IS TO NOTIFY THE DESIGN ENGINEER OF ANY
- 7) THE CONTRACTOR SHALL CALL AND COORDINATE WITH DIG-SAFE (1-888-344-7233) 72 HOURS PRIOR TO
- CONSTRUCTION SINCE THE DISTURBANCE EXCEEDS ONE ACRE. THE CONSTRUCTION SITE OPERATOR SHALL DEVELOP AND IMPLEMENT A CONSTRUCTION STORM WATER POLLUTION PREVENTION PLAN (SWPPP), WHICH SHALL REMAIN ON SITE AND MADE ACCESSIBLE TO THE PUBLIC. A COMPLETED NOTICE OF TERMINATION (NOT) SHALL BE SUBMITTED TO NPDES PERMITTING AUTHORITY WITHIN 30 DAYS AFTER EITHER OF THE FOLLÓWING CONDITIONS HAVE BEEN MET: FINAL STABILIZATION HAS BEEN ACHIEVED ON ALL PORTIONS OF THE SITE FOR WHICH THE PERMITTEE IS RESPONSIBLE; OR ANOTHER OPERATOR/PERMITTEE HAS ASSUMED CONTROL OVER ALL AREAS OF THE SITE THAT HAVE NOT BEEN FINALLY STABILIZED.
- 10) CONTRACTOR TO USE EXTREME CAUTION TO INSURE THAT NO PONDING OCCURS AT PROPOSED DRIVEWAYS.
- 11) ALL CONSTRUCTION SHALL CONFORM TO MUNICIPAL DPW AND ALL APPLICABLE STATE AND FEDERAL
- 12) ALL TRAFFIC CONTROL AND TEMPORARY CONSTRUCTION SIGNAGE ARRANGEMENTS, ACCEPTABLE TO THE PORTSMOUTH DEPARTMENT OF PUBLIC WORKS AND NHDOT, SHALL BE EMPLOYED DURING OPERATIONS WITHIN
- 13) ALL ADA ACCESSIBLE WALKWAYS CANNOT EXCEED 5% RUNNING SLOPE AND 2% CROSS SLOPE, RAMPS CANNOT EXCEED 8.33% RUNNING SLOPE AND 2% CROSS SLOPE, AND HC PARKING STALLS AND ACCESS AISLES CANNOT EXCEED 2% SLOPE IN ANY DIRECTION. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL
- 14) SEE EROSION & SEDIMENT CONTROL PLAN FOR CONSTRUCTION SEQUENCE AND EROSION CONTROL
- 15) THE SITE WILL REQUIRE A NHDES ALTERATION OF TERRAIN (AOT) PERMIT SINCE THE PROJECT WILL DISTURB MORE THAN 100,000 SF OF TERRAIN. CONTRACTOR SHALL COMPLY WITH ALL CONDITIONS IN THAT PERMIT.
- 16) THE GENERAL CONTRACTOR IS TO PROVIDE 2" RIGID POLYSTYRENE THERMAL INSULATION WITH A MINIMUM "R VALUE OF 10 AT LOCATIONS WHERE THERE IS LESS THAN 3' OF COVER OVER STORM DRAINS. SEE DETAIL
- 17) ALL CATCH BASINS SHALL BE FITTED WITH A OIL-WATER-DEBRIS HOODS ON THE OUTLET PIPE.
- 18) FOR DRAINAGE STRUCTURE DETAILS SEE DETAIL SHEETS.
- 19) ALL PIPE DATA IS CALCULATED TO CENTER OF STRUCTURE, TYP.
- MANAGEMENT SYSTEMS FOR SITE MAINTENANCE DURING AND AFTER CONSTRUCTION.
- 21) ALL UNDERGROUND SYSTEMS TO BE CONSTRUCTED WITH RISERS AND CLEANOUTS.

2	MISC. REVISIONS PER TAC	СМТ	3/9/20
· 1	MISC. REVISIONS PER TAC	СМТ	2/20/20
NO.	DESCRIPTION	BY	DATE
	REVISIONS		

### GRADING & DRAINAGE PLAN

ASSESSORS MAP 252 - LOTS 4,5 & 9 1400 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE PREPARED FOR: 4 AMIGOS, LLC


321 LAFAYETTE ROAD UNIT D HAMPTON, NEW HAMPSHIRE 03842


**GPINET.COM** 


Greenman-Pedersen, Inc. 44 Stiles Road Construction Management Suite One

Salem, NH 03079


DRAWING NO. 4582SP.DWG DATE: JANUARY 20, 2020 CHECKED BY: PROJECT NO. SHEET NO. 458219 6 OF 15

















11" MAX

ALL BENDS ARE TO BE 36" RADIUS SWEEPS

(NO PLUMBERS BENDS)
-LLIC SWEEPS REQUIRED ON ALL RUNS IN EXCESS OF 225'

FINISH GRADE

FOR OUR PERSONNEL AND FURNISHED WITH A PULL.

STRING CAPABLE OF A 200 TO 300 POUND PULL

A #6 AWG COPPER GROUND WIRE SHALL BE CONNECTED TO THE POWER CO. TRANSFORMER / SECTOR CABINET GRID A

EACH TRANSFORMER / SECTOR CABINET LOCATION AND RUP

FROM THERE TO THE TEL CONDUIT LEAVING A 3 FOOT COIL SECURED TO THE CONDUIT TO PREVENT ITS LOSS

Copyright © 2020 by Greenman-Pedersen, Inc. All Rights Reserved.

PRIMARY CABLE INSTALLATION

NORTHEAST UTILITIES CONSTRUCTION STANDARD DTR 50.102

Slab Dimensions in Inches

80 x 92

OIL DETENTION FOR PAD-MOUNTED TRANSFORMERS

NORTHEAST UTILITIES | CONSTRUCTION STANDARD | DTR 58.311

90 x 96

Public Service

of New Hampshire

CONSTRUCTION REQUIREMENT

MONTEIRO

603.893.0720

FRANK

ISSUE DATE
Original 2/1/83
Play. 1/14/98

. 1" PVC CONDINT FOR GROUND LEADS.

. CONDUITS CUT 4" ABOVE BASE OF SLAB.

Public Service

. ALL REBAR TO BE BOD.

Construction Management Suite One **GPINET.COM** 

Greenman-Pedersen, Inc. 44 Stiles Road

Salem, NH 03079

BY DATE

COMPACTED CRUSHED STONE TO BE PLACED

TOP OF PROP.

SIZE VARIES)


WATERLINE (PIPE

BETWEEN SIDES OF


MAIN TRENCH

SPRING LINE

DRAWING NO. 4582DET.DWG SCALE: 1"=20' DRAWN BY: CHECKED BY: PROJECT NO. SHEET NO. 458219 12 OF 15



- 2) CONTRACTOR SHOULD CONFIRM SYSTEM PARTS AND PROVIDE SHOP DRAWINGS FROM MANUFACTURER. SUBSTITUTIONS AND SHOP DRAWINGS SHOULD BE APPROVED BY THE ENGINEER.
- 3) PARTS SPECIFICATIONS SHOWN ARE AS PROVIDED BY ADS, INC., OR APPROVED EQUAL. ANY CHANGES TO THESE



NOTE:	FOR	ADDITIONAL	DETAILS,	SEE	ADS	STD-702	&	STD-703.	

UN	IDERGROUN	D STORMW	ATER INFILT	RATION SY	STEM TAE	3LE	
UG INFILTRATION SYSTEM	LENGTH (X)	WIDTH (Y)	SPACING (Y1) (O.C. TYP.)	PIPE SIZE (INCHES) PERF	INV. PIPE ELEV. (A)	# PIPE ROWS	STONE BED
INFILTRATION SYS#1	57'	24.5'	63"	36"	41.75	5	27.5'x60'
INFILTRATION SYS#2	92'	19.25'	63"	36"	40.50	4	22.25'x95'
INFILTRATION SYS#3	57'	24.5'	63"	36"	40.00	5	27.5'x60'
INFILTRATION SYS#4	32'	19.25'	63"	36"	40.50	4	22.25'x35'

Table 5-2 Classes of Embedment and Backfill Materials

erin in transfering i en frankrigering parter i parter propriet propriet propriet propriet propriet propriet p		MINISTER HANDEN HER	n it ensumes den som sing en bestyre in 148 den sjørste stade 1798 den stade	NAMES OF THE PERSONS ASSESSED.	Mit.	AST N D2221																									
ASTM D2321 <sup>(1)</sup> Class Description			ASTM D2467 Description	AASHTO M43	Compaction Required (Std	Percenta	ige Passing	Sleve Sizes	Atterberg Limits	Coeff	icients																				
		Notation		Notation		1 ½ in. (40mm)	No. 4 (4.75min)	No. 200 (0.075mm)	LL PI	Uniformity Cu	Curvature Cc																				
<sub>[Д</sub> (4)	Open-graded, clean manufactured aggregates	женик жаланы прима РФ/А	Angular crushed stone or rock, crushed gravel, crushed stag; large voids with little or no fines	and in a more in marries was and		100%	510%	< 5%	Non Plastic		enang ing aproximati																				
623	Dense-graded clean manufactured, processed aggregates	MA	Angular crushed stone or other Class IA material and stone/sand mixtures with gradations selected to minimize migration of adjacent soils; little or no fines	5 56	Dumped to Slight	100%	≲50%	<5%	Non Plastic	N	VA																				
14 14 14 Tu	ing ing palakan panggan ang Aria	GW	Well-graded gravel, graval- eand mixtures; little or no fines			-	<50% of "Coarse			>4	1 to 3																				
	Clean, coarse-	GP	Poorly-graded grave/s, gravel-sand mixtures; little or no fines	57 6	DOCUMENT OF THE PROPERTY OF TH	100%	Fraction"	<5%	Non Plastic	<4	<1 or >3																				
ANA ANA	grained solfs	SVV	Well-graded sands, graveil sands; little or no fines	67	Moderate (85%)		>50% of "Coarse			>6	i to 3																				
	CLEMANICANICALINA MALTACISI PSICHISMA	SP	Poorly-graded sands, gravelly sands; little or no fines	Sachlesan bedan		in in Marian in stransiste stansistem strans	Fraction		sampupus apikus is Al-AsaKais Alaba	<6	<1 01 >3																				
	Coarse-Graine Soils, borderlin clean to witine	GW-GC, SI SM	Sands and gravels which are borderline between clean and with fines	NΙΑ		100%	Varies	5% to 12%	Non Plastic	Same as for and	GW, GP, SV I SP																				
·	**************************************	GH	Sity gravels, gravel-sand-s mixtures		-	-	<50% of		<4 or <"A" Line																						
	Coarse-grained	GC	Clayey gravels, gravel-sand clay mixtures	Gravel & sand with <10% fine	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	sand with	Moderate to	100%	Fraction"	12% to 50%	N/A EncourageMilities	N	I/A
		SM	Silty sands, sand-silt mixtures					ings (our)	ings (30 A)		>50% of "Coarse		>4 or <"A" Line																		
*******	oppiska kalenda kura kalenda k	SC	Clayey sands, sand-clay mixtures				Fraction"	Augustalandismi automi kusuk	>7 & >"A" Line	MARINES	KANGGERICHER STATE																				
VA <sup>(2)</sup>	Inorganic fine-	ML.	Inorganic sits and very fine sands, rock flour, sity or clayey fine sands, sits with slight plasticity	N/A	á±/D	Ąš/D	A STAR	AND CO	Target and the same and the sam	N/R		NI/R	N/R	₩.	hi/R	N/R	₩/R	₩.	ħā/R		N/R	100%	100%	>50%	<4 or <"A" Line	٨	VA.				
	grained solls	CL.	Inorganic clays of low to medium plasticity; gravelly, sandy, or slity clays; lean clays	N/A	ANCHOR STATEMENT OF STATEMENT O			and the second	>7 & >"A" Line																						
IVB	isorganic fine- grained solis	<u>жинишиний</u> <u>В</u> ЕН	Inorganic sits, micaceous of diatomaceous the sandy of sity solfs, elastic sits		N/R	100%	100%	>50%	<"A" Line >50	N	VA																				
lestske <del>ld</del>	ANNAMANIANSKA SANIANIANIANIANIANIANIANIANIANIANIANIANIA	милиний (СН СН	Inorganic clays of high plasticity, fat clays	МА МА		audionissississississississississississississ	and material standard sees		>"A" Line	AL HOMBOS SHORES IN UTILITIES SHORE	ns. o français por la la maiorite de la colonia de la c																				
		Ol.	Organic silts and organic sity clays of low plasticity	PHA	PARTICIONAL PROPERTY OF THE PR		Action of the second	cockskektokos	<4 or <50 <*A* Line	No.																					
Ą.	Organic solts o Highly organic solls		Organic clays of medium t high plasticity, organic sits	- N/A	N/R	100%	100%	>50%	<*A* Line >50	encooning and a second	I/A																				
-		FT	Peat and other high organi soils	1VA	DOCUMENT OF THE PROPERTY OF TH		establishment of the second	-	TITE CONTRACTOR	chemotor	-																				

1) Refer to ASTM D2321 for more complete soil descriptions.

Inlet pipe(s) can

enter anywhere

ITEM SIZE (in) DESCRIPTION

I.D. PRECAST MANHOLE

SEPARATION MODULE

INLET PIPE (BY OTHERS)


(OR GRATE) (ROUND)

5 30 OUTLET PIPE (BY OTHERS)

6 30 FRAME AND COVER


LEDGER SUPPORT


- 2) Class IVA material has limited applications and can be difficult to place and compact, use ONLY with the approval of a soil expert. Contact ADS for additional information regarding suitability of this backfill material.
- 3) N/R indicates that use of this material and/or compaction level is not recommended by ASTM D2321 for the backfill
- 4) When using open-graded material, additional precaution must be taken to reduce or eliminate the risk of migration of fines from adjacent material. Refer to ASTM D2321 for more complete information.




			OUTLE	T CON	TROL STE	RUCTURE	TABLE				
ocs	RIM	ORIFICE	SIZE (IN.)	ELEV.	INV.IN (SIZE)	INV.IN (ELEV)	INV.OUT (SIZE)	INV.OUT (ELEV)			
		Α	9" DIA.	42.90							
#1 4	48.00	-		-	24"	24"	24"	41.75	12"	41.75	
		С	12" DIA.	45.40			11.				
		A	6" DIA.	41.25							
#2	48.50	-		_	24"	24"	24"	24" 40.	40.50	15"	40.30
		C	15" DIA.	44.15							
		Α	6" DIA.	41.10							
#3	45.90	- 1	_		24"	40.00	12"	40.00			
		C	12" DIA.	43.65	1						


PRECAST CONCRETE OUTLET CONTROL STRUCTURE (OCS) FOR UNDERGROUND INFILTRATION SYSTEM






Enlarged Section 2-2






THE ELIMINATOR CATCH BASIN **OIL & DEBRIS** TRAP





**Enlarged Front View** 





<u>w/ Integral Handle</u>














- \* H1. H2 = 12" FOR UP TO AND INCLUDING 48" N-12
- \* H1, H2 = 24" FOR 60" N-12 \* FOR TRAFFIC LOAD INSTALLATIONS PROVIDE 24" COVER FOR 42"-60" N-12

		-	'		
	NOMINAL DIAMETER	NOMINAL O.D.	TYPICAL SPACING "S"	TYPICAL SPACING "C"	TYPICAL SIDE WALL "X
	12"	14.5"	11"	25.4"	8"
	15"	18"	12"	28.9"	8"
	18"	21"	13"	33.9"	9"
	24"	28"	13"	40.7"	10"
U.G. INF	30"	36"	18"	53.1"	18"
	36"	42"	22"	63"	18"
	42"	48"	24"	71.9"	18"

- 1. ALL UNDERGROUND SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, "STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS", LATEST EDITION.
- 2. MEASURES SHOULD BE TAKEN TO PREVENT MIGRATION OF NATIVE FINES INTO BACKFILL MATERIAL, WHEN REQUIRED.
- 3. SEE GRADING & DRAINAGE PLAN FOR INVERT DATA. 4. EXISTING TOPSOIL, BRUSH, TREES, BOULDERS, FILL AND DEBRIS TO BE REMOVED FOR 5' ALL AROUND UNDERGROUND SYSTEMS DOWN TO NATIVE MATERIAL. BACKFILL WITH STONE BEDDING MATERIAL (CLASS 1A OR 1B).


## **GENERAL NOTES:**


- ALL REFERENCES TO SAND, STONE, OR GRAVEL MATERIAL ARE PER ASTM D2321 "STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS", LATEST EDITION.
- . ALL RETENTION AND DETENTION SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, LATEST EDITION AND THE MANUFACTURER'S PUBLISHED INSTALLATION GUIDELINES.
- . MEASURES SHOULD BE TAKEN TO PREVENT THE MIGRATION OF NATIVE FINES INTO THE BACKFILL MATERIAL, WHEN REQUIRED. SEE ASTM D2321.
- 4. NO STORMWATER FLOWS ARE TO BE DIRECTED TO THE INFILTRATION SYSTEMS UNTIL ALL CONTRIBUTING AREAS HAVE BEEN FULLY STABILIZED.
- . <u>FILTER FABRIC:</u> GEOTEXTILE FABRIC SHALL BE MIRAFI 140N (OR APPROVED EQ.) TO PREVENT THE MIGRATION OF FINES FROM THE NATIVE SOIL INTO THE SELECT BACKFILL MATERIAL. FOUNDATION: WHERE THE TRENCH BOTTOM IS UNSTABLE OR UNSUITABLE FOR INFILTRATION, THE CONTRACTOR SHALL EXCAVATE TO A DEPTH REQUIRED

BY THE GEOTECHNICAL ENGINEER AND REPLACE WITH SUITABLE MATERIAL AS SPECIFIED BY THE GEOTECHNICAL ENGINEER. AS AN ALTERNATIVE AND AT THE DISCRETION OF THE GEOTECHNICAL ENGINEER, THE TRENCH BOTTOM MAY BE STABILIZED USING A GEOTEXTILE MATERIAL. ALL DELETERIOUS OR UNSUITABLE


- FILL MATERIAL SHALL BE REMOVED BELOW THE TRENCH BOTTOM UNTIL NATIVE MATERIAL IS ENCOUNTERED. . <u>BEDDING:</u> SUITABLE MATERIAL SHALL BE CLEAN COMPACT SAND. THE CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER.
- 8. INITIAL BACKFILL: SUITABLE MATERIAL SHALL BE PLACED IN THE PIPE ZONE EXTENDING NOT LESS THAN 6" ABOVE CROWN OF PIPE. THE CONTRACTOR HALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER. MATERIAL SHALL BE INSTALLED AS REQUIRED IN ASTM D2321, LATEST
- MINIMUM COVER: MINIMUM COVER OVER ALL RETENTION/DETENTION SYSTEMS IN NON-TRAFFIC APPLICATIONS (GRASS OR LANDSCAPE AREAS) IS 12" FROM TOP OF PIPE TO GROUND SURFACE. ADDITIONAL COVER MAY BE REQUIRED TO PREVENT FLOATATION. FOR TRAFFIC APPLICATIONS, MINIMUM COVER IS 12" UP TO 36" DIAMETER PIPE AND 24" OF COVER FOR 42" - 60" DIAMETER PIPE, MEASURED FROM TOP OF PIPE TO BOTTOM OF FLEXIBLE PAVEMENT OR

#### TYPICAL UNDERGROUND INFILTRATION SYSTEM CROSS SECTION NOT TO SCALE





DMH PLAN VIEW



TYPICAL RISER AND CLEANOUT DETAILS NOT TO SCALE

---

SECTION A-A

المتحدمية

VARIES (SEE NOTE 5)

PIPE INVERTS: 78 1/4 in / 6.52 ft

SUMP: 0' in / 0.00 ft

. MULTIPLE INLET PIPES POSSIBLE (REFER TO PROJECT PLANS).

GENERAL ARRANGEMENT DRAWINGS ONLY. CONTACT HYDRO INTERNATIONAL FOR SITE SPECIFIC FABRICATION DRAWINGS.

THE DIAMETER OF THE INLET & OUTLET PIPES MAY BE NO MORE THAN 24".

INLET/OUTLET PIPE ANGLE CAN VARY TO ALIGN WITH DRAINAGE NETWORK (REFER TO PROJECT PLANS).

5. PEAK FLOW RATE AND MINIMUM HEIGHT LIMITED BY AVAILABLE COVER AND PIPE DIAMETER.

6. LARGER SEDIMENT STORAGE CAPACITY MAY BE PROVIDED WITH A DEEPER SUMP DEPTH.

A. THE TREATMENT SYSTEM SHALL USE AN INDUCED VORTEX TO SEPARATE POLLUTANTS FROM STORMWATER

RUNOFF.

B. THE TREATMENT SYSTEM SHALL FIT WITHIN THE LIMITS OF EXCAVATION (AREA AND DEPTH) AS SHOWN IN THE PROJECT PLANS AND WILL NOT EXCEED THE DIMENSIONS FOR THE DESIGN FLOW RATES SPECIFIED HEREIN.

C. THE TREATMENT SYSTEM SHALL REMOVE GREATER THAN OR EQUAL TO 90% OF TSS BASED ON THE TARGET

PARTICLE SIZE (TPS) OF 106 MICRONS AND/OR 80% OF TSS BASED ON THE TPS OF 230 MICRONS AT 0.7 CFS AND 1.2 CFS, RESPECTIVELY.

THE TREATMENT SYSTEM SHALL CONVEY THE PEAK ON-LINE FLOW RATES OF UP TO 18 CFS WITHOUT CAUSING UPSTREAM SURCHARGE CONDITIONS. FULL-SCALE INDEPENDENT LABORATORY SCOUR TESTING


AUJUA OF MIRK-1UD.


THE TREATMENT SYSTEM SHALL BE CAPABLE OF CAPTURING AND RETAINING FINE SILT AND SAND SIZE PARTICLES. ANALYSIS OF CAPTURED SEDIMENT FROM FULL-SCALE FIELD INSTALLATIONS SHALL DEMONSTRATE PARTICLE SIZES PREDOMINATELY IN THE 20-MICRON RANGE


SHALL DEMONSTRATE EFFLUENT CONTROL OF LESS THAN OR EQUAL TO 5 MG/L FOR ALL FLOWS UP TO 200% OF MTFR-106.

PREASSEMBLY REFERENCE: 54 % in / 4.57 ft


BOTTOM OF INTERNALS: 37 ½ in / 3.13 ft







PRECAST CONCRETE DRAIN MANHOLE



PRECAST CONCRETE CATCH BASIN WITH HOOD NOT TO SCALE


	-			
-				
	NO.	DESCRIPTION	BY	DATE
		REVISIONS		

## DETAIL SHEET

ASSESSORS MAP 252 - LOTS 4,5 & 9 1400 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

PREPARED FOR: 4 AMIGOS, LLC

321 LAFAYETTE ROAD UNIT D HAMPTON, NEW HAMPSHIRE 03842






Engineering Planning Construction Management **GPINET.COM** 

Greenman-Pedersen, Inc. 44 Stiles Road Suite One

Salem, NH 03079

DRAWING NO. 4582DET.DWG SCALE: 1"=20' DATE: DRAWN BY: CHECKED BY: PROJECT NO. SHEET NO. CPS CMT 458219 14 OF 15



<u> "FIRST DEFENSE" UNIT DETAIL – FD-6HC</u>

NOT TO SCALE

Copyright © 2020 by Greenman-Pedersen, Inc. All Rights Reserved.

PLAN VIEW

CRITERIA FOR SILT FENCES: 1) SILT FENCE FILTER CLOTH: THE FABRIC FOR THE SILT FENCE SHALL MEET THE FOLLOWING SPECIFICATIONS:

MINIMUM **ACCEPTABLE FABRIC PROPERTIES:** TEST METHOD GRAB TENSILE STRENGTH (Ibs) ASTM D1682 ELONGATION AT FAILURE (%) ASTM D1682 MULLEN BURST STRENGTH (PSI) ASTM D3786 PUNCTURE STRENGTH (lbs) ASTM D751 40-80 EQUIVELANT OPENING SIZE US STD SIEVE 2) FENCE POSTS (FOR FABRICATED UNITS) - THE POSTS SHALL BE A MINIMUM OF 36 INCHES LONG, WOOD POSTS WILL BE

FENCE POSTS (FOR FABRICATED UNITS) — THE POSTS SHALL BE A MINIMUM OF 30 INCHES STORES WILL BE OF SOUND QUALITY HARDWOOD WITH A MINIMUM CROSS SECTIONAL AREA OF 3.0 SQUARE INCHES. STEEL POSTS WILL BE STANDARD T OR U SECTIONS WEIGHING NOT LESS THAN 1 POUND PER LINEAR FOOT. MAXIMUM SPACING SHALL BE 6

3) WIRE FENCE (FOR FABRICATED UNITS) - WIRE FENCING SHALL BE A MINIMUM 14.5 GUAGE WITH A MAXIMUM 6 INCH MESH

4) PREFABRICATED UNITS - PREFABRICATED UNITS MAY BE USED IN LIEU OF THE ABOVE METHOD PROVIDING: (1) THE FILTER CLOTH AND FENCE POSTS MEET THE ABOVE CRITERIA; AND (2) THE UNIT IS INTALLED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.

1) SILT FENCES SHALL BE INSPECTED IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REPAIRS THAT ARE REQUIRED SHALL BE MADE IMMEDIATELY.

2) IF THE FABRIC ON A SILT FENCE SHOULD DECOMPOSE OR BECOME INEFFECTIVE DURING THE EXPECTED LIFE OF THE FENCE, THE FABRIC SHALL BE REPLACED PROMPTLY.

3) SEDIMENT DEPOSITS SHOULD BE INSPECTED AFTER EVERY STORM EVENT. THE DEPOSITS SHOULD BE REMOVED WHEN THEY REACH APPROXIMTELY ONE-HALF THE HEIGHT OF THE BARRIER.

4) SEDIMENT DEPOSITS THAT ARE REMOVED OR LEFT IN PLACE AFTER THE FABRIC HAS BEEN REMOVED SHALL BE GRADED TO CONFORM WITH THE EXISTING TOPOGRAPHY AND VEGETATED. CONSTRUCTION SPECIFICATIONS:

1) THE GEOTEXTILE FABRIC SHALL MEET THE DESIGN CRITERIA FOR SILT FENCES.

2) THE FABRIC SHALL BE <u>EMBEDDED A MINIMUM OF 8 INCHES INTO THE GROUND</u> (4" DEEP & 4" WIDE) AND THE SOIL COMPACTED OVER THE <u>EMBEDDED FABRIC</u>.


3) WOVEN WIRE FENCE SHALL BE FASTENED SECURELY TO THE FENCE POSTS WITH WIRE TIES OR STAPLES.

4) FILTER CLOTH SHALL BE FASTENED SECURELY TO THE WOVEN WIRE FENCE WITH TIES SPACED EVERY 24 INCHES AT THE

5) WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EAC OTHER, THEY SHALL BE OVERLAPPED BY 6 INCHES (24" IS PREFERRED), FOLDED, AND STAPLED.

6) POSTS TO BE SPACED AT A MAXIMUM OF 6' ON CENTER.

#### SEDIMENT CONTROL FENCE NOT TO SCALE



INSPECTION AND MAINTENANCE

Routine inspection should be conducted within 24 hrs of a runoff event or as designated by the regulating authority. Sediment control should be regularly inspected to make sure they maintain their shape and are producing adequate hydraulic flowthrough. If ponding becomes excessive, additional Sediment control may be required to reduce effective slope length or sediment removal may be necessary. Sediment control shall be inspected until area above has been permanently stabilized and construction

activity has ceased 1. The Contractor shall maintain the Sediment control in a functional condition at all times and

it shall be routinely inspected. 2. If the Sediment control has been damaged, it shall be repaired, or replaced if beyond repair.


3. The Contractor shall remove sediment at the base of the upslope side of the Sediment control when accumulation has reached 1/2 of the effective height of the Sediment control, or as directed by the Engineer. Alternatively, a new Sediment control can be placed on top of and slightly behind the original one creating more sediment storage capacity without soil disturbance.

4. Sediment control shall be maintained until disturbed area above the device has been permanently stabilized and construction activity

5. The FilterMedia™ will be dispersed on site once disturbed area has been permanently stabilized. construction activity has ceased, or as determined by the Engineer.


6. For long-term sediment and pollution control applications, Sediment control can be seeded at the time of installation to create a vegetative filtering system for prolonged and increased filtration of sediment and soluble pollucants (contained vegetative filter strip). The appropriate seed mix shall be determined by the Engineer.

### FILTREXX® SILT S□XX™



## GRAVEL CONSTRUCTION EXIT

NOT TO SCALE



## MATERIALS STOCKPILE DETAIL

4 Amigos LLC

Portsmouth, NH

December 16, 2019

Diane Pantermoller

12-1

>54"

12-2

>120"

>120"

12-3

>122"

>122"

12-4

>120"

>120°

12-5

>120"

>120"

Soil Texture

Loamy Sand

Loamy Sand

Soil Texture

Loamy Sand

Loamy Sand

Loamy Sand

Soil Texture

Mixed

Soils/pavement

Loamy Sand

Soil Texture

Mixed Soils

Soil Texture

Mixed Soils

Loamy Sand

44 Stiles Road, Suite One

54"

458219

Horizon

Α

Horizon

Α

Horizon

Fill

Horizon

Fill

Horizon

Fill

1400 Lafayette Road

**TEST PIT DATA** 

Color

10yr 3/2

10vr 5/6

Color

10 yr 3/2

10vr 5/6

7.5yr 4/3

Color

7.5 yr 4/3

Color

Color

7.5yr 4/3

An Equal Opportunity Employer

SCS Soil:

Roots:

Standing Water:

Standing Water:

Standing Water:

Standing Water

Standing Water

Consistence

FR

FR

Consistence

FR

FR

FR

FR

Consistence

Consistence

Salem, NH 03079

Former:

Mile Dassi, a Censultants, and the particular of the part

Project Address:

Town, State:

Job Number:

Performed by

**Test Pit No** 

Depth

0-48

48-54"

Test Pit No

Depth

9-18"

18-120"

**Test Pit No** 

Depth

0-30"

30-122"

Test Pit No.

0-120"

Test Pit No

Depth

0-36"

36-120"

Greenman-Pedersen, Inc.

ESHWT:

Refusal:

ESHWT:

Refusal:

ESHWT:

Refusal:


0-9"

ESHWT:

Refusal:

ESHWT:

Refusal:



\* \* \*

1. BEGIN AT THE TOP OF BLANKET INSTALLATION AREA BY ANCHORING BLANKET IN A 6" DEEP TRENCH. BACKFILL AND COMPACT TRENCH AFTER STAPLING.

2. ROLL THE BLANKET DOWN THE SWALE IN THE DIRECTION OF THE WATER FLOW. LAY BLANKETS LOOSELY & MAINTAIN DIRECT CONTACT WITH SOIL —

MATS/BLANKETS SHOULD

BE INSTALLED

OVER END WITH 6 INCH (MIN.) OVERLAP AND ANCHOR DOWN SLOPE
BLANKET IN A 6 INCH DEEP TRENCH.

5. BLANKETS SHALL BE STAPLED ENOUGH TO ANCHOR BLANKET WHILE
MAINTAINING CONTACT WITH SOIL. STAPLES SHALL BE PLACED DOWN THE
CENTER & STAGGERED WITH THE STAPLES PLACED ALONG EDGES. PATTERN
& AMOUNT OF STAPLES VARIES BY MANUFACTURER, SO FOLLOW
MANUFACTURERS DECOMMENDATIONS

6. BLANKET SHALL BE NORTH AMERICAN GREEN SC-150 OR APPROVED EQUAL. MAINTENANCE & MATS

1. BLANKETS SHALL BE INSPECTED WEEKLY DURING CONSTRUCTION & AFTER A

RAINFALL IN EXCESS OF 1/2" IN A 24-HOUR PERIOD. 2. FAILURES SHALL BE REPAIRED IMMEDIATELY. IF ANY OF THE FOLLOWING OCCUR; SLOPE WASHOUT, MAT DISPLACEMENT, DAMAGE TO MAT, THE AFFECTED AREA SHALL BE REPAIRED & RESEEDED & MAT SHALL BE

Engineering | Design | Planning | Construction Managemen

None

None

None

None

None

None

None

None

Chatfield-Hollis-Canton

Mottles; Quantity/Contrast

None visible

Mottles; Quantity/Contrast

20% Gravel

Mottles; Quantity/Contrast

Mixed Soils/Urban

Fill/Pavement Gravel

20% Gravel

Mottles; Quantity/Contrast

Bricks, Urban Fill

Mottles; Quantity/Contrast

Bricks, Urban Fill

20% Gravel

p 603-893-0720

Chatfield-Hollis-Canton


Chatfield-Hollis-Canton

Chatfield-Hollis-Canton

Chatfield-Hollis-Canton

## BLANKET SLOPE PROTECTION FOR EROSION CONTROL


NOT TO SCALE



## LOW POINT SEDIMENTATION CONTROL BARRIER

NOT TO SCALE

NOT TO SCALE



1) A WIRE MESH SHOULD BE PLACED OVER THE DROP INLET OR CURB OPENING SO THAT THE ENTIRE OPENING AND A MINIMUM OF 12 INCHES AROUND THE OPENING ARE COVERED BY THE MESH. THE MESH MAY BE ORDINARY HARDWARE CLOTH OR WIRE MESH WITH OPENINGS UP TO 1/2 INCH.

I THE WIRE MESH SHOULD BE COVERED WITH CLEAN COARSE AGGREGATE SUCH AS SEWER STONE FOR A MINIMUM 3) THE COARSE AGGREGATE SHOULD EXTEND AT LEAST 18 INCHES ON ALL SIDES OF THE DRAIN OPENING.

MAINTENANCE: ALL STRUCTURES SHOULD BE INSPECTED AFTER EVERY RAIN STORM AND REPAIRS MADE AS NECESSARY, SEDIMENT SHOULD BE PENOVED EDOMETHS TO SERVE AS NECESSARY. SEDIMENT SHOULD BE REMOVED FROM THE TRAPPING DEVICES AFTER THE SEDIMENT HAS REACHED A MAXIMUM OF ONE HALF THE DEPTH OF THE TRAP. THE SEDIMENT SHOULD BE DISPOSED OF IN A SUITABLE AREA AND PROTECTED FROM EROSION BY EITHER STRUCTURAL OR VEGETATIVE MEANS. THE TEMPORARY TRAPS SHOULD BE REMOVED AND THE AREA REPAIRED AS SOON AS THE CONTRIBUTING DRAINAGE AREA TO THE INLET HAS BEEN

ON-SITE INLET PROTECTION DETAIL NOT TO SCALE

#### WINTER STABILIZATION NOTES:

MAINTENANCE MEASURES SHOULD CONTINUE AS NEEDED THROUGHOUT CONSTRUCTION, INCLUDING THE OVER-WINTER PERIOD. AFTER EACH RAINFALL, SNOWSTORM, OR PERIOD OF THAWING AND RUNOFF, THE SITE CONTRACTOR SHOULD CONDUCT AN INSPECTION OF ALL INSTALLED FROSION CONTROL MEASURES AND PERFORM REPAIRS AS NEEDED TO INSURE THEIR CONTINUING FUNCTION. FOR ANY AREA STABILIZED BY TEMPORARY OR PERMANENT SEEDING PRIOR TO THE ONSET OF THE WINTER SEASON, THE CONTRACTOR SHOULD CONDUCT AN INSPECTION IN THE SPRING TO ASCERTAIN THE CONDITION OF VEGETATION COVER, AND REPAIR ANY DAMAGE AREAS OR BARE SPOTS AND RESEED AS REQUIRED TO ACHIEVE

AN ESTABLISHED VEGETATIVE COVER (AT LEAST 85% OF AREA VEGETATED WITH HEALTHY, VIGOROUS GROWTH). O ADEQUATELY PROTECT WATER QUALITY DURING COLD WEATHER AND DURING SPRING RUNOFF, THE FOLLOWING STABILIZATION TECHNIQUES SHOULD BE EMPLOYED DURING THE PERIOD FROM OCTOBER 15TH

1. THE AREA OF EXPOSED, UNSTABILIZED SOIL SHOULD BE LIMITED TO ONE ACRE AND SHOULD BE PROTECTED AGAINST EROSION BY THE METHODS DESCRIBED IN THIS SECTION PRIOR TO ANY THAW OR SPRING MELT EVENT. SUBJECT TO APPLICABLE REGULATIONS, THE ALLOWABLE AREA OF EXPOSED SOIL MAY BE INCREASED IF ACTIVITIES ARE CONDUCTED ACCORDING TO A WINTER CONSTRUCTION PLAN, DEVELOPED BY A PROFESSIONAL ENGINEER LICENSED TO PRACTICE IN THE STATE OF NEW HAMPSHIRE OR A CERTIFIED PROFESSIONAL IN EROSION AND SEDIMENT CONTROL AS CERTIFIED BY THE CSPESC COUNCIL OF ENVIROCERT INTERNATIONAL, INC.

2. STABILIZATION AS FOLLOWS SHOULD BE COMPLETED WITHIN A DAY OF ESTABLISHING THE GRADE THAT IS FINAL OR THAT OTHERWISE WILL EXIST FOR MORE THAN 5 DAYS: A. ALL PROPOSED VEGETATED AREAS HAVING A SLOPE OF LESS THAN 15% WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHOULD BE SEEDED AND COVERED WITH 3 TO 4 TONS OF HAY OR STRAW MULCH PER ACRE SECURED WITH ANCHORED NETTING, OR 2 INCHES OF EROSION CONTROL MIX (SEE DESCRIPTION OF EROSION CONTROL MIX

BERMS FOR MATERIAL SPECIFICATION). B. ALL PROPOSED VEGETATED AREAS HAVING A SLOPE OF GREATER THAN 15% WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHOULD BE SEEDED AND COVERED WITH A PROPERLY INSTALLED AND ANCHORED EROSION CONTROL BLANKET OR WITH A MINIMUM 4 INCH THICKNESS OF EROSION CONTROL MIX, UNLESS OTHERWISE SPECIFIED BY THE MANUFACTURER. NOTE THAT COMPOST BLANKETS SHOULD NOT EXCEED 2 INCHES IN THICKNESS OR THEY MAY OVERHEAT.

3. ALL STONE-COVERED SLOPES MUST BE CONSTRUCTED AND STABILIZED BY OCTOBER 15.

4. INSTALLATION OF ANCHORED HAY MULCH OR EROSION CONTROL MIX SHOULD NOT OCCUR OVER SNOW OF GREATER THAN ONE INCH IN DEPTH.

5. ALL MULCH APPLIED DURING WINTER SHOULD BE ANCHORED (E.G., BY NETTING, TRACKING, WOOD CELLULOSE

6. STOCKPILES OF SOIL MATERIALS SHOULD BE MULCHED FOR OVER WINTER PROTECTION WITH HAY OR STRAW AT TWICE THE NORMAL RATE OR WITH A FOUR-INCH LAYER OF EROSION CONTROL MIX. MULCHING SHOULD BE DONE WITHIN 24 HOURS OF STOCKING, AND RE-ESTABLISHED PRIOR TO ANY RAINFALL OR SNOWFALL. NO SOIL STOCKPILE SHOULD BE PLACED (EVEN COVERED WITH MULCH) WITHIN 100 FEET FROM ANY WETLAND OR OTHER WATER RESOURCE AREA.

7. FROZEN MATERIALS, (E.G., FROST LAYER THAT IS REMOVED DURING WINTER CONSTRUCTION), SHOULD BE STOCKPILED SEPARATELY AND IN A LOCATION THAT IS AWAY FROM ANY AREA NEEDING TO BE PROTECTED STOCKPILES OF FROZEN MATERIAL CAN MELT IN THE SPRING AND BECOME UNWORKABLE AND DIFFICULT TO RANSPORT DUE TO THE HIGH MOISTURE CONTENT IN THE SOIL.

8. INSTALLATION OF EROSION CONTROL BLANKETS SHOULD NOT OCCUR OVER SNOW OF GREATER THAN ONE INCH IN DEPTH OR ON FROZEN GROUND.

9. ALL GRASS-LINED DITCHES AND CHANNELS SHOULD BE CONSTRUCTED AND STABILIZED BY SEPTEMBER ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHOULD BE STABILIZED TEMPORARILY WITH STONE OR ÉROSION CONTROL BLANKETS APPROPRIATE FOR THÉ DESIGN FLOW CONDITIONS, AS DETERMINED BY A QUALIFIED PROFESSIONAL ENGINEER OR A CERTIFIED PROFESSIONAL IN FROSION AND SEDIMENT CONTROL AS CERTIFIED BY THE CSPESC COUNCIL OF ENVIROCERT INTERNATIONAL, INC. IF A STONE LINING IS NECESSARY, THE CONTRACTOR MAY NEED TO RE-GRADE THE DITCH AS REQUIRED TO PROVIDE ADEQUATE CROSS-SECTION AFTER ALLOWING FOR PLACEMENT OF THE STONE

10. ALL STONE-LINED DITCHES AND CHANNELS MUST BE CONSTRUCTED AND STABILIZED BY OCTOBER 15.

11. AFTER NOVEMBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT

12. SEDIMENT BARRIERS THAT ARE INSTALLED DURING FROZEN CONDITIONS SHOULD CONSIST OF EROSION CONTROL MIX BERMS, OR CONTINUOUS CONTAINED BERMS. SILT FENCES AND HAY BALES SHOULD NOT BE INSTALLED WHEN FROZEN CONDITIONS PREVENT PROPER EMBEDMENT OF THESE BARRIERS.

#### CONSTRUCTION SEQUENCE NOTES:

1. SEDIMENT AND EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO ANY ON-SITE CONSTRUCTION AS SHOWN. ADDITIONAL TEMPORARY SEDIMENT AND EROSION CONTROL MEASURES SHALL BE INSTALLED AS

2. CONSTRUCT TEMPORARY STABILIZED CONSTRUCTION ENTRANCE AS SHOWN ON THIS SHEET.

3. CUT AND STUMP AREAS OF PROPOSED CONSTRUCTION.

4. REMOVE AND STOCKPILE TOPSOIL. STOCKPILE SHALL BE SEEDED TO PREVENT EROSION.

5. CONSTRUCT PONDS, SWALES & LEVEL SPREADERS & STABILIZE PRIOR TO DIRECTING ANY RUNOFF TO THEM.

6. CONSTRUCT ROADWAYS AND PERFORM SITE GRADING, PLACING HAY BALES AND SILTATION FENCES AS REQUIRED TO CONTROL SOIL EROSION. STABILIZE ROADS, PARKING LOTS AND CUT/FILL SLOPES WITHIN 72-HOURS OF ACHIEVING FINISH GRADES.

7. CONSTRUCT RELOCATED DRAINAGE LINE PRIOR TO REMOVING THE EXISTING DRAINAGE LINE AS SHOWN ON DEMOLITION PLAN AND CONNECT RELOCATED DRAINAGE LINE.

8. INSTALL UNDERGROUND UTILITIES AND DRAINAGE SYSTEM. 9. BEGIN TEMPORARY AND PERMANENT SEEDING AND MULCHING. ALL CUT AND FILL SLOPES SHALL BE SEEDED OR MULCHED WITHIN 72-HOURS OF ACHIEVING FINISHED GRADES.

10. DAILY, OR AS REQUIRED, CONSTRUCT, INSPECT, AND IF NECESSARY, RECONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, SILT FENCES AND SEDIMENT TRAPS INCLUDING MULCHING AND SEEDING. AT A MINIMUM, INSPECT EROSION CONTROLS WEEKLY AND AFTER EVERY 1/2" OF RAINFALL.

11. BEGIN EXCAVATION FOR CONSTRUCTION OF BUILDINGS.

12. FINISH PAVING ALL ROADWAYS AND DRIVEWAYS. 13. COMPLETE PERMANENT SEEDING AND LANDSCAPING

Oats (No later than May 15)

14. AFTER GRASS HAS BEEN FULLY GERMINATED IN ALL SEEDED AREAS, REMOVE ALL TEMPORARY

15. APPLICATION OF GRASS SEED, FERTILIZERS AND MULCH SHALL BE ACCOMPLISHED BY

BROADCAST SEEDING OR HYDROSEEDING AT THE RATES OUTLINED BELOW:

Limestone: 138 lbs./1,000 square feet. ertilizer: 13.8 lbs./1,000 SF straw mulch approximately 3 tons/acre unless erosion control matting is used. Permanent Seed Mix lbs./acre Creeping Red Fescue Tall Fescue Redtop TOTAL 42 Temporary Seed Mix: lbs./acre Winter Rye (Aug. 15-Sept. 15) 112

16. NEWLY GRADED AREAS REQUIRING SLOPE PROTECTION OUTSIDE OF NORMAL SEEDING SEASON SHALL RECEIVE HAY MULCH AT THE APPROXIMATE RATE OF NO MORE THAN 2 TONS PER ACRE

17. THE CONTRACTOR AND DEVELOPER MUST MANAGE THE PROJECT TO MEET THE REQUIREMENTS AND INTENT OF RSA 430:53 AND AGR 3800 RELATIVE TO INVASIVE SPECIES.

18. FUGITIVE DUST MUST BE CONTROLLED IN ACCORDANCE WITH ENV-A 1000.

#### **EROSION CONTROL NOTES:**

THE FROSION CONTROL PROCEDURES SHALL CONFORM TO THE NH STORMWATER MANUAL VOLUME 3, EROSION & SEDIMENT CONTROLS DURING CONSTRUCTION, DECEMBER 2008.

2. DURING CONSTRUCTION AND THEREAFTER, EROSION CONTROL MEASURES ARE TO BE IMPLEMENTED AS NOTED: THE SMALLEST PRACTICAL AREA OF LAND SHOULD BE EXPOSED AT ANY ONE TIME DURING DEVELOPMENT. WHEN LAND IS EXPOSED DURING DEVELOPMENT, THE EXPOSURE SHOULD BE KEPT TO THE SHORTEST PRACTICAL PERIOD OF TIME AS APPROVED BY THE ENGINEER. LAND SHOULD NOT BE LEFT EXPOSED DURING THE WINTER

3. LIMIT OF MAXIMUM AREA OF EXPOSED SOIL AT ANY ONE TIME TO LESS THAN 5 ACRES. THE EXPOSED AREA THAT IS BEING ACTIVELY WORKED DURING WINTER IS TO BE LESS THAN 3 ACRES DURING THE WINTER SEASON

4. ALL PERMANENT STORM WATER STRUCTURES SHALL BE STABILIZED PRIOR TO DIRECTING FLOW INTO THEM. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED: A) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED. B) A MINIMUM OF 85 PERCENT VEGETATED GROWTH HAS BEEN ESTABL'SHED. C) A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RÍP-RAP HAS BEEN INSTALLED D) OR, EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.

5. SILT FENCE SHALL BE INSTALLED AND MAINTAINED DURING AND AFTER DEVELOPMENT TO REMOVE SEDIMENT FROM RUNOFF WATER AND FROM LAND UNDERGOING DEVELOPMENT. WHERE POSSIBLE, NATURAL DRAINAGE WAYS SHOULD BE UTILIZED AND LEFT OPEN TO REMOVE EXCESS SURFACE WATER. SILT FENCE TO BE MAINTAINED AND CLEANED UNTIL ALL SLOPES HAVE A HEALTHY STAND OF GRASS.

6. ALL DISTURBED AREAS AND SIDE SLOPES WHICH ARE FINISHED GRADED, WITH NO FURTHER CONSTRUCTION TO TAKE PLACE, SHALL BE LOAMED AND SEEDED WITHIN 72 HOURS AFTER FINAL GRADING. A MINIMUM OF 4" OF LOAM SHALL BE INSTALLED WITH NOT LESS THAN ONE POUND OF SEED PER 50 SQUARE YARDS OF AREA. THE SEED MIX SHALL BE AS DESIGNATED BELOW.

7. ANY DISTURBED AREAS WHICH ARE TO BE LEFT TEMPORARILY, AND WHICH WILL BE REGRADED LATER DURING CONSTRUCTION SHALL BE MACHINE HAY MULCHED AND SEEDED WITH RYE GRASS TO PREVENT EROSION. THE MAXIMUM LENGTH OF TIME FOR THE EXPOSURE OF DISTURBED SOILS SHALL BE 45 DAYS, HAY OR STRAW MUICH SHALL BE APPLIED TO ALL FRESHLY SEEDED AREAS AT THE RATE OF 2 TONS PER ACRE. BALES SHALL BE UNSPOILED, AIR DRIED, AND FREE FROM WEED, SEEDS AND ANY COARSE

8. DURING GRADING OPERATIONS INSTALL HAY BALE BARRIERS ALONG TOE OF SLOPE OF FILL AREAS WHERE SHOWN. BARRIERS ARE TO BE MAINTAINED UNTIL DISTURBED AREAS

9. THE FILL MATERIAL SHALL BE OF APPROVED SOIL TYPE FREE FROM STUMPS, ROOTS, WOOD, ETC. TO BE PLACED IN 12" LIFTS OR AS SPECIFIED. BULLDOZERS, TRUCKS, TRACTORS, OR ROLLERS MAY BE USED FOR COMPACTION BY ROUTING THE EQUIPMENT TO ALL AREAS OR EACH LAYER.

10. AVOID THE USE OF FUTURE OPEN SPACES (LOAM & SEED) WHEREVER POSSIBLE DURING CONSTRUCTION. CONSTRUCTION TRAFFIC SHALL USE THE ROADBEDS OF FUTURE ROADS.

#### TEMPORARY EROSION CONTROL MEASURES:

1. THE SMALLEST PRACTICAL AREA OF LAND SHALL BE EXPOSED AT ANY ONE TIME. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.

2. HAY BALE BARRIERS AND SEDIMENT TRAPS SHALL BE INSTALLED AS REQUIRED. BARRIERS AND TRAPS ARE TO BE MAINTAINED AND CLEANED UNTIL ALL SLOPES HAVE

3. BALED HAY AND MULCH SHALL BE MOWINGS OF ACCEPTABLE HERBACEOUS GROWTH, FREE FROM NOXIOUS WEEDS OR WOODY STEMS, AND SHALL BE DRY. NO SALT HAY SHALL BE USED.

4. FILL MATERIAL SHALL BE FREE FROM STUMPS, WOOD, ROOTS, ETC.

5. STOCKPILED MATERIALS SHALL BE PLACED ONLY IN AREAS SHOWN ON THE PLANS. STOCKPILES SHALL BE PROTECTED BY SILTATION FENCE AND SEEDED TO PREVENT ROSION. THESE MEASURES SHALL REMAIN UNTIL ALL MATERIAL HAS BEEN PLACED OR

6. ALL DISTURBED AREAS SHALL BE LOAMED AND SEEDED. A MINIMUM OF 4 INCHES OF LOAM SHALL BE INSTALLED AND SEEDING AS SPECIFIED.

7. AFTER ALL DISTURBED AREAS HAVE BEEN STABILIZED THE TEMPORARY EROSION


CONTROL MEASURES ARE TO BE REMOVED. 8. PAVED ROADWAYS MUST BE KEPT CLEAN AT ALL TIMES.

9. ALL CATCH BASIN INLETS WILL BE PROTECTED WITH LOW POINT SEDIMENTATION BARRIER.

10. ALL STORM DRAINAGE OUTLETS WILL BE STABILIZED AND CLEANED AS REQUIRED, BEFORE THE DISCHARGE POINTS BECOME OPERATIONAL.

11. ALL DEWATERING OPERATIONS MUST DISCHARGE DIRECTLY INTO A SEDIMENT FILTER

12. JUTE MATTING OR APPROVED EQUIVALENT SHALL BE PROVIDED ON ALL SLOPES



## INLET PROTECTION DETAIL

ATLANTIC CONSTRUCTION FABRICS, INC

NOT TO SCALE

"SILTSACK" AS MANUFACTURED BY

**DESCRIPTION** DATE REVISIONS

### DETAIL SHEET

ASSESSORS MAP 252 - LOTS 4.5 & 9 1400 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE PREPARED FOR: 4 AMIGOS, LLC 321 LAFAYETTE ROAD UNIT D

HAMPTON, NEW HAMPSHIRE 03842

603.893.0720


Design Planning


Construction Management GPINET.COM


Greenman-Pedersen, Inc 44 Stiles Road Suite One Salem, NH 03079


SCALE: 1"=20' DATE: 4582DET.DWG DRAWN BY: SHEET NO. CHECKED BY: PROJECT NO. CMT 458219 15 OF 15











		SMH-2 STA:2+21 RIM=47.80 RIN:N=39.64 INV.N=39.54	SMH-3 STA:0+65 RIM=48.20 INV.IN=42.50(DROP) INV.OUT=40.42	SMH-4 STA:0+00 RIM=47.85 INV.OUT=42.83
EX.SMH  STA:4+01  RIM=45.74  INV.IN=38.54  INV.IN=38.92  INV.IN=38.92  INV.OUT=38.82			APPROX. PROPOSED GRADE	
	121LF 8"PVC S=0.005ft/ft	18"HDPE I	61LF 8"PVC	C S=0.005ft/ft
51LF 8"PVC S=0.005ft/ft				
45.22	46.01	46.70	45.41	48.77

FRANK C. MONTEIRO No. 7152

CMT 2/20/20 MISC. REVISIONS PER TAC BY DATE DESCRIPTION **REVISIONS** 

MISC. REVISIONS PER TAC

SEWER PLAN/PROFILE

ASSESSORS MAP 252 - LOTS 4,5 & 9
1400 LAFAYETTE ROAD
PORTSMOUTH, NEW HAMPSHIRE PREPARED FOR:

4 AMIGOS, LLC

321 LAFAYETTE ROAD UNIT D
HAMPTON, NEW HAMPSHIRE 03842

603.893.0720


Engineering
Design
Planning Construction Management Suite One

Greenman-Pedersen, Inc. 44 Stiles Road Salem, NH 03079

CMT 3/9/20

DRAWING NO. 4582SP.DWG SCALE: 1"=30" DATE: JANUARY 20, 2020 DRAWN BY: CHECKED BY: PROJECT NO. SHEET NO. CCC 458219 1 OF 1

**GPINET.COM** 





**PROFILE** 

SCALE: 1"=30'H/3'V

OWNER OF RECORD: MAP 252 LOTS 4, 5 & 9 4 AMIGOS LLC 321 LAFAYETTE ROAD, UNIT D HAMPTON, NH 03842

Copyright © 2020 by Greenman-Pedersen, Inc. All Rights Reserved.







**WEST ELEVATION** 

SCALE: 1" = 10'-0"



NORTH ELEVATION
SCALE: 1" = 10'-0"



EAST ELEVATION
SCALE: 1" = 10'-0"



EAST ELEVATION DIMENSIONED

SCALE: 1" = 10'-0"

OPEN PARKING GARAGE COMPUTATION

PARKING GARAGE PERIMETER

548 L.F. X 0.40 = 219.2 L.F. REQUIRED OPENING LENGTH

221.0 L.F PROPOSED

PARKING GARAGE WALL AREA
5,207 S.F X 0.20 = 1,041.5 S.F. REQUIRED OPENING
1,390.0 S.F. PROPOSED

FACADE MODULATION WHERE REQUIRED IS PROPOSED TO BE ACHIEVED BY MATERIAL CHANGES ROOF, DORMERS AND FENESTRATION VARIATIONS

 SOUTH SIDE FIRST FLOOR FACADE OPENINGS

 SOUTH SIDE FIRST FLOOR 1
 273.13 S.F.
 149.00 S.F.
 50.4 %

 SOUTH SIDE FIRST FLOOR 2
 1,657.50 S.F.
 433.0 S.F.
 26.0 %

 273.13 S.F.
 0 S.F.
 0 %

GROSS SOUTH SIDE FIRST FLOOR FACADE OPENINGS 1,930.62 S.F. 582 S.F. 30.1 %



APPROX AVERAGE GRADE TO BE VERIFIED

Michael J. Keane Architects, PLLC

ARCHITECTURE
PLANNING
DESIGN
101 Kent Place
Newmarket, NH
03857

603-292-1400 mjkarchitects.com

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC, Newmarket, NH. © 2018

CONSULTANTS

REVISIONS

APPROVALS

CONCEPT NOT FOR CONSTRUCTION 3/9/2020

Accept only origianl stamp and signature copies may contain unauthorized modifications

PROJECT

MAP 252-LOTS 4, 5 &9 1400 LAFAYETTE ROAD PORTSMOUTH NH

ŧΟB

4 AMIGOS,LLC 321 LAFAYETTE ROAD HAMPTON, NH 03842,

TITLE

BUILDING A CONCEPT

DRAWN BY: CHECKED BY:

DRAWING NO.

A-1.A




Michael J. Keane Architects, PLLC


mjkarchitects.com

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC, Newmarket, NH. © 2018


CONCEPT NOT FOR CONSTRUCTION








TYPICAL SECOND FLOOR PLAN SCALE: 3/16" = 1'-0"



TYPICAL THIRD FLOOR PLAN
SCALE: 3/16" = 1'-0"



ASSUMED AVERAGE GRADE TO BE VERIFIED FACADE MODULATION WHERE REQUIRED IS PROPOSED TO BE ACHIEVED BY MATERIAL CHANGES, ROOF VARIATIONS AND PROJECTED BAY VARIATIONS

GROUND LEVEL FENSTRATION RATIO (20%) WHERE REQUIRED IS 35 S.F REQUIRED AND 35 S.F PROPOSED

FRONT ELEVATION DIMENSION SCALE: 3/16" = 1'-0"

Michael J. Keane Architects, PLLC

> DESIGN 101 Kent Place Newmarket, NH 03857

603-292-1400 mjkarchitects.com

Newmarket, NH. © 2018

PLANNING

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC,

CONSULTANTS

APPROVALS

CONCEPT NOT FOR CONSTRUCTION 3/9/2020

Accept only origianl stamp and signature copies may contain unauthorized modifications

PROJECT

MAP 252- LOTS 4,5 &9 1400 LAFAYETTE ROAD PORTSMOUTH NH

FOR

4 AMIGOS, LLC 321 LAFAYETTE ROAD HAMPTON NH 03842,

TITLE

BUILDING B TYPICAL UNIT

DRAWN BY: CHECKED BY:

DATE:


SCALE: AS NOTED

DRAWING NO.

A-1.B



REAR ELEVATION
SCALE: 1/8" = 1'-0"




LEFT ELEVATION

SCALE: 1/8" = 1'-0"



FRONT ELEVATION
SCALE: 1/8" = 1'-0"



GARAGE LEVEL PLAN
SCALE: 1/8" = 1'-0"



RIGHT ELEVATION
SCALE: 1/8" = 1'-0"

mjk
Michael J. Keane
Architects, PLLC

ARCHITECTURE
PLANNING
DESIGN
101 Kent Place
Newmarket, NH
03857

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC, Newmarket, NH. © 2018

603-292-1400 mjkarchitects.com

CONSULTANTS

DEVICION	ıc	
REVISION	15	

CONCEPT NOT FOR CONSTRUCTION

3/9/2020

APPROVALS

Accept only original stamp and signature copies may contain unauthorized modifications

PROJECT

MAP 252- LOTS 4,5 &9 1400 LAFAYETTE ROAD PORTSMOUTH NH

FOR

4 AMIGOS, LLC 321 LAFAYETTE ROAD HAMPTON NH 03842,

TITLE

BUILDING B PLANS AND ELEV

DRAWN BY:
CHECKED BY:


DRAMING NO

DRAWING NO.

A-2.B



## NORTH ELEVATION SCALE: 1/8" = 1'-0"






WEST ELEVATION
SCALE: 1/8" = 1'-0"




SOUTH ELEVATION
SCALE: 1/8" = 1'-0"

## TYPICAL SECOND AND THIRD FLOOR PLAN SCALE: 1/8" = 1'-0"



EAST ELEVATION
SCALE: 1/8" = 1'-0"



CONCEPT SECTION
SCALE: 1/8" = 1'-0"

Michael J. Keane Architects, PLLC

ARCHITECTURE
PLANNING
DESIGN
101 Kent Place
Newmarket, NH
03857

603-292-1400 mjkarchitects.com

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC, Newmarket, NH. © 2018

CONSULTANTS

REVISIONS

CONCEPT NOT FOR CONSTRUCTION

3/9/2020

Accept only origianl stamp and signature copies may contain unauthorized modifications

PROJECT

APPROVALS

MAP 252-LOTS 4, 5 & 9
1400 LAFAYETTE ROAD
PORTSMOUTH NH

FOR

4 AMIGOS,LLC 321 LAFAYETTE ROAD HAMPTON, NH 03842,

TITLE

BUILDING C CONCEPT PLANS

DRAWN BY: CHECKED BY:

DATE:

SCALE: AS NOTED

DRAWING NO.

A-1.C

CONCEPT PARKING LEVEL PLAN
SCALE: 1/8" = 1'-0"







## Michael J. Keane Architects, PLLC

ARCHITECTURE PLANNING DESIGN 101 Kent Place Newmarket, NH 03857

603-292-1400 mjkarchitects.com

All drawings and written materials appearing herein constitute original unpublished work of Michael J. Keane Architects, PLLC and may not be duplicated, used, or disclosed without the written consent of Michael J. Keane Architects, PLLC, Newmarket, NH. © 2018

CONSULTANTS

REVISION	<b>IS</b>

APPROVALS

CONCEPT NOT FOR CONSTRUCTION 1/19/2020

Accept only origianl stamp and signature copies may contain unauthorized modifications

PROJECT

MAP 252-LOTS 4, 5 &9 140 LAFAYETTE ROAD PORTSMOUTH NH

FOR

4 AMIGOS,LLC 321 LAFAYETTE ROAD HAMPTON, NH 03842,

TITLE

BUILDING C RENDER CONCEPTS

CHECKED BY:

SCALE: AS NOTED DRAWING NO.

## TRIP GENERATION COMPARISON – PROPOSED RESIDENTIAL VS. APPROVED RETAIL

Time Period / Direction	Currently Proposed Residential Development	Previously Approved Retail	Difference
Weekday Daily	290	868	-578
Weekday PM Peak Hour Enter Exit Total Saturday Daily	15	37	-22
	<u>10</u>	<u>38</u>	<u>-28</u>
	25	75	-50
	270	1,010	-740
Saturday Midday Peak Hour Enter Exit Total	15	51	-36
	<u>15</u>	<u>48</u>	<u>-33</u>
	30	99	-69

## TRIP GENERATION COMPARISON – APPROVED TRIPS VS. CURRENT TRIPS

Time Period / Direction	Previously Approved Trips	Current Site Trips	Difference
Weekday PM Peak Hour Enter Exit Total	124	77	-47
	<u>118</u>	<u>67</u>	<u>-51</u>
	242	144	-98
Saturday Midday Peak Hour Enter Exit Total	114	93	-21
	<u>108</u>	<u>101</u>	<u>-7</u>
	222	194	-28

#### **GUIDELINES FOR PEDESTRIAN CROSSING TREATMENTS**

This spreadsheet combines Worksheet 1 and Worksheet 2 (Appendix A, pages 69-70) of TCRP Report 112/NCHRP Report 562 (Improving Pedestrian Safety at Unsignalized Intersections) into an electronic format. This spreadsheet should be used in conjunction with, and not independent of, Appendix A documentation.

Key

This spreadsheet is still under development, please inform TTI if errors are identified.


Blue fields contain descriptive information.

Green fields are required and must be completed.

Tan fields are adjustments that are filled out only under certain conditions (follow instructions to the left of the cell).

Gray fields are automatically calculated and should not be edited.

<b>Analyst and Site Infor</b>	mation							
	Analyst RLB Major Street Peverly Hill Road							
Analysis Date	.,							
Data Collection Date J	·							
Step 1: Select worksh			r cak i loui	ויוז כד.כ טו ויוז כד.דן				
•						30		
Posted or statutory speed limit (or 85th percentile speed) on the major street (mph)					1a			
Is the population of the surrounding area <10,000? (enter <b>YES</b> or <b>NO</b> )  Step 2: Does the crossing meet minimum pedestrian volumes to be considered for a traffic control device?								
Peak-hour pedestrian volum		iestrian voiumes	to be co	insidered for a traffic	2a	5		
•	11	oncione traffic calmi	ng otc ac	fosciblo	Zd	3		
Result: Consider raised median islands, curb extensions, traffic calming, etc. as feasible.  Step 3: Does the crossing meet the pedestrian warrant for a traffic signal?								
			ramic sig	nair	2-	660		
•	both approaches during peak ho	( . , , maj s			<i>3a</i>	668		
[Calculated automatically] Preliminary (before min. threshold) peak hour pedestrian volume to meet warrant					<i>3b</i>	444		
[Calculated automatically] Minimum required peak hour pedestrian volume to meet traffic signal warrant					3c	444		
Is 15th percentile crossing speed of pedestrians less than 3.5 ft/s (1.1 m/s)? (enter <b>YES</b> or <b>NO</b> )					3d	NO		
3 7			duction for 3c (up to 50%)	3e				
(1.1 m/s), then reduce <i>3c</i>	R	educed valu	ue or <i>3c</i>	3f	444			
Result:								
Step 4: Estimate pede								
Pedestrian crossing distance, curb to curb (ft), L					4a	47		
Pedestrian walking speed (ft/s), $S_p$ (suggested speed = 3.5 ft/s)					4b	3.5		
Pedestrian start-up time and end clearance time (s), $t_s$ (suggested start-up time = 3 sec)					4c	3		
[Calculated automatically] Critical gap required for crossing pedestrian (s), t <sub>c</sub>					4d	16		
Major road volume, total both approaches OR approach being crossed if raised median island is present, during peak hour (veh/h), $V_{\text{maj-d}}$					4e	668		
Major road flow rate (veh/s), v					4f	0.19		
Average pedestrian delay (s/person), d <sub>p</sub>					<i>4g</i>	98		
Total pedestrian delay (h), D <sub>n</sub> The value in 4h is the calculated estimated delay for all pedestrians crossing the					4h	0.1		
major roadway without a crossing treatment (assumes 0% compliance). If the actual total pedestrian delay has been measured at the site, that value can be entered in 4i to replace the calculated value in 4h.					4i			
Step 5: Select treatm	ent based up on total pe	edestrian delay a	nd expe	cted motorist complia	ance.			
Expected motorist complian Compliance	ce at pedestrian crossings in regi	ion: enter <i>HIGH for H</i>	igh Compi	liance or LOW for Low	5a	low		
Treatment	Category: Con	sider raised med	ian islan	ds, curb extensions, feasible.	traffic calm	ing, etc. as		



This worksheet provides general recommendations on pedestrian crossing treatments to consider at unsignalized intersections; in all cases, engineering judgment should be used in selecting a specific treatment for installation. This worksheet does not apply to school crossings. In addition to the results provided by this worksheet, users should consider whether a pedestrian treatment could present an increased

safety risk to pedestrians, such as where there is poor sight distance, complex geometrics, or nearby traffic signals.

Spreadsheet developed by
Texas Transportation Institute Printed 3/3/2020